

Package: ggseg.meshes (via r-universe)

July 16, 2026

Title Additional Brain Surface Meshes for the 'ggsegverse' Ecosystem

Version 0.0.1

Description Provides additional brain surface meshes for cortical and cerebellar visualisation in the 'ggsegverse' ecosystem. Cortical surfaces include pial, white, midthickness, semi-inflated, sphere, smoothwm, and orig at fsaverage5 resolution. Cerebellar surfaces include the Spatially Unbiased Infratentorial Template (SUIT) flatmap. All meshes follow the same vertices/faces data frame format used by 'ggseg.formats' and 'ggseg3d'.

License MIT + file LICENSE

Depends R (>= 4.1.0)

Imports cli

Suggests freesurfer, freesurferformats, gifti, ggseg.formats, knitr, rmarkdown, testthat (>= 3.0.0)

VignetteBuilder knitr

Config/testthat/edition 3

Config/Needs/website ggsegverse/ggseg.docs

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

URL <https://github.com/ggsegverse/ggseg.meshes>,
<https://ggsegverse.github.io/ggseg.meshes/>

BugReports <https://github.com/ggsegverse/ggseg.meshes/issues>

Repository <https://r-multiverse-staging.r-universe.dev>

Date/Publication 2026-04-09 10:08:18 UTC

RemoteUrl <https://github.com/ggsegverse/ggseg.meshes>

RemoteRef v0.0.1

RemoteSha 964f1f59d9b224c31b7a67994007ac3024263962

Contents

available_cerebellar_surfaces	2
available_cortical_surfaces	2
get_cerebellar_flatmap	3
get_cortical_mesh	3
Index	5

available_cerebellar_surfaces	
<i>List available cerebellar surfaces</i>	

Description

List available cerebellar surfaces

Usage

available_cerebellar_surfaces()

Value

Character vector of available surface names.

Examples

available_cerebellar_surfaces()

available_cortical_surfaces	
<i>List available cortical surfaces</i>	

Description

List available cortical surfaces

Usage

available_cortical_surfaces()

Value

Character vector of available surface names.

Examples

available_cortical_surfaces()

`get_cerebellar_flatmap`*Get SUIIT cerebellar flatmap mesh*

Description

Retrieves the SUIIT cerebellar flatmap surface mesh. This is a 2D flattened representation of the cerebellar cortex, useful for visualising cerebellar parcellations without 3D rendering.

Usage

```
get_cerebellar_flatmap(surface = .cerebellar_surfaces)
```

Arguments

`surface` Surface type. Currently only "suit_flat".

Details

The flatmap has z-coordinates near zero (flat projection). Vertex count matches the SUIIT 3D pial surface in ggseg.formats, so vertex indices from cerebellar atlases map directly to this mesh.

Value

A list with vertices (data.frame with x, y, z) and faces (data.frame with i, j, k, 0-based indices matching ggseg.formats convention for cerebellar meshes). Has attribute `face_index_base = 0L`.

Examples

```
mesh <- get_cerebellar_flatmap()
nrow(mesh$vertices)
```

`get_cortical_mesh`*Get cortical brain surface mesh*

Description

Retrieves a cortical brain surface mesh for the specified hemisphere and surface type. All surfaces are fsaverage5 resolution (10,242 vertices, 20,480 faces per hemisphere).

Usage

```
get_cortical_mesh(hemisphere = c("lh", "rh"), surface = .cortical_surfaces)
```

Arguments

hemisphere	"lh" or "rh"
surface	Surface type: "pial", "white", "midthickness", "semi-inflated", "sphere", "smoothwm", or "orig"

Value

A list with vertices (data.frame with x, y, z) and faces (data.frame with i, j, k, 1-based indices).
Has attribute `face_index_base = 1L`.

Examples

```
mesh <- get_cortical_mesh("lh", "pial")  
nrow(mesh$vertices)
```

Index

`available_cerebellar_surfaces`, [2](#)

`available_cortical_surfaces`, [2](#)

`get_cerebellar_flatmap`, [3](#)

`get_cortical_mesh`, [3](#)