Package: polars0 (via r-universe)

October 5, 2026

Title Lightning-Fast 'DataFrame' Library

Version 1.0.0

Depends R (>= 4.2)

Imports utils, codetools, methods

Description Lightning-fast 'DataFrame' library written in 'Rust'. Convert R data to 'Polars' data and vice versa. Perform fast, lazy, larger-than-memory and optimized data queries. 'Polars' is interoperable with the package 'arrow', as both are based on the 'Apache Arrow' Columnar Format.

License MIT + file LICENSE

Language en-US

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

SystemRequirements Cargo (rustc package manager), cmake

URL https://rpolars.github.io/r-polars0/,

https://github.com/rpolars/r-polars0,

https://rpolars.r-universe.dev/polars0

Suggests arrow (>= 15.0.1), bench, bit64, callr, clock (>= 0.7.0), curl, ggplot2, jsonlite, knitr (>= 1.49.0), lubridate, nanoarrow (>= 0.6.0), nycflights13, patrick (>= 0.3.0), quickcheck, pillar, rlang, rmarkdown, testthat (>= 3.2.1), tibble, tools, vctrs, withr, xfun (>= 0.48)

Config/Needs/website altdoc, future.apply, here, magrittr, pkgload, yaml

Config/Needs/dev devtools, dplyr, RcppTOML, readr, github::extendr/rextendr@v0.4.0, spelling, stringr, styler

Config/testthat/edition 3

Collate 'utils.R' 'extendr-wrappers.R' 'after-wrappers.R' 'Field.R' 'PTime.R' 'as_polars.R' 'autocompletion.R' 'construction.R' 'dataframe__frame.R' 'datatype.R' 'docs.R' 'dotdotdot.R' 'error__rpolarserr.R' 'error__string.R' 'error__trait.R' 'error_conversion.R' 'expr__array.R' 'expr__binary.R' 'expr__categorical.R' 'expr__datetime.R' 'expr__expr.R' 'expr__list.R' 'expr__meta.R' 'expr__name.R' 'expr__string.R' 'expr__struct.R' 'functions__eager.R' 'functions__lazy.R' 'functions__whenthen.R' 'group_by.R' 'group_by_dynamic.R' 'group_by_rolling.R' 'io_csv.R' 'io_ipc.R' 'io_json.R' 'io_parquet.R' 'is_polars.R' 'lazyframe__group_by.R' 'lazyframe__lazy.R' 'parse_as_duration.R' 'pkg-arrow.R' 'pkg-knitr.R' 'pkg-nanoarrow.R' 'polars-package.R' 'polars_envvars.R' 'polars_info.R' 'polars_options.R' 'rbackground.R' 'rust_result.R' 's3-methods.R' 's3-methods-operator.R' 'series__series.R' 'sql.R' 'vctrs.R' 'zzz.R'

Config/rextendr/version 0.4.0

VignetteBuilder knitr

Config/polars0/LibVersion 0.45.3

Config/polars0/RustToolchainVersion nightly-2024-11-28

Config/pak/sysreqs cmake libclang-dev

Repository https://r-multiverse-staging.r-universe.dev

Date/Publication 2025-07-12 13:32:23 UTC

RemoteUrl https://github.com/rpolars/r-polars0

RemoteRef v1.0.0

RemoteSha 8972f0106e87e1f02da005613855fe99628d66db

Contents

[.RPolarsDataFrame . . . 17
as.character.RPolarsSeries . . . 18
as.data.frame.RPolarsDataFrame . . . 18
as.matrix.RPolarsDataFrame . . . 21
as.vector.RPolarsSeries . . . 21
as_arrow_table.RPolarsDataFrame . . . 22
as_nanoarrow_array_stream.RPolarsDataFrame . . . 23
as_polars_df . . . 24
as_polars_lf . . . 28
as_polars_series . . . 28
as_record_batch_reader.RPolarsDataFrame . . . 30
c.RPolarsSeries . . . 31
DataFrame_cast . . . 32
DataFrame_class . . . 33
DataFrame_clear . . . 35

DataFrame_clone . . . 36
DataFrame_describe . . . 37
DataFrame_drop . . . 38
DataFrame_drop_in_place . . . 39
DataFrame_drop_nulls . . . 39
DataFrame_dtype_strings . . . 40
DataFrame_equals . . . 40
DataFrame_estimated_size . . . 41
DataFrame_explode . . . 42
DataFrame_fill_nan . . . 43
DataFrame_fill_null . . . 43
DataFrame_filter . . . 44
DataFrame_first . . . 45
DataFrame_gather_every . . . 45
DataFrame_get_column . . . 46
DataFrame_get_columns . . . 46
DataFrame_glimpse . . . 47
DataFrame_group_by . . . 48
DataFrame_group_by_dynamic . . . 49
DataFrame_head . . . 52
DataFrame_item . . . 53
DataFrame_join . . . 53
DataFrame_join_asof . . . 55
DataFrame_join_where . . . 58
DataFrame_last . . . 59
DataFrame_lazy . . . 59
DataFrame_max . . . 60
DataFrame_mean . . . 60
DataFrame_median . . . 61
DataFrame_min . . . 61
DataFrame_n_chunks . . . 62
DataFrame_null_count . . . 63
DataFrame_partition_by . . . 64
DataFrame_pivot . . . 65
DataFrame_quantile . . . 67
DataFrame_rechunk . . . 67
DataFrame_rename . . . 69
DataFrame_reverse . . . 70
DataFrame_rolling . . . 70
DataFrame_sample . . . 72
DataFrame_select . . . 73
DataFrame_select_seq . . . 74
DataFrame_shift . . . 75
DataFrame_slice . . . 75
DataFrame_sort . . . 76
DataFrame_sql . . . 77
DataFrame_std . . . 78
DataFrame_sum . . . 79

DataFrame_tail . . . 79
DataFrame_to_data_frame . . . 80
DataFrame_to_dummies . . . 81
DataFrame_to_list . . . 82
DataFrame_to_raw_ipc . . . 84
DataFrame_to_series . . . 85
DataFrame_to_struct . . . 86
DataFrame_transpose . . . 87
DataFrame_unique . . . 88
DataFrame_unnest . . . 89
DataFrame_unpivot . . . 89
DataFrame_var . . . 91
DataFrame_with_columns . . . 91
DataFrame_with_columns_seq . . . 92
DataFrame_with_row_index . . . 93
DataFrame_write_csv . . . 94
DataFrame_write_ipc . . . 95
DataFrame_write_json . . . 96
DataFrame_write_ndjson . . . 97
DataFrame_write_parquet . . . 98
DataType_Array . . . 100
DataType_Categorical . . . 100
DataType_contains_categoricals . . . 101
DataType_contains_views . . . 102
DataType_Datetime . . . 102
DataType_Duration . . . 103
DataType_Enum . . . 104
DataType_is_array . . . 105
DataType_is_binary . . . 105
DataType_is_bool . . . 106
DataType_is_categorical . . . 106
DataType_is_enum . . . 107
DataType_is_float . . . 107
DataType_is_integer . . . 108
DataType_is_known . . . 108
DataType_is_list . . . 109
DataType_is_logical . . . 109
DataType_is_nested . . . 110
DataType_is_null . . . 110
DataType_is_numeric . . . 111
DataType_is_ord . . . 111
DataType_is_primitive . . . 112
DataType_is_signed_integer . . . 112
DataType_is_string . . . 113
DataType_is_struct . . . 113
DataType_is_temporal . . . 114
DataType_is_unsigned_integer . . . 114
DataType_List . . . 115

DataType_Struct . . . 115
dim.RPolarsDataFrame . . . 116
dimnames.RPolarsDataFrame . . . 117
docs_translations . . . 117
DynamicGroupBy_agg . . . 119
DynamicGroupBy_class . . . 121
DynamicGroupBy_ungroup . . . 121
Expr_abs . . . 122
Expr_add . . . 122
Expr_agg_groups . . . 123
Expr_alias . . . 124
Expr_all . . . 124
Expr_and . . . 125
Expr_any . . . 126
Expr_append . . . 126
Expr_approx_n_unique . . . 127
Expr_arccos . . . 128
Expr_arccosh . . . 128
Expr_arcsin . . . 129
Expr_arcsinh . . . 129
Expr_arctan . . . 130
Expr_arctanh . . . 130
Expr_arg_max . . . 131
Expr_arg_min . . . 131
Expr_arg_sort . . . 132
Expr_arg_unique . . . 132
Expr_backward_fill . . . 133
Expr_bottom_k . . . 133
Expr_cast . . . 134
Expr_ceil . . . 135
Expr_class . . . 135
Expr_clip . . . 136
Expr_cos . . . 137
Expr_cosh . . . 137
Expr_count . . . 138
Expr_cum_count . . . 138
Expr_cum_max . . . 139
Expr_cum_min . . . 140
Expr_cum_prod . . . 140
Expr_cum_sum . . . 141
Expr_cumulative_eval . . . 142
Expr_cut . . . 142
Expr_diff . . . 144
Expr_div . . . 144
Expr_dot . . . 145
Expr_drop_nans . . . 146
Expr_drop_nulls . . . 146
Expr_entropy . . . 147

Expr_eq . . . 147
Expr_eq_missing . . . 148
Expr_ewm_mean . . . 149
Expr_ewm_std . . . 150
Expr_ewm_var . . . 151
Expr_exclude . . . 152
Expr_exp . . . 153
Expr_explode . . . 154
Expr_extend_constant . . . 154
Expr_fill_nan . . . 155
Expr_fill_null . . . 155
Expr_filter . . . 156
Expr_first . . . 157
Expr_flatten . . . 157
Expr_floor . . . 158
Expr_floor_div . . . 158
Expr_forward_fill . . . 159
Expr_gather . . . 160
Expr_gather_every . . . 160
Expr_gt . . . 161
Expr_gt_eq . . . 161
Expr_has_nulls . . . 162
Expr_hash . . . 162
Expr_head . . . 163
Expr_implode . . . 163
Expr_inspect . . . 164
Expr_interpolate . . . 164
Expr_is_between . . . 165
Expr_is_duplicated . . . 166
Expr_is_finite . . . 167
Expr_is_first_distinct . . . 167
Expr_is_in . . . 168
Expr_is_infinite . . . 168
Expr_is_last_distinct . . . 169
Expr_is_nan . . . 169
Expr_is_not_nan . . . 170
Expr_is_not_null . . . 170
Expr_is_null . . . 171
Expr_is_unique . . . 171
Expr_kurtosis . . . 172
Expr_last . . . 172
Expr_limit . . . 173
Expr_log . . . 173
Expr_log10 . . . 174
Expr_lower_bound . . . 174
Expr_lt . . . 175
Expr_lt_eq . . . 175
Expr_map_batches . . . 176

Expr_map_elements . . . 178
Expr_max . . . 181
Expr_mean . . . 182
Expr_median . . . 182
Expr_min . . . 183
Expr_mod . . . 183
Expr_mode . . . 184
Expr_mul . . . 184
Expr_n_unique . . . 185
Expr_nan_max . . . 185
Expr_nan_min . . . 186
Expr_neq . . . 186
Expr_neq_missing . . . 187
Expr_not . . . 188
Expr_null_count . . . 188
Expr_or . . . 189
Expr_over . . . 189
Expr_pct_change . . . 191
Expr_peak_max . . . 192
Expr_peak_min . . . 192
Expr_pow . . . 193
Expr_product . . . 194
Expr_qcut . . . 194
Expr_quantile . . . 195
Expr_rank . . . 196
Expr_rechunk . . . 197
Expr_reinterpret . . . 198
Expr_rep . . . 198
Expr_repeat_by . . . 199
Expr_replace . . . 199
Expr_replace_strict . . . 200
Expr_reshape . . . 202
Expr_reverse . . . 203
Expr_rle . . . 203
Expr_rle_id . . . 204
Expr_rolling . . . 204
Expr_rolling_max . . . 206
Expr_rolling_max_by . . . 207
Expr_rolling_mean . . . 208
Expr_rolling_mean_by . . . 209
Expr_rolling_median . . . 210
Expr_rolling_median_by . . . 211
Expr_rolling_min . . . 213
Expr_rolling_min_by . . . 214
Expr_rolling_quantile . . . 215
Expr_rolling_quantile_by . . . 216
Expr_rolling_skew . . . 217
Expr_rolling_std . . . 218

Expr_rolling_std_by . . . 219
Expr_rolling_sum . . . 221
Expr_rolling_sum_by . . . 222
Expr_rolling_var . . . 223
Expr_rolling_var_by . . . 224
Expr_round . . . 225
Expr_sample . . . 226
Expr_search_sorted . . . 227
Expr_set_sorted . . . 228
Expr_shift . . . 228
Expr_shrink_dtype . . . 229
Expr_shuffle . . . 230
Expr_sign . . . 230
Expr_sin . . . 231
Expr_sinh . . . 231
Expr_skew . . . 232
Expr_slice . . . 232
Expr_sort . . . 233
Expr_sort_by . . . 234
Expr_sqrt . . . 235
Expr_std . . . 235
Expr_sub . . . 236
Expr_sum . . . 237
Expr_tail . . . 237
Expr_tan . . . 238
Expr_tanh . . . 238
Expr_to_physical . . . 239
Expr_to_r . . . 239
Expr_to_series . . . 240
Expr_top_k . . . 241
Expr_unique . . . 241
Expr_unique_counts . . . 242
Expr_upper_bound . . . 242
Expr_value_counts . . . 243
Expr_var . . . 243
Expr_when_then_otherwise . . . 244
Expr_xor . . . 246
ExprArr_all . . . 246
ExprArr_any . . . 247
ExprArr_arg_max . . . 247
ExprArr_arg_min . . . 248
ExprArr_contains . . . 248
ExprArr_get . . . 249
ExprArr_join . . . 250
ExprArr_max . . . 250
ExprArr_median . . . 251
ExprArr_min . . . 252
ExprArr_reverse . . . 252

ExprArr_shift . . . 253
ExprArr_sort . . . 253
ExprArr_std . . . 254
ExprArr_sum . . . 254
ExprArr_to_list . . . 255
ExprArr_to_struct . . . 256
ExprArr_unique . . . 257
ExprArr_var . . . 257
ExprBin_contains . . . 258
ExprBin_decode . . . 259
ExprBin_encode . . . 260
ExprBin_ends_with . . . 260
ExprBin_size . . . 261
ExprBin_starts_with . . . 262
ExprCat_get_categories . . . 262
ExprCat_set_ordering . . . 263
ExprDT_cast_time_unit . . . 264
ExprDT_combine . . . 265
ExprDT_convert_time_zone . . . 266
ExprDT_day . . . 266
ExprDT_epoch . . . 267
ExprDT_hour . . . 268
ExprDT_is_leap_year . . . 268
ExprDT_iso_year . . . 269
ExprDT_microsecond . . . 270
ExprDT_millisecond . . . 270
ExprDT_minute . . . 271
ExprDT_month . . . 272
ExprDT_nanosecond . . . 272
ExprDT_offset_by . . . 273
ExprDT_ordinal_day . . . 274
ExprDT_quarter . . . 275
ExprDT_replace_time_zone . . . 276
ExprDT_round . . . 277
ExprDT_second . . . 278
ExprDT_strftime . . . 279
ExprDT_time . . . 280
ExprDT_timestamp . . . 280
ExprDT_total_days . . . 281
ExprDT_total_hours . . . 282
ExprDT_total_microseconds . . . 282
ExprDT_total_milliseconds . . . 283
ExprDT_total_minutes . . . 284
ExprDT_total_nanoseconds . . . 284
ExprDT_total_seconds . . . 285
ExprDT_truncate . . . 286
ExprDT_week . . . 287
ExprDT_weekday . . . 287

ExprDT_with_time_unit . . . 288
ExprDT_year . . . 289
ExprList_all . . . 289
ExprList_any . . . 290
ExprList_arg_max . . . 290
ExprList_arg_min . . . 291
ExprList_concat . . . 291
ExprList_contains . . . 292
ExprList_diff . . . 293
ExprList_eval . . . 293
ExprList_explode . . . 294
ExprList_first . . . 295
ExprList_gather . . . 295
ExprList_gather_every . . . 296
ExprList_get . . . 297
ExprList_head . . . 298
ExprList_join . . . 298
ExprList_last . . . 299
ExprList_len . . . 300
ExprList_max . . . 300
ExprList_mean . . . 301
ExprList_min . . . 301
ExprList_n_unique . . . 302
ExprList_reverse . . . 302
ExprList_sample . . . 303
ExprList_set_difference . . . 304
ExprList_set_intersection . . . 304
ExprList_set_symmetric_difference . . . 305
ExprList_set_union . . . 306
ExprList_shift . . . 307
ExprList_slice . . . 307
ExprList_sort . . . 308
ExprList_sum . . . 309
ExprList_tail . . . 309
ExprList_to_struct . . . 310
ExprList_unique . . . 311
ExprMeta_eq . . . 312
ExprMeta_has_multiple_outputs . . . 312
ExprMeta_is_regex_projection . . . 313
ExprMeta_neq . . . 313
ExprMeta_output_name . . . 314
ExprMeta_pop . . . 315
ExprMeta_root_names . . . 316
ExprMeta_tree_format . . . 316
ExprMeta_undo_aliases . . . 317
ExprName_keep . . . 317
ExprName_prefix . . . 318
ExprName_prefix_fields . . . 318

ExprName_suffix . . . 319
ExprName_suffix_fields . . . 320
ExprName_to_lowercase . . . 320
ExprName_to_uppercase . . . 321
ExprStr_contains . . . 321
ExprStr_contains_any . . . 322
ExprStr_count_matches . . . 323
ExprStr_decode . . . 324
ExprStr_encode . . . 324
ExprStr_ends_with . . . 325
ExprStr_extract . . . 326
ExprStr_extract_all . . . 326
ExprStr_extract_groups . . . 327
ExprStr_extract_many . . . 328
ExprStr_find . . . 329
ExprStr_head . . . 330
ExprStr_join . . . 331
ExprStr_json_decode . . . 332
ExprStr_json_path_match . . . 332
ExprStr_len_bytes . . . 333
ExprStr_len_chars . . . 334
ExprStr_pad_end . . . 335
ExprStr_pad_start . . . 335
ExprStr_replace . . . 336
ExprStr_replace_all . . . 337
ExprStr_replace_many . . . 339
ExprStr_reverse . . . 340
ExprStr_slice . . . 340
ExprStr_split . . . 341
ExprStr_split_exact . . . 341
ExprStr_splitn . . . 342
ExprStr_starts_with . . . 343
ExprStr_strip_chars . . . 343
ExprStr_strip_chars_end . . . 344
ExprStr_strip_chars_start . . . 345
ExprStr_strptime . . . 345
ExprStr_tail . . . 348
ExprStr_to_date . . . 349
ExprStr_to_datetime . . . 350
ExprStr_to_integer . . . 351
ExprStr_to_lowercase . . . 352
ExprStr_to_time . . . 352
ExprStr_to_titlecase . . . 353
ExprStr_to_uppercase . . . 353
ExprStr_zfill . . . 354
ExprStruct_field . . . 355
ExprStruct_rename_fields . . . 355
ExprStruct_with_fields . . . 356

global_rpool_cap . . . 357
GroupBy_agg . . . 358
GroupBy_class . . . 359
GroupBy_first . . . 359
GroupBy_last . . . 360
GroupBy_max . . . 360
GroupBy_mean . . . 361
GroupBy_median . . . 362
GroupBy_min . . . 362
GroupBy_null_count . . . 363
GroupBy_quantile . . . 363
GroupBy_shift . . . 364
GroupBy_std . . . 364
GroupBy_sum . . . 365
GroupBy_ungroup . . . 365
GroupBy_var . . . 366
head.RPolarsDataFrame . . . 366
infer_nanoarrow_schema.RPolarsDataFrame . . . 368
is_polars_df . . . 369
is_polars_dtype . . . 369
is_polars_lf . . . 370
is_polars_series . . . 370
knit_print.RPolarsDataFrame . . . 371
LazyFrame_cast . . . 372
LazyFrame_class . . . 373
LazyFrame_clear . . . 375
LazyFrame_clone . . . 376
LazyFrame_collect . . . 377
LazyFrame_collect_in_background . . . 379
LazyFrame_drop . . . 380
LazyFrame_drop_nulls . . . 380
LazyFrame_explain . . . 381
LazyFrame_explode . . . 382
LazyFrame_fetch . . . 383
LazyFrame_fill_nan . . . 385
LazyFrame_fill_null . . . 386
LazyFrame_filter . . . 386
LazyFrame_first . . . 387
LazyFrame_gather_every . . . 387
LazyFrame_group_by . . . 388
LazyFrame_group_by_dynamic . . . 389
LazyFrame_head . . . 392
LazyFrame_join . . . 393
LazyFrame_join_asof . . . 395
LazyFrame_join_where . . . 398
LazyFrame_last . . . 399
LazyFrame_max . . . 399
LazyFrame_mean . . . 400

LazyFrame_median . . . 400
LazyFrame_min . . . 401
LazyFrame_print . . . 401
LazyFrame_profile . . . 402
LazyFrame_quantile . . . 404
LazyFrame_rename . . . 404
LazyFrame_reverse . . . 405
LazyFrame_rolling . . . 406
LazyFrame_select . . . 408
LazyFrame_select_seq . . . 409
LazyFrame_serialize . . . 409
LazyFrame_shift . . . 410
LazyFrame_sink_csv . . . 411
LazyFrame_sink_ipc . . . 413
LazyFrame_sink_ndjson . . . 414
LazyFrame_sink_parquet . . . 416
LazyFrame_slice . . . 418
LazyFrame_sort . . . 418
LazyFrame_sql . . . 419
LazyFrame_std . . . 421
LazyFrame_sum . . . 421
LazyFrame_tail . . . 422
LazyFrame_to_dot . . . 422
LazyFrame_unique . . . 424
LazyFrame_unnest . . . 425
LazyFrame_unpivot . . . 426
LazyFrame_var . . . 427
LazyFrame_with_columns . . . 427
LazyFrame_with_columns_seq . . . 428
LazyFrame_with_context . . . 429
LazyFrame_with_row_index . . . 430
LazyGroupBy_agg . . . 431
LazyGroupBy_class . . . 431
LazyGroupBy_head . . . 432
LazyGroupBy_print . . . 432
LazyGroupBy_tail . . . 433
LazyGroupBy_ungroup . . . 433
length.RPolarsDataFrame . . . 434
max.RPolarsDataFrame . . . 434
mean.RPolarsDataFrame . . . 435
median.RPolarsDataFrame . . . 435
min.RPolarsDataFrame . . . 436
na.omit.RPolarsLazyFrame . . . 436
names.RPolarsDataFrame . . . 437
pl_all . . . 437
pl_all_horizontal . . . 438
pl_any_horizontal . . . 439
pl_approx_n_unique . . . 439

pl_arg_sort_by . . . 440
pl_arg_where . . . 441
pl_coalesce . . . 442
pl_col . . . 443
pl_concat . . . 444
pl_concat_list . . . 445
pl_concat_str . . . 446
pl_corr . . . 447
pl_count . . . 448
pl_cov . . . 449
pl_DataFrame . . . 449
pl_date . . . 450
pl_date_range . . . 451
pl_date_ranges . . . 453
pl_datetime . . . 454
pl_datetime_range . . . 456
pl_datetime_ranges . . . 458
pl_deserialize_lf . . . 460
pl_disable_string_cache . . . 461
pl_dtypes . . . 461
pl_duration . . . 462
pl_element . . . 463
pl_enable_string_cache . . . 464
pl_field . . . 465
pl_Field_class . . . 465
pl_first . . . 466
pl_fold . . . 467
pl_from_epoch . . . 468
pl_head . . . 469
pl_implode . . . 470
pl_int_range . . . 470
pl_int_ranges . . . 471
pl_is_schema . . . 472
pl_last . . . 473
pl_LazyFrame . . . 474
pl_len . . . 475
pl_lit . . . 475
pl_max . . . 476
pl_max_horizontal . . . 477
pl_mean . . . 478
pl_mean_horizontal . . . 478
pl_median . . . 479
pl_mem_address . . . 480
pl_min . . . 481
pl_min_horizontal . . . 482
pl_n_unique . . . 482
pl_pl . . . 483
pl_PTime . . . 484

pl_raw_list . . . 485
pl_read_csv . . . 486
pl_read_ipc . . . 489
pl_read_ndjson . . . 490
pl_read_parquet . . . 491
pl_reduce . . . 494
pl_rolling_corr . . . 495
pl_rolling_cov . . . 496
pl_scan_csv . . . 496
pl_scan_ipc . . . 499
pl_scan_ndjson . . . 501
pl_scan_parquet . . . 502
pl_select . . . 505
pl_Series . . . 505
pl_SQLContext . . . 507
pl_std . . . 507
pl_struct . . . 508
pl_sum . . . 509
pl_sum_horizontal . . . 510
pl_tail . . . 511
pl_thread_pool_size . . . 512
pl_time . . . 512
pl_using_string_cache . . . 513
pl_var . . . 514
pl_with_string_cache . . . 515
polars_class_object . . . 516
polars_code_completion_activate . . . 516
polars_duration_string . . . 517
polars_envvars . . . 518
polars_info . . . 520
polars_options . . . 521
print.RPolarsSeries . . . 522
RollingGroupBy_agg . . . 523
RollingGroupBy_class . . . 524
RollingGroupBy_ungroup . . . 524
row.names.RPolarsDataFrame . . . 525
RThreadHandle_class . . . 525
RThreadHandle_is_finished . . . 526
RThreadHandle_join . . . 526
S3_arithmetic . . . 527
Series_add . . . 529
Series_alias . . . 530
Series_all . . . 530
Series_any . . . 531
Series_append . . . 531
Series_arg_max . . . 532
Series_arg_min . . . 533
Series_chunk_lengths . . . 533

Series_class . . . 534
Series_clear . . . 537
Series_clone . . . 537
Series_div . . . 538
Series_equals . . . 539
Series_floor_div . . . 540
Series_is_numeric . . . 540
Series_is_sorted . . . 541
Series_item . . . 541
Series_len . . . 542
Series_map_elements . . . 542
Series_max . . . 543
Series_mean . . . 544
Series_median . . . 544
Series_min . . . 545
Series_mod . . . 545
Series_mul . . . 546
Series_n_chunks . . . 547
Series_n_unique . . . 547
Series_pow . . . 548
Series_print . . . 548
Series_rename . . . 549
Series_rep . . . 549
Series_set_sorted . . . 550
Series_sort . . . 551
Series_std . . . 552
Series_sub . . . 552
Series_sum . . . 553
Series_to_frame . . . 553
Series_to_lit . . . 554
Series_to_r . . . 554
Series_value_counts . . . 556
Series_var . . . 557
show_all_public_functions . . . 557
show_all_public_methods . . . 558
SQLContext_class . . . 558
SQLContext_execute . . . 559
SQLContext_register . . . 559
SQLContext_register_globals . . . 560
SQLContext_register_many . . . 561
SQLContext_tables . . . 562
SQLContext_unregister . . . 562
sum.RPolarsDataFrame . . . 563
unique.RPolarsDataFrame . . . 564

Index **565**

[.RPolarsDataFrame *Extract Parts of a Polars Object*

Description

Mimics the behavior of [x[i, j, drop = TRUE]][Extract] for data.frame or R vector.

Usage

```
## S3 method for class 'RPolarsDataFrame'
x[i, j, drop = TRUE]

## S3 method for class 'RPolarsLazyFrame'
x[i, j, drop = TRUE]

## S3 method for class 'RPolarsSeries'
x[i]
```

Arguments

x	A DataFrame, LazyFrame, or Series
i	Rows to select. Integer vector, logical vector, or an Expression.
j	Columns to select. Integer vector, logical vector, character vector, or an Expression. For LazyFrames, only an Expression can be used.
drop	Convert to a Polars Series if only one column is selected. For LazyFrames, if the result has one column and drop = TRUE, an error will occur.

Details

<Series>[i] is equivalent to pl$select(<Series>)[i, , drop = TRUE].

See Also

<DataFrame>$select(), <LazyFrame>$select(), <DataFrame>$filter(), <LazyFrame>$filter()

Examples

```
df = as_polars_df(data.frame(a = 1:3, b = letters[1:3]))
lf = df$lazy()

# Select a row
df[1, ]

# If only `i` is specified, it is treated as `j`
# Select a column
df[1]

# Select a column by name (and convert to a Series)
```

```
df[, "b"]

# Can use Expression for filtering and column selection
lf[pl$col("a") >= 2, pl$col("b")$alias("new"), drop = FALSE] |>
  as.data.frame()
```

---

as.character.RPolarsSeries

Convert to a character vector

Description

Convert to a character vector

Usage

```
## S3 method for class 'RPolarsSeries'
as.character(x, ..., str_length = NULL)
```

Arguments

x	A Polars Series
...	Not used.
str_length	An integer. If specified, utf8 or categorical type Series will be formatted to a string of this length.

Examples

```
s = as_polars_series(c("foo", "barbaz"))
as.character(s)
as.character(s, str_length = 3)
```

---

as.data.frame.RPolarsDataFrame

Convert to a data.frame

Description

Equivalent to `as_polars_df(x, ...)$to_data_frame(...)`.

Usage

```
## S3 method for class 'RPolarsDataFrame'
as.data.frame(x, ..., int64_conversion = polars_options()$int64_conversion)

## S3 method for class 'RPolarsLazyFrame'
as.data.frame(
  x,
  ...,
  n_rows = Inf,
  type_coercion = TRUE,
  predicate_pushdown = TRUE,
  projection_pushdown = TRUE,
  simplify_expression = TRUE,
  slice_pushdown = TRUE,
  comm_subplan_elim = TRUE,
  comm_subexpr_elim = TRUE,
  cluster_with_columns = TRUE,
  streaming = FALSE,
  no_optimization = FALSE,
  collect_in_background = FALSE
)
```

Arguments

`x` An object to convert to a data.frame.

`...` Additional arguments passed to methods.

`int64_conversion`
How should Int64 values be handled when converting a polars object to R?

- `"double"` (default) converts the integer values to double.
- `"bit64"` uses `bit64::as.integer64()` to do the conversion (requires the package `bit64` to be attached).
- `"string"` converts Int64 values to character.

`n_rows` Number of rows to fetch. Defaults to `Inf`, meaning all rows.

`type_coercion` Logical. Coerce types such that operations succeed and run on minimal required memory.

`predicate_pushdown`
Logical. Applies filters as early as possible at scan level.

`projection_pushdown`
Logical. Select only the columns that are needed at the scan level.

`simplify_expression`
Logical. Various optimizations, such as constant folding and replacing expensive operations with faster alternatives.

`slice_pushdown` Logical. Only load the required slice from the scan level. Don't materialize sliced outputs (e.g. `join$head(10)`).

`comm_subplan_elim`
Logical. Will try to cache branching subplans that occur on self-joins or unions.

comm_subexpr_elim
: Logical. Common subexpressions will be cached and reused.

cluster_with_columns
: Combine sequential independent calls to `with_columns()`.

streaming
: Logical. Run parts of the query in a streaming fashion (this is in an alpha state).

no_optimization
: Logical. Sets the following parameters to `FALSE`: `predicate_pushdown`, `projection_pushdown`, `slice_pushdown`, `comm_subplan_elim`, `comm_subexpr_elim`, `cluster_with_columns`.

collect_in_background
: Logical. Detach this query from R session. Computation will start in background. Get a handle which later can be converted into the resulting DataFrame. Useful in interactive mode to not lock R session.

Conversion to R data types considerations

When converting Polars objects, such as DataFrames to R objects, for example via the `as.data.frame()` generic function, each type in the Polars object is converted to an R type. In some cases, an error may occur because the conversion is not appropriate. In particular, there is a high possibility of an error when converting a Datetime type without a time zone. A Datetime type without a time zone in Polars is converted to the POSIXct type in R, which takes into account the time zone in which the R session is running (which can be checked with the `Sys.timezone()` function). In this case, if ambiguous times are included, a conversion error will occur. In such cases, change the session time zone using `Sys.setenv(TZ = "UTC")` and then perform the conversion, or use the `$dt$replace_time_zone()` method on the Datetime type column to explicitly specify the time zone before conversion.

```
# Due to daylight savings, clocks were turned forward 1 hour on Sunday, March 8, 2020, 2:00:00 am
# so this particular date-time doesn't exist
non_existent_time = as_polars_series("2020-03-08 02:00:00")$str$strptime(pl$Datetime(), "%F %T")

withr::with_timezone(
  "America/New_York",
  {
    tryCatch(
      # This causes an error due to the time zone (the `TZ` env var is affected).
      as.vector(non_existent_time),
      error = function(e) e
    )
  }
)
#> <error: in $to_vector(): in to_r: ComputeError(ErrString("datetime '2020-03-08 02:00:00' is non-exis

withr::with_timezone(
  "America/New_York",
  {
    # This is safe.
    as.vector(non_existent_time$dt$replace_time_zone("UTC"))
  }
```

```
)
#> [1] "2020-03-08 02:00:00 UTC"
```

See Also

- as_polars_df()
- <DataFrame>$to_data_frame()

---

as.matrix.RPolarsDataFrame

Convert to a matrix

Description

Equivalent to `as.data.frame(x, ...) |> as.matrix()`.

Usage

```
## S3 method for class 'RPolarsDataFrame'
as.matrix(x, ...)

## S3 method for class 'RPolarsLazyFrame'
as.matrix(x, ...)
```

Arguments

x	An object to convert to a matrix.
...	Additional arguments passed to methods.

---

as.vector.RPolarsSeries

Convert to a vector

Description

Convert to a vector

Usage

```
## S3 method for class 'RPolarsSeries'
as.vector(x, mode)
```

Arguments

x	A Polars Series
mode	Not used.

Conversion to R data types considerations

When converting Polars objects, such as DataFrames to R objects, for example via the `as.data.frame()` generic function, each type in the Polars object is converted to an R type. In some cases, an error may occur because the conversion is not appropriate. In particular, there is a high possibility of an error when converting a Datetime type without a time zone. A Datetime type without a time zone in Polars is converted to the POSIXct type in R, which takes into account the time zone in which the R session is running (which can be checked with the `Sys.timezone()` function). In this case, if ambiguous times are included, a conversion error will occur. In such cases, change the session time zone using `Sys.setenv(TZ = "UTC")` and then perform the conversion, or use the `$dt$replace_time_zone()` method on the Datetime type column to explicitly specify the time zone before conversion.

```
# Due to daylight savings, clocks were turned forward 1 hour on Sunday, March 8, 2020, 2:00:00 am
# so this particular date-time doesn't exist
non_existent_time = as_polars_series("2020-03-08 02:00:00")$str$strptime(pl$Datetime(), "%F %T")

withr::with_timezone(
  "America/New_York",
  {
    tryCatch(
     # This causes an error due to the time zone (the `TZ` env var is affected).
      as.vector(non_existent_time),
      error = function(e) e
    )
  }
)
#> <error: in $to_vector(): in to_r: ComputeError(ErrString("datetime '2020-03-08 02:00:00' is non-exis

withr::with_timezone(
  "America/New_York",
  {
    # This is safe.
    as.vector(non_existent_time$dt$replace_time_zone("UTC"))
  }
)
#> [1] "2020-03-08 02:00:00 UTC"
```

---

as_arrow_table.RPolarsDataFrame

Create a arrow Table from a Polars object

Description

Create a arrow Table from a Polars object

Usage

```
## S3 method for class 'RPolarsDataFrame'
as_arrow_table(x, ..., compat_level = FALSE)
```

Arguments

x	A Polars DataFrame
...	Ignored
compat_level	Use a specific compatibility level when exporting Polars' internal data structures. This can be: • an integer indicating the compatibility version (currently only 0 for oldest and 1 for newest); • a logical value with TRUE for the newest version and FALSE for the oldest version.

Examples

```
library(arrow)

pl_df = as_polars_df(mtcars)
as_arrow_table(pl_df)
```

---

as_nanoarrow_array_stream.RPolarsDataFrame

Create a nanoarrow_array_stream from a Polars object

Description

Create a nanoarrow_array_stream from a Polars object

Usage

```
## S3 method for class 'RPolarsDataFrame'
as_nanoarrow_array_stream(x, ..., schema = NULL, compat_level = FALSE)

## S3 method for class 'RPolarsSeries'
as_nanoarrow_array_stream(x, ..., schema = NULL, compat_level = FALSE)
```

Arguments

x	A polars object
...	Ignored
schema	must stay at default value NULL
compat_level	Use a specific compatibility level when exporting Polars' internal data structures. This can be:

- an integer indicating the compatibility version (currently only 0 for oldest and 1 for newest);
- a logical value with TRUE for the newest version and FALSE for the oldest version.

Examples

```
library(nanoarrow)

pl_df = as_polars_df(mtcars)$head(5)
pl_s = as_polars_series(letters[1:5])

as.data.frame(as_nanoarrow_array_stream(pl_df))
as.vector(as_nanoarrow_array_stream(pl_s))
```

---

as_polars_df *To polars DataFrame*

Description

as_polars_df() is a generic function that converts an R object to a polars DataFrame.

Usage

```
as_polars_df(x, ...)

## Default S3 method:
as_polars_df(x, ...)

## S3 method for class 'data.frame'
as_polars_df(
  x,
  ...,
  rownames = NULL,
  make_names_unique = TRUE,
  schema = NULL,
  schema_overrides = NULL
)

## S3 method for class 'RPolarsDataFrame'
as_polars_df(x, ...)

## S3 method for class 'RPolarsGroupBy'
as_polars_df(x, ...)

## S3 method for class 'RPolarsRollingGroupBy'
as_polars_df(x, ...)
```

```
## S3 method for class 'RPolarsDynamicGroupBy'
as_polars_df(x, ...)

## S3 method for class 'RPolarsSeries'
as_polars_df(x, ...)

## S3 method for class 'RPolarsLazyFrame'
as_polars_df(
  x,
  n_rows = Inf,
  ...,
  type_coercion = TRUE,
  predicate_pushdown = TRUE,
  projection_pushdown = TRUE,
  simplify_expression = TRUE,
  slice_pushdown = TRUE,
  comm_subplan_elim = TRUE,
  comm_subexpr_elim = TRUE,
  cluster_with_columns = TRUE,
  streaming = FALSE,
  no_optimization = FALSE,
  collect_in_background = FALSE
)

## S3 method for class 'RPolarsLazyGroupBy'
as_polars_df(x, ...)

## S3 method for class 'ArrowTabular'
as_polars_df(
  x,
  ...,
  rechunk = TRUE,
  schema = NULL,
  schema_overrides = NULL,
  experimental = FALSE
)

## S3 method for class 'RecordBatchReader'
as_polars_df(x, ..., experimental = FALSE)

## S3 method for class 'nanoarrow_array'
as_polars_df(x, ...)

## S3 method for class 'nanoarrow_array_stream'
as_polars_df(x, ..., experimental = FALSE)
```

Arguments

`x` Object to convert to a polars DataFrame.

`...` Additional arguments passed to methods.

`rownames` How to treat existing row names of a data frame:

- `NULL`: Remove row names. This is the default.
- A string: The name of a new column, which will contain the row names. If `x` already has a column with that name, an error is thrown.

`make_names_unique` A logical flag to replace duplicated column names with unique names. If `FALSE` and there are duplicated column names, an error is thrown.

`schema` named list of DataTypes, or character vector of column names. Should match the number of columns in `x` and correspond to each column in `x` by position. If a column in `x` does not match the name or type at the same position, it will be renamed/recast. If `NULL` (default), convert columns as is.

`schema_overrides` named list of DataTypes. Cast some columns to the DataType.

`n_rows` Number of rows to fetch. Defaults to `Inf`, meaning all rows.

`type_coercion` Logical. Coerce types such that operations succeed and run on minimal required memory.

`predicate_pushdown` Logical. Applies filters as early as possible at scan level.

`projection_pushdown` Logical. Select only the columns that are needed at the scan level.

`simplify_expression` Logical. Various optimizations, such as constant folding and replacing expensive operations with faster alternatives.

`slice_pushdown` Logical. Only load the required slice from the scan level. Don't materialize sliced outputs (e.g. `join$head(10)`).

`comm_subplan_elim` Logical. Will try to cache branching subplans that occur on self-joins or unions.

`comm_subexpr_elim` Logical. Common subexpressions will be cached and reused.

`cluster_with_columns` Combine sequential independent calls to `with_columns()`.

`streaming` Logical. Run parts of the query in a streaming fashion (this is in an alpha state).

`no_optimization` Logical. Sets the following parameters to `FALSE`: `predicate_pushdown`, `projection_pushdown`, `slice_pushdown`, `comm_subplan_elim`, `comm_subexpr_elim`, `cluster_with_columns`.

`collect_in_background` Logical. Detach this query from R session. Computation will start in background. Get a handle which later can be converted into the resulting DataFrame. Useful in interactive mode to not lock R session.

`rechunk` A logical flag (default `TRUE`). Make sure that all data of each column is in contiguous memory.

experimental — If TRUE, use experimental Arrow C stream interface inside the function. This argument is experimental and may be removed in the future.

Details

For LazyFrame objects, this function is a shortcut for $collect() or $fetch(), depending on whether the number of rows to fetch is infinite or not.

Value

a DataFrame

Examples

```
# Convert the row names of a data frame to a column
as_polars_df(mtcars, rownames = "car")

# Convert a data frame, with renaming all columns
as_polars_df(
  data.frame(x = 1, y = 2),
  schema = c("a", "b")
)

# Convert a data frame, with renaming and casting all columns
as_polars_df(
  data.frame(x = 1, y = 2),
  schema = list(b = pl$Int64, a = pl$String)
)

# Convert a data frame, with casting some columns
as_polars_df(
  data.frame(x = 1, y = 2),
  schema_overrides = list(y = pl$String) # cast some columns
)

# Convert an arrow Table to a polars DataFrame
at = arrow::arrow_table(x = 1:5, y = 6:10)
as_polars_df(at)

# Create a polars DataFrame from a data.frame
lf = as_polars_df(mtcars)$lazy()

# Collect all rows from the LazyFrame
as_polars_df(lf)

# Fetch 5 rows from the LazyFrame
as_polars_df(lf, 5)
```

as_polars_lf *To polars LazyFrame*

Description

`as_polars_lf()` is a generic function that converts an R object to a polars LazyFrame. It is basically a shortcut for as_polars_df(x, ...) with the $lazy() method.

Usage

```
as_polars_lf(x, ...)

## Default S3 method:
as_polars_lf(x, ...)

## S3 method for class 'RPolarsLazyFrame'
as_polars_lf(x, ...)

## S3 method for class 'RPolarsLazyGroupBy'
as_polars_lf(x, ...)
```

Arguments

`x`	Object to convert to a polars DataFrame.
`...`	Additional arguments passed to methods.

Value

a LazyFrame

Examples

```
as_polars_lf(mtcars)
```

as_polars_series *To polars Series*

Description

`as_polars_series()` is a generic function that converts an R object to a polars Series.

Usage

```
as_polars_series(x, name = NULL, ...)

## Default S3 method:
as_polars_series(x, name = NULL, ...)

## S3 method for class 'RPolarsSeries'
as_polars_series(x, name = NULL, ...)

## S3 method for class 'RPolarsExpr'
as_polars_series(x, name = NULL, ...)

## S3 method for class 'RPolarsThen'
as_polars_series(x, name = NULL, ...)

## S3 method for class 'RPolarsChainedThen'
as_polars_series(x, name = NULL, ...)

## S3 method for class 'POSIXlt'
as_polars_series(x, name = NULL, ...)

## S3 method for class 'data.frame'
as_polars_series(x, name = NULL, ...)

## S3 method for class 'vctrs_rcrd'
as_polars_series(x, name = NULL, ...)

## S3 method for class 'Array'
as_polars_series(x, name = NULL, ..., rechunk = TRUE)

## S3 method for class 'ChunkedArray'
as_polars_series(x, name = NULL, ..., rechunk = TRUE)

## S3 method for class 'RecordBatchReader'
as_polars_series(x, name = NULL, ...)

## S3 method for class 'nanoarrow_array'
as_polars_series(x, name = NULL, ...)

## S3 method for class 'nanoarrow_array_stream'
as_polars_series(x, name = NULL, ..., experimental = FALSE)

## S3 method for class 'clock_time_point'
as_polars_series(x, name = NULL, ...)

## S3 method for class 'clock_sys_time'
as_polars_series(x, name = NULL, ...)
```

```
## S3 method for class 'clock_zoned_time'
as_polars_series(x, name = NULL, ...)

## S3 method for class 'list'
as_polars_series(x, name = NULL, ...)
```

Arguments

x	Object to convert into a polars Series.
name	A character to use as the name of the Series. If NULL (default), the name of x is used or an empty character "" will be used if x has no name.
...	Additional arguments passed to methods.
rechunk	A logical flag (default TRUE). Make sure that all data is in contiguous memory.
experimental	If TRUE, use experimental Arrow C stream interface inside the function. This argument is experimental and may be removed in the future.

Value

a Series

Examples

```
as_polars_series(1:4)

as_polars_series(list(1:4))

as_polars_series(data.frame(a = 1:4))

as_polars_series(as_polars_series(1:4, name = "foo"))

as_polars_series(pl$lit(1:4))

# Nested type support
as_polars_series(list(data.frame(a = I(list(1:4)))))
```

---

as_record_batch_reader.RPolarsDataFrame

Create a arrow RecordBatchReader from a Polars object

Description

Create a arrow RecordBatchReader from a Polars object

Usage

```
## S3 method for class 'RPolarsDataFrame'
as_record_batch_reader(x, ..., compat_level = FALSE)
```

Arguments

x	A Polars DataFrame
...	Ignored
compat_level	Use a specific compatibility level when exporting Polars' internal data structures. This can be: • an integer indicating the compatibility version (currently only 0 for oldest and 1 for newest); • a logical value with TRUE for the newest version and FALSE for the oldest version.

Examples

```
library(arrow)

pl_df = as_polars_df(mtcars)
as_record_batch_reader(pl_df)
```

---

c.RPolarsSeries *Combine to a Series*

Description

Combine to a Series

Usage

```
## S3 method for class 'RPolarsSeries'
c(x, ...)
```

Arguments

x	A Polars Series
...	Series(s) or any object that can be converted to a Series.

Details

All objects must have the same datatype. Combining does not rechunk. Read more about R vectors, Series and chunks in docs_translations:

Value

a combined Series

Examples

```
s = c(as_polars_series(1:5), 3:1, NA_integer_)
s$chunk_lengths() # the series contain three unmerged chunks
```

DataFrame_cast — *Cast DataFrame column(s) to the specified dtype*

Description

This allows to convert all columns to a datatype or to convert only specific columns. Contrarily to the Python implementation, it is not possible to convert all columns of a specific datatype to another datatype.

Usage

```
DataFrame_cast(dtypes, ..., strict = TRUE)
```

Arguments

`dtypes`	Either a datatype or a list where the names are column names and the values are the datatypes to convert to.
`...`	Ignored.
`strict`	If `TRUE` (default), throw an error if a cast could not be done (for instance, due to an overflow). Otherwise, return `null`.

Value

A DataFrame

Examples

```
df = pl$DataFrame(
  foo = 1:3,
  bar = c(6, 7, 8),
  ham = as.Date(c("2020-01-02", "2020-03-04", "2020-05-06"))
)

# Cast only some columns
df$cast(list(foo = pl$Float32, bar = pl$UInt8))

# Cast all columns to the same type
df$cast(pl$String)
```

DataFrame_class *Inner workings of the DataFrame-class*

Description

The DataFrame-class is simply two environments of respectively the public and private methods/function calls to the polars Rust side. The instantiated DataFrame-object is an externalptr to a low-level Rust polars DataFrame object.

The S3 method .DollarNames.RPolarsDataFrame exposes all public $foobar()-methods which are callable onto the object. Most methods return another DataFrame- class instance or similar which allows for method chaining. This class system could be called "environment classes" (in lack of a better name) and is the same class system extendr provides, except here there are both a public and private set of methods. For implementation reasons, the private methods are external and must be called from .pr$DataFrame$methodname(). Also, all private methods must take any self as an argument, thus they are pure functions. Having the private methods as pure functions solved/simplified self-referential complications.

Details

Check out the source code in R/dataframe_frame.R to see how public methods are derived from private methods. Check out extendr-wrappers.R to see the extendr-auto-generated methods. These are moved to .pr and converted into pure external functions in after-wrappers.R. In zzz.R (named zzz to be last file sourced) the extendr-methods are removed and replaced by any function prefixed DataFrame_.

Active bindings

columns:
$columns returns a character vector with the column names.

dtypes:
$dtypes returns a unnamed list with the data type of each column.

flags:
$flags returns a nested list with column names at the top level and column flags in each sublist.

Flags are used internally to avoid doing unnecessary computations, such as sorting a variable that we know is already sorted. The number of flags varies depending on the column type: columns of type array and list have the flags SORTED_ASC, SORTED_DESC, and FAST_EXPLODE, while other column types only have the former two.

- SORTED_ASC is set to TRUE when we sort a column in increasing order, so that we can use this information later on to avoid re-sorting it.
- SORTED_DESC is similar but applies to sort in decreasing order.

height:
$height returns the number of rows in the DataFrame.

schema:
`$schema` returns a named list with the data type of each column.

shape:
`$shape` returns a numeric vector of length two with the number of rows and the number of columns.

width:
`$width` returns the number of columns in the DataFrame.

Conversion to R data types considerations

When converting Polars objects, such as DataFrames to R objects, for example via the `as.data.frame()` generic function, each type in the Polars object is converted to an R type. In some cases, an error may occur because the conversion is not appropriate. In particular, there is a high possibility of an error when converting a Datetime type without a time zone. A Datetime type without a time zone in Polars is converted to the POSIXct type in R, which takes into account the time zone in which the R session is running (which can be checked with the `Sys.timezone()` function). In this case, if ambiguous times are included, a conversion error will occur. In such cases, change the session time zone using `Sys.setenv(TZ = "UTC")` and then perform the conversion, or use the `$dt$replace_time_zone()` method on the Datetime type column to explicitly specify the time zone before conversion.

```
# Due to daylight savings, clocks were turned forward 1 hour on Sunday, March 8, 2020, 2:00:00 am
# so this particular date-time doesn't exist
non_existent_time = as_polars_series("2020-03-08 02:00:00")$str$strptime(pl$Datetime(), "%F %T")

withr::with_timezone(
  "America/New_York",
  {
    tryCatch(
     # This causes an error due to the time zone (the `TZ` env var is affected).
      as.vector(non_existent_time),
      error = function(e) e
    )
  }
)
#> <error: in $to_vector(): in to_r: ComputeError(ErrString("datetime '2020-03-08 02:00:00' is non-exis

withr::with_timezone(
  "America/New_York",
  {
    # This is safe.
    as.vector(non_existent_time$dt$replace_time_zone("UTC"))
  }
)
#> [1] "2020-03-08 02:00:00 UTC"
```

Examples

```
# see all public exported method names (normally accessed via a class
# instance with $)
ls(.pr$env$RPolarsDataFrame)

# see all private methods (not intended for regular use)
ls(.pr$DataFrame)

# make an object
df = as_polars_df(iris)

# call an active binding
df$shape

# use a private method, which has mutability
result = .pr$DataFrame$set_column_from_robj(df, 150:1, "some_ints")

# Column exists in both dataframes-objects now, as they are just pointers to
# the same object
# There are no public methods with mutability.
df2 = df

df$columns
df2$columns

# Show flags
df$sort("Sepal.Length")$flags

# set_column_from_robj-method is fallible and returned a result which could
# be "ok" or an error.
# No public method or function will ever return a result.
# The `result` is very close to the same as output from functions decorated
# with purrr::safely.
# To use results on the R side, these must be unwrapped first such that
# potentially errors can be thrown. `unwrap(result)` is a way to communicate
# errors happening on the Rust side to the R side. `Extendr` default behavior
# is to use `panic!`(s) which would cause some unnecessarily confusing and
# some very verbose error messages on the inner workings of rust.
# `unwrap(result)` in this case no error, just a NULL because this mutable
# method does not return any ok-value.

# Try unwrapping an error from polars due to unmatching column lengths
err_result = .pr$DataFrame$set_column_from_robj(df, 1:10000, "wrong_length")
tryCatch(unwrap(err_result, call = NULL), error = \(e) cat(as.character(e)))
```

`DataFrame_clear` *Create an empty or n-row null-filled copy of the DataFrame*

Description

Returns a n-row null-filled DataFrame with an identical schema. `n` can be greater than the current number of rows in the DataFrame.

Usage

```
DataFrame_clear(n = 0)
```

Arguments

`n`	Number of (null-filled) rows to return in the cleared frame.

Value

A n-row null-filled DataFrame with an identical schema

Examples

```
df = pl$DataFrame(
  a = c(NA, 2, 3, 4),
  b = c(0.5, NA, 2.5, 13),
  c = c(TRUE, TRUE, FALSE, NA)
)

df$clear()

df$clear(n = 5)
```

`DataFrame_clone` *Clone a DataFrame*

Description

This makes a very cheap deep copy/clone of an existing `DataFrame`. Rarely useful as `DataFrame`s are nearly 100% immutable. Any modification of a `DataFrame` should lead to a clone anyways, but this can be useful when dealing with attributes (see examples).

Usage

```
DataFrame_clone()
```

Value

A DataFrame

Examples

```
df1 = as_polars_df(iris)

# Make a function to take a DataFrame, add an attribute, and return a DataFrame
give_attr = function(data) {
  attr(data, "created_on") = "2024-01-29"
  data
}
df2 = give_attr(df1)

# Problem: the original DataFrame also gets the attribute while it shouldn't!
attributes(df1)

# Use $clone() inside the function to avoid that
give_attr = function(data) {
  data = data$clone()
  attr(data, "created_on") = "2024-01-29"
  data
}
df1 = as_polars_df(iris)
df2 = give_attr(df1)

# now, the original DataFrame doesn't get this attribute
attributes(df1)
```

DataFrame_describe *Summary statistics for a DataFrame*

Description

This returns the total number of rows, the number of missing values, the mean, standard deviation, min, max, median and the percentiles specified in the argument `percentiles`.

Usage

```
DataFrame_describe(percentiles = c(0.25, 0.75), interpolation = "nearest")
```

Arguments

`percentiles`	One or more percentiles to include in the summary statistics. All values must be in the range `[0; 1]`.
`interpolation`	Interpolation method for computing quantiles. One of `"nearest"`, `"higher"`, `"lower"`, `"midpoint"`, or `"linear"`.

Value

DataFrame

Examples

```
as_polars_df(iris)$describe()

# string, date, boolean columns are also supported:
df = pl$DataFrame(
  int = 1:3,
  string = c(letters[1:2], NA),
  date = c(as.Date("2024-01-20"), as.Date("2024-01-21"), NA),
  cat = factor(c(letters[1:2], NA)),
  bool = c(TRUE, FALSE, NA)
)
df

df$describe()
```

DataFrame_drop *Drop columns of a DataFrame*

Description

Drop columns of a DataFrame

Usage

```
DataFrame_drop(..., strict = TRUE)
```

Arguments

`...`	Characters of column names to drop. Passed to `pl$col()`.
`strict`	Validate that all column names exist in the schema and throw an exception if a column name does not exist in the schema.

Value

DataFrame

Examples

```
as_polars_df(mtcars)$drop(c("mpg", "hp"))

# equivalent
as_polars_df(mtcars)$drop("mpg", "hp")
```

DataFrame_drop_in_place *Drop in place*

Description

Drop a single column in-place and return the dropped column.

Usage

```
DataFrame_drop_in_place(name)
```

Arguments

name	string Name of the column to drop.

Value

Series

Examples

```
dat = as_polars_df(iris)
x = dat$drop_in_place("Species")
x
dat$columns
```

DataFrame_drop_nulls *Drop nulls (missing values)*

Description

Drop all rows that contain nulls (which correspond to NA in R).

Usage

```
DataFrame_drop_nulls(subset = NULL)
```

Arguments

subset	A character vector with the names of the column(s) for which nulls are considered. If NULL (default), use all columns.

Value

DataFrame

Examples

```
tmp = mtcars
tmp[1:3, "mpg"] = NA
tmp[4, "hp"] = NA
tmp = as_polars_df(tmp)

# number of rows in `tmp` before dropping nulls
tmp$height

tmp$drop_nulls()$height
tmp$drop_nulls("mpg")$height
tmp$drop_nulls(c("mpg", "hp"))$height
```

DataFrame_dtype_strings *Data types information*

Description

Get the data type of all columns as strings. You can see all available types with `names(pl$dtypes)`. The data type of each column is also shown when printing the DataFrame.

Usage

```
DataFrame_dtype_strings()
```

Value

A character vector with the data type of each column

Examples

```
as_polars_df(iris)$dtype_strings()
```

DataFrame_equals *Compare two DataFrames*

Description

Check if two DataFrames are equal.

Usage

```
DataFrame_equals(other)
```

Arguments

`other`	DataFrame to compare with.

Value

A logical value

Examples

```
dat1 = as_polars_df(iris)
dat2 = as_polars_df(iris)
dat3 = as_polars_df(mtcars)
dat1$equals(dat2)
dat1$equals(dat3)
```

DataFrame_estimated_size *Estimated size*

Description

Return an estimation of the total (heap) allocated size of the DataFrame.

Usage

```
DataFrame_estimated_size()
```

Format

function

Value

Estimated size in bytes

Examples

```
as_polars_df(mtcars)$estimated_size()
```

DataFrame_explode *Explode columns containing a list of values*

Description

Explode columns containing a list of values

Usage

```
DataFrame_explode(...)
```

Arguments

...	Column(s) to be exploded as individual `Into<Expr>` or list/vector of `Into<Expr>`. In a handful of places in rust-polars, only the plain variant `Expr::Column` is accepted. This is currenly one of such places. Therefore `pl$col("name")` and `pl$all()` is allowed, not `pl$col("name")$alias("newname")`. `"name"` is implicitly converted to `pl$col("name")`.

Value

DataFrame

Examples

```
df = pl$DataFrame(
  letters = letters[1:4],
  numbers = list(1, c(2, 3), c(4, 5), c(6, 7, 8)),
  numbers_2 = list(0, c(1, 2), c(3, 4), c(5, 6, 7)) # same structure as numbers
)
df

# explode a single column, append others
df$explode("numbers")

# explode two columns of same nesting structure, by names or the common dtype
# "List(Float64)"
df$explode("numbers", "numbers_2")
df$explode(pl$col(pl$List(pl$Float64)))
```

DataFrame_fill_nan *Fill floating point NaN value with a fill value*

Description

Fill floating point NaN value with a fill value

Usage

```
DataFrame_fill_nan(value)
```

Arguments

value	Value used to fill NaN values.

Value

DataFrame

Examples

```
df = pl$DataFrame(
  a = c(1.5, 2, NaN, 4),
  b = c(1.5, NaN, NaN, 4)
)
df$fill_nan(99)
```

DataFrame_fill_null *Fill nulls*

Description

Fill null values (which correspond to NA in R) using the specified value or strategy.

Usage

```
DataFrame_fill_null(fill_value)
```

Arguments

fill_value	Value to fill nulls with.

Value

DataFrame

Examples

```
df = pl$DataFrame(
  a = c(1.5, 2, NA, 4),
  b = c(1.5, NA, NA, 4)
)

df$fill_null(99)

df$fill_null(pl$col("a")$mean())
```

DataFrame_filter *Filter rows of a DataFrame*

Description

Filter rows with an Expression defining a boolean column. Multiple expressions are combined with & (AND). This is equivalent to `dplyr::filter()`.

Usage

```
DataFrame_filter(...)
```

Arguments

...	Polars expressions which will evaluate to a boolean.

Details

Rows where the condition returns `NA` are dropped.

Value

A DataFrame with only the rows where the conditions are `TRUE`.

Examples

```
df = as_polars_df(iris)

df$filter(pl$col("Sepal.Length") > 5)

# This is equivalent to
# df$filter(pl$col("Sepal.Length") > 5 & pl$col("Petal.Width") < 1)
df$filter(pl$col("Sepal.Length") > 5, pl$col("Petal.Width") < 1)

# rows where condition is NA are dropped
iris2 = iris
iris2[c(1, 3, 5), "Species"] = NA
df = as_polars_df(iris2)

df$filter(pl$col("Species") == "setosa")
```

DataFrame_first *Get the first row of the DataFrame.*

Description

Get the first row of the DataFrame.

Usage

```
DataFrame_first()
```

Value

A DataFrame with one row.

Examples

```
as_polars_df(mtcars)$first()
```

DataFrame_gather_every *Take every nth row in the DataFrame*

Description

Take every nth row in the DataFrame

Usage

```
DataFrame_gather_every(n, offset = 0)
```

Arguments

n	Gather every n-th row.
offset	Starting index.

Value

A DataFrame

Examples

```
df = pl$DataFrame(a = 1:4, b = 5:8)
df$gather_every(2)

df$gather_every(2, offset = 1)
```

DataFrame_get_column *Get column (as one Series)*

Description

Extract a DataFrame column as a Polars series.

Usage

```
DataFrame_get_column(name)
```

Arguments

name	Name of the column to extract.

Value

Series

Examples

```
df = as_polars_df(iris[1:2, ])
df$get_column("Species")
```

DataFrame_get_columns *Get the DataFrame as a List of Series*

Description

Get the DataFrame as a List of Series

Usage

```
DataFrame_get_columns()
```

Value

A list of Series

See Also

- `<DataFrame>$to_list()`: Similar to this method but returns a list of vectors instead of Series.

Examples

```
df = pl$DataFrame(foo = 1L:3L, bar = 4L:6L)
df$get_columns()

df = pl$DataFrame(
  a = 1:4,
  b = c(0.5, 4, 10, 13),
  c = c(TRUE, TRUE, FALSE, TRUE)
)
df$get_columns()
```

DataFrame_glimpse *Show a dense preview of the DataFrame*

Description

The formatting shows one line per column so that wide DataFrames display cleanly. Each line shows the column name, the data type, and the first few values.

Usage

```
DataFrame_glimpse(
  ...,
  max_items_per_column = 10,
  max_colname_length = 50,
  return_as_string = FALSE
)
```

Arguments

`...` Ignored.

`max_items_per_column` Maximum number of items to show per column.

`max_colname_length` Maximum length of the displayed column names. Values that exceed this value are truncated with a trailing ellipsis.

`return_as_string` Logical (default `FALSE`). If `TRUE`, return the output as a string.

Value

DataFrame

Examples

```
as_polars_df(iris)$glimpse()
```

DataFrame_group_by *Group a DataFrame*

Description

This doesn't modify the data but only stores information about the group structure. This structure can then be used by several functions (`$agg()`, `$filter()`, etc.).

Usage

```
DataFrame_group_by(..., maintain_order = polars_options()$maintain_order)
```

Arguments

`...`	Column(s) to group by. Accepts expression input. Characters are parsed as column names.
`maintain_order`	Ensure that the order of the groups is consistent with the input data. This is slower than a default group by. Setting this to `TRUE` blocks the possibility to run on the streaming engine. The default value can be changed with `options(polars.maintain_order = TRUE)`.

Details

Within each group, the order of the rows is always preserved, regardless of the `maintain_order` argument.

Value

GroupBy (a DataFrame with special groupby methods like `$agg()`)

See Also

- `<DataFrame>$partition_by()`

Examples

```
df = pl$DataFrame(
  a = c("a", "b", "a", "b", "c"),
  b = c(1, 2, 1, 3, 3),
  c = c(5, 4, 3, 2, 1)
)

df$group_by("a")$agg(pl$col("b")$sum())

# Set `maintain_order = TRUE` to ensure the order of the groups is consistent with the input.
df$group_by("a", maintain_order = TRUE)$agg(pl$col("c"))

# Group by multiple columns by passing a list of column names.
```

```
df$group_by(c("a", "b"))$agg(pl$max("c"))

# Or pass some arguments to group by multiple columns in the same way.
# Expressions are also accepted.
df$group_by("a", pl$col("b") %/% 2)$agg(
  pl$col("c")$mean()
)

# The columns will be renamed to the argument names.
df$group_by(d = "a", e = pl$col("b") %/% 2)$agg(
  pl$col("c")$mean()
)
```

DataFrame_group_by_dynamic

Group based on a date/time or integer column

Description

If you have a time series <t_0, t_1, ..., t_n>, then by default the windows created will be:

- (t_0 - period, t_0]
- (t_1 - period, t_1]
- ...
- (t_n - period, t_n]

whereas if you pass a non-default offset, then the windows will be:

- (t_0 + offset, t_0 + offset + period]
- (t_1 + offset, t_1 + offset + period]
- ...
- (t_n + offset, t_n + offset + period]

Usage

```
DataFrame_group_by_dynamic(
  index_column,
  ...,
  every,
  period = NULL,
  offset = NULL,
  include_boundaries = FALSE,
  closed = "left",
  label = "left",
  group_by = NULL,
  start_by = "window"
)
```

Arguments

`index_column` Column used to group based on the time window. Often of type Date/Datetime. This column must be sorted in ascending order (or, if by is specified, then it must be sorted in ascending order within each group). In case of a rolling group by on indices, dtype needs to be either Int32 or Int64. Note that Int32 gets temporarily cast to Int64, so if performance matters use an Int64 column.

`...` Ignored.

`every` Interval of the window.

`period` A character representing the length of the window, must be non-negative. See the `Polars duration string language` section for details.

`offset` A character representing the offset of the window, or `NULL` (default). If `NULL`, `-period` is used. See the `Polars duration string language` section for details.

`include_boundaries`
Add two columns `"_lower_boundary"` and `"_upper_boundary"` columns that show the boundaries of the window. This will impact performance because it's harder to parallelize.

`closed` Define which sides of the temporal interval are closed (inclusive). This can be either `"left"`, `"right"`, `"both"` or `"none"`.

`label` Define which label to use for the window:

- `"left"`: lower boundary of the window
- `"right"`: upper boundary of the window
- `"datapoint"`: the first value of the index column in the given window. If you don't need the label to be at one of the boundaries, choose this option for maximum performance.

`group_by` Also group by this column/these columns.

`start_by` The strategy to determine the start of the first window by:

- `"window"`: start by taking the earliest timestamp, truncating it with `every`, and then adding `offset`. Note that weekly windows start on Monday.
- `"datapoint"`: start from the first encountered data point.
- a day of the week (only takes effect if `every` contains `"w"`): `"monday"` starts the window on the Monday before the first data point, etc.

Details

In case of a rolling operation on an integer column, the windows are defined by:

- "1i" # length 1
- "10i" # length 10

Value

A GroupBy object

See Also

- <DataFrame>$rolling()

Examples

```
df = pl$DataFrame(
  time = pl$datetime_range(
    start = strptime("2021-12-16 00:00:00", format = "%Y-%m-%d %H:%M:%S", tz = "UTC"),
    end = strptime("2021-12-16 03:00:00", format = "%Y-%m-%d %H:%M:%S", tz = "UTC"),
    interval = "30m"
  ),
  n = 0:6
)

# get the sum in the following hour relative to the "time" column
df$group_by_dynamic("time", every = "1h")$agg(
  vals = pl$col("n"),
  sum = pl$col("n")$sum()
)

# using "include_boundaries = TRUE" is helpful to see the period considered
df$group_by_dynamic("time", every = "1h", include_boundaries = TRUE)$agg(
  vals = pl$col("n")
)

# in the example above, the values didn't include the one *exactly* 1h after
# the start because "closed = 'left'" by default.
# Changing it to "right" includes values that are exactly 1h after. Note that
# the value at 00:00:00 now becomes included in the interval [23:00:00 - 00:00:00],
# even if this interval wasn't there originally
df$group_by_dynamic("time", every = "1h", closed = "right")$agg(
  vals = pl$col("n")
)
# To keep both boundaries, we use "closed = 'both'". Some values now belong to
# several groups:
df$group_by_dynamic("time", every = "1h", closed = "both")$agg(
  vals = pl$col("n")
)

# Dynamic group bys can also be combined with grouping on normal keys
df = df$with_columns(
  groups = as_polars_series(c("a", "a", "a", "b", "b", "a", "a"))
)
df

df$group_by_dynamic(
  "time",
  every = "1h",
  closed = "both",
  group_by = "groups",
  include_boundaries = TRUE
)$agg(pl$col("n"))
```

```
# We can also create a dynamic group by based on an index column
df = pl$LazyFrame(
  idx = 0:5,
  A = c("A", "A", "B", "B", "B", "C")
)$with_columns(pl$col("idx")$set_sorted())
df

df$group_by_dynamic(
  "idx",
  every = "2i",
  period = "3i",
  include_boundaries = TRUE,
  closed = "right"
)$agg(A_agg_list = pl$col("A"))
```

`DataFrame_head` *Get the first* `n` *rows.*

Description

Get the first `n` rows.

Usage

```
DataFrame_head(n = 5L)

DataFrame_limit(n = 5L)
```

Arguments

`n`	Number of rows to return. If a negative value is passed, return all rows except the last `abs(n)`.

Details

`$limit()` is an alias for `$head()`.

Value

A DataFrame

Examples

```
df = pl$DataFrame(foo = 1:5, bar = 6:10, ham = letters[1:5])

df$head(3)

# Pass a negative value to get all rows except the last `abs(n)`.
df$head(-3)
```

DataFrame_item — *Return the element at the given row/column.*

Description

If row and column location are not specified, the DataFrame must have dimensions (1, 1).

Usage

```
DataFrame_item(row = NULL, column = NULL)
```

Arguments

row	Optional row index (0-indexed).
column	Optional column index (0-indexed) or name.

Value

A value of length 1

Examples

```
df = pl$DataFrame(a = c(1, 2, 3), b = c(4, 5, 6))

df$select((pl$col("a") * pl$col("b"))$sum())$item()

df$item(1, 1)

df$item(2, "b")
```

DataFrame_join — *Join DataFrames*

Description

This function can do both mutating joins (adding columns based on matching observations, for example with `how = "left"`) and filtering joins (keeping observations based on matching observations, for example with `how = "inner"`).

Usage

```
DataFrame_join(
  other,
  on = NULL,
  how = "inner",
  ...,
  left_on = NULL,
  right_on = NULL,
  suffix = "_right",
  validate = "m:m",
  join_nulls = FALSE,
  allow_parallel = TRUE,
  force_parallel = FALSE,
  coalesce = NULL
)
```

Arguments

`other` DataFrame to join with.

`on` Either a vector of column names or a list of expressions and/or strings. Use `left_on` and `right_on` if the column names to match on are different between the two DataFrames.

`how` One of the following methods: "inner", "left", "right", "full", "semi", "anti", "cross".

`...` Ignored.

`left_on`, `right_on` Same as `on` but only for the left or the right DataFrame. They must have the same length.

`suffix` Suffix to add to duplicated column names.

`validate` Checks if join is of specified type:

- `"m:m"` (default): many-to-many, doesn't perform any checks;
- `"1:1"`: one-to-one, check if join keys are unique in both left and right datasets;
- `"1:m"`: one-to-many, check if join keys are unique in left dataset
- `"m:1"`: many-to-one, check if join keys are unique in right dataset

Note that this is currently not supported by the streaming engine, and is only supported when joining by single columns.

`join_nulls` Join on null values. By default null values will never produce matches.

`allow_parallel` Allow the physical plan to optionally evaluate the computation of both DataFrames up to the join in parallel.

`force_parallel` Force the physical plan to evaluate the computation of both DataFrames up to the join in parallel.

`coalesce` Coalescing behavior (merging of join columns).

- `NULL`: join specific.
- `TRUE`: Always coalesce join columns.
- `FALSE`: Never coalesce join columns.

Value

DataFrame

Examples

```
# inner join by default
df1 = pl$DataFrame(list(key = 1:3, payload = c("f", "i", NA)))
df2 = pl$DataFrame(list(key = c(3L, 4L, 5L, NA_integer_)))
df1$join(other = df2, on = "key")

# cross join
df1 = pl$DataFrame(x = letters[1:3])
df2 = pl$DataFrame(y = 1:4)
df1$join(other = df2, how = "cross")
```

DataFrame_join_asof *Perform joins on nearest keys*

Description

This is similar to a left-join except that we match on nearest key rather than equal keys.

Usage

```
DataFrame_join_asof(
  other,
  ...,
  left_on = NULL,
  right_on = NULL,
  on = NULL,
  by_left = NULL,
  by_right = NULL,
  by = NULL,
  strategy = c("backward", "forward", "nearest"),
  suffix = "_right",
  tolerance = NULL,
  allow_parallel = TRUE,
  force_parallel = FALSE,
  coalesce = TRUE
)
```

Arguments

other	DataFrame or LazyFrame
...	Not used, blocks use of further positional arguments
left_on, right_on	Same as on but only for the left or the right DataFrame. They must have the same length.

`on` Either a vector of column names or a list of expressions and/or strings. Use `left_on` and `right_on` if the column names to match on are different between the two DataFrames.

`by_left, by_right` Same as `by` but only for the left or the right table. They must have the same length.

`by` Join on these columns before performing asof join. Either a vector of column names or a list of expressions and/or strings. Use `left_by` and `right_by` if the column names to match on are different between the two tables.

`strategy` Strategy for where to find match:

- "backward" (default): search for the last row in the right table whose `on` key is less than or equal to the left key.
- "forward": search for the first row in the right table whose `on` key is greater than or equal to the left key.
- "nearest": search for the last row in the right table whose value is nearest to the left key. String keys are not currently supported for a nearest search.

`suffix` Suffix to add to duplicated column names.

`tolerance` Numeric tolerance. By setting this the join will only be done if the near keys are within this distance. If an asof join is done on columns of dtype "Date", "Datetime", "Duration" or "Time", use the Polars duration string language. About the language, see the `Polars duration string language` section for details.

There may be a circumstance where R types are not sufficient to express a numeric tolerance. In that case, you can use the expression syntax like `tolerance = pl$lit(42)$cast(pl$Uint64)`

`allow_parallel` Allow the physical plan to optionally evaluate the computation of both DataFrames up to the join in parallel.

`force_parallel` Force the physical plan to evaluate the computation of both DataFrames up to the join in parallel.

`coalesce` Coalescing behavior (merging of `on` / `left_on` / `right_on` columns):

- `TRUE`: Always coalesce join columns;
- `FALSE`: Never coalesce join columns. Note that joining on any other expressions than `col` will turn off coalescing.

Details

Both tables (DataFrames or LazyFrames) must be sorted by the asof_join key.

Value

New joined DataFrame

Polars duration string language

Polars duration string language is a simple representation of durations. It is used in many Polars functions that accept durations.

It has the following format:

- 1ns (1 nanosecond)
- 1us (1 microsecond)
- 1ms (1 millisecond)
- 1s (1 second)
- 1m (1 minute)
- 1h (1 hour)
- 1d (1 calendar day)
- 1w (1 calendar week)
- 1mo (1 calendar month)
- 1q (1 calendar quarter)
- 1y (1 calendar year)

Or combine them: `"3d12h4m25s"` # 3 days, 12 hours, 4 minutes, and 25 seconds

By "calendar day", we mean the corresponding time on the next day (which may not be 24 hours, due to daylight savings). Similarly for "calendar week", "calendar month", "calendar quarter", and "calendar year".

Examples

```
# create two DataFrames to join asof
gdp = pl$DataFrame(
  date = as.Date(c("2015-1-1", "2016-1-1", "2017-5-1", "2018-1-1", "2019-1-1")),
  gdp = c(4321, 4164, 4411, 4566, 4696),
  group = c("b", "a", "a", "b", "b")
)

pop = pl$DataFrame(
  date = as.Date(c("2016-5-12", "2017-5-12", "2018-5-12", "2019-5-12")),
  population = c(82.19, 82.66, 83.12, 83.52),
  group = c("b", "b", "a", "a")
)

# optional make sure tables are already sorted with "on" join-key
gdp = gdp$sort("date")
pop = pop$sort("date")

# Left-join_asof DataFrame pop with gdp on "date"
# Look backward in gdp to find closest matching date
pop$join_asof(gdp, on = "date", strategy = "backward")

# .... and forward
pop$join_asof(gdp, on = "date", strategy = "forward")

# join by a group: "only look within within group"
pop$join_asof(gdp, on = "date", by = "group", strategy = "backward")

# only look 2 weeks and 2 days back
pop$join_asof(gdp, on = "date", strategy = "backward", tolerance = "2w2d")
```

```
# only look 11 days back (numeric tolerance depends on polars type, <date> is in days)
pop$join_asof(gdp, on = "date", strategy = "backward", tolerance = 11)
```

`DataFrame_join_where` *Perform a join based on one or multiple (in)equality predicates*

Description

This performs an inner join, so only rows where all predicates are true are included in the result, and a row from either DataFrame may be included multiple times in the result.

Note that the row order of the input DataFrames is not preserved.

Usage

```
DataFrame_join_where(other, ..., suffix = "_right")
```

Arguments

`other`	DataFrame to join with.
`...`	(In)Equality condition to join the two tables on. When a column name occurs in both tables, the proper suffix must be applied in the predicate. For example, if both tables have a column "x" that you want to use in the conditions, you must refer to the column of the right table as "x<suffix>".
`suffix`	Suffix to append to columns with a duplicate name.

Value

A DataFrame

Examples

```
east = pl$DataFrame(
  id = c(100, 101, 102),
  dur = c(120, 140, 160),
  rev = c(12, 14, 16),
  cores = c(2, 8, 4)
)

west = pl$DataFrame(
  t_id = c(404, 498, 676, 742),
  time = c(90, 130, 150, 170),
  cost = c(9, 13, 15, 16),
  cores = c(4, 2, 1, 4)
)

east$join_where(
  west,
```

```
  pl$col("dur") < pl$col("time"),
  pl$col("rev") < pl$col("cost")
)
```

`DataFrame_last` *Get the last row of the DataFrame.*

Description

Get the last row of the DataFrame.

Usage

```
DataFrame_last()
```

Value

A DataFrame with one row.

Examples

```
as_polars_df(mtcars)$last()
```

`DataFrame_lazy` *Convert an existing DataFrame to a LazyFrame*

Description

Start a new lazy query from a DataFrame.

Usage

```
DataFrame_lazy()
```

Value

A LazyFrame

Examples

```
as_polars_df(iris)$lazy()
```

DataFrame_max *Max*

Description

Aggregate the columns in the DataFrame to their maximum value.

Usage

```
DataFrame_max()
```

Value

A DataFrame with one row.

Examples

```
as_polars_df(mtcars)$max()
```

DataFrame_mean *Mean*

Description

Aggregate the columns in the DataFrame to their mean value.

Usage

```
DataFrame_mean()
```

Value

A DataFrame with one row.

Examples

```
as_polars_df(mtcars)$mean()
```

DataFrame_median *Median*

Description

Aggregate the columns in the DataFrame to their median value.

Usage

```
DataFrame_median()
```

Value

A DataFrame with one row.

Examples

```
as_polars_df(mtcars)$median()
```

DataFrame_min *Min*

Description

Aggregate the columns in the DataFrame to their minimum value.

Usage

```
DataFrame_min()
```

Value

A DataFrame with one row.

Examples

```
as_polars_df(mtcars)$min()
```

DataFrame_n_chunks *Number of chunks of the Series in a DataFrame*

Description

Number of chunks (memory allocations) for all or first Series in a DataFrame.

Usage

```
DataFrame_n_chunks(strategy = "first")
```

Arguments

strategy	Either "all" or "first". "first" only returns chunks for the first Series.

Details

A DataFrame is a vector of Series. Each Series in rust-polars is a wrapper around a ChunkedArray, which is like a virtual contiguous vector physically backed by an ordered set of chunks. Each chunk of values has a contiguous memory layout and is an arrow array. Arrow arrays are a fast, thread-safe and cross-platform memory layout.

In R, combining with `c()` or `rbind()` requires immediate vector re-allocation to place vector values in contiguous memory. This is slow and memory consuming, and it is why repeatedly appending to a vector in R is discouraged.

In polars, when we concatenate or append to Series or DataFrame, the re-allocation can be avoided or delayed by simply appending chunks to each individual Series. However, if chunks become many and small or are misaligned across Series, this can hurt the performance of subsequent operations.

Most places in the polars api where chunking could occur, the user have to typically actively opt-out by setting an argument `rechunk = FALSE`.

Value

A real vector of chunk counts per Series.

See Also

`<DataFrame>$rechunk()`

Examples

```
# create DataFrame with misaligned chunks
df = pl$concat(
  1:10, # single chunk
  pl$concat(1:5, 1:5, rechunk = FALSE, how = "vertical")$rename("b"), # two chunks
  how = "horizontal"
)
df
```

```
df$n_chunks()

# rechunk a chunked DataFrame
df$rechunk()$n_chunks()

# rechunk is not an in-place operation
df$n_chunks()

# The following toy example emulates the Series "chunkyness" in R. Here it a
# S3-classed list with same type of vectors and where have all relevant S3
# generics implemented to make behave as if it was a regular vector.
"+.chunked_vector" = \(x, y) structure(list(unlist(x) + unlist(y)), class = "chunked_vector")
print.chunked_vector = \(x, ...) print(unlist(x), ...)
c.chunked_vector = \(...) {
  structure(do.call(c, lapply(list(...), unclass)), class = "chunked_vector")
}
rechunk = \(x) structure(unlist(x), class = "chunked_vector")
x = structure(list(1:4, 5L), class = "chunked_vector")
x
x + 5:1
lapply(x, tracemem) # trace chunks to verify no re-allocation
z = c(x, x)
z # looks like a plain vector
lapply(z, tracemem) # mem allocation  in z are the same from x
str(z)
z = rechunk(z)
str(z)
```

`DataFrame_null_count` *Count null values*

Description

Create a new DataFrame that shows the null (which correspond to `NA` in R) counts per column.

Usage

```
DataFrame_null_count()
```

Format

function

Value

DataFrame

Examples

```
x = mtcars
x[1, 2:3] = NA
pl$DataFrame(x)$null_count()
```

DataFrame_partition_by

Split a DataFrame into multiple DataFrames

Description

Similar to `$group_by()`. Group by the given columns and return the groups as separate DataFrames. It is useful to use this in combination with functions like `lapply()` or `purrr::map()`.

Usage

```
DataFrame_partition_by(
  ...,
  maintain_order = TRUE,
  include_key = TRUE,
  as_nested_list = FALSE
)
```

Arguments

`...`	Characters of column names to group by. Passed to `pl$col()`.
`maintain_order`	If `TRUE`, ensure that the order of the groups is consistent with the input data. This is slower than a default partition by operation.
`include_key`	If `TRUE`, include the columns used to partition the DataFrame in the output.
`as_nested_list`	This affects the format of the output. If `FALSE` (default), the output is a flat list of DataFrames. IF `TRUE` and one of the `maintain_order` or `include_key` argument is `TRUE`, then each element of the output has two children: `key` and `data`. See the examples for more details.

Value

A list of DataFrames. See the examples for details.

See Also

- `<DataFrame>$group_by()`

Examples

```
df = pl$DataFrame(
  a = c("a", "b", "a", "b", "c"),
  b = c(1, 2, 1, 3, 3),
  c = c(5, 4, 3, 2, 1)
)
df

# Pass a single column name to partition by that column.
df$partition_by("a")

# Partition by multiple columns.
df$partition_by("a", "b")

# Partition by column data type
df$partition_by(pl$String)

# If `as_nested_list = TRUE`, the output is a list whose elements have a `key` and a `data` field.
# The `key` is a named list of the key values, and the `data` is the DataFrame.
df$partition_by("a", "b", as_nested_list = TRUE)

# `as_nested_list = TRUE` should be used with `maintain_order = TRUE` or `include_key = TRUE`.
tryCatch(
 df$partition_by("a", "b", maintain_order = FALSE, include_key = FALSE, as_nested_list = TRUE),
  warning = function(w) w
)

# Example of using with lapply(), and printing the key and the data summary
df$partition_by("a", "b", maintain_order = FALSE, as_nested_list = TRUE) |>
  lapply(\(x) {
   sprintf("\nThe key value of `a` is %s and the key value of `b` is %s\n", x$key$a, x$key$b) |>
      cat()
    x$data$drop(names(x$key))$describe() |>
      print()
    invisible(NULL)
  }) |>
  invisible()
```

DataFrame_pivot *Pivot data from long to wide*

Description

Pivot data from long to wide

Usage

```
DataFrame_pivot(
  on,
```

```
  ...,
  index,
  values,
  aggregate_function = NULL,
  maintain_order = TRUE,
  sort_columns = FALSE,
  separator = "_"
)
```

Arguments

on	Name of the column(s) whose values will be used as the header of the output DataFrame.
...	Not used.
index	One or multiple keys to group by.
values	Column values to aggregate. Can be multiple columns if the on arguments contains multiple columns as well.
aggregate_function	One of: • string indicating the expressions to aggregate with, such as 'first', 'sum', 'max', 'min', 'mean', 'median', 'last', 'count'), • an Expr e.g. `pl$element()$sum()`
maintain_order	Sort the grouped keys so that the output order is predictable.
sort_columns	Sort the transposed columns by name. Default is by order of discovery.
separator	Used as separator/delimiter in generated column names.

Value

DataFrame

Examples

```
df = pl$DataFrame(
  foo = c("one", "one", "one", "two", "two", "two"),
  bar = c("A", "B", "C", "A", "B", "C"),
  baz = c(1, 2, 3, 4, 5, 6)
)
df

df$pivot(
  values = "baz", index = "foo", on = "bar"
)

# Run an expression as aggregation function
df = pl$DataFrame(
  col1 = c("a", "a", "a", "b", "b", "b"),
  col2 = c("x", "x", "x", "x", "y", "y"),
  col3 = c(6, 7, 3, 2, 5, 7)
```

```
)
df

df$pivot(
  index = "col1",
  on = "col2",
  values = "col3",
  aggregate_function = pl$element()$tanh()$mean()
)
```

DataFrame_quantile *Quantile*

Description

Aggregate the columns in the DataFrame to a unique quantile value. Use `$describe()` to specify several quantiles.

Usage

```
DataFrame_quantile(quantile, interpolation = "nearest")
```

Arguments

`quantile`	Numeric of length 1 between 0 and 1.
`interpolation`	One of `"nearest"`, `"higher"`, `"lower"`, `"midpoint"`, or `"linear"`.

Value

DataFrame

Examples

```
as_polars_df(mtcars)$quantile(.4)
```

DataFrame_rechunk *Rechunk a DataFrame*

Description

Rechunking re-allocates any "chunked" memory allocations to speed-up e.g. vectorized operations.

Usage

```
DataFrame_rechunk()
```

Details

A DataFrame is a vector of Series. Each Series in rust-polars is a wrapper around a ChunkedArray, which is like a virtual contiguous vector physically backed by an ordered set of chunks. Each chunk of values has a contiguous memory layout and is an arrow array. Arrow arrays are a fast, thread-safe and cross-platform memory layout.

In R, combining with `c()` or `rbind()` requires immediate vector re-allocation to place vector values in contiguous memory. This is slow and memory consuming, and it is why repeatedly appending to a vector in R is discouraged.

In polars, when we concatenate or append to Series or DataFrame, the re-allocation can be avoided or delayed by simply appending chunks to each individual Series. However, if chunks become many and small or are misaligned across Series, this can hurt the performance of subsequent operations.

Most places in the polars api where chunking could occur, the user have to typically actively opt-out by setting an argument `rechunk = FALSE`.

Value

A DataFrame

See Also

`<DataFrame>$n_chunks()`

Examples

```
# create DataFrame with misaligned chunks
df = pl$concat(
  1:10, # single chunk
  pl$concat(1:5, 1:5, rechunk = FALSE, how = "vertical")$rename("b"), # two chunks
  how = "horizontal"
)
df
df$n_chunks()

# rechunk a chunked DataFrame
df$rechunk()$n_chunks()

# rechunk is not an in-place operation
df$n_chunks()

# The following toy example emulates the Series "chunkyness" in R. Here it a
# S3-classed list with same type of vectors and where have all relevant S3
# generics implemented to make behave as if it was a regular vector.
"+.chunked_vector" = \(x, y) structure(list(unlist(x) + unlist(y)), class = "chunked_vector")
print.chunked_vector = \(x, ...) print(unlist(x), ...)
c.chunked_vector = \(...) {
  structure(do.call(c, lapply(list(...), unclass)), class = "chunked_vector")
}
rechunk = \(x) structure(unlist(x), class = "chunked_vector")
x = structure(list(1:4, 5L), class = "chunked_vector")
x
```

```
x + 5:1
lapply(x, tracemem) # trace chunks to verify no re-allocation
z = c(x, x)
z # looks like a plain vector
lapply(z, tracemem) # mem allocation  in z are the same from x
str(z)
z = rechunk(z)
str(z)
```

`DataFrame_rename` *Rename column names of a DataFrame*

Description

Rename column names of a DataFrame

Usage

```
DataFrame_rename(...)
```

Arguments

`...` One of the following:

- Key value pairs that map from old name to new name, like `old_name = "new_name"`.
- As above but with params wrapped in a list
- An R function that takes the old names character vector as input and returns the new names character vector.

Details

If existing names are swapped (e.g. `A` points to `B` and `B` points to `A`), polars will block projection and predicate pushdowns at this node.

Value

DataFrame

Examples

```
df = pl$DataFrame(
  foo = 1:3,
  bar = 6:8,
  ham = letters[1:3]
)

df$rename(foo = "apple")
```

```
df$rename(
  \(column_name) paste0("c", substr(column_name, 2, 100))
)
```

`DataFrame_reverse` *Reverse*

Description

Reverse the DataFrame (the last row becomes the first one, etc.).

Usage

```
DataFrame_reverse()
```

Value

DataFrame

Examples

```
as_polars_df(mtcars)$reverse()
```

`DataFrame_rolling` *Create rolling groups based on a date/time or integer column*

Description

If you have a time series `<t_0, t_1, ..., t_n>`, then by default the windows created will be:

- (t_0 - period, t_0]
- (t_1 - period, t_1]
- ...
- (t_n - period, t_n]

whereas if you pass a non-default offset, then the windows will be:

- (t_0 + offset, t_0 + offset + period]
- (t_1 + offset, t_1 + offset + period]
- ...
- (t_n + offset, t_n + offset + period]

Usage

```
DataFrame_rolling(
  index_column,
  ...,
  period,
  offset = NULL,
  closed = "right",
  group_by = NULL
)
```

Arguments

`index_column`	Column used to group based on the time window. Often of type Date/Datetime. This column must be sorted in ascending order (or, if by is specified, then it must be sorted in ascending order within each group). In case of a rolling group by on indices, dtype needs to be either Int32 or Int64. Note that Int32 gets temporarily cast to Int64, so if performance matters use an Int64 column.
`...`	Ignored.
`period`	A character representing the length of the window, must be non-negative. See the `Polars duration string language` section for details.
`offset`	A character representing the offset of the window, or `NULL` (default). If `NULL`, `-period` is used. See the `Polars duration string language` section for details.
`closed`	Define which sides of the temporal interval are closed (inclusive). This can be either `"left"`, `"right"`, `"both"` or `"none"`.
`group_by`	Also group by this column/these columns.

Details

In case of a rolling operation on an integer column, the windows are defined by:

- "1i" # length 1
- "10i" # length 10

Value

A RollingGroupBy object

Polars duration string language

Polars duration string language is a simple representation of durations. It is used in many Polars functions that accept durations.

It has the following format:

- 1ns (1 nanosecond)
- 1us (1 microsecond)
- 1ms (1 millisecond)

- 1s (1 second)
- 1m (1 minute)
- 1h (1 hour)
- 1d (1 calendar day)
- 1w (1 calendar week)
- 1mo (1 calendar month)
- 1q (1 calendar quarter)
- 1y (1 calendar year)

Or combine them: `"3d12h4m25s"` # 3 days, 12 hours, 4 minutes, and 25 seconds

By "calendar day", we mean the corresponding time on the next day (which may not be 24 hours, due to daylight savings). Similarly for "calendar week", "calendar month", "calendar quarter", and "calendar year".

See Also

- `<DataFrame>$group_by_dynamic()`

Examples

```
date = c(
  "2020-01-01 13:45:48",
  "2020-01-01 16:42:13",
  "2020-01-01 16:45:09",
  "2020-01-02 18:12:48",
  "2020-01-03 19:45:32",
  "2020-01-08 23:16:43"
)
df = pl$DataFrame(dt = date, a = c(3, 7, 5, 9, 2, 1))$with_columns(
  pl$col("dt")$str$strptime(pl$Datetime())$set_sorted()
)

df$rolling(index_column = "dt", period = "2d")$agg(
  sum_a = pl$sum("a"),
  min_a = pl$min("a"),
  max_a = pl$max("a")
)
```

DataFrame_sample *Take a sample of rows from a DataFrame*

Description

Take a sample of rows from a DataFrame

Usage

```
DataFrame_sample(
  n = NULL,
  ...,
  fraction = NULL,
  with_replacement = FALSE,
  shuffle = FALSE,
  seed = NULL
)
```

Arguments

`n`	Number of rows to return. Cannot be used with `fraction`.
`...`	Ignored.
`fraction`	Fraction of rows to return. Cannot be used with `n`. Can be larger than 1 if `with_replacement` is `TRUE`.
`with_replacement`	Allow values to be sampled more than once.
`shuffle`	If `TRUE`, the order of the sampled rows will be shuffled. If `FALSE` (default), the order of the returned rows will be neither stable nor fully random.
`seed`	Seed for the random number generator. If set to `NULL` (default), a random seed is generated for each sample operation.

Value

DataFrame

Examples

```
df = as_polars_df(iris)
df$sample(n = 20)
df$sample(fraction = 0.1)
```

`DataFrame_select` *Select and modify columns of a DataFrame*

Description

Similar to `dplyr::mutate()`. However, it discards unmentioned columns (like `.()` in `data.table`).

Usage

```
DataFrame_select(...)
```

Arguments

...	Columns to keep. Those can be expressions (e.g `pl$col("a")`), column names (e.g `"a"`), or list containing expressions or column names (e.g `list(pl$col("a"))`).

Value

DataFrame

Examples

```
as_polars_df(iris)$select(
  pl$col("Sepal.Length")$abs()$alias("abs_SL"),
  (pl$col("Sepal.Length") + 2)$alias("add_2_SL")
)
```

`DataFrame_select_seq` *Select and modify columns of a DataFrame*

Description

Similar to `dplyr::mutate()`. However, it discards unmentioned columns (like `.()` in `data.table`).

This will run all expression sequentially instead of in parallel. Use this when the work per expression is cheap. Otherwise, `$select()` should be preferred.

Usage

```
DataFrame_select_seq(...)
```

Arguments

...	Columns to keep. Those can be expressions (e.g `pl$col("a")`), column names (e.g `"a"`), or list containing expressions or column names (e.g `list(pl$col("a"))`).

Value

DataFrame

Examples

```
as_polars_df(iris)$select_seq(
  pl$col("Sepal.Length")$abs()$alias("abs_SL"),
  (pl$col("Sepal.Length") + 2)$alias("add_2_SL")
)
```

DataFrame_shift *Shift a DataFrame*

Description

Shift the values by a given period. If the period (n) is positive, then n rows will be inserted at the top of the DataFrame and the last n rows will be discarded. Vice-versa if the period is negative. In the end, the total number of rows of the DataFrame doesn't change.

Usage

```
DataFrame_shift(n = 1, fill_value = NULL)
```

Arguments

n	Number of indices to shift forward. If a negative value is passed, values are shifted in the opposite direction instead.
fill_value	Fill the resulting null values with this value. Accepts expression input. Non-expression inputs are parsed as literals.

Value

DataFrame

Examples

```
df = pl$DataFrame(a = 1:4, b = 5:8)

df$shift(2)

df$shift(-2)

df$shift(-2, fill_value = 100)
```

DataFrame_slice *Slice*

Description

Get a slice of the DataFrame.

Usage

```
DataFrame_slice(offset, length = NULL)
```

Arguments

`offset`	Start index, can be a negative value. This is 0-indexed, so `offset = 1` doesn't include the first row.
`length`	Length of the slice. If `NULL` (default), all rows starting at the offset will be selected.

Value

DataFrame

Examples

```
# skip the first 2 rows and take the 4 following rows
as_polars_df(mtcars)$slice(2, 4)

# this is equivalent to:
mtcars[3:6, ]
```

`DataFrame_sort` *Sort a DataFrame*

Description

Sort a DataFrame

Usage

```
DataFrame_sort(
  by,
  ...,
  descending = FALSE,
  nulls_last = FALSE,
  maintain_order = FALSE
)
```

Arguments

`by`	Column(s) to sort by. Can be character vector of column names, a list of Expr(s) or a list with a mix of Expr(s) and column names.
`...`	More columns to sort by as above but provided one Expr per argument.
`descending`	Logical. Sort in descending order (default is `FALSE`). This must be either of length 1 or a logical vector of the same length as the number of Expr(s) specified in `by` and `...`.
`nulls_last`	A logical or logical vector of the same length as the number of columns. If `TRUE`, place `null` values last insead of first.
`maintain_order`	Whether the order should be maintained if elements are equal. If `TRUE`, streaming is not possible and performance might be worse since this requires a stable search.

Value

DataFrame

Examples

```
df = mtcars
df$mpg[1] = NA
df = pl$DataFrame(df)
df$sort("mpg")
df$sort("mpg", nulls_last = TRUE)
df$sort("cyl", "mpg")
df$sort(c("cyl", "mpg"))
df$sort(c("cyl", "mpg"), descending = TRUE)
df$sort(c("cyl", "mpg"), descending = c(TRUE, FALSE))
df$sort(pl$col("cyl"), pl$col("mpg"))
```

DataFrame_sql *Execute a SQL query against the DataFrame*

Description

The calling frame is automatically registered as a table in the SQL context under the name `"self"`. All DataFrames and LazyFrames found in the `envir` are also registered, using their variable name. More control over registration and execution behaviour is available by the SQLContext object.

Usage

```
DataFrame_sql(query, ..., table_name = NULL, envir = parent.frame())
```

Arguments

`query`	A character of the SQL query to execute.
`...`	Ignored.
`table_name`	`NULL` (default) or a character of an explicit name for the table that represents the calling frame (the alias `"self"` will always be registered/available).
`envir`	The environment to search for polars DataFrames/LazyFrames.

Details

This functionality is considered **unstable**, although it is close to being considered stable. It may be changed at any point without it being considered a breaking change.

Value

DataFrame

See Also

- SQLContext

Examples

```
df1 = pl$DataFrame(
  a = 1:3,
  b = c("zz", "yy", "xx"),
  c = as.Date(c("1999-12-31", "2010-10-10", "2077-08-08"))
)

# Query the DataFrame using SQL:
df1$sql("SELECT c, b FROM self WHERE a > 1")

# Join two DataFrames using SQL.
df2 = pl$DataFrame(a = 3:1, d = c(125, -654, 888))
df1$sql(
  "
SELECT self.*, d
FROM self
INNER JOIN df2 USING (a)
WHERE a > 1 AND EXTRACT(year FROM c) < 2050
"
)

# Apply transformations to a DataFrame using SQL, aliasing "self" to "frame".
df1$sql(
  query = r"(
SELECT
a,
MOD(a, 2) == 0 AS a_is_even,
CONCAT_WS(':', b, b) AS b_b,
EXTRACT(year FROM c) AS year,
0::float AS 'zero'
FROM frame
)",
  table_name = "frame"
)
```

DataFrame_std *Std*

Description

Aggregate the columns of this DataFrame to their standard deviation values.

Usage

```
DataFrame_std(ddof = 1)
```

Arguments

ddof	Delta Degrees of Freedom: the divisor used in the calculation is N - ddof, where N represents the number of elements. By default ddof is 1.

Value

A DataFrame with one row.

Examples

```
as_polars_df(mtcars)$std()
```

DataFrame_sum *Sum*

Description

Aggregate the columns of this DataFrame to their sum values.

Usage

```
DataFrame_sum()
```

Value

A DataFrame with one row.

Examples

```
as_polars_df(mtcars)$sum()
```

DataFrame_tail *Get the last* n *rows.*

Description

Get the last n rows.

Usage

```
DataFrame_tail(n = 5L)
```

Arguments

n	Number of rows to return. If a negative value is passed, return all rows except the first abs(n).

Value

A DataFrame

Examples

```
df = pl$DataFrame(foo = 1:5, bar = 6:10, ham = letters[1:5])

df$tail(3)

# Pass a negative value to get all rows except the first `abs(n)`.
df$tail(-3)
```

DataFrame_to_data_frame

Return Polars DataFrame as R data.frame

Description

Return Polars DataFrame as R data.frame

Usage

```
DataFrame_to_data_frame(
  ...,
  int64_conversion = polars_options()$int64_conversion
)
```

Arguments

`...` Any args pased to `as.data.frame()`.

`int64_conversion` How should Int64 values be handled when converting a polars object to R?

- `"double"` (default) converts the integer values to double.
- `"bit64"` uses `bit64::as.integer64()` to do the conversion (requires the package `bit64` to be attached).
- `"string"` converts Int64 values to character.

Value

An R data.frame

Conversion to R data types considerations

When converting Polars objects, such as DataFrames to R objects, for example via the `as.data.frame()` generic function, each type in the Polars object is converted to an R type. In some cases, an error may occur because the conversion is not appropriate. In particular, there is a high possibility of an error when converting a Datetime type without a time zone. A Datetime type without a time zone in Polars is converted to the POSIXct type in R, which takes into account the time zone in which the R session is running (which can be checked with the `Sys.timezone()` function). In this case, if ambiguous times are included, a conversion error will occur. In such cases, change the session time zone using `Sys.setenv(TZ = "UTC")` and then perform the conversion, or use the `$dt$replace_time_zone()` method on the Datetime type column to explicitly specify the time zone before conversion.

```
# Due to daylight savings, clocks were turned forward 1 hour on Sunday, March 8, 2020, 2:00:00 am
# so this particular date-time doesn't exist
non_existent_time = as_polars_series("2020-03-08 02:00:00")$str$strptime(pl$Datetime(), "%F %T")

withr::with_timezone(
  "America/New_York",
  {
    tryCatch(
     # This causes an error due to the time zone (the `TZ` env var is affected).
      as.vector(non_existent_time),
      error = function(e) e
    )
  }
)
#> <error: in $to_vector(): in to_r: ComputeError(ErrString("datetime '2020-03-08 02:00:00' is non-exis

withr::with_timezone(
  "America/New_York",
  {
    # This is safe.
    as.vector(non_existent_time$dt$replace_time_zone("UTC"))
  }
)
#> [1] "2020-03-08 02:00:00 UTC"
```

Examples

```
df = as_polars_df(iris[1:3, ])
df$to_data_frame()
```

`DataFrame_to_dummies` *Convert variables into dummy/indicator variables*

Description

Convert variables into dummy/indicator variables

Usage

```
DataFrame_to_dummies(columns = NULL, ..., separator = "_", drop_first = FALSE)
```

Arguments

columns	Column name(s) or selector(s) that should be converted to dummy variables. If NULL (default), convert all columns.
...	Ignored.
separator	Separator/delimiter used when generating column names.
drop_first	Remove the first category from the variables being encoded.

Value

A DataFrame

Examples

```
df = pl$DataFrame(foo = 1:2, bar = 3:4, ham = c("a", "b"))

df$to_dummies()

df$to_dummies(drop_first = TRUE)

df$to_dummies(c("foo", "bar"), separator = "::")
```

DataFrame_to_list *Return Polars DataFrame as a list of vectors*

Description

Return Polars DataFrame as a list of vectors

Usage

```
DataFrame_to_list(
  unnest_structs = TRUE,
  ...,
  int64_conversion = polars_options()$int64_conversion
)
```

Arguments

`unnest_structs` Logical. If `TRUE` (default), then `$unnest()` is applied on any struct column.

`...` Any args pased to `as.data.frame()`.

`int64_conversion`
How should Int64 values be handled when converting a polars object to R?

- `"double"` (default) converts the integer values to double.
- `"bit64"` uses `bit64::as.integer64()` to do the conversion (requires the package `bit64` to be attached).
- `"string"` converts Int64 values to character.

Details

For simplicity reasons, this implementation relies on unnesting all structs before exporting to R. If `unnest_structs = FALSE`, then `struct` columns will be returned as nested lists, where each row is a list of values. Such a structure is not very typical or efficient in R.

Value

R list of vectors

Conversion to R data types considerations

When converting Polars objects, such as DataFrames to R objects, for example via the `as.data.frame()` generic function, each type in the Polars object is converted to an R type. In some cases, an error may occur because the conversion is not appropriate. In particular, there is a high possibility of an error when converting a Datetime type without a time zone. A Datetime type without a time zone in Polars is converted to the POSIXct type in R, which takes into account the time zone in which the R session is running (which can be checked with the `Sys.timezone()` function). In this case, if ambiguous times are included, a conversion error will occur. In such cases, change the session time zone using `Sys.setenv(TZ = "UTC")` and then perform the conversion, or use the `$dt$replace_time_zone()` method on the Datetime type column to explicitly specify the time zone before conversion.

```
# Due to daylight savings, clocks were turned forward 1 hour on Sunday, March 8, 2020, 2:00:00 am
# so this particular date-time doesn't exist
non_existent_time = as_polars_series("2020-03-08 02:00:00")$str$strptime(pl$Datetime(), "%F %T")

withr::with_timezone(
  "America/New_York",
  {
    tryCatch(
     # This causes an error due to the time zone (the `TZ` env var is affected).
      as.vector(non_existent_time),
      error = function(e) e
    )
  }
)
```

```
#> <error: in $to_vector(): in to_r: ComputeError(ErrString("datetime '2020-03-08 02:00:00' is non-exis

withr::with_timezone(
  "America/New_York",
  {
    # This is safe.
    as.vector(non_existent_time$dt$replace_time_zone("UTC"))
  }
)
#> [1] "2020-03-08 02:00:00 UTC"
```

See Also

- `<DataFrame>$get_columns()`: Similar to this method but returns a list of Series instead of vectors.

Examples

```
as_polars_df(iris)$to_list()
```

DataFrame_to_raw_ipc *Write Arrow IPC data to a raw vector*

Description

Write Arrow IPC data to a raw vector

Usage

```
DataFrame_to_raw_ipc(
  compression = c("uncompressed", "zstd", "lz4"),
  ...,
  compat_level = FALSE
)
```

Arguments

`compression`	`NULL` or a character of the compression method, `"uncompressed"` or "lz4" or "zstd". `NULL` is equivalent to `"uncompressed"`. Choose "zstd" for good compression performance. Choose "lz4" for fast compression/decompression.
`...`	Ignored.
`compat_level`	Use a specific compatibility level when exporting Polars' internal data structures. This can be: • an integer indicating the compatibility version (currently only 0 for oldest and 1 for newest); • a logical value with `TRUE` for the newest version and `FALSE` for the oldest version.

Value

A raw vector

See Also

- <DataFrame>$write_ipc()

Examples

```
df = pl$DataFrame(
  foo = 1:5,
  bar = 6:10,
  ham = letters[1:5]
)

raw_ipc = df$to_raw_ipc()

pl$read_ipc(raw_ipc)

if (require("arrow", quietly = TRUE)) {
  arrow::read_ipc_file(raw_ipc, as_data_frame = FALSE)
}
```

DataFrame_to_series *Get column by index*

Description

Extract a DataFrame column (by index) as a Polars series. Unlike `get_column()`, this method will not fail but will return a `NULL` if the index doesn't exist in the DataFrame. Keep in mind that Polars is 0-indexed so "0" is the first column.

Usage

```
DataFrame_to_series(idx = 0)
```

Arguments

`idx`	Index of the column to return as Series. Defaults to 0, which is the first column.

Value

Series or NULL

Examples

```
df = as_polars_df(iris[1:10, ])

# default is to extract the first column
df$to_series()

# Polars is 0-indexed, so we use idx = 1 to extract the *2nd* column
df$to_series(idx = 1)

# doesn't error if the column isn't there
df$to_series(idx = 8)
```

DataFrame_to_struct *Convert DataFrame to a Series of type "struct"*

Description

Convert DataFrame to a Series of type "struct"

Usage

```
DataFrame_to_struct(name = "")
```

Arguments

name	Name given to the new Series

Value

A Series of type "struct"

Examples

```
# round-trip conversion from DataFrame with two columns
df = pl$DataFrame(a = 1:5, b = c("one", "two", "three", "four", "five"))
s = df$to_struct()
s

# convert to an R list
s$to_r()

# Convert back to a DataFrame
df_s = s$to_frame()
df_s
```

DataFrame_transpose *Transpose a DataFrame over the diagonal.*

Description

Transpose a DataFrame over the diagonal.

Usage

```
DataFrame_transpose(
  include_header = FALSE,
  header_name = "column",
  column_names = NULL
)
```

Arguments

include_header	If TRUE, the column names will be added as first column.
header_name	If include_header is TRUE, this determines the name of the column that will be inserted.
column_names	Character vector indicating the new column names. If NULL (default), the columns will be named as "column_1", "column_2", etc. The length of this vector must match the number of rows of the original input.

Details

This is a very expensive operation.

Transpose may be the fastest option to perform non foldable (see fold() or reduce()) row operations like median.

Polars transpose is currently eager only, likely because it is not trivial to deduce the schema.

Value

DataFrame

Examples

```
# simple use-case
as_polars_df(mtcars)$transpose(include_header = TRUE, column_names = rownames(mtcars))

# All rows must have one shared supertype, recast Categorical to String which is a supertype
# of f64, and then dataset "Iris" can be transposed
as_polars_df(iris)$with_columns(pl$col("Species")$cast(pl$String))$transpose()
```

DataFrame_unique *Drop duplicated rows*

Description

Drop duplicated rows

Usage

```
DataFrame_unique(subset = NULL, ..., keep = "any", maintain_order = FALSE)
```

Arguments

`subset`	A character vector with the names of the column(s) to use to identify duplicates. If `NULL` (default), use all columns.
`...`	Not used.
`keep`	Which of the duplicate rows to keep: • `"any"` (default): Does not give any guarantee of which row is kept. This allows more optimizations. • `"first"`: Keep first unique row. • `"last"`: Keep last unique row. • `"none"`: Don't keep duplicate rows.
`maintain_order`	Keep the same order as the original data. Setting this to `TRUE` makes it more expensive to compute and blocks the possibility to run on the streaming engine.

Value

DataFrame

Examples

```
df = pl$DataFrame(
  x = c(1:3, 1:3, 3:1, 1L),
  y = c(1:3, 1:3, 1:3, 1L)
)
df$height

df$unique()$height

# subset to define unique, keep only last or first
df$unique(subset = "x", keep = "last")
df$unique(subset = "x", keep = "first")

# only keep unique rows
df$unique(keep = "none")
```

DataFrame_unnest *Unnest the Struct columns of a DataFrame*

Description

Unnest the Struct columns of a DataFrame

Usage

```
DataFrame_unnest(...)
```

Arguments

...	Names of the struct columns to unnest. This doesn't accept Expr. If nothing is provided, then all columns of datatype Struct are unnested.

Value

A DataFrame where some or all columns of datatype Struct are unnested.

Examples

```
df = pl$DataFrame(
  a = 1:5,
  b = c("one", "two", "three", "four", "five"),
  c = 6:10
)$
  select(
  pl$struct("b"),
  pl$struct(c("a", "c"))$alias("a_and_c")
)
df

# by default, all struct columns are unnested
df$unnest()

# we can specify specific columns to unnest
df$unnest("a_and_c")
```

DataFrame_unpivot *Unpivot a Frame from wide to long format*

Description

Unpivot a Frame from wide to long format

Usage

```
DataFrame_unpivot(
  on = NULL,
  ...,
  index = NULL,
  variable_name = NULL,
  value_name = NULL
)
```

Arguments

on	Values to use as identifier variables. If value_vars is empty all columns that are not in id_vars will be used.
...	Not used.
index	Columns to use as identifier variables.
variable_name	Name to give to the new column containing the names of the melted columns. Defaults to "variable".
value_name	Name to give to the new column containing the values of the melted columns. Defaults to "value".

Details

Optionally leaves identifiers set.

This function is useful to massage a Frame into a format where one or more columns are identifier variables (id_vars), while all other columns, considered measured variables (value_vars), are "unpivoted" to the row axis, leaving just two non-identifier columns, 'variable' and 'value'.

Value

A new DataFrame

Examples

```
df = pl$DataFrame(
  a = c("x", "y", "z"),
  b = c(1, 3, 5),
  c = c(2, 4, 6),
  d = c(7, 8, 9)
)
df$unpivot(index = "a", on = c("b", "c", "d"))
```

DataFrame_var *Var*

Description

Aggregate the columns of this DataFrame to their variance values.

Usage

```
DataFrame_var(ddof = 1)
```

Arguments

ddof	Delta Degrees of Freedom: the divisor used in the calculation is N - ddof, where N represents the number of elements. By default ddof is 1.

Value

A DataFrame with one row.

Examples

```
as_polars_df(mtcars)$var()
```

DataFrame_with_columns *Modify/append column(s)*

Description

Add columns or modify existing ones with expressions. This is the equivalent of `dplyr::mutate()` as it keeps unmentioned columns (unlike `$select()`).

Usage

```
DataFrame_with_columns(...)
```

Arguments

...	Any expressions or string column name, or same wrapped in a list. If first and only element is a list, it is unwrapped as a list of args.

Value

A DataFrame

Examples

```
as_polars_df(iris)$with_columns(
  pl$col("Sepal.Length")$abs()$alias("abs_SL"),
  (pl$col("Sepal.Length") + 2)$alias("add_2_SL")
)

# same query
l_expr = list(
  pl$col("Sepal.Length")$abs()$alias("abs_SL"),
  (pl$col("Sepal.Length") + 2)$alias("add_2_SL")
)
as_polars_df(iris)$with_columns(l_expr)

as_polars_df(iris)$with_columns(
  pl$col("Sepal.Length")$abs(), # not named expr will keep name "Sepal.Length"
  SW_add_2 = (pl$col("Sepal.Width") + 2)
)
```

DataFrame_with_columns_seq

Modify/append column(s)

Description

Add columns or modify existing ones with expressions. This is the equivalent of `dplyr::mutate()` as it keeps unmentioned columns (unlike `$select()`).

This will run all expression sequentially instead of in parallel. Use this when the work per expression is cheap. Otherwise, `$with_columns()` should be preferred.

Usage

```
DataFrame_with_columns_seq(...)
```

Arguments

...	Any expressions or string column name, or same wrapped in a list. If first and only element is a list, it is unwrapped as a list of args.

Value

A DataFrame

Examples

```
as_polars_df(iris)$with_columns_seq(
  pl$col("Sepal.Length")$abs()$alias("abs_SL"),
  (pl$col("Sepal.Length") + 2)$alias("add_2_SL")
)
```

```
# same query
l_expr = list(
  pl$col("Sepal.Length")$abs()$alias("abs_SL"),
  (pl$col("Sepal.Length") + 2)$alias("add_2_SL")
)
as_polars_df(iris)$with_columns_seq(l_expr)

as_polars_df(iris)$with_columns_seq(
  pl$col("Sepal.Length")$abs(), # not named expr will keep name "Sepal.Length"
  SW_add_2 = (pl$col("Sepal.Width") + 2)
)
```

DataFrame_with_row_index

Add a column for row indices

Description

Add a new column at index 0 that counts the rows

Usage

```
DataFrame_with_row_index(name, offset = NULL)
```

Arguments

name	string name of the created column
offset	positive integer offset for the start of the counter

Value

A new DataFrame object with a counter column in front

Examples

```
df = as_polars_df(mtcars)

# by default, the index starts at 0 (to mimic the behavior of Python Polars)
df$with_row_index("idx")

# but in R, we use a 1-index
df$with_row_index("idx", offset = 1)
```

DataFrame_write_csv *Write to comma-separated values (CSV) file*

Description

Write to comma-separated values (CSV) file

Usage

```
DataFrame_write_csv(
  file,
  ...,
  include_bom = FALSE,
  include_header = TRUE,
  separator = ",",
  line_terminator = "\n",
  quote_char = "\"",
  batch_size = 1024,
  datetime_format = NULL,
  date_format = NULL,
  time_format = NULL,
  float_precision = NULL,
  null_values = "",
  quote_style = "necessary"
)
```

Arguments

`file`	File path to which the result should be written.
`...`	Ignored.
`include_bom`	Whether to include UTF-8 BOM (byte order mark) in the CSV output.
`include_header`	Whether to include header in the CSV output.
`separator`	Separate CSV fields with this symbol.
`line_terminator`	String used to end each row.
`quote_char`	Byte to use as quoting character.
`batch_size`	Number of rows that will be processed per thread.
`datetime_format`	A format string, with the specifiers defined by the chrono Rust crate. If no format specified, the default fractional-second precision is inferred from the maximum timeunit found in the frame's Datetime cols (if any).
`date_format`	A format string, with the specifiers defined by the chrono Rust crate.
`time_format`	A format string, with the specifiers defined by the chrono Rust crate.

`float_precision`
: Number of decimal places to write, applied to both Float32 and Float64 datatypes.

`null_values`
: A string representing null values (defaulting to the empty string).

`quote_style`
: Determines the quoting strategy used.

- `"necessary"` (default): This puts quotes around fields only when necessary. They are necessary when fields contain a quote, delimiter or record terminator. Quotes are also necessary when writing an empty record (which is indistinguishable from a record with one empty field). This is the default.
- `"always"`: This puts quotes around every field.
- `"non_numeric"`: This puts quotes around all fields that are non-numeric. Namely, when writing a field that does not parse as a valid float or integer, then quotes will be used even if they aren't strictly necessary.
- `"never"`: This never puts quotes around fields, even if that results in invalid CSV data (e.g. by not quoting strings containing the separator).

Value

Invisibly returns the input DataFrame.

Examples

```
dat = as_polars_df(mtcars)

destination = tempfile(fileext = ".csv")
dat$select(pl$col("drat", "mpg"))$write_csv(destination)

pl$read_csv(destination)
```

DataFrame_write_ipc *Write to Arrow IPC file (a.k.a Feather file)*

Description

Write to Arrow IPC file (a.k.a Feather file)

Usage

```
DataFrame_write_ipc(
  file,
  compression = c("uncompressed", "zstd", "lz4"),
  ...,
  compat_level = TRUE
)
```

Arguments

`file`	File path to which the result should be written.
`compression`	`NULL` or a character of the compression method, `"uncompressed"` or "lz4" or "zstd". `NULL` is equivalent to `"uncompressed"`. Choose "zstd" for good compression performance. Choose "lz4" for fast compression/decompression.
`...`	Ignored.
`compat_level`	Use a specific compatibility level when exporting Polars' internal data structures. This can be: • an integer indicating the compatibility version (currently only 0 for oldest and 1 for newest); • a logical value with `TRUE` for the newest version and `FALSE` for the oldest version.

Value

Invisibly returns the input DataFrame.

See Also

- `<DataFrame>$to_raw_ipc()`

Examples

```
dat = as_polars_df(mtcars)

destination = tempfile(fileext = ".arrow")
dat$write_ipc(destination)

if (require("arrow", quietly = TRUE)) {
  arrow::read_ipc_file(destination, as_data_frame = FALSE)
}
```

`DataFrame_write_json` *Write to JSON file*

Description

Write to JSON file

Usage

```
DataFrame_write_json(file, ..., pretty = FALSE, row_oriented = FALSE)
```

Arguments

`file`	File path to which the result should be written.
`...`	Ignored.
`pretty`	Pretty serialize JSON.
`row_oriented`	Write to row-oriented JSON. This is slower, but more common.

Value

Invisibly returns the input DataFrame.

Examples

```
if (require("jsonlite", quiet = TRUE)) {
  dat = as_polars_df(head(mtcars))
  destination = tempfile()

  dat$select(pl$col("drat", "mpg"))$write_json(destination)
  jsonlite::fromJSON(destination)

  dat$select(pl$col("drat", "mpg"))$write_json(destination, row_oriented = TRUE)
  jsonlite::fromJSON(destination)
}
```

DataFrame_write_ndjson

Write to NDJSON file

Description

Write to NDJSON file

Usage

```
DataFrame_write_ndjson(file)
```

Arguments

`file`	File path to which the result should be written.

Value

Invisibly returns the input DataFrame.

Examples

```
dat = as_polars_df(head(mtcars))

destination = tempfile()
dat$select(pl$col("drat", "mpg"))$write_ndjson(destination)

pl$read_ndjson(destination)
```

DataFrame_write_parquet

Write to parquet file

Description

Write to parquet file

Usage

```
DataFrame_write_parquet(
  file,
  ...,
  compression = "zstd",
  compression_level = 3,
  statistics = TRUE,
  row_group_size = NULL,
  data_page_size = NULL,
  partition_by = NULL,
  partition_chunk_size_bytes = 4294967296
)
```

Arguments

`file`	File path to which the result should be written. This should be a path to a directory if writing a partitioned dataset.
`...`	Ignored.
`compression`	String. The compression method. One of: • "lz4": fast compression/decompression. • "uncompressed" • "snappy": this guarantees that the parquet file will be compatible with older parquet readers. • "gzip" • "lzo" • "brotli" • "zstd": good compression performance.

`compression_level`
: NULL or Integer. The level of compression to use. Only used if method is one of 'gzip', 'brotli', or 'zstd'. Higher compression means smaller files on disk:

- "gzip": min-level: 0, max-level: 10.
- "brotli": min-level: 0, max-level: 11.
- "zstd": min-level: 1, max-level: 22.

`statistics`
: Whether statistics should be written to the Parquet headers. Possible values:

- TRUE: enable default set of statistics (default)
- FALSE: disable all statistics
- "full": calculate and write all available statistics.
- A named list where all values must be TRUE or FALSE, e.g. `list(min = TRUE, max = FALSE)`. Statistics available are "min", "max", "distinct_count", "null_count".

`row_group_size`
: NULL or Integer. Size of the row groups in number of rows. If NULL (default), the chunks of the DataFrame are used. Writing in smaller chunks may reduce memory pressure and improve writing speeds.

`data_page_size`
: Size of the data page in bytes. If NULL (default), it is set to 1024^2 bytes. will be ~1MB.

`partition_by`
: Column(s) to partition by. A partitioned dataset will be written if this is specified.

`partition_chunk_size_bytes`
: Approximate size to split DataFrames within a single partition when writing. Note this is calculated using the size of the DataFrame in memory - the size of the output file may differ depending on the file format / compression.

Value

Invisibly returns the input DataFrame.

Examples

```
dat = as_polars_df(mtcars)

# write data to a single parquet file
destination = withr::local_tempfile(fileext = ".parquet")
dat$write_parquet(destination)

# write data to folder with a hive-partitioned structure
dest_folder = withr::local_tempdir()
dat$write_parquet(dest_folder, partition_by = c("gear", "cyl"))
list.files(dest_folder, recursive = TRUE)
```

DataType_Array *Create Array DataType*

Description

The Array and List datatypes are very similar. The only difference is that sub-arrays all have the same length while sublists can have different lengths. Array methods can be accessed via the `$arr` subnamespace.

Usage

```
DataType_Array(datatype = "unknown", width)
```

Arguments

`datatype`	An inner DataType. The default is `"Unknown"` and is only a placeholder for when inner DataType does not matter, e.g. as used in example.
`width`	The length of the arrays.

Value

An array DataType with an inner DataType

Examples

```
# basic Array
pl$Array(pl$Int32, 4)
# some nested Array
pl$Array(pl$Array(pl$Boolean, 3), 2)
```

DataType_Categorical *Create Categorical DataType*

Description

Create Categorical DataType

Usage

```
DataType_Categorical(ordering = "physical")
```

Arguments

`ordering`	Either `"physical"` (default) or `"lexical"`.

Details

When a categorical variable is created, its string values (or "lexical" values) are stored and encoded as integers ("physical" values) by order of appearance. Therefore, sorting a categorical value can be done either on the lexical or on the physical values. See Examples.

Value

A Categorical DataType

Examples

```
# default is to order by physical values
df = pl$DataFrame(x = c("z", "z", "k", "a", "z"), schema = list(x = pl$Categorical()))
df$sort("x")

# when setting ordering = "lexical", sorting will be based on the strings
df_lex = pl$DataFrame(
  x = c("z", "z", "k", "a", "z"),
  schema = list(x = pl$Categorical("lexical"))
)
df_lex$sort("x")
```

DataType_contains_categoricals

Check whether the data type contains categoricals

Description

Check whether the data type contains categoricals

Usage

```
DataType_contains_categoricals()
```

Value

A logical value

Examples

```
pl$List(pl$Categorical())$contains_categoricals()
pl$List(pl$Enum(c("a", "b")))$contains_categoricals()
pl$List(pl$Float32)$contains_categoricals()
pl$List(pl$List(pl$Categorical()))$contains_categoricals()
```

DataType_contains_views

Check whether the data type contains views

Description

Check whether the data type contains views

Usage

```
DataType_contains_views()
```

Value

A logical value

Examples

```
pl$List(pl$String)$contains_views()
pl$List(pl$Binary)$contains_views()
pl$List(pl$Float32)$contains_views()
pl$List(pl$List(pl$Binary))$contains_views()
```

DataType_Datetime

Data type representing a calendar date and time of day.

Description

The underlying representation of this type is a 64-bit signed integer. The integer indicates the number of time units since the Unix epoch (1970-01-01 00:00:00). The number can be negative to indicate datetimes before the epoch.

Usage

```
DataType_Datetime(time_unit = "us", time_zone = NULL)
```

Arguments

`time_unit`	Unit of time. One of `"ms"`, `"us"` (default) or `"ns"`.
`time_zone`	Time zone string, as defined in `OlsonNames()`. Setting `timezone = "*"` will match any timezone, which can be useful to select all Datetime columns containing a timezone.

Value

Datetime DataType

Examples

```
pl$Datetime("ns", "Pacific/Samoa")

df = pl$DataFrame(
  naive_time = as.POSIXct("1900-01-01"),
  zoned_time = as.POSIXct("1900-01-01", "UTC")
)
df

df$select(pl$col(pl$Datetime("us", "*")))
```

DataType_Duration *Data type representing a time duration*

Description

Data type representing a time duration

Usage

```
DataType_Duration(time_unit = "us")
```

Arguments

time_unit	Unit of time. One of "ms", "us" (default) or "ns".

Value

Duration DataType

Examples

```
test = pl$DataFrame(
  a = 1:2,
  b = c("a", "b"),
  c = pl$duration(weeks = c(1, 2), days = c(0, 2))
)

# select all columns of type "duration"
test$select(pl$col(pl$Duration()))
```

DataType_Enum *Create Enum DataType*

Description

An Enum is a fixed set categorical encoding of a set of strings. It is similar to the Categorical data type, but the categories are explicitly provided by the user and cannot be modified.

Usage

```
DataType_Enum(categories)
```

Arguments

categories	A character vector specifying the categories of the variable.

Details

This functionality is **unstable**. It is a work-in-progress feature and may not always work as expected. It may be changed at any point without it being considered a breaking change.

Value

An Enum DataType

Examples

```
pl$DataFrame(
  x = c("Polar", "Panda", "Brown", "Brown", "Polar"),
  schema = list(x = pl$Enum(c("Polar", "Panda", "Brown")))
)

# All values of the variable have to be in the categories
dtype = pl$Enum(c("Polar", "Panda", "Brown"))
tryCatch(
  pl$DataFrame(
    x = c("Polar", "Panda", "Brown", "Brown", "Polar", "Black"),
    schema = list(x = dtype)
  ),
  error = function(e) e
)

# Comparing two Enum is only valid if they have the same categories
df = pl$DataFrame(
  x = c("Polar", "Panda", "Brown", "Brown", "Polar"),
  y = c("Polar", "Polar", "Polar", "Brown", "Brown"),
  z = c("Polar", "Polar", "Polar", "Brown", "Brown"),
  schema = list(
    x = pl$Enum(c("Polar", "Panda", "Brown")),
```

```
    y = pl$Enum(c("Polar", "Panda", "Brown")),
    z = pl$Enum(c("Polar", "Black", "Brown"))
  )
)

# Same categories
df$with_columns(x_eq_y = pl$col("x") == pl$col("y"))

# Different categories
tryCatch(
  df$with_columns(x_eq_z = pl$col("x") == pl$col("z")),
  error = function(e) e
)
```

DataType_is_array *Check whether the data type is an array type*

Description

Check whether the data type is an array type

Usage

```
DataType_is_array()
```

Value

A logical value

Examples

```
pl$Array(width = 2)$is_array()
pl$Float32$is_array()
```

DataType_is_binary *Check whether the data type is a binary type*

Description

Check whether the data type is a binary type

Usage

```
DataType_is_binary()
```

Value

A logical value

Examples

```
pl$Binary$is_binary()
pl$Float32$is_binary()
```

DataType_is_bool *Check whether the data type is a boolean type*

Description

Check whether the data type is a boolean type

Usage

```
DataType_is_bool()
```

Value

A logical value

Examples

```
pl$Boolean$is_bool()
pl$Float32$is_bool()
```

DataType_is_categorical *Check whether the data type is a Categorical type*

Description

Check whether the data type is a Categorical type

Usage

```
DataType_is_categorical()
```

Value

A logical value

Examples

```
pl$Categorical()$is_categorical()
pl$Enum(c("a", "b"))$is_categorical()
```

DataType_is_enum — *Check whether the data type is an Enum type*

Description

Check whether the data type is an Enum type

Usage

```
DataType_is_enum()
```

Value

A logical value

Examples

```
pl$Enum(c("a", "b"))$is_enum()
pl$Categorical()$is_enum()
```

DataType_is_float — *Check whether the data type is a float type*

Description

Check whether the data type is a float type

Usage

```
DataType_is_float()
```

Value

A logical value

Examples

```
pl$Float32$is_float()
pl$Int32$is_float()
```

DataType_is_integer *Check whether the data type is an integer type*

Description

Check whether the data type is an integer type

Usage

```
DataType_is_integer()
```

Value

A logical value

Examples

```
pl$Int32$is_integer()
pl$Float32$is_integer()
```

DataType_is_known *Check whether the data type is known*

Description

Check whether the data type is known

Usage

```
DataType_is_known()
```

Value

A logical value

Examples

```
pl$String$is_known()
pl$Unknown$is_known()
```

DataType_is_list *Check whether the data type is a list type*

Description

Check whether the data type is a list type

Usage

```
DataType_is_list()
```

Value

A logical value

Examples

```
pl$List()$is_list()
pl$Float32$is_list()
```

DataType_is_logical *Check whether the data type is a logical type*

Description

Check whether the data type is a logical type

Usage

```
DataType_is_logical()
```

Value

A logical value

DataType_is_nested *Check whether the data type is a nested type*

Description

Check whether the data type is a nested type

Usage

```
DataType_is_nested()
```

Value

A logical value

Examples

```
pl$List()$is_nested()
pl$Array(width = 2)$is_nested()
pl$Float32$is_nested()
```

DataType_is_null *Check whether the data type is a null type*

Description

Check whether the data type is a null type

Usage

```
DataType_is_null()
```

Value

A logical value

Examples

```
pl$Null$is_null()
pl$Float32$is_null()
```

DataType_is_numeric *Check whether the data type is a numeric type*

Description

Check whether the data type is a numeric type

Usage

```
DataType_is_numeric()
```

Value

A logical value

Examples

```
pl$Float32$is_numeric()
pl$Int32$is_numeric()
pl$String$is_numeric()
```

DataType_is_ord *Check whether the data type is an ordinal type*

Description

Check whether the data type is an ordinal type

Usage

```
DataType_is_ord()
```

Value

A logical value

Examples

```
pl$String$is_ord()
pl$Categorical()$is_ord()
```

DataType_is_primitive *Check whether the data type is a primitive type*

Description

Check whether the data type is a primitive type

Usage

```
DataType_is_primitive()
```

Value

A logical value

Examples

```
pl$Float32$is_primitive()
pl$List()$is_primitive()
```

DataType_is_signed_integer *Check whether the data type is a signed integer type*

Description

Check whether the data type is a signed integer type

Usage

```
DataType_is_signed_integer()
```

Value

A logical value

Examples

```
pl$Int32$is_signed_integer()
pl$UInt32$is_signed_integer()
```

DataType_is_string *Check whether the data type is a String type*

Description

Check whether the data type is a String type

Usage

```
DataType_is_string()
```

Value

A logical value

Examples

```
pl$String$is_string()
pl$Float32$is_string()
```

DataType_is_struct *Check whether the data type is a temporal type*

Description

Check whether the data type is a temporal type

Usage

```
DataType_is_struct()
```

Value

A logical value

Examples

```
pl$Struct()$is_struct()
pl$Float32$is_struct()
```

DataType_is_temporal *Check whether the data type is a temporal type*

Description

Check whether the data type is a temporal type

Usage

```
DataType_is_temporal()
```

Value

A logical value

Examples

```
pl$Date$is_temporal()
pl$Float32$is_temporal()
```

DataType_is_unsigned_integer *Check whether the data type is an unsigned integer type*

Description

Check whether the data type is an unsigned integer type

Usage

```
DataType_is_unsigned_integer()
```

Value

A logical value

Examples

```
pl$UInt32$is_unsigned_integer()
pl$Int32$is_unsigned_integer()
```

DataType_List — *Create List DataType*

Description

Create List DataType

Usage

```
DataType_List(datatype = "unknown")
```

Arguments

datatype	The inner DataType.

Value

A list DataType with an inner DataType

Examples

```
# some nested List
pl$List(pl$List(pl$Boolean))

# check if some maybe_list is a List DataType
maybe_List = pl$List(pl$UInt64)
pl$same_outer_dt(maybe_List, pl$List())
```

DataType_Struct — *Create Struct DataType*

Description

One can create a `Struct` data type with `pl$Struct()`. There are also multiple ways to create columns of data type `Struct` in a `DataFrame` or a `Series`, see the examples.

Usage

```
DataType_Struct(...)
```

Arguments

...	Either named inputs of the form `field_name = datatype` or objects of class `RPolarsField` created by `pl$Field()`.

Value

A Struct DataType containing a list of Fields

Examples

```
# create a Struct-DataType
pl$Struct(foo = pl$Int32, pl$Field("bar", pl$Boolean))

# check if an element is any kind of Struct()
test = pl$Struct(a = pl$UInt64)
pl$same_outer_dt(test, pl$Struct())

# `test` is a type of Struct, but it doesn't mean it is equal to an empty Struct
test == pl$Struct()

# The way to create a `Series` of type `Struct` is a bit convoluted as it involves
# `data.frame()`, `list()`, and `I()`:
as_polars_series(
  data.frame(a = 1:2, b = I(list(c("x", "y"), "z")))
)

# A slightly simpler way would be via `tibble::tibble()` or
# `data.table::data.table()`:
if (requireNamespace("tibble", quietly = TRUE)) {
  as_polars_series(
    tibble::tibble(a = 1:2, b = list(c("x", "y"), "z"))
  )
}

# Finally, one can use `pl$struct()` to convert existing columns or `Series`
# to a `Struct`:
x = pl$DataFrame(
  a = 1:2,
  b = list(c("x", "y"), "z")
)

out = x$select(pl$struct(c("a", "b")))
out

out$schema
```

---

dim.RPolarsDataFrame *Get the dimensions*

Description

Get the dimensions

Usage

```
## S3 method for class 'RPolarsDataFrame'
dim(x)

## S3 method for class 'RPolarsLazyFrame'
dim(x)
```

Arguments

x	A DataFrame or LazyFrame

---

dimnames.RPolarsDataFrame *Get the row and column names*

Description

Get the row and column names

Usage

```
## S3 method for class 'RPolarsDataFrame'
dimnames(x)

## S3 method for class 'RPolarsLazyFrame'
dimnames(x)
```

Arguments

x	A DataFrame or LazyFrame

---

docs_translations *Translation definitions across python, R and polars.*

Description

#Comments for how the R and python world translates into polars:

R and python are both high-level glue languages great for Data Science. Rust is a pedantic low-level language with similar use cases as C and C++. Polars is written in ~100k lines of rust and has a rust API. Py-polars the python API for polars, is implemented as an interface with the rust API. r-polars is very parallel to py-polars except it interfaces with R. The performance and behavior are unexpectedly quite similar as the 'engine' is the exact same rust code and data structures.

Format

info

Value

Not applicable

Translation details

R and the integerish:

R only has a native Int32 type, no Uint32, Int64, UInt64 , ... types. These days Int32 is getting a bit small, to refer to more rows than ~ 2^31-1. There are packages which provide int64, but the most normal hack' is to just use floats as 'integerish'. There is an unique float64 value for every integer up to about 2^52 which is plenty for all practical concerns. Some polars methods may accept or return a floats even though an integer ideally would be more accurate. Most R functions intermix Int32 (integer) and Float64 (double) seamlessly.

Missingness:

R has allocated a value in every vector type to signal missingness, these are collectively called `NAs`. Polars uses a bool bitmask to signal `NA`-like missing value and it is called `Null` and `Nulls` in plural. Not to confuse with R `NULL` (see paragraph below). Polars supports missingness for any possible type as it kept separately in the bitmask. In python lists the symbol `None` can carry a similar meaning. R `NA` ~ polars `Null` ~ py-polars `[None]` (in a py list)

Sorting and comparisons:

From writing a lot of tests for all implementations, it appears polars does not have a fully consistent nor well documented behavior, when it comes to comparisons and sorting of floats. Though some general thumb rules do apply: Polars have chosen to define in sorting that `Null` is a value lower than `-Inf` as in `Expr.arg_min()` However except when `Null` is ignored `Expr.min()`, there is a `Expr.nan_min()` but no `Expr.nan_min()`. `NaN` is sometimes a value higher than Inf and sometimes regarded as a `Null`. Polars conventions `NaN` > `Inf` > `99` > `-99` > `-Inf` > `Null` `Null` == `Null` yields often times false, sometimes true, sometimes `Null`. The documentation or examples do not reveal this variations. The best to do, when in doubt, is to do test sort on a small Series/Column of all values.

#' R `NaN` ~ polars `NaN` ~ python `[float("NaN")]` #only floats have `NaNs`

R `Inf` ~ polars `inf` ~ python `[float("inf")]` #only floats have `Inf`

NULL IS NOT Null is not NULL:

The R NULL does not exist inside polars frames and series and so on. It resembles the Option::None in the hidden rust code. It resembles the python `None`. In all three languages the `NULL`/`None`/`None` are used in this context as function argument to signal default behavior or perhaps a deactivated feature. R `NULL` does NOT translate into the polars bitmask `Null`, that is `NA`. R `NULL` ~ rust-polars `Option::None` ~ pypolars `None` #typically used for function arguments

LISTS, FRAMES AND DICTS:

The following translations are relevant when loading data into polars. The R list appears similar to python dictionary (hashmap), but is implemented more similar to the python list (array of pointers). R list do support string naming elements via a string vector. In polars both lists (of vectors or series) and data.frames can be used to construct a polars DataFrame, just a as dictionaries would be used in python. In terms of loading in/out data the follow translation holds: R `data.frame`/`list` ~ polars `DataFrame` ~ python `dictonary`

Series and Vectors:

The R vector (Integer, Double, Character, ...) resembles the Series as both are external from any frame and can be of any length. The implementation is quite different. E.g. `for`-loop appending to an R vector is considered quite bad for performance. The vector will be fully rewritten in memory for every append. The polars Series has chunked memory allocation, which allows any append data to be written only. However fragmented memory is not great for fast computations and polars objects have a `rechunk()`-method, to reallocate chunks into one. Rechunk might be called implicitly by polars. In the context of constructing. Series and extracting data , the following translation holds: R `vector` ~ polars `Series/column` ~ python `list`

Expressions:

The polars Expr do not have any base R counterpart. Expr are analogous to how ggplot split plotting instructions from the rendering. Base R plot immediately pushes any instruction by adding e.g. pixels to a .png canvas. `ggplot` collects instructions and in the end when executed the rendering can be performed with optimization across all instructions. Btw `ggplot` command-syntax is a monoid meaning the order does not matter, that is not the case for polars Expr. Polars Expr's can be understood as a DSL (domain specific language) that expresses syntax trees of instructions. R expressions evaluate to syntax trees also, but it difficult to optimize the execution order automatically, without rewriting the code. A great selling point of Polars is that any query will be optimized. Expr are very light-weight symbols chained together.

`DynamicGroupBy_agg` *Aggregate over a DynamicGroupBy*

Description

Aggregate a DataFrame over a time or integer window created with `$group_by_dynamic()`.

Usage

```
DynamicGroupBy_agg(...)
```

Arguments

`...`	Exprs to aggregate over. Those can also be passed wrapped in a list, e.g `$agg(list(e1,e2,e3))`.

Value

An aggregated DataFrame

Examples

```
df = pl$DataFrame(
  time = pl$datetime_range(
    start = strptime("2021-12-16 00:00:00", format = "%Y-%m-%d %H:%M:%S", tz = "UTC"),
    end = strptime("2021-12-16 03:00:00", format = "%Y-%m-%d %H:%M:%S", tz = "UTC"),
    interval = "30m"
  ),
```

```
  n = 0:6
)

# get the sum in the following hour relative to the "time" column
df$group_by_dynamic("time", every = "1h")$agg(
  vals = pl$col("n"),
  sum = pl$col("n")$sum()
)

# using "include_boundaries = TRUE" is helpful to see the period considered
df$group_by_dynamic("time", every = "1h", include_boundaries = TRUE)$agg(
  vals = pl$col("n")
)

# in the example above, the values didn't include the one *exactly* 1h after
# the start because "closed = 'left'" by default.
# Changing it to "right" includes values that are exactly 1h after. Note that
# the value at 00:00:00 now becomes included in the interval [23:00:00 - 00:00:00],
# even if this interval wasn't there originally
df$group_by_dynamic("time", every = "1h", closed = "right")$agg(
  vals = pl$col("n")
)
# To keep both boundaries, we use "closed = 'both'". Some values now belong to
# several groups:
df$group_by_dynamic("time", every = "1h", closed = "both")$agg(
  vals = pl$col("n")
)

# Dynamic group bys can also be combined with grouping on normal keys
df = df$with_columns(
  groups = as_polars_series(c("a", "a", "a", "b", "b", "a", "a"))
)
df

df$group_by_dynamic(
  "time",
  every = "1h",
  closed = "both",
  group_by = "groups",
  include_boundaries = TRUE
)$agg(pl$col("n"))

# We can also create a dynamic group by based on an index column
df = pl$LazyFrame(
  idx = 0:5,
  A = c("A", "A", "B", "B", "B", "C")
)$with_columns(pl$col("idx")$set_sorted())
df

df$group_by_dynamic(
  "idx",
  every = "2i",
  period = "3i",
```

```
  include_boundaries = TRUE,
  closed = "right"
)$agg(A_agg_list = pl$col("A"))
```

DynamicGroupBy_class *Operations on Polars DataFrame grouped on time or integer values*

Description

This class comes from <DataFrame>$group_by_dynamic().

Examples

```
df = pl$DataFrame(
  time = pl$datetime_range(
    start = strptime("2021-12-16 00:00:00", format = "%Y-%m-%d %H:%M:%S", tz = "UTC"),
    end = strptime("2021-12-16 03:00:00", format = "%Y-%m-%d %H:%M:%S", tz = "UTC"),
    interval = "30m"
  ),
  n = 0:6
)

# get the sum in the following hour relative to the "time" column
df$group_by_dynamic("time", every = "1h")
```

DynamicGroupBy_ungroup

Ungroup a DynamicGroupBy object

Description

Revert the $group_by_dynamic() operation. Doing <DataFrame>$group_by_dynamic(...)$ungroup() returns the original DataFrame.

Usage

```
DynamicGroupBy_ungroup()
```

Value

DataFrame

Examples

```
df = pl$DataFrame(
  time = pl$datetime_range(
    start = strptime("2021-12-16 00:00:00", format = "%Y-%m-%d %H:%M:%S", tz = "UTC"),
    end = strptime("2021-12-16 03:00:00", format = "%Y-%m-%d %H:%M:%S", tz = "UTC"),
    interval = "30m"
  ),
  n = 0:6
)
df

df$group_by_dynamic("time", every = "1h")$ungroup()
```

Expr_abs *Compute the absolute values*

Description

Compute the absolute values

Usage

```
Expr_abs()
```

Value

Expr

Examples

```
pl$DataFrame(a = -1:1)$
  with_columns(abs = pl$col("a")$abs())
```

Expr_add *Add two expressions*

Description

Method equivalent of addition operator `expr + other`.

Usage

```
Expr_add(other)
```

Arguments

`other`	numeric or string value; accepts expression input.

Value

Expr

See Also

- Arithmetic operators

Examples

```
df = pl$DataFrame(x = 1:5)

df$with_columns(
  `x+int` = pl$col("x")$add(2L),
  `x+expr` = pl$col("x")$add(pl$col("x")$cum_prod())
)

df = pl$DataFrame(
  x = c("a", "d", "g"),
  y = c("b", "e", "h"),
  z = c("c", "f", "i")
)

df$with_columns(
  pl$col("x")$add(pl$col("y"))$add(pl$col("z"))$alias("xyz")
)
```

Expr_agg_groups *Aggregate groups*

Description

Get the group indexes of the group by operation. Should be used in aggregation context only.

Usage

```
Expr_agg_groups()
```

Value

Expr

Examples

```
df = pl$DataFrame(list(
  group = c("one", "one", "one", "two", "two", "two"),
  value = c(94, 95, 96, 97, 97, 99)
))
df$group_by("group", maintain_order = TRUE)$agg(pl$col("value")$agg_groups())
```

Expr_alias — *Rename Expr output*

Description

Rename the output of an expression.

Usage

```
Expr_alias(name)
```

Arguments

name	New name of output

Value

Expr

Examples

```
pl$col("bob")$alias("alice")
```

Expr_all — *Apply logical AND on a column*

Description

Check if all values in a Boolean column are TRUE. This method is an expression - not to be confused with pl$all() which is a function to select all columns.

Usage

```
Expr_all(..., ignore_nulls = TRUE)
```

Arguments

...	Ignored.
ignore_nulls	If TRUE (default), ignore null values. If FALSE, Kleene logic is used to deal with nulls: if the column contains any null values and no TRUE values, the output is null.

Value

A logical value

Examples

```
df = pl$DataFrame(
  a = c(TRUE, TRUE),
  b = c(TRUE, FALSE),
  c = c(NA, TRUE),
  d = c(NA, NA)
)

# By default, ignore null values. If there are only nulls, then all() returns
# TRUE.
df$select(pl$col("*")$all())

# If we set ignore_nulls = FALSE, then we don't know if all values in column
# "c" are TRUE, so it returns null
df$select(pl$col("*")$all(ignore_nulls = FALSE))
```

Expr_and *Apply logical AND on two expressions*

Description

Combine two boolean expressions with AND.

Usage

```
Expr_and(other)
```

Arguments

other	numeric or string value; accepts expression input.

Value

Expr

Examples

```
pl$lit(TRUE) & TRUE
pl$lit(TRUE)$and(pl$lit(TRUE))
```

Expr_any — *Apply logical OR on a column*

Description

Check if any boolean value in a Boolean column is `TRUE`.

Usage

```
Expr_any(..., ignore_nulls = TRUE)
```

Arguments

`...`	Ignored.
`ignore_nulls`	If `TRUE` (default), ignore null values. If `FALSE`, Kleene logic is used to deal with nulls: if the column contains any null values and no `TRUE` values, the output is null.

Value

A logical value

Examples

```
df = pl$DataFrame(
  a = c(TRUE, FALSE),
  b = c(FALSE, FALSE),
  c = c(NA, FALSE)
)

df$select(pl$col("*")$any())

# If we set ignore_nulls = FALSE, then we don't know if any values in column
# "c" is TRUE, so it returns null
df$select(pl$col("*")$any(ignore_nulls = FALSE))
```

Expr_append — *Append expressions*

Description

This is done by adding the chunks of `other` to this `output`.

Usage

```
Expr_append(other, upcast = TRUE)
```

Arguments

other	Expr or something coercible to an Expr.
upcast	Cast both Expr to a common supertype if they have one.

Value

Expr

Examples

```
# append bottom to to row
df = pl$DataFrame(list(a = 1:3, b = c(NA_real_, 4, 5)))
df$select(pl$all()$head(1)$append(pl$all()$tail(1)))

# implicit upcast, when default = TRUE
pl$DataFrame(list())$select(pl$lit(42)$append(42L))
pl$DataFrame(list())$select(pl$lit(42)$append(FALSE))
pl$DataFrame(list())$select(pl$lit("Bob")$append(FALSE))
```

Expr_approx_n_unique *Approx count unique values*

Description

This is done using the HyperLogLog++ algorithm for cardinality estimation.

Usage

```
Expr_approx_n_unique()
```

Value

Expr

Examples

```
as_polars_df(mtcars)$select(count = pl$col("cyl")$approx_n_unique())
```

Expr_arccos *Compute inverse cosine*

Description

Compute inverse cosine

Usage

```
Expr_arccos()
```

Value

Expr

Examples

```
pl$DataFrame(a = c(-1, cos(0.5), 0, 1, NA_real_))$
  with_columns(arccos = pl$col("a")$arccos())
```

Expr_arccosh *Compute inverse hyperbolic cosine*

Description

Compute inverse hyperbolic cosine

Usage

```
Expr_arccosh()
```

Value

Expr

Examples

```
pl$DataFrame(a = c(-1, cosh(0.5), 0, 1, NA_real_))$
  with_columns(arccosh = pl$col("a")$arccosh())
```

Expr_arcsin — *Compute inverse sine*

Description

Compute inverse sine

Usage

```
Expr_arcsin()
```

Value

Expr

Examples

```
pl$DataFrame(a = c(-1, sin(0.5), 0, 1, NA_real_))$
  with_columns(arcsin = pl$col("a")$arcsin())
```

Expr_arcsinh — *Compute inverse hyperbolic sine*

Description

Compute inverse hyperbolic sine

Usage

```
Expr_arcsinh()
```

Value

Expr

Examples

```
pl$DataFrame(a = c(-1, sinh(0.5), 0, 1, NA_real_))$
  with_columns(arcsinh = pl$col("a")$arcsinh())
```

Expr_arctan — *Compute inverse tangent*

Description

Compute inverse tangent

Usage

```
Expr_arctan()
```

Value

Expr

Examples

```
pl$DataFrame(a = c(-1, tan(0.5), 0, 1, NA_real_))$
  with_columns(arctan = pl$col("a")$arctan())
```

Expr_arctanh — *Compute inverse hyperbolic tangent*

Description

Compute inverse hyperbolic tangent

Usage

```
Expr_arctanh()
```

Value

Expr

Examples

```
pl$DataFrame(a = c(-1, tanh(0.5), 0, 1, NA_real_))$
  with_columns(arctanh = pl$col("a")$arctanh())
```

Expr_arg_max *Index of max value*

Description

Get the index of the maximal value.

Usage

```
Expr_arg_max()
```

Value

Expr

Examples

```
pl$DataFrame(
  a = c(6, 1, 0, NA, Inf, NaN)
)$with_columns(arg_max = pl$col("a")$arg_max())
```

Expr_arg_min *Index of min value*

Description

Get the index of the minimal value.

Usage

```
Expr_arg_min()
```

Value

Expr

Examples

```
pl$DataFrame(
  a = c(6, 1, 0, NA, Inf, NaN)
)$with_columns(arg_min = pl$col("a")$arg_min())
```

Expr_arg_sort *Index of a sort*

Description

Get the index values that would sort this column.

Usage

```
Expr_arg_sort(descending = FALSE, nulls_last = FALSE)
```

Arguments

descending	A logical. If TRUE, sort in descending order.
nulls_last	A logical. If TRUE, place null values last insead of first.

Value

Expr

See Also

pl$arg_sort_by() to find the row indices that would sort multiple columns.

Examples

```
pl$DataFrame(
  a = c(6, 1, 0, NA, Inf, NaN)
)$with_columns(arg_sorted = pl$col("a")$arg_sort())
```

Expr_arg_unique *Index of first unique values*

Description

This finds the position of first occurrence of each unique value.

Usage

```
Expr_arg_unique()
```

Value

Expr

Examples

```
pl$select(pl$lit(c(1:2, 1:3))$arg_unique())
```

Expr_backward_fill *Fill null values backward*

Description

Fill missing values with the next to be seen values. Syntactic sugar for `$fill_null(strategy = "backward")`.

Usage

```
Expr_backward_fill(limit = NULL)
```

Arguments

`limit`	Number of consecutive null values to fill when using the `"forward"` or `"backward"` strategy.

Value

Expr

Examples

```
pl$DataFrame(a = c(NA, 1, NA, 2, NA))$
  with_columns(
  backward = pl$col("a")$backward_fill()
)
```

Expr_bottom_k *Bottom k values*

Description

Return the `k` smallest elements. This has time complexity: $O(n + k$
$logn - \frac{k}{2})$

Usage

```
Expr_bottom_k(k)
```

Arguments

`k`	Number of top values to get.

Value

Expr

Examples

```
pl$DataFrame(a = c(6, 1, 0, NA, Inf, NaN))$select(pl$col("a")$bottom_k(5))
```

Expr_cast *Cast between DataType*

Description

Cast between DataType

Usage

```
Expr_cast(dtype, strict = TRUE)
```

Arguments

dtype	DataType to cast to.
strict	If TRUE (default), an error will be thrown if cast failed at resolve time.

Value

Expr

Examples

```
df = pl$DataFrame(a = 1:3, b = c(1, 2, 3))
df$with_columns(
  pl$col("a")$cast(pl$dtypes$Float64),
  pl$col("b")$cast(pl$dtypes$Int32)
)

# strict FALSE, inserts null for any cast failure
pl$lit(c(100, 200, 300))$cast(pl$dtypes$UInt8, strict = FALSE)$to_series()

# strict TRUE, raise any failure as an error when query is executed.
tryCatch(
  {
    pl$lit("a")$cast(pl$dtypes$Float64, strict = TRUE)$to_series()
  },
  error = function(e) e
)
```

Expr_ceil *Ceiling*

Description

Rounds up to the nearest integer value. Only works on floating point Series.

Usage

```
Expr_ceil()
```

Value

Expr

Examples

```
pl$DataFrame(a = c(0.33, 0.5, 1.02, 1.5, NaN, NA, Inf, -Inf))$with_columns(
  ceiling = pl$col("a")$ceil()
)
```

Expr_class *Polars Expressions*

Description

Expressions are all the functions and methods that are applicable to a Polars DataFrame or LazyFrame object. Some methods are under the sub-namespaces.

Sub-namespaces

arr:
`$arr` stores all array related methods.

bin:
`$bin` stores all binary related methods.

cat:
`$cat` stores all categorical related methods.

dt:
`$dt` stores all temporal related methods.

list:
`$list` stores all list related methods.

meta:
`$meta` stores all methods for working with the meta data.

name:
`$name` stores all name related methods.

str:
`$str` stores all string related methods.

struct:
`$struct` stores all struct related methods.

Examples

```
df = pl$DataFrame(
  a = 1:2,
  b = list(1:2, 3:4),
  schema = list(a = pl$Int64, b = pl$Array(pl$Int64, 2))
)

df$select(pl$col("a")$first())

df$select(pl$col("b")$arr$sum())
```

`Expr_clip` *Clip elements*

Description

Set values outside the given boundaries to the boundary value. This only works for numeric and temporal values.

Usage

```
Expr_clip(lower_bound = NULL, upper_bound = NULL)
```

Arguments

`lower_bound`	Lower bound. Accepts expression input. Strings are parsed as column names and other non-expression inputs are parsed as literals.
`upper_bound`	Upper bound. Accepts expression input. Strings are parsed as column names and other non-expression inputs are parsed as literals.

Value

Expr

Examples

```
df = pl$DataFrame(foo = c(-50L, 5L, NA_integer_, 50L), bound = c(1, 10, 1, 1))

# With the two bounds
df$with_columns(clipped = pl$col("foo")$clip(1, 10))

# Without lower bound
df$with_columns(clipped = pl$col("foo")$clip(upper_bound = 10))

# Using another column as lower bound
df$with_columns(clipped = pl$col("foo")$clip(lower_bound = "bound"))
```

Expr_cos *Compute cosine*

Description

Compute cosine

Usage

```
Expr_cos()
```

Value

Expr

Examples

```
pl$DataFrame(a = c(0, pi / 2, pi, NA_real_))$
  with_columns(cosine = pl$col("a")$cos())
```

Expr_cosh *Compute hyperbolic cosine*

Description

Compute hyperbolic cosine

Usage

```
Expr_cosh()
```

Value

Expr

Examples

```
pl$DataFrame(a = c(-1, acosh(2), 0, 1, NA_real_))$
  with_columns(cosh = pl$col("a")$cosh())
```

Expr_count *Count elements*

Description

Count the number of elements in this expression. Note that `NULL` values are also counted. `$len()` is an alias.

Usage

```
Expr_count()

Expr_len()
```

Value

Expr

Examples

```
pl$DataFrame(
  all = c(TRUE, TRUE),
  any = c(TRUE, FALSE),
  none = c(FALSE, FALSE)
)$select(
  pl$all()$count()
)
```

Expr_cum_count *Cumulative count*

Description

Get an array with the cumulative count (zero-indexed) computed at every element.

Usage

```
Expr_cum_count(reverse = FALSE)
```

Arguments

`reverse`	If `TRUE`, reverse the count.

Details

The Dtypes Int8, UInt8, Int16 and UInt16 are cast to Int64 before summing to prevent overflow issues.
`$cum_count()` does not seem to count within lists.

Value

Expr

Examples

```
pl$DataFrame(a = 1:4)$with_columns(
  pl$col("a")$cum_count()$alias("cum_count"),
  pl$col("a")$cum_count(reverse = TRUE)$alias("cum_count_reversed")
)
```

Expr_cum_max *Cumulative maximum*

Description

Get an array with the cumulative max computed at every element.

Usage

```
Expr_cum_max(reverse = FALSE)
```

Arguments

`reverse`	If `TRUE`, start from the last value.

Details

The Dtypes Int8, UInt8, Int16 and UInt16 are cast to Int64 before summing to prevent overflow issues.

Value

Expr

Examples

```
pl$DataFrame(a = c(1:4, 2L))$with_columns(
  pl$col("a")$cum_max()$alias("cummax"),
  pl$col("a")$cum_max(reverse = TRUE)$alias("cum_max_reversed")
)
```

Expr_cum_min *Cumulative minimum*

Description

Get an array with the cumulative min computed at every element.

Usage

```
Expr_cum_min(reverse = FALSE)
```

Arguments

reverse	If TRUE, start from the last value.

Details

The Dtypes Int8, UInt8, Int16 and UInt16 are cast to Int64 before summing to prevent overflow issues.

Value

Expr

Examples

```
pl$DataFrame(a = c(1:4, 2L))$with_columns(
  pl$col("a")$cum_min()$alias("cum_min"),
  pl$col("a")$cum_min(reverse = TRUE)$alias("cum_min_reversed")
)
```

Expr_cum_prod *Cumulative product*

Description

Get an array with the cumulative product computed at every element.

Usage

```
Expr_cum_prod(reverse = FALSE)
```

Arguments

reverse	If TRUE, start with the total product of elements and divide each row one by one.

Details

The Dtypes Int8, UInt8, Int16 and UInt16 are cast to Int64 before summing to prevent overflow issues.

Value

Expr

Examples

```
pl$DataFrame(a = 1:4)$with_columns(
  pl$col("a")$cum_prod()$alias("cum_prod"),
  pl$col("a")$cum_prod(reverse = TRUE)$alias("cum_prod_reversed")
)
```

Expr_cum_sum *Cumulative sum*

Description

Get an array with the cumulative sum computed at every element.

Usage

```
Expr_cum_sum(reverse = FALSE)
```

Arguments

`reverse`	If `TRUE`, start with the total sum of elements and substract each row one by one.

Details

The Dtypes Int8, UInt8, Int16 and UInt16 are cast to Int64 before summing to prevent overflow issues.

Value

Expr

Examples

```
pl$DataFrame(a = 1:4)$with_columns(
  pl$col("a")$cum_sum()$alias("cum_sum"),
  pl$col("a")$cum_sum(reverse = TRUE)$alias("cum_sum_reversed")
)
```

Expr_cumulative_eval *Cumulative evaluation of expressions*

Description

Run an expression over a sliding window that increases by 1 slot every iteration.

Usage

```
Expr_cumulative_eval(expr, min_periods = 1L, parallel = FALSE)
```

Arguments

expr	Expression to evaluate.
min_periods	Number of valid (non-null) values there should be in the window before the expression is evaluated.
parallel	Run in parallel. Don't do this in a groupby or another operation that already has much parallelization.

Details

This can be really slow as it can have O(n^2) complexity. Don't use this for operations that visit all elements.

Value

Expr

Examples

```
pl$lit(1:5)$cumulative_eval(
  pl$element()$first() - pl$element()$last()^2
)$to_r()
```

Expr_cut *Bin continuous values into discrete categories*

Description

Bin continuous values into discrete categories

Usage

```
Expr_cut(
  breaks,
  ...,
  labels = NULL,
  left_closed = FALSE,
  include_breaks = FALSE
)
```

Arguments

breaks	Unique cut points.
...	Ignored.
labels	Names of the categories. The number of labels must be equal to the number of cut points plus one.
left_closed	Set the intervals to be left-closed instead of right-closed.
include_breaks	Include a column with the right endpoint of the bin each observation falls in. This will change the data type of the output from a Categorical to a Struct.

Value

Expr of data type Categorical is include_breaks is FALSE and of data type Struct if include_breaks is TRUE.

See Also

$qcut()

Examples

```
df = pl$DataFrame(foo = c(-2, -1, 0, 1, 2))

df$with_columns(
  cut = pl$col("foo")$cut(c(-1, 1), labels = c("a", "b", "c"))
)

# Add both the category and the breakpoint
df$with_columns(
  cut = pl$col("foo")$cut(c(-1, 1), include_breaks = TRUE)
)$unnest("cut")
```

Expr_diff *Difference*

Description

Calculate the n-th discrete difference.

Usage

```
Expr_diff(n = 1, null_behavior = c("ignore", "drop"))
```

Arguments

n	Number of slots to shift.
null_behavior	String, either "ignore" (default), else "drop".

Value

Expr

Examples

```
pl$DataFrame(a = c(20L, 10L, 30L, 40L))$with_columns(
  diff_default = pl$col("a")$diff(),
  diff_2_ignore = pl$col("a")$diff(2, "ignore")
)
```

Expr_div *Divide two expressions*

Description

Method equivalent of float division operator `expr / other`.

Usage

```
Expr_div(other)
```

Arguments

other	Numeric literal or expression value.

Details

Zero-division behaviour follows IEEE-754:

- `0/0`: Invalid operation - mathematically undefined, returns `NaN`.
- `n/0`: On finite operands gives an exact infinite result, e.g.: ±infinity.

Value

Expr

See Also

- Arithmetic operators
- `<Expr>$floor_div()`

Examples

```
df = pl$DataFrame(
  x = -2:2,
  y = c(0.5, 0, 0, -4, -0.5)
)

df$with_columns(
  `x/2` = pl$col("x")$div(2),
  `x/y` = pl$col("x")$div(pl$col("y"))
)
```

Expr_dot *Dot product*

Description

Compute the dot/inner product between two Expressions.

Usage

```
Expr_dot(other)
```

Arguments

other	numeric or string value; accepts expression input.

Value

Expr

Examples

```
pl$DataFrame(
  a = 1:4, b = c(1, 2, 3, 4)
)$with_columns(
  pl$col("a")$dot(pl$col("b"))$alias("a dot b"),
  pl$col("a")$dot(pl$col("a"))$alias("a dot a")
)
```

Expr_drop_nans *Drop NaN*

Description

Drop NaN

Usage

```
Expr_drop_nans()
```

Details

Note that `NaN` values are not `null` values. Null values correspond to NA in R.

Value

Expr

See Also

`drop_nulls()`

Examples

```
pl$DataFrame(list(x = c(1, 2, NaN, NA)))$select(pl$col("x")$drop_nans())
```

Expr_drop_nulls *Drop missing values*

Description

Drop missing values

Usage

```
Expr_drop_nulls()
```

Value

Expr

See Also

`drop_nans()`

Examples

```
pl$DataFrame(list(x = c(1, 2, NaN, NA)))$select(pl$col("x")$drop_nulls())
```

Expr_entropy *Entropy*

Description

The entropy is measured with the formula `-sum(pk * log(pk))` where `pk` are discrete probabilities.

Usage

```
Expr_entropy(base = base::exp(1), normalize = TRUE)
```

Arguments

`base`	Given exponential base, defaults to `exp(1)`.
`normalize`	Normalize `pk` if it doesn't sum to 1.

Value

Expr

Examples

```
pl$DataFrame(x = c(1, 2, 3, 2))$
  with_columns(entropy = pl$col("x")$entropy(base = 2))
```

Expr_eq *Check equality*

Description

Method equivalent of addition operator `expr + other`.

Usage

```
Expr_eq(other)
```

Arguments

`other`	numeric or string value; accepts expression input.

Value

Expr

See Also

Expr_eq_missing

Examples

```
pl$lit(2) == 2
pl$lit(2) == pl$lit(2)
pl$lit(2)$eq(pl$lit(2))
```

`Expr_eq_missing` *Check equality without* `null` *propagation*

Description

Method equivalent of addition operator `expr + other`.

Usage

```
Expr_eq_missing(other)
```

Arguments

`other`	numeric or string value; accepts expression input.

Value

Expr

See Also

Expr_eq

Examples

```
df = pl$DataFrame(x = c(NA, FALSE, TRUE), y = c(TRUE, TRUE, TRUE))
df$with_columns(
  eq = pl$col("x")$eq("y"),
  eq_missing = pl$col("x")$eq_missing("y")
)
```

Expr_ewm_mean *Exponentially-weighted moving average*

Description

Exponentially-weighted moving average

Usage

```
Expr_ewm_mean(
  com = NULL,
  span = NULL,
  half_life = NULL,
  alpha = NULL,
  adjust = TRUE,
  min_periods = 1L,
  ignore_nulls = TRUE
)
```

Arguments

com	Specify decay in terms of center of mass, γ, with $\alpha = \frac{1}{1+\gamma}\ \forall\ \gamma \geq 0$
span	Specify decay in terms of span, θ, with $\alpha = \frac{2}{\theta+1}\ \forall\ \theta \geq 1$
half_life	Specify decay in terms of half-life, :math:\lambda, with $\alpha = 1 - \exp\left\{\frac{-\ln(2)}{\lambda}\right\}$ $\forall\ \lambda > 0$
alpha	Specify smoothing factor alpha directly, $0 < \alpha \leq 1$.
adjust	Divide by decaying adjustment factor in beginning periods to account for imbalance in relative weightings: • When adjust=TRUE the EW function is calculatedusing weights $w_i = (1-\alpha)^i$ • When adjust=FALSE the EW function is calculated recursively by $y_0 = x_0$ $y_t = (1-\alpha)y_{t-1} + \alpha x_t$
min_periods	Minimum number of observations in window required to have a value (otherwise result is null).
ignore_nulls	Ignore missing values when calculating weights: • When TRUE (default), weights are based on relative positions. For example, the weights of x_0 and x_2 used in calculating the final weighted average of [x_0, None, x_2] are $1-\alpha$ and 1 if adjust=TRUE, and $1-\alpha$ and α if adjust=FALSE. • When FALSE, weights are based on absolute positions. For example, the weights of :math:x_0 and :math:x_2 used in calculating the final weighted average of [x_0, None, x_2\] are $1-\alpha)^2$ and 1 if adjust=TRUE, and $(1-\alpha)^2$ and α if adjust=FALSE.

Value

Expr

Examples

```
pl$DataFrame(a = 1:3)$
  with_columns(ewm_mean = pl$col("a")$ewm_mean(com = 1))
```

Expr_ewm_std — *Exponentially-weighted moving standard deviation*

Description

Exponentially-weighted moving standard deviation

Usage

```
Expr_ewm_std(
  com = NULL,
  span = NULL,
  half_life = NULL,
  alpha = NULL,
  adjust = TRUE,
  bias = FALSE,
  min_periods = 1L,
  ignore_nulls = TRUE
)
```

Arguments

`com`	Specify decay in terms of center of mass, γ, with $\alpha = \frac{1}{1+\gamma}\ \forall\ \gamma \geq 0$
`span`	Specify decay in terms of span, θ, with $\alpha = \frac{2}{\theta+1}\ \forall\ \theta \geq 1$
`half_life`	Specify decay in terms of half-life, :math:`\lambda`, with $\alpha = 1 - \exp\left\{\frac{-\ln(2)}{\lambda}\right\}$ $\forall\ \lambda > 0$
`alpha`	Specify smoothing factor alpha directly, $0 < \alpha \leq 1$.
`adjust`	Divide by decaying adjustment factor in beginning periods to account for imbalance in relative weightings: • When `adjust=TRUE` the EW function is calculatedusing weights $w_i = (1-\alpha)^i$ • When `adjust=FALSE` the EW function is calculated recursively by $y_0 = x_0$ $y_t = (1-\alpha)y_{t-1} + \alpha x_t$
`bias`	If `FALSE`, the calculations are corrected for statistical bias.
`min_periods`	Minimum number of observations in window required to have a value (otherwise result is null).

`ignore_nulls` Ignore missing values when calculating weights:

- When `TRUE` (default), weights are based on relative positions. For example, the weights of x_0 and x_2 used in calculating the final weighted average of `[` x_0, None, x_2`]` are $1 - \alpha$ and 1 if `adjust=TRUE`, and $1 - \alpha$ and α if `adjust=FALSE`.
- When `FALSE`, weights are based on absolute positions. For example, the weights of :math:`x_0` and :math:`x_2` used in calculating the final weighted average of `[` x_0, None, x_2`\]` are $1-\alpha)^2$ and 1 if `adjust=TRUE`, and $(1-\alpha)^2$ and α if `adjust=FALSE`.

Value

Expr

Examples

```
pl$DataFrame(a = 1:3)$
  with_columns(ewm_std = pl$col("a")$ewm_std(com = 1))
```

`Expr_ewm_var` *Exponentially-weighted moving variance*

Description

Exponentially-weighted moving variance

Usage

```
Expr_ewm_var(
  com = NULL,
  span = NULL,
  half_life = NULL,
  alpha = NULL,
  adjust = TRUE,
  bias = FALSE,
  min_periods = 1L,
  ignore_nulls = TRUE
)
```

Arguments

`com`	Specify decay in terms of center of mass, γ, with $\alpha = \frac{1}{1+\gamma}\ \forall\ \gamma \geq 0$
`span`	Specify decay in terms of span, θ, with $\alpha = \frac{2}{\theta+1}\ \forall\ \theta \geq 1$
`half_life`	Specify decay in terms of half-life, :math:`\lambda`, with $\alpha = 1 - \exp\left\{\frac{-\ln(2)}{\lambda}\right\}$ $\forall\ \lambda > 0$
`alpha`	Specify smoothing factor alpha directly, $0 < \alpha \leq 1$.

`adjust` Divide by decaying adjustment factor in beginning periods to account for imbalance in relative weightings:

- When `adjust=TRUE` the EW function is calculatedusing weights $w_i = (1-\alpha)^i$
- When `adjust=FALSE` the EW function is calculated recursively by $y_0 = x_0$ $y_t = (1-\alpha)y_{t-1} + \alpha x_t$

`bias` If `FALSE`, the calculations are corrected for statistical bias.

`min_periods` Minimum number of observations in window required to have a value (otherwise result is null).

`ignore_nulls` Ignore missing values when calculating weights:

- When `TRUE` (default), weights are based on relative positions. For example, the weights of x_0 and x_2 used in calculating the final weighted average of `[` x_0, None, x_2`]` are $1-\alpha$ and 1 if `adjust=TRUE`, and $1-\alpha$ and α if `adjust=FALSE`.
- When `FALSE`, weights are based on absolute positions. For example, the weights of :math:`x_0` and :math:`x_2` used in calculating the final weighted average of `[` x_0, None, x_2\`]` are $1-\alpha)^2$ and 1 if `adjust=TRUE`, and $(1-\alpha)^2$ and α if `adjust=FALSE`.

Value

Expr

Examples

```
pl$DataFrame(a = 1:3)$
  with_columns(ewm_var = pl$col("a")$ewm_var(com = 1))
```

`Expr_exclude` *Exclude certain columns from selection*

Description

Exclude certain columns from selection

Usage

```
Expr_exclude(columns)
```

Arguments

`columns` Given param type:

- string: single column name or regex starting with ^ and ending with $
- character vector: exclude all these column names, no regex allowed
- DataType: Exclude any of this DataType
- List(DataType): Exclude any of these DataType(s)

Value

Expr

Examples

```
# make DataFrame
df = as_polars_df(iris)

# by name(s)
df$select(pl$all()$exclude("Species"))

# by type
df$select(pl$all()$exclude(pl$Categorical()))
df$select(pl$all()$exclude(list(pl$Categorical(), pl$Float64)))

# by regex
df$select(pl$all()$exclude("^Sepal.*$"))
```

Expr_exp *Compute the exponential of the elements*

Description

Compute the exponential of the elements

Usage

```
Expr_exp()
```

Value

Expr

Examples

```
pl$DataFrame(a = -1:3)$with_columns(a_exp = pl$col("a")$exp())
```

Expr_explode — *Explode a list or String Series*

Description

This means that every item is expanded to a new row.

Usage

```
Expr_explode()
```

Details

Categorical values are not supported.

Value

Expr

Examples

```
df = pl$DataFrame(x = c("abc", "ab"), y = c(list(1:3), list(3:5)))
df

df$select(pl$col("y")$explode())
```

Expr_extend_constant — *Extend Series with a constant*

Description

Extend the Series with given number of values.

Usage

```
Expr_extend_constant(value, n)
```

Arguments

value	The value to extend the Series with. This value may be NULL to fill with nulls.
n	The number of values to extend.

Value

Expr

Examples

```
pl$select(pl$lit(1:4)$extend_constant(10.1, 2))
pl$select(pl$lit(1:4)$extend_constant(NULL, 2))
```

Expr_fill_nan *Fill floating point NaN value with a fill value*

Description

Fill floating point NaN value with a fill value

Usage

```
Expr_fill_nan(value = NULL)
```

Arguments

value	Value used to fill NaN values.

Value

Expr

Examples

```
pl$DataFrame(a = c(NaN, 1, NaN, 2, NA))$
  with_columns(
  literal = pl$col("a")$fill_nan(999),
  # implicit coercion to string
  string = pl$col("a")$fill_nan("invalid")
)
```

Expr_fill_null *Fill null values with a value or strategy*

Description

Fill null values with a value or strategy

Usage

```
Expr_fill_null(value = NULL, strategy = NULL, limit = NULL)
```

Arguments

`value`	Expr or something coercible in an Expr
`strategy`	Possible choice are `NULL` (default, requires a non-null `value`), `"forward"`, `"backward"`, `"min"`, `"max"`, `"mean"`, `"zero"`, `"one"`.
`limit`	Number of consecutive null values to fill when using the `"forward"` or `"backward"` strategy.

Value

Expr

Examples

```
pl$DataFrame(a = c(NA, 1, NA, 2, NA))$
  with_columns(
  value = pl$col("a")$fill_null(999),
  backward = pl$col("a")$fill_null(strategy = "backward"),
  mean = pl$col("a")$fill_null(strategy = "mean")
)
```

`Expr_filter` *Filter a single column.*

Description

Mostly useful in an aggregation context. If you want to filter on a DataFrame level, use `DataFrame$filter()` (or `LazyFrame$filter()`).

Usage

```
Expr_filter(predicate)
```

Arguments

`predicate`	An Expr or something coercible to an Expr. Must return a boolean.

Value

Expr

Examples

```
df = pl$DataFrame(
  group_col = c("g1", "g1", "g2"),
  b = c(1, 2, 3)
)
df

df$group_by("group_col")$agg(
  lt = pl$col("b")$filter(pl$col("b") < 2),
  gte = pl$col("b")$filter(pl$col("b") >= 2)
)
```

`Expr_first` *Get the first value.*

Description

Get the first value.

Usage

```
Expr_first()
```

Value

Expr

Examples

```
pl$DataFrame(x = 3:1)$with_columns(first = pl$col("x")$first())
```

`Expr_flatten` *Explode a list or String Series*

Description

This is an alias for `<Expr>$explode()`.

Usage

```
Expr_flatten()
```

Value

Expr

Examples

```
df = pl$DataFrame(x = c("abc", "ab"), y = c(list(1:3), list(3:5)))
df

df$select(pl$col("y")$flatten())
```

Expr_floor *Floor*

Description

Rounds down to the nearest integer value. Only works on floating point Series.

Usage

```
Expr_floor()
```

Value

Expr

Examples

```
pl$DataFrame(a = c(0.33, 0.5, 1.02, 1.5, NaN, NA, Inf, -Inf))$with_columns(
  floor = pl$col("a")$floor()
)
```

Expr_floor_div *Floor divide two expressions*

Description

Method equivalent of floor division operator `expr %/% other`.

Usage

```
Expr_floor_div(other)
```

Arguments

`other`	Numeric literal or expression value.

Value

Expr

See Also

- Arithmetic operators
- `<Expr>$div()`
- `<Expr>$mod()`

Examples

```
df = pl$DataFrame(x = 1:5)

df$with_columns(
  `x/2` = pl$col("x")$div(2),
  `x%/%2` = pl$col("x")$floor_div(2)
)
```

Expr_forward_fill *Fill null values forward*

Description

Fill missing values with the last seen values. Syntactic sugar for `$fill_null(strategy = "forward")`.

Usage

```
Expr_forward_fill(limit = NULL)
```

Arguments

`limit`	Number of consecutive null values to fill when using the `"forward"` or `"backward"` strategy.

Value

Expr

Examples

```
pl$DataFrame(a = c(NA, 1, NA, 2, NA))$
  with_columns(
  backward = pl$col("a")$forward_fill()
)
```

Expr_gather — *Gather values by index*

Description

Gather values by index

Usage

```
Expr_gather(indices)
```

Arguments

indices	R vector or Series, or Expr that leads to a Series of dtype Int64. (0-indexed)

Value

Expr

Examples

```
df = pl$DataFrame(a = 1:10)

df$select(pl$col("a")$gather(c(0, 2, 4, -1)))
```

Expr_gather_every — *Gather every nth element*

Description

Gather every nth value in the Series and return as a new Series.

Usage

```
Expr_gather_every(n, offset = 0)
```

Arguments

n	Positive integer.
offset	Starting index.

Value

Expr

Examples

```
pl$DataFrame(a = 0:24)$select(pl$col("a")$gather_every(6))
```

Expr_gt — *Check strictly greater inequality*

Description

Method equivalent of addition operator `expr + other`.

Usage

```
Expr_gt(other)
```

Arguments

`other`	numeric or string value; accepts expression input.

Value

Expr

Examples

```
pl$lit(2) > 1
pl$lit(2) > pl$lit(1)
pl$lit(2)$gt(pl$lit(1))
```

Expr_gt_eq — *Check greater or equal inequality*

Description

Method equivalent of addition operator `expr + other`.

Usage

```
Expr_gt_eq(other)
```

Arguments

`other`	numeric or string value; accepts expression input.

Value

Expr

Examples

```
pl$lit(2) >= 2
pl$lit(2) >= pl$lit(2)
pl$lit(2)$gt_eq(pl$lit(2))
```

Expr_has_nulls *Check whether the expression contains one or more null values*

Description

Check whether the expression contains one or more null values

Usage

```
Expr_has_nulls()
```

Value

Expr

Examples

```
df = pl$DataFrame(
  a = c(NA, 1, NA),
  b = c(1, NA, 2),
  c = c(1, 2, 3)
)

df$select(pl$all()$has_nulls())
```

Expr_hash *Hash elements*

Description

The hash value is of type `UInt64`.

Usage

```
Expr_hash(seed = 0, seed_1 = NULL, seed_2 = NULL, seed_3 = NULL)
```

Arguments

`seed` Random seed parameter. Defaults to 0. Doesn't have any effect for now.

`seed_1, seed_2, seed_3` Random seed parameter. Defaults to arg seed. The column will be coerced to UInt32.

Value

Expr

Examples

```
df = as_polars_df(iris[1:3, c(1, 2)])
df$with_columns(pl$all()$hash(1234)$name$suffix("_hash"))
```

Expr_head *Get the first n elements*

Description

Get the first n elements

Usage

```
Expr_head(n = 10)
```

Arguments

n	Number of elements to take.

Value

Expr

Examples

```
pl$DataFrame(x = 1:11)$select(pl$col("x")$head(3))
```

Expr_implode *Wrap column in list*

Description

Aggregate values into a list.

Usage

```
Expr_implode()
```

Details

Use `$to_struct()` to wrap a DataFrame.

Value

Expr

Examples

```
df = pl$DataFrame(
  a = 1:3,
  b = 4:6
)
df$select(pl$all()$implode())
```

Expr_inspect *Inspect evaluated Series*

Description

Print the value that this expression evaluates to and pass on the value. The printing will happen when the expression evaluates, not when it is formed.

Usage

```
Expr_inspect(fmt = "{}")
```

Arguments

fmt	format string, should contain one set of {} where object will be printed. This formatting mimics python "string".format() use in py-polars.

Value

Expr

Examples

```
pl$select(pl$lit(1:5)$inspect(
  "Here's what the Series looked like before keeping the first two values: {}"
)$head(2))
```

Expr_interpolate *Interpolate null values*

Description

Fill nulls with linear interpolation using non-missing values. Can also be used to regrid data to a new grid - see examples below.

Usage

```
Expr_interpolate(method = "linear")
```

Arguments

method	String, either "linear" (default) or "nearest".

Value

Expr

Examples

```
pl$DataFrame(x = c(1, NA, 4, NA, 100, NaN, 150))$
  with_columns(
  interp_lin = pl$col("x")$interpolate(),
  interp_near = pl$col("x")$interpolate("nearest")
)

# x, y interpolation over a grid
df_original_grid = pl$DataFrame(
  grid_points = c(1, 3, 10),
  values = c(2.0, 6.0, 20.0)
)
df_original_grid
df_new_grid = pl$DataFrame(grid_points = (1:10) * 1.0)
df_new_grid

# Interpolate from this to the new grid
df_new_grid$join(
  df_original_grid,
  on = "grid_points", how = "left"
)$with_columns(pl$col("values")$interpolate())
```

Expr_is_between — *Check if an expression is between the given lower and upper bounds*

Description

Check if an expression is between the given lower and upper bounds

Usage

```
Expr_is_between(lower_bound, upper_bound, closed = "both")
```

Arguments

lower_bound	Lower bound, can be an Expr. Strings are parsed as column names.
upper_bound	Upper bound, can be an Expr. Strings are parsed as column names.
closed	Define which sides of the interval are closed (inclusive). This can be either "left", "right", "both" or "none".

Details

Note that in polars, NaN are equal to other NaNs, and greater than any non-NaN value.

Value

Expr

Examples

```
df = pl$DataFrame(num = 1:5)
df$with_columns(
  is_between = pl$col("num")$is_between(2, 4),
  is_between_excl_upper = pl$col("num")$is_between(2, 4, closed = "left"),
  is_between_excl_both = pl$col("num")$is_between(2, 4, closed = "none")
)

# lower and upper bounds can also be column names or expr
df = pl$DataFrame(
  num = 1:5,
  lower = c(0, 2, 3, 3, 3),
  upper = c(6, 4, 4, 8, 3.5)
)
df$with_columns(
  is_between_cols = pl$col("num")$is_between("lower", "upper"),
  is_between_expr = pl$col("num")$is_between(pl$col("lower") / 2, "upper")
)
```

Expr_is_duplicated *Check whether each value is duplicated*

Description

This is syntactic sugar for `$is_unique()$not()`.

Usage

```
Expr_is_duplicated()
```

Value

Expr

Examples

```
as_polars_df(head(mtcars[, 1:2]))$
  with_columns(is_duplicated = pl$col("mpg")$is_duplicated())
```

Expr_is_finite *Check if elements are finite*

Description

Returns a boolean Series indicating which values are finite.

Usage

```
Expr_is_finite()
```

Value

Expr

Examples

```
pl$DataFrame(list(alice = c(0, NaN, NA, Inf, -Inf)))$
  with_columns(finite = pl$col("alice")$is_finite())
```

Expr_is_first_distinct *Check whether each value is the first occurrence*

Description

Check whether each value is the first occurrence

Usage

```
Expr_is_first_distinct()
```

Value

Expr

Examples

```
as_polars_df(head(mtcars[, 1:2]))$
  with_columns(is_ufirst = pl$col("mpg")$is_first_distinct())
```

Expr_is_in — *Check whether a value is in a vector*

Description

Notice that to check whether a factor value is in a vector of strings, you need to use the string cache, either with `pl$enable_string_cache()` or with `pl$with_string_cache()`. See examples.

Usage

```
Expr_is_in(other)
```

Arguments

`other`	numeric or string value; accepts expression input.

Value

Expr

Examples

```
pl$DataFrame(a = c(1:4, NA_integer_))$with_columns(
  in_1_3 = pl$col("a")$is_in(c(1, 3)),
  in_NA = pl$col("a")$is_in(pl$lit(NA_real_))
)

# this fails because we can't compare factors to strings
# pl$DataFrame(a = factor(letters[1:5]))$with_columns(
#   in_abc = pl$col("a")$is_in(c("a", "b", "c"))
# )

# need to use the string cache for this
pl$with_string_cache({
  pl$DataFrame(a = factor(letters[1:5]))$with_columns(
    in_abc = pl$col("a")$is_in(c("a", "b", "c"))
  )
})
```

Expr_is_infinite — *Check if elements are infinite*

Description

Returns a boolean Series indicating which values are infinite.

Usage

```
Expr_is_infinite()
```

Value

Expr

Examples

```
pl$DataFrame(list(alice = c(0, NaN, NA, Inf, -Inf)))$
  with_columns(infinite = pl$col("alice")$is_infinite())
```

Expr_is_last_distinct *Check whether each value is the last occurrence*

Description

Check whether each value is the last occurrence

Usage

```
Expr_is_last_distinct()
```

Value

Expr

Examples

```
as_polars_df(head(mtcars[, 1:2]))$
  with_columns(is_ulast = pl$col("mpg")$is_last_distinct())
```

Expr_is_nan *Check if elements are NaN*

Description

Returns a boolean Series indicating which values are NaN.

Usage

```
Expr_is_nan()
```

Value

Expr

Examples

```
pl$DataFrame(list(alice = c(0, NaN, NA, Inf, -Inf)))$
  with_columns(nan = pl$col("alice")$is_nan())
```

Expr_is_not_nan *Check if elements are not NaN*

Description

Returns a boolean Series indicating which values are not NaN. Syntactic sugar for `$is_nan()$not()`.

Usage

```
Expr_is_not_nan()
```

Value

Expr

Examples

```
pl$DataFrame(list(alice = c(0, NaN, NA, Inf, -Inf)))$
  with_columns(not_nan = pl$col("alice")$is_not_nan())
```

Expr_is_not_null *Check if elements are not NULL*

Description

Returns a boolean Series indicating which values are not null. Syntactic sugar for `$is_null()$not()`.

Usage

```
Expr_is_not_null()
```

Value

Expr

Examples

```
pl$DataFrame(list(x = c(1, NA, 3)))$select(pl$col("x")$is_not_null())
```

Expr_is_null — *Check if elements are NULL*

Description

Returns a boolean Series indicating which values are null.

Usage

```
Expr_is_null()
```

Value

Expr

Examples

```
pl$DataFrame(list(x = c(1, NA, 3)))$select(pl$col("x")$is_null())
```

Expr_is_unique — *Check whether each value is unique*

Description

Check whether each value is unique

Usage

```
Expr_is_unique()
```

Value

Expr

Examples

```
as_polars_df(head(mtcars[, 1:2]))$
  with_columns(is_unique = pl$col("mpg")$is_unique())
```

Expr_kurtosis *Kurtosis*

Description

Compute the kurtosis (Fisher or Pearson) of a dataset.

Usage

```
Expr_kurtosis(fisher = TRUE, bias = TRUE)
```

Arguments

fisher	If TRUE (default), Fisher's definition is used (normal, centered at 0). Otherwise, Pearson's definition is used (normal, centered at 3).
bias	If FALSE, the calculations are corrected for statistical bias.

Details

Kurtosis is the fourth central moment divided by the square of the variance. If Fisher's definition is used, then 3 is subtracted from the result to give 0 for a normal distribution.

If bias is FALSE, then the kurtosis is calculated using k statistics to eliminate bias coming from biased moment estimators.

Value

Expr

Examples

```
pl$DataFrame(a = c(1:3, 2:1))$
  with_columns(kurt = pl$col("a")$kurtosis())
```

Expr_last *Get the last value*

Description

Get the last value

Usage

```
Expr_last()
```

Value

Expr

Examples

```
pl$DataFrame(x = 3:1)$with_columns(last = pl$col("x")$last())
```

Expr_limit *Get the first n elements*

Description

This is an alias for `<Expr>$head()`.

Usage

```
Expr_limit(n = 10)
```

Arguments

`n`	Number of elements to take.

Value

Expr

Examples

```
pl$DataFrame(x = 1:11)$select(pl$col("x")$limit(3))
```

Expr_log *Compute the logarithm of elements*

Description

Compute the logarithm of elements

Usage

```
Expr_log(base = base::exp(1))
```

Arguments

`base`	Numeric base value for logarithm, default is `exp(1)`.

Value

Expr

Examples

```
pl$DataFrame(a = c(1, 2, 3, exp(1)))$
  with_columns(log = pl$col("a")$log())
```

Expr_log10 *Compute the base-10 logarithm of elements*

Description

Compute the base-10 logarithm of elements

Usage

```
Expr_log10()
```

Value

Expr

Examples

```
pl$DataFrame(a = c(1, 2, 3, exp(1)))$
  with_columns(log10 = pl$col("a")$log10())
```

Expr_lower_bound *Find the lower bound of a DataType*

Description

Find the lower bound of a DataType

Usage

```
Expr_lower_bound()
```

Value

Expr

Examples

```
pl$DataFrame(
  x = 1:3, y = 1:3,
  schema = list(x = pl$UInt32, y = pl$Int32)
)$
  select(pl$all()$lower_bound())
```

Expr_lt *Check strictly lower inequality*

Description

Method equivalent of addition operator `expr + other`.

Usage

```
Expr_lt(other)
```

Arguments

`other`	numeric or string value; accepts expression input.

Value

Expr

Examples

```
pl$lit(5) < 10
pl$lit(5) < pl$lit(10)
pl$lit(5)$lt(pl$lit(10))
```

Expr_lt_eq *Check lower or equal inequality*

Description

Method equivalent of addition operator `expr + other`.

Usage

```
Expr_lt_eq(other)
```

Arguments

`other`	numeric or string value; accepts expression input.

Value

Expr

Examples

```
pl$lit(2) <= 2
pl$lit(2) <= pl$lit(2)
pl$lit(2)$lt_eq(pl$lit(2))
```

Expr_map_batches *Map an expression with an R function*

Description

Map an expression with an R function

Usage

```
Expr_map_batches(
  f,
  output_type = NULL,
  agg_list = FALSE,
  in_background = FALSE
)
```

Arguments

f	a function to map with
output_type	NULL or a type available in names(pl$dtypes). If NULL (default), the output datatype will match the input datatype. This is used to inform schema of the actual return type of the R function. Setting this wrong could theoretically have some downstream implications to the query.
agg_list	Aggregate list. Map from vector to group in group_by context.
in_background	Logical. Whether to execute the map in a background R process. Combined with setting e.g. options(polars.rpool_cap = 4) it can speed up some slow R functions as they can run in parallel R sessions. The communication speed between processes is quite slower than between threads. This will likely only give a speed-up in a "low IO - high CPU" use case. If there are multiple $map_batches(in_background = TRUE) calls in the query, they will be run in parallel.

Details

It is sometimes necessary to apply a specific R function on one or several columns. However, note that using R code in `$map_batches()` is slower than native polars. The user function must take one polars `Series` as input and the return should be a `Series` or any Robj convertible into a `Series` (e.g. vectors). Map fully supports `browser()`.

If `in_background = FALSE` the function can access any global variable of the R session. However, note that several calls to `$map_batches()` will sequentially share the same main R session, so the global environment might change between the start of the query and the moment a `$map_batches()` call is evaluated. Any native polars computations can still be executed meanwhile. If `in_background = TRUE`, the map will run in one or more other R sessions and will not have access to global variables. Use `options(polars.rpool_cap = 4)` and `polars_options()$rpool_cap` to set and view number of parallel R sessions.

Value

Expr

Examples

```
as_polars_df(iris)$
  select(
  pl$col("Sepal.Length")$map_batches(\(x) {
    paste("cheese", as.character(x$to_vector()))
  }, pl$dtypes$String)
)

# R parallel process example, use Sys.sleep() to imitate some CPU expensive
# computation.

# map a,b,c,d sequentially
pl$LazyFrame(a = 1, b = 2, c = 3, d = 4)$select(
  pl$all()$map_batches(\(s) {
    Sys.sleep(.1)
    s * 2
  })
)$collect() |> system.time()

# map in parallel 1: Overhead to start up extra R processes / sessions
options(polars.rpool_cap = 0) # drop any previous processes, just to show start-up overhead
options(polars.rpool_cap = 4) # set back to 4, the default
polars_options()$rpool_cap
pl$LazyFrame(a = 1, b = 2, c = 3, d = 4)$select(
  pl$all()$map_batches(\(s) {
    Sys.sleep(.1)
    s * 2
  }, in_background = TRUE)
)$collect() |> system.time()

# map in parallel 2: Reuse R processes in "polars global_rpool".
polars_options()$rpool_cap
pl$LazyFrame(a = 1, b = 2, c = 3, d = 4)$select(
```

```
  pl$all()$map_batches(\(s) {
    Sys.sleep(.1)
    s * 2
  }, in_background = TRUE)
)$collect() |> system.time()
```

`Expr_map_elements` *Map a custom/user-defined function (UDF) to each element of a column*

Description

The UDF is applied to each element of a column. See Details for more information on specificities related to the context.

Usage

```
Expr_map_elements(
  f,
  return_type = NULL,
  strict_return_type = TRUE,
  allow_fail_eval = FALSE,
  in_background = FALSE
)
```

Arguments

`f`	Function to map
`return_type`	DataType of the output Series. If `NULL`, the dtype will be `pl$Unknown`.
`strict_return_type`	If `TRUE` (default), error if not correct datatype returned from R. If `FALSE`, the output will be converted to a polars null value.
`allow_fail_eval`	If `FALSE` (default), raise an error if the function fails. If `TRUE`, the result will be converted to a polars null value.
`in_background`	Whether to run the function in a background R process, default is `FALSE`. Combined with setting e.g. `options(polars.rpool_cap = 4)`, this can speed up some slow R functions as they can run in parallel R sessions. The communication speed between processes is quite slower than between threads. This will likely only give a speed-up in a "low IO - high CPU" usecase. A single map will not be paralleled, only in case of multiple `$map_elements()` in the query can these run in parallel.

Details

Note that, in a GroupBy context, the column will have been pre-aggregated and so each element will itself be a Series. Therefore, depending on the context, requirements for function differ:

- in `$select()` or `$with_columns()` (selection context), the function must operate on R values of length 1. Polars will convert each element into an R value and pass it to the function. The output of the user function will be converted back into a polars type (the return type must match, see argument `return_type`). Using `$map_elements()` in this context should be avoided as a `lapply()` has half the overhead.
- in `$agg()` (GroupBy context), the function must take a `Series` and return a `Series` or an R object convertible to `Series`, e.g. a vector. In this context, it is much faster if there are the number of groups is much lower than the number of rows, as the iteration is only across the groups. The R user function could e.g. convert the `Series` to a vector with `$to_r()` and perform some vectorized operations.

Note that it is preferred to express your function in polars syntax, which will almost always be *significantly* faster and more memory efficient because:

- the native expression engine runs in Rust; functions run in R.
- use of R functions forces the DataFrame to be materialized in memory.
- Polars-native expressions can be parallelized (R functions cannot).
- Polars-native expressions can be logically optimized (R functions cannot).

Wherever possible you should strongly prefer the native expression API to achieve the best performance and avoid using `$map_elements()`.

Value

Expr

Examples

```
# apply over groups: here, the input must be a Series
# prepare two expressions, one to compute the sum of each variable, one to
# get the first two values of each variable and store them in a list
e_sum = pl$all()$map_elements(\(s) sum(s$to_r()))$name$suffix("_sum")
e_head = pl$all()$map_elements(\(s) head(s$to_r(), 2))$name$suffix("_head")
as_polars_df(iris)$group_by("Species")$agg(e_sum, e_head)

# apply a function on each value (should be avoided): here the input is an R
# value of length 1
# select only Float64 columns
my_selection = pl$col(pl$dtypes$Float64)

# prepare two expressions, the first one only adds 10 to each element, the
# second returns the letter whose index matches the element
e_add10 = my_selection$map_elements(\(x)  {
  x + 10
})$name$suffix("_sum")
```

```
e_letter = my_selection$map_elements(\(x) {
  letters[ceiling(x)]
}, return_type = pl$dtypes$String)$name$suffix("_letter")
as_polars_df(iris)$select(e_add10, e_letter)


# Small benchmark --------------------------------

# Using `$map_elements()` is much slower than a more polars-native approach.
# First we multiply each element of a Series of 1M elements by 2.
n = 1000000L
set.seed(1)
df = pl$DataFrame(list(
  a = 1:n,
  b = sample(letters, n, replace = TRUE)
))

system.time({
  df$with_columns(
    bob = pl$col("a")$map_elements(\(x) {
      x * 2L
    })
  )
})

# Comparing this to the standard polars syntax:
system.time({
  df$with_columns(
    bob = pl$col("a") * 2L
  )
})


# Running in parallel --------------------------------

# here, we use Sys.sleep() to imitate some CPU expensive computation.

# use apply over each Species-group in each column equal to 12 sequential
# runs ~1.2 sec.
system.time({
  as_polars_lf(iris)$group_by("Species")$agg(
    pl$all()$map_elements(\(s) {
      Sys.sleep(.1)
      s$sum()
    })
  )$collect()
})

# first run in parallel: there is some overhead to start up extra R processes
# drop any previous processes, just to show start-up overhead here
options(polars.rpool_cap = 0)
# set back to 4, the default
options(polars.rpool_cap = 4)
```

```
polars_options()$rpool_cap

system.time({
  as_polars_lf(iris)$group_by("Species")$agg(
    pl$all()$map_elements(\(s) {
      Sys.sleep(.1)
      s$sum()
    }, in_background = TRUE)
  )$collect()
})

# second run in parallel: this reuses R processes in "polars global_rpool".
polars_options()$rpool_cap
system.time({
  as_polars_lf(iris)$group_by("Species")$agg(
    pl$all()$map_elements(\(s) {
      Sys.sleep(.1)
      s$sum()
    }, in_background = TRUE)
  )$collect()
})
```

Expr_max *Get maximum value*

Description

Get maximum value

Usage

```
Expr_max()
```

Value

Expr

Examples

```
pl$DataFrame(x = c(1, NA, 3))$
  with_columns(max = pl$col("x")$max())
```

Expr_mean — *Get mean value*

Description

Get mean value

Usage

```
Expr_mean()
```

Value

Expr

Examples

```
pl$DataFrame(x = c(1L, NA, 2L))$
  with_columns(mean = pl$col("x")$mean())
```

Expr_median — *Get median value*

Description

Get median value

Usage

```
Expr_median()
```

Value

Expr

Examples

```
pl$DataFrame(x = c(1L, NA, 2L))$
  with_columns(median = pl$col("x")$median())
```

Expr_min — *Get minimum value*

Description

Get minimum value

Usage

```
Expr_min()
```

Value

Expr

Examples

```
pl$DataFrame(x = c(1, NA, 3))$
  with_columns(min = pl$col("x")$min())
```

Expr_mod — *Modulo two expressions*

Description

Method equivalent of modulus operator `expr %% other`.

Usage

```
Expr_mod(other)
```

Arguments

`other`	Numeric literal or expression value.

Value

Expr

See Also

- Arithmetic operators
- `<Expr>$floor_div()`

Examples

```
df = pl$DataFrame(x = -5L:5L)

df$with_columns(
  `x%%2` = pl$col("x")$mod(2)
)
```

Expr_mode *Mode*

Description

Compute the most occurring value(s). Can return multiple values if there are ties.

Usage

```
Expr_mode()
```

Value

Expr

Examples

```
df = pl$DataFrame(a = 1:6, b = c(1L, 1L, 3L, 3L, 5L, 6L), c = c(1L, 1L, 2L, 2L, 3L, 3L))
df$select(pl$col("a")$mode())
df$select(pl$col("b")$mode())
df$select(pl$col("c")$mode())
```

Expr_mul *Multiply two expressions*

Description

Method equivalent of multiplication operator `expr * other`.

Usage

```
Expr_mul(other)
```

Arguments

`other`	Numeric literal or expression value.

Value

Expr

See Also

- Arithmetic operators

Examples

```
df = pl$DataFrame(x = c(1, 2, 4, 8, 16))

df$with_columns(
  `x*2` = pl$col("x")$mul(2),
  `x * xlog2` = pl$col("x")$mul(pl$col("x")$log(2))
)
```

Expr_n_unique — *Count number of unique values*

Description

Count number of unique values

Usage

```
Expr_n_unique()
```

Value

Expr

Examples

```
as_polars_df(iris[, 4:5])$with_columns(count = pl$col("Species")$n_unique())
```

Expr_nan_max — *Get maximum value with NaN*

Description

Get maximum value, but returns NaN if there are any.

Usage

```
Expr_nan_max()
```

Value

Expr

Examples

```
pl$DataFrame(x = c(1, NA, 3, NaN, Inf))$
  with_columns(nan_max = pl$col("x")$nan_max())
```

`Expr_nan_min` *Get minimum value with NaN*

Description

Get minimum value, but returns `NaN` if there are any.

Usage

```
Expr_nan_min()
```

Value

Expr

Examples

```
pl$DataFrame(x = c(1, NA, 3, NaN, Inf))$
  with_columns(nan_min = pl$col("x")$nan_min())
```

`Expr_neq` *Check inequality*

Description

Method equivalent of addition operator `expr + other`.

Usage

```
Expr_neq(other)
```

Arguments

`other`	numeric or string value; accepts expression input.

Value

Expr

See Also

Expr_neq_missing

Examples

```
pl$lit(1) != 2
pl$lit(1) != pl$lit(2)
pl$lit(1)$neq(pl$lit(2))
```

Expr_neq_missing *Check inequality without* `null` *propagation*

Description

Method equivalent of addition operator `expr + other`.

Usage

```
Expr_neq_missing(other)
```

Arguments

`other`	numeric or string value; accepts expression input.

Value

Expr

See Also

Expr_neq

Examples

```
df = pl$DataFrame(x = c(NA, FALSE, TRUE), y = c(TRUE, TRUE, TRUE))
df$with_columns(
  neq = pl$col("x")$neq("y"),
  neq_missing = pl$col("x")$neq_missing("y")
)
```

Expr_not *Negate a boolean expression*

Description

Method equivalent of negation operator `!expr`.

Usage

```
Expr_not()
```

Value

Expr

Examples

```
# two syntaxes same result
pl$lit(TRUE)$not()
!pl$lit(TRUE)
```

Expr_null_count *Count missing values*

Description

Count missing values

Usage

```
Expr_null_count()
```

Value

Expr

Examples

```
pl$DataFrame(x = c(NA, "a", NA, "b"))$
  with_columns(n_missing = pl$col("x")$null_count())
```

Expr_or — *Apply logical OR on two expressions*

Description

Combine two boolean expressions with OR.

Usage

```
Expr_or(other)
```

Arguments

other	numeric or string value; accepts expression input.

Value

Expr

Examples

```
pl$lit(TRUE) | FALSE
pl$lit(TRUE)$or(pl$lit(TRUE))
```

Expr_over — *Compute expressions over the given groups*

Description

This expression is similar to performing a group by aggregation and joining the result back into the original DataFrame. The outcome is similar to how window functions work in PostgreSQL.

Usage

```
Expr_over(..., order_by = NULL, mapping_strategy = "group_to_rows")
```

Arguments

...	Column(s) to group by. Accepts expression input. Characters are parsed as column names.
order_by	Order the window functions/aggregations with the partitioned groups by the result of the expression passed to `order_by`. Can be an Expr. Strings are parsed as column names.
mapping_strategy	One of the following:

- "group_to_rows" (default): if the aggregation results in multiple values, assign them back to their position in the DataFrame. This can only be done if the group yields the same elements before aggregation as after.
- "join": join the groups as List<group_dtype> to the row positions. Note that this can be memory intensive.
- "explode": don't do any mapping, but simply flatten the group. This only makes sense if the input data is sorted.

Value

Expr

Examples

```
# Pass the name of a column to compute the expression over that column.
df = pl$DataFrame(
  a = c("a", "a", "b", "b", "b"),
  b = c(1, 2, 3, 5, 3),
  c = c(5, 4, 2, 1, 3)
)

df$with_columns(
  pl$col("c")$max()$over("a")$name$suffix("_max")
)

# Expression input is supported.
df$with_columns(
  pl$col("c")$max()$over(pl$col("b") %/% 2)$name$suffix("_max")
)

# Group by multiple columns by passing a character vector of column names
# or list of expressions.
df$with_columns(
  pl$col("c")$min()$over(c("a", "b"))$name$suffix("_min")
)

df$with_columns(
  pl$col("c")$min()$over(list(pl$col("a"), pl$col("b")))$name$suffix("_min")
)

# Or use positional arguments to group by multiple columns in the same way.
df$with_columns(
  pl$col("c")$min()$over("a", pl$col("b") %% 2)$name$suffix("_min")
)

# Alternative mapping strategy: join values in a list output
df$with_columns(
  top_2 = pl$col("c")$top_k(2)$over("a", mapping_strategy = "join")
)

# order_by specifies how values are sorted within a group, which is
# essential when the operation depends on the order of values
```

```
df = pl$DataFrame(
  g = c(1, 1, 1, 1, 2, 2, 2, 2),
  t = c(1, 2, 3, 4, 4, 1, 2, 3),
  x = c(10, 20, 30, 40, 10, 20, 30, 40)
)

# without order_by, the first and second values in the second group would
# be inverted, which would be wrong
df$with_columns(
  x_lag = pl$col("x")$shift(1)$over("g", order_by = "t")
)
```

Expr_pct_change *Percentage change*

Description

Computes percentage change (as fraction) between current element and most- recent non-null element at least n period(s) before the current element. Computes the change from the previous row by default.

Usage

```
Expr_pct_change(n = 1)
```

Arguments

n	Periods to shift for computing percent change.

Value

Expr

Examples

```
pl$DataFrame(a = c(10L, 11L, 12L, NA_integer_, 12L))$
  with_columns(pct_change = pl$col("a")$pct_change())
```

Expr_peak_max *Find local maxima*

Description

A local maximum is the point that marks the transition between an increase and a decrease in a Series. The first and last values of the Series can never be a peak.

Usage

```
Expr_peak_max()
```

Value

Expr

See Also

`$peak_min()`

Examples

```
df = pl$DataFrame(x = c(1, 2, 3, 2, 3, 4, 5, 2))
df

df$with_columns(peak_max = pl$col("x")$peak_max())
```

Expr_peak_min *Find local minima*

Description

A local minimum is the point that marks the transition between a decrease and an increase in a Series. The first and last values of the Series can never be a peak.

Usage

```
Expr_peak_min()
```

Value

Expr

See Also

`$peak_max()`

Examples

```
df = pl$DataFrame(x = c(1, 2, 3, 2, 3, 4, 5, 2))
df

df$with_columns(peak_min = pl$col("x")$peak_min())
```

Expr_pow *Exponentiation two expressions*

Description

Method equivalent of exponentiation operator `expr ^ exponent`.

Usage

```
Expr_pow(exponent)
```

Arguments

`exponent`	Numeric literal or expression value.

Value

Expr

See Also

- Arithmetic operators

Examples

```
df = pl$DataFrame(x = c(1, 2, 4, 8))

df$with_columns(
  cube = pl$col("x")$pow(3),
  `x^xlog2` = pl$col("x")$pow(pl$col("x")$log(2))
)
```

Expr_product *Product*

Description

Compute the product of an expression.

Usage

```
Expr_product()
```

Value

Expr

Examples

```
pl$DataFrame(x = c(2L, NA, 2L))$
  with_columns(product = pl$col("x")$product())
```

Expr_qcut *Bin continuous values into discrete categories based on their quantiles*

Description

Bin continuous values into discrete categories based on their quantiles

Usage

```
Expr_qcut(
  quantiles,
  ...,
  labels = NULL,
  left_closed = FALSE,
  allow_duplicates = FALSE,
  include_breaks = FALSE
)
```

Arguments

quantiles	Either a vector of quantile probabilities between 0 and 1 or a positive integer determining the number of bins with uniform probability.
...	Ignored.
labels	Names of the categories. The number of labels must be equal to the number of cut points plus one.

left_closed Set the intervals to be left-closed instead of right-closed.

allow_duplicates
If set to TRUE, duplicates in the resulting quantiles are dropped, rather than raising an error. This can happen even with unique probabilities, depending on the data.

include_breaks Include a column with the right endpoint of the bin each observation falls in. This will change the data type of the output from a Categorical to a Struct.

Value

Expr of data type Categorical is include_breaks is FALSE and of data type Struct if include_breaks is TRUE.

See Also

$cut()

Examples

```
df = pl$DataFrame(foo = c(-2, -1, 0, 1, 2))

# Divide a column into three categories according to pre-defined quantile
# probabilities
df$with_columns(
  qcut = pl$col("foo")$qcut(c(0.25, 0.75), labels = c("a", "b", "c"))
)

# Divide a column into two categories using uniform quantile probabilities.
df$with_columns(
  qcut = pl$col("foo")$qcut(2, labels = c("low", "high"), left_closed = TRUE)
)

# Add both the category and the breakpoint
df$with_columns(
  qcut = pl$col("foo")$qcut(c(0.25, 0.75), include_breaks = TRUE)
)$unnest("qcut")
```

Expr_quantile *Get quantile value.*

Description

Get quantile value.

Usage

```
Expr_quantile(quantile, interpolation = "nearest")
```

Arguments

quantile	Either a numeric value or an Expr whose value must be between 0 and 1.
interpolation	One of "nearest", "higher", "lower", "midpoint", or "linear".

Details

Null values are ignored and NaNs are ranked as the largest value. For linear interpolation NaN poisons Inf, that poisons any other value.

Value

Expr

Examples

```
pl$DataFrame(x = -5:5)$
  select(pl$col("x")$quantile(0.5))
```

Expr_rank *Rank elements*

Description

Assign ranks to data, dealing with ties appropriately.

Usage

```
Expr_rank(
  method = c("average", "min", "max", "dense", "ordinal", "random"),
  descending = FALSE,
  seed = NULL
)
```

Arguments

method	String, one of "average" (default), "min", "max", "dense", "ordinal", "random". The method used to assign ranks to tied elements: • "average": The average of the ranks that would have been assigned to all the tied values is assigned to each value. • "min": The minimum of the ranks that would have been assigned to all the tied values is assigned to each value. (This is also referred to as "competition" ranking.) • "max" : The maximum of the ranks that would have been assigned to all the tied values is assigned to each value. • "dense": Like 'min', but the rank of the next highest element is assigned the rank immediately after those assigned to the tied elements.

- "ordinal" : All values are given a distinct rank, corresponding to the order that the values occur in the Series.
- "random" : Like 'ordinal', but the rank for ties is not dependent on the order that the values occur in the Series.

descending — Rank in descending order.

seed — string parsed or number converted into uint64. Used if method="random".

Value

Expr

Examples

```
#  The 'average' method:
pl$DataFrame(a = c(3, 6, 1, 1, 6))$
  with_columns(rank = pl$col("a")$rank())

#  The 'ordinal' method:
pl$DataFrame(a = c(3, 6, 1, 1, 6))$
  with_columns(rank = pl$col("a")$rank("ordinal"))
```

Expr_rechunk *Rechunk memory layout*

Description

Create a single chunk of memory for this Series.

Usage

```
Expr_rechunk()
```

Details

See rechunk() explained here docs_translations.

Value

Expr

Examples

```
# get chunked lengths with/without rechunk
series_list = pl$DataFrame(list(a = 1:3, b = 4:6))$select(
  pl$col("a")$append(pl$col("b"))$alias("a_chunked"),
  pl$col("a")$append(pl$col("b"))$rechunk()$alias("a_rechunked")
)$get_columns()
lapply(series_list, \(x) x$chunk_lengths())
```

Expr_reinterpret *Reinterpret bits*

Description

Reinterpret the underlying bits as a signed/unsigned integer. This operation is only allowed for Int64. For lower bits integers, you can safely use the cast operation.

Usage

```
Expr_reinterpret(signed = TRUE)
```

Arguments

signed	If TRUE (default), reinterpret into Int64. Otherwise, it will be reinterpreted in UInt64.

Value

Expr

Examples

```
df = pl$DataFrame(x = 1:5, schema = list(x = pl$Int64))
df$select(pl$all()$reinterpret())
```

Expr_rep *Repeat a Series*

Description

This expression takes input and repeats it n times and append chunk.

Usage

```
Expr_rep(n, rechunk = TRUE)
```

Arguments

n	The number of times to repeat, must be non-negative and finite.
rechunk	If TRUE (default), memory layout will be rewritten.

Details

If the input has length 1, this uses a special faster implementation that doesn't require rechunking (so rechunk = TRUE has no effect).

Value

Expr

Examples

```
pl$select(pl$lit("alice")$rep(n = 3))
pl$select(pl$lit(1:3)$rep(n = 2))
```

Expr_repeat_by *Repeat values*

Description

Repeat the elements in this Series as specified in the given expression. The repeated elements are expanded into a `List`.

Usage

```
Expr_repeat_by(by)
```

Arguments

by	Expr that determines how often the values will be repeated. The column will be coerced to UInt32.

Value

Expr

Examples

```
df = pl$DataFrame(a = c("w", "x", "y", "z"), n = c(-1, 0, 1, 2))
df$with_columns(repeated = pl$col("a")$repeat_by("n"))
```

Expr_replace *Replace the given values by different values of the same data type.*

Description

This allows one to recode values in a column, leaving all other values unchanged. See `$replace_strict()` to give a default value to all other values and to specify the output datatype.

Usage

```
Expr_replace(old, new)
```

Arguments

`old` Can be several things:

- a vector indicating the values to recode;
- if `new` is missing, this can be a named list e.g `list(old = "new")` where the names are the old values and the values are the replacements. Note that if old values are numeric, the names must be wrapped in backticks;
- an Expr

`new` Either a vector of length 1, a vector of same length as `old` or an Expr. If missing, `old` must be a named list.

Value

Expr

Examples

```
df = pl$DataFrame(a = c(1, 2, 2, 3))

# "old" and "new" can take vectors of length 1 or of same length
df$with_columns(replaced = pl$col("a")$replace(2, 100))
df$with_columns(replaced = pl$col("a")$replace(c(2, 3), c(100, 200)))

# "old" can be a named list where names are values to replace, and values are
# the replacements
mapping = list(`2` = 100, `3` = 200)
df$with_columns(replaced = pl$col("a")$replace(mapping))

df = pl$DataFrame(a = c("x", "y", "z"))
mapping = list(x = 1, y = 2, z = 3)
df$with_columns(replaced = pl$col("a")$replace(mapping))

# "old" and "new" can take Expr
df = pl$DataFrame(a = c(1, 2, 2, 3), b = c(1.5, 2.5, 5, 1))
df$with_columns(
  replaced = pl$col("a")$replace(
    old = pl$col("a")$max(),
    new = pl$col("b")$sum()
  )
)
```

Expr_replace_strict *Replace all values by different values.*

Description

This changes all the values in a column, either using a specific replacement or a default one. See `$replace()` to replace only a subset of values.

Usage

```
Expr_replace_strict(old, new, default = NULL, return_dtype = NULL)
```

Arguments

old	Can be several things: • a vector indicating the values to recode; • if new is missing, this can be a named list e.g `list(old = "new")` where the names are the old values and the values are the replacements. Note that if old values are numeric, the names must be wrapped in backticks; • an Expr
new	Either a vector of length 1, a vector of same length as `old` or an Expr. If missing, `old` must be a named list.
default	The default replacement if the value is not in `old`. Can be an Expr. If `NULL` (default), then the value doesn't change.
return_dtype	The data type of the resulting expression. If set to `NULL` (default), the data type is determined automatically based on the other inputs.

Value

Expr

Examples

```
df = pl$DataFrame(a = c(1, 2, 2, 3))

# "old" and "new" can take vectors of length 1 or of same length
df$with_columns(replaced = pl$col("a")$replace_strict(2, 100, default = 1))
df$with_columns(
  replaced = pl$col("a")$replace_strict(c(2, 3), c(100, 200), default = 1)
)

# "old" can be a named list where names are values to replace, and values are
# the replacements
mapping = list(`2` = 100, `3` = 200)
df$with_columns(replaced = pl$col("a")$replace_strict(mapping, default = -1))

# one can specify the data type to return instead of automatically
# inferring it
df$with_columns(
  replaced = pl$col("a")$replace_strict(mapping, default = 1, return_dtype = pl$Int32)
)

# "old", "new", and "default" can take Expr
df = pl$DataFrame(a = c(1, 2, 2, 3), b = c(1.5, 2.5, 5, 1))
df$with_columns(
  replaced = pl$col("a")$replace_strict(
    old = pl$col("a")$max(),
    new = pl$col("b")$sum(),
```

```
    default = pl$col("b"),
  )
)
```

Expr_reshape *Reshape this Expr to a flat Series or a Series of Lists*

Description

Reshape this Expr to a flat Series or a Series of Lists

Usage

```
Expr_reshape(dimensions)
```

Arguments

dimensions	A integer vector of length of the dimension size. If -1 is used in any of the dimensions, that dimension is inferred. Currently, more than two dimensions not supported.

Value

Expr. If a single dimension is given, results in an expression of the original data type. If a multiple dimensions are given, results in an expression of data type List with shape equal to the dimensions.

Examples

```
df = pl$DataFrame(foo = 1:9)

df$select(pl$col("foo")$reshape(9))
df$select(pl$col("foo")$reshape(c(3, 3)))

# Use `-1` to infer the other dimension
df$select(pl$col("foo")$reshape(c(-1, 3)))
df$select(pl$col("foo")$reshape(c(3, -1)))

# One can specify more than 2 dimensions by using the Array type
df = pl$DataFrame(foo = 1:12)
df$select(
  pl$col("foo")$reshape(c(3, 2, 2))
)
```

Expr_reverse — *Reverse a variable*

Description

Reverse a variable

Usage

```
Expr_reverse()
```

Value

Expr

Examples

```
pl$DataFrame(list(a = 1:5))$select(pl$col("a")$reverse())
```

Expr_rle — *Get the lengths of runs of identical values*

Description

Get the lengths of runs of identical values

Usage

```
Expr_rle()
```

Value

Expr

Examples

```
df = pl$DataFrame(s = c(1, 1, 2, 1, NA, 1, 3, 3))
df$select(pl$col("s")$rle())$unnest("s")
```

Expr_rle_id — *Map values to run IDs*

Description

Similar to $rle(), but it maps each value to an ID corresponding to the run into which it falls. This is especially useful when you want to define groups by runs of identical values rather than the values themselves. Note that the ID is 0-indexed.

Usage

```
Expr_rle_id()
```

Value

Expr

Examples

```
df = pl$DataFrame(a = c(1, 2, 1, 1, 1, 4))
df$with_columns(a_r = pl$col("a")$rle_id())
```

Expr_rolling — *Create rolling groups based on a time or numeric column*

Description

If you have a time series `<t_0, t_1, ..., t_n>`, then by default the windows created will be:

- (t_0 - period, t_0]
- (t_1 - period, t_1]
- ...
- (t_n - period, t_n]

whereas if you pass a non-default offset, then the windows will be:

- (t_0 + offset, t_0 + offset + period]
- (t_1 + offset, t_1 + offset + period]
- ...
- (t_n + offset, t_n + offset + period]

Usage

```
Expr_rolling(index_column, ..., period, offset = NULL, closed = "right")
```

Arguments

`index_column`	Column used to group based on the time window. Often of type Date/Datetime. This column must be sorted in ascending order. If this column represents an index, it has to be either Int32 or Int64. Note that Int32 gets temporarily cast to Int64, so if performance matters use an Int64 column.
`...`	Ignored.
`period`	A character representing the length of the window, must be non-negative. See the `Polars duration string language` section for details.
`offset`	A character representing the offset of the window, or `NULL` (default). If `NULL`, `-period` is used. See the `Polars duration string language` section for details.
`closed`	Define which sides of the temporal interval are closed (inclusive). This can be either `"left"`, `"right"`, `"both"` or `"none"`.

Details

In case of a rolling operation on an integer column, the windows are defined by:

- "1i" # length 1
- "10i" # length 10

Value

Expr

Polars duration string language

Polars duration string language is a simple representation of durations. It is used in many Polars functions that accept durations.

It has the following format:

- 1ns (1 nanosecond)
- 1us (1 microsecond)
- 1ms (1 millisecond)
- 1s (1 second)
- 1m (1 minute)
- 1h (1 hour)
- 1d (1 calendar day)
- 1w (1 calendar week)
- 1mo (1 calendar month)
- 1q (1 calendar quarter)
- 1y (1 calendar year)

Or combine them: `"3d12h4m25s"` # 3 days, 12 hours, 4 minutes, and 25 seconds

By "calendar day", we mean the corresponding time on the next day (which may not be 24 hours, due to daylight savings). Similarly for "calendar week", "calendar month", "calendar quarter", and "calendar year".

Examples

```
# create a DataFrame with a Datetime column and an f64 column
dates = c(
  "2020-01-01 13:45:48", "2020-01-01 16:42:13", "2020-01-01 16:45:09",
  "2020-01-02 18:12:48", "2020-01-03 19:45:32", "2020-01-08 23:16:43"
)

df = pl$DataFrame(dt = dates, a = c(3, 7, 5, 9, 2, 1))$
  with_columns(
  pl$col("dt")$str$strptime(pl$Datetime("us"), format = "%Y-%m-%d %H:%M:%S")$set_sorted()
)

df$with_columns(
  sum_a = pl$sum("a")$rolling(index_column = "dt", period = "2d"),
  min_a = pl$min("a")$rolling(index_column = "dt", period = "2d"),
  max_a = pl$max("a")$rolling(index_column = "dt", period = "2d")
)

# we can use "offset" to change the start of the window period. Here, with
# offset = "1d", we start the window one day after the value in "dt", and
# then we add a 2-day window relative to the window start.
df$with_columns(
  sum_a_offset1 = pl$sum("a")$rolling(index_column = "dt", period = "2d", offset = "1d")
)
```

`Expr_rolling_max` *Rolling maximum*

Description

Compute the rolling (= moving) max over the values in this array. A window of length `window_size` will traverse the array. The values that fill this window will (optionally) be multiplied with the weights given by the `weight` vector.

Usage

```
Expr_rolling_max(
  window_size,
  weights = NULL,
  min_periods = NULL,
  ...,
  center = FALSE
)
```

Arguments

`window_size`	Integer specifying the length of the window.
`weights`	An optional slice with the same length as the window that will be multiplied elementwise with the values in the window.

min_periods	The number of values in the window that should be non-null before computing a result. If NULL, it will be set equal to window size.
...	Ignored.
center	Set the labels at the center of the window

Details

If you want to compute multiple aggregation statistics over the same dynamic window, consider using $rolling() this method can cache the window size computation.

Value

Expr

Examples

```
pl$DataFrame(a = c(1, 3, 2, 4, 5, 6))$
  with_columns(roll_max = pl$col("a")$rolling_max(window_size = 2))
```

Expr_rolling_max_by *Apply a rolling max based on another column.*

Description

Apply a rolling max based on another column.

Usage

```
Expr_rolling_max_by(by, window_size, ..., min_periods = 1, closed = "right")
```

Arguments

by	This column must of dtype Date or Datetime.
window_size	The length of the window. Can be a fixed integer size, or a dynamic temporal size indicated by the following string language: • 1ns (1 nanosecond) • 1us (1 microsecond) • 1ms (1 millisecond) • 1s (1 second) • 1m (1 minute) • 1h (1 hour) • 1d (1 day) • 1w (1 week) • 1mo (1 calendar month) • 1y (1 calendar year)

- 1i (1 index count) If the dynamic string language is used, the by and closed arguments must also be set.

...	Ignored.
min_periods	The number of values in the window that should be non-null before computing a result. If NULL, it will be set equal to window size.
closed	Define which sides of the temporal interval are closed (inclusive). This can be either "left", "right", "both" or "none".

Details

If you want to compute multiple aggregation statistics over the same dynamic window, consider using $rolling() this method can cache the window size computation.

Value

Expr

Examples

```
df_temporal = pl$DataFrame(
  date = pl$datetime_range(as.Date("2001-1-1"), as.Date("2001-1-2"), "1h")
)$with_row_index("index")

df_temporal

df_temporal$with_columns(
  rolling_row_max = pl$col("index")$rolling_max_by("date", window_size = "3h")
)
```

Expr_rolling_mean *Rolling mean*

Description

Compute the rolling (= moving) mean over the values in this array. A window of length window_size will traverse the array. The values that fill this window will (optionally) be multiplied with the weights given by the weight vector.

Usage

```
Expr_rolling_mean(
  window_size,
  weights = NULL,
  min_periods = NULL,
  ...,
  center = FALSE
)
```

Arguments

`window_size`	Integer specifying the length of the window.
`weights`	An optional slice with the same length as the window that will be multiplied elementwise with the values in the window.
`min_periods`	The number of values in the window that should be non-null before computing a result. If `NULL`, it will be set equal to window size.
`...`	Ignored.
`center`	Set the labels at the center of the window

Details

If you want to compute multiple aggregation statistics over the same dynamic window, consider using `$rolling()` this method can cache the window size computation.

Value

Expr

Examples

```
pl$DataFrame(a = c(1, 3, 2, 4, 5, 6))$
  with_columns(roll_mean = pl$col("a")$rolling_mean(window_size = 2))
```

`Expr_rolling_mean_by` *Apply a rolling mean based on another column.*

Description

Apply a rolling mean based on another column.

Usage

```
Expr_rolling_mean_by(by, window_size, ..., min_periods = 1, closed = "right")
```

Arguments

`by`	This column must of dtype `Date` or `Datetime`.
`window_size`	The length of the window. Can be a fixed integer size, or a dynamic temporal size indicated by the following string language: • 1ns (1 nanosecond) • 1us (1 microsecond) • 1ms (1 millisecond) • 1s (1 second) • 1m (1 minute) • 1h (1 hour)

- 1d (1 day)
- 1w (1 week)
- 1mo (1 calendar month)
- 1y (1 calendar year)
- 1i (1 index count) If the dynamic string language is used, the by and closed arguments must also be set.

`...` Ignored.

`min_periods` The number of values in the window that should be non-null before computing a result. If NULL, it will be set equal to window size.

`closed` Define which sides of the temporal interval are closed (inclusive). This can be either "left", "right", "both" or "none".

Details

If you want to compute multiple aggregation statistics over the same dynamic window, consider using $rolling() this method can cache the window size computation.

Value

Expr

Examples

```
df_temporal = pl$DataFrame(
  date = pl$datetime_range(as.Date("2001-1-1"), as.Date("2001-1-2"), "1h")
)$with_row_index("index")

df_temporal

df_temporal$with_columns(
  rolling_row_mean = pl$col("index")$rolling_mean_by("date", window_size = "3h")
)
```

Expr_rolling_median *Rolling median*

Description

Compute the rolling (= moving) median over the values in this array. A window of length window_size will traverse the array. The values that fill this window will (optionally) be multiplied with the weights given by the weight vector.

Usage

```
Expr_rolling_median(
  window_size,
  weights = NULL,
  min_periods = NULL,
  center = FALSE
)
```

Arguments

window_size	Integer specifying the length of the window.
weights	An optional slice with the same length as the window that will be multiplied elementwise with the values in the window.
min_periods	The number of values in the window that should be non-null before computing a result. If NULL, it will be set equal to window size.
center	Set the labels at the center of the window

Details

If you want to compute multiple aggregation statistics over the same dynamic window, consider using `$rolling()` this method can cache the window size computation.

Value

Expr

Examples

```
pl$DataFrame(a = c(1, 3, 2, 4, 5, 6))$
  with_columns(roll_median = pl$col("a")$rolling_median(window_size = 2))
```

Expr_rolling_median_by

Apply a rolling median based on another column.

Description

Apply a rolling median based on another column.

Usage

```
Expr_rolling_median_by(by, window_size, ..., min_periods = 1, closed = "right")
```

Arguments

by	This column must of dtype Date or Datetime.
window_size	The length of the window. Can be a fixed integer size, or a dynamic temporal size indicated by the following string language: • 1ns (1 nanosecond) • 1us (1 microsecond) • 1ms (1 millisecond) • 1s (1 second) • 1m (1 minute) • 1h (1 hour) • 1d (1 day) • 1w (1 week) • 1mo (1 calendar month) • 1y (1 calendar year) • 1i (1 index count) If the dynamic string language is used, the by and closed arguments must also be set.
...	Ignored.
min_periods	The number of values in the window that should be non-null before computing a result. If NULL, it will be set equal to window size.
closed	Define which sides of the temporal interval are closed (inclusive). This can be either "left", "right", "both" or "none".

Details

If you want to compute multiple aggregation statistics over the same dynamic window, consider using $rolling() this method can cache the window size computation.

Value

Expr

Examples

```
df_temporal = pl$DataFrame(
  date = pl$datetime_range(as.Date("2001-1-1"), as.Date("2001-1-2"), "1h")
)$with_row_index("index")

df_temporal

df_temporal$with_columns(
  rolling_row_median = pl$col("index")$rolling_median_by("date", window_size = "3h")
)
```

Expr_rolling_min *Rolling minimum*

Description

Compute the rolling (= moving) min over the values in this array. A window of length `window_size` will traverse the array. The values that fill this window will (optionally) be multiplied with the weights given by the `weight` vector.

Usage

```
Expr_rolling_min(
  window_size,
  weights = NULL,
  min_periods = NULL,
  ...,
  center = FALSE
)
```

Arguments

`window_size`	Integer specifying the length of the window.
`weights`	An optional slice with the same length as the window that will be multiplied elementwise with the values in the window.
`min_periods`	The number of values in the window that should be non-null before computing a result. If `NULL`, it will be set equal to window size.
`...`	Ignored.
`center`	Set the labels at the center of the window

Details

If you want to compute multiple aggregation statistics over the same dynamic window, consider using `$rolling()` this method can cache the window size computation.

Value

Expr

Examples

```
pl$DataFrame(a = c(1, 3, 2, 4, 5, 6))$
  with_columns(roll_min = pl$col("a")$rolling_min(window_size = 2))
```

`Expr_rolling_min_by` *Apply a rolling min based on another column.*

Description

Apply a rolling min based on another column.

Usage

```
Expr_rolling_min_by(by, window_size, ..., min_periods = 1, closed = "right")
```

Arguments

`by`	This column must of dtype `Date` or `Datetime`.
`window_size`	The length of the window. Can be a fixed integer size, or a dynamic temporal size indicated by the following string language: • 1ns (1 nanosecond) • 1us (1 microsecond) • 1ms (1 millisecond) • 1s (1 second) • 1m (1 minute) • 1h (1 hour) • 1d (1 day) • 1w (1 week) • 1mo (1 calendar month) • 1y (1 calendar year) • 1i (1 index count) If the dynamic string language is used, the `by` and `closed` arguments must also be set.
`...`	Ignored.
`min_periods`	The number of values in the window that should be non-null before computing a result. If `NULL`, it will be set equal to window size.
`closed`	Define which sides of the temporal interval are closed (inclusive). This can be either `"left"`, `"right"`, `"both"` or `"none"`.

Details

If you want to compute multiple aggregation statistics over the same dynamic window, consider using `$rolling()` this method can cache the window size computation.

Value

Expr

Examples

```
df_temporal = pl$DataFrame(
  date = pl$datetime_range(as.Date("2001-1-1"), as.Date("2001-1-2"), "1h")
)$with_row_index("index")

df_temporal

df_temporal$with_columns(
  rolling_row_min = pl$col("index")$rolling_min_by("date", window_size = "3h")
)
```

Expr_rolling_quantile *Rolling quantile*

Description

Compute the rolling (= moving) quantile over the values in this array. A window of length `window_size` will traverse the array. The values that fill this window will (optionally) be multiplied with the weights given by the `weight` vector.

Usage

```
Expr_rolling_quantile(
  quantile,
  interpolation = "nearest",
  window_size,
  weights = NULL,
  min_periods = NULL,
  ...,
  center = FALSE
)
```

Arguments

`quantile`	Quantile between 0 and 1.
`interpolation`	String, one of `"nearest"`, `"higher"`, `"lower"`, `"midpoint"`, `"linear"`.
`window_size`	Integer specifying the length of the window.
`weights`	An optional slice with the same length as the window that will be multiplied elementwise with the values in the window.
`min_periods`	The number of values in the window that should be non-null before computing a result. If `NULL`, it will be set equal to window size.
`...`	Ignored.
`center`	Set the labels at the center of the window

Details

If you want to compute multiple aggregation statistics over the same dynamic window, consider using `$rolling()` this method can cache the window size computation.

Value

Expr

Examples

```
pl$DataFrame(a = c(1, 3, 2, 4, 5, 6))$
  with_columns(roll_quant = pl$col("a")$rolling_quantile(0.3, window_size = 2))
```

Expr_rolling_quantile_by

Compute a rolling quantile based on another column

Description

Compute a rolling quantile based on another column

Usage

```
Expr_rolling_quantile_by(
  by,
  window_size,
  ...,
  quantile,
  interpolation = "nearest",
  min_periods = 1,
  closed = "right"
)
```

Arguments

`by`	This column must of dtype `Date` or `Datetime`.
`window_size`	The length of the window. Can be a fixed integer size, or a dynamic temporal size indicated by the following string language: • 1ns (1 nanosecond) • 1us (1 microsecond) • 1ms (1 millisecond) • 1s (1 second) • 1m (1 minute) • 1h (1 hour) • 1d (1 day)

- 1w (1 week)
- 1mo (1 calendar month)
- 1y (1 calendar year)
- 1i (1 index count) If the dynamic string language is used, the by and closed arguments must also be set.

...	Ignored.
quantile	Either a numeric value or an Expr whose value must be between 0 and 1.
interpolation	One of "nearest", "higher", "lower", "midpoint", or "linear".
min_periods	The number of values in the window that should be non-null before computing a result. If NULL, it will be set equal to window size.
closed	Define which sides of the temporal interval are closed (inclusive). This can be either "left", "right", "both" or "none".

Details

If you want to compute multiple aggregation statistics over the same dynamic window, consider using $rolling() this method can cache the window size computation.

Value

Expr

Examples

```
df_temporal = pl$DataFrame(
  date = pl$datetime_range(as.Date("2001-1-1"), as.Date("2001-1-2"), "1h")
)$with_row_index("index")

df_temporal

df_temporal$with_columns(
  rolling_row_quantile = pl$col("index")$rolling_quantile_by(
    "date",
    window_size = "2h", quantile = 0.3
  )
)
```

Expr_rolling_skew *Rolling skew*

Description

Compute the rolling (= moving) skewness over the values in this array. A window of length window_size will traverse the array.

Usage

```
Expr_rolling_skew(window_size, bias = TRUE)
```

Arguments

`window_size`	Integer specifying the length of the window.
`bias`	If `FALSE`, the calculations are corrected for statistical bias.

Details

For normally distributed data, the skewness should be about zero. For uni-modal continuous distributions, a skewness value greater than zero means that there is more weight in the right tail of the distribution.

Value

Expr

Examples

```
pl$DataFrame(a = c(1, 3, 2, 4, 5, 6))$
  with_columns(roll_skew = pl$col("a")$rolling_skew(window_size = 2))
```

`Expr_rolling_std` *Rolling standard deviation*

Description

Compute the rolling (= moving) standard deviation over the values in this array. A window of length `window_size` will traverse the array. The values that fill this window will (optionally) be multiplied with the weights given by the `weight` vector.

Usage

```
Expr_rolling_std(
  window_size,
  weights = NULL,
  min_periods = NULL,
  ...,
  center = FALSE,
  ddof = 1
)
```

Arguments

`window_size`	Integer specifying the length of the window.
`weights`	An optional slice with the same length as the window that will be multiplied elementwise with the values in the window.
`min_periods`	The number of values in the window that should be non-null before computing a result. If `NULL`, it will be set equal to window size.
`...`	Ignored.
`center`	Set the labels at the center of the window
`ddof`	An integer representing "Delta Degrees of Freedom": the divisor used in the calculation is `N - ddof`, where `N` represents the number of elements. By default ddof is `1`.

Details

If you want to compute multiple aggregation statistics over the same dynamic window, consider using `$rolling()` this method can cache the window size computation.

Value

Expr

Examples

```
pl$DataFrame(a = c(1, 3, 2, 4, 5, 6))$
  with_columns(roll_std = pl$col("a")$rolling_std(window_size = 2))
```

`Expr_rolling_std_by` *Compute a rolling standard deviation based on another column*

Description

Compute a rolling standard deviation based on another column

Usage

```
Expr_rolling_std_by(
  by,
  window_size,
  ...,
  min_periods = 1,
  closed = "right",
  ddof = 1
)
```

Arguments

by	This column must of dtype Date or Datetime.
window_size	The length of the window. Can be a fixed integer size, or a dynamic temporal size indicated by the following string language: • 1ns (1 nanosecond) • 1us (1 microsecond) • 1ms (1 millisecond) • 1s (1 second) • 1m (1 minute) • 1h (1 hour) • 1d (1 day) • 1w (1 week) • 1mo (1 calendar month) • 1y (1 calendar year) • 1i (1 index count) If the dynamic string language is used, the by and closed arguments must also be set.
...	Ignored.
min_periods	The number of values in the window that should be non-null before computing a result. If NULL, it will be set equal to window size.
closed	Define which sides of the temporal interval are closed (inclusive). This can be either "left", "right", "both" or "none".
ddof	An integer representing "Delta Degrees of Freedom": the divisor used in the calculation is N - ddof, where N represents the number of elements. By default ddof is 1.

Details

If you want to compute multiple aggregation statistics over the same dynamic window, consider using $rolling() this method can cache the window size computation.

Value

Expr

Examples

```
df_temporal = pl$DataFrame(
  date = pl$datetime_range(as.Date("2001-1-1"), as.Date("2001-1-2"), "1h")
)$with_row_index("index")

df_temporal

# Compute the rolling std with the temporal windows closed on the right (default)
df_temporal$with_columns(
  rolling_row_std = pl$col("index")$rolling_std_by("date", window_size = "2h")
)
```

```
# Compute the rolling std with the closure of windows on both sides
df_temporal$with_columns(
 rolling_row_std = pl$col("index")$rolling_std_by("date", window_size = "2h", closed = "both")
)
```

`Expr_rolling_sum` *Rolling sum*

Description

Compute the rolling (= moving) sum over the values in this array. A window of length `window_size` will traverse the array. The values that fill this window will (optionally) be multiplied with the weights given by the `weight` vector.

Usage

```
Expr_rolling_sum(
  window_size,
  weights = NULL,
  min_periods = NULL,
  center = FALSE
)
```

Arguments

`window_size`	Integer specifying the length of the window.
`weights`	An optional slice with the same length as the window that will be multiplied elementwise with the values in the window.
`min_periods`	The number of values in the window that should be non-null before computing a result. If `NULL`, it will be set equal to window size.
`center`	Set the labels at the center of the window

Details

If you want to compute multiple aggregation statistics over the same dynamic window, consider using `$rolling()` this method can cache the window size computation.

Value

Expr

Examples

```
pl$DataFrame(a = c(1, 3, 2, 4, 5, 6))$
  with_columns(roll_sum = pl$col("a")$rolling_sum(window_size = 2))
```

`Expr_rolling_sum_by` *Apply a rolling sum based on another column.*

Description

Apply a rolling sum based on another column.

Usage

```
Expr_rolling_sum_by(by, window_size, ..., min_periods = 1, closed = "right")
```

Arguments

`by`	This column must of dtype `Date` or `Datetime`.
`window_size`	The length of the window. Can be a fixed integer size, or a dynamic temporal size indicated by the following string language: • 1ns (1 nanosecond) • 1us (1 microsecond) • 1ms (1 millisecond) • 1s (1 second) • 1m (1 minute) • 1h (1 hour) • 1d (1 day) • 1w (1 week) • 1mo (1 calendar month) • 1y (1 calendar year) • 1i (1 index count) If the dynamic string language is used, the `by` and `closed` arguments must also be set.
`...`	Ignored.
`min_periods`	The number of values in the window that should be non-null before computing a result. If `NULL`, it will be set equal to window size.
`closed`	Define which sides of the temporal interval are closed (inclusive). This can be either `"left"`, `"right"`, `"both"` or `"none"`.

Details

If you want to compute multiple aggregation statistics over the same dynamic window, consider using `$rolling()` this method can cache the window size computation.

Value

Expr

Examples

```
df_temporal = pl$DataFrame(
  date = pl$datetime_range(as.Date("2001-1-1"), as.Date("2001-1-2"), "1h")
)$with_row_index("index")

df_temporal

df_temporal$with_columns(
  rolling_row_sum = pl$col("index")$rolling_sum_by("date", window_size = "3h")
)
```

`Expr_rolling_var` *Rolling variance*

Description

Compute the rolling (= moving) variance over the values in this array. A window of length `window_size` will traverse the array. The values that fill this window will (optionally) be multiplied with the weights given by the `weight` vector.

Usage

```
Expr_rolling_var(
  window_size,
  weights = NULL,
  min_periods = NULL,
  ...,
  center = FALSE,
  ddof = 1
)
```

Arguments

`window_size`	Integer specifying the length of the window.
`weights`	An optional slice with the same length as the window that will be multiplied elementwise with the values in the window.
`min_periods`	The number of values in the window that should be non-null before computing a result. If `NULL`, it will be set equal to window size.
`...`	Ignored.
`center`	Set the labels at the center of the window
`ddof`	An integer representing "Delta Degrees of Freedom": the divisor used in the calculation is `N - ddof`, where `N` represents the number of elements. By default ddof is `1`.

Details

If you want to compute multiple aggregation statistics over the same dynamic window, consider using `$rolling()` this method can cache the window size computation.

Value

Expr

Examples

```
pl$DataFrame(a = c(1, 3, 2, 4, 5, 6))$
  with_columns(roll_var = pl$col("a")$rolling_var(window_size = 2))
```

Expr_rolling_var_by *Compute a rolling variance based on another column*

Description

Compute a rolling variance based on another column

Usage

```
Expr_rolling_var_by(
  by,
  window_size,
  ...,
  min_periods = 1,
  closed = "right",
  ddof = 1
)
```

Arguments

`by`	This column must of dtype `Date` or `Datetime`.
`window_size`	The length of the window. Can be a fixed integer size, or a dynamic temporal size indicated by the following string language: • 1ns (1 nanosecond) • 1us (1 microsecond) • 1ms (1 millisecond) • 1s (1 second) • 1m (1 minute) • 1h (1 hour) • 1d (1 day) • 1w (1 week) • 1mo (1 calendar month)

- 1y (1 calendar year)
- 1i (1 index count) If the dynamic string language is used, the by and `closed` arguments must also be set.

`...` Ignored.

`min_periods` The number of values in the window that should be non-null before computing a result. If `NULL`, it will be set equal to window size.

`closed` Define which sides of the temporal interval are closed (inclusive). This can be either `"left"`, `"right"`, `"both"` or `"none"`.

`ddof` An integer representing "Delta Degrees of Freedom": the divisor used in the calculation is `N - ddof`, where `N` represents the number of elements. By default ddof is `1`.

Details

If you want to compute multiple aggregation statistics over the same dynamic window, consider using `$rolling()` this method can cache the window size computation.

Value

Expr

Examples

```
df_temporal = pl$DataFrame(
  date = pl$datetime_range(as.Date("2001-1-1"), as.Date("2001-1-2"), "1h")
)$with_row_index("index")

df_temporal

# Compute the rolling var with the temporal windows closed on the right (default)
df_temporal$with_columns(
  rolling_row_var = pl$col("index")$rolling_var_by("date", window_size = "2h")
)

# Compute the rolling var with the closure of windows on both sides
df_temporal$with_columns(
 rolling_row_var = pl$col("index")$rolling_var_by("date", window_size = "2h", closed = "both")
)
```

`Expr_round` *Round*

Description

Round underlying floating point data by `decimals` digits.

Usage

```
Expr_round(decimals)
```

Arguments

decimals	Number of decimals to round by.

Value

Expr

Examples

```
pl$DataFrame(a = c(0.33, 0.5, 1.02, 1.5, NaN, NA, Inf, -Inf))$with_columns(
  round = pl$col("a")$round(1)
)
```

Expr_sample *Take a sample*

Description

Take a sample

Usage

```
Expr_sample(
  n = NULL,
  ...,
  fraction = NULL,
  with_replacement = FALSE,
  shuffle = FALSE,
  seed = NULL
)
```

Arguments

n	Number of items to return. Cannot be used with `fraction`.
...	Ignored.
fraction	Fraction of items to return. Cannot be used with `n`. Can be larger than 1 if `with_replacement` is `TRUE`.
with_replacement	If `TRUE` (default), allow values to be sampled more than once.
shuffle	Shuffle the order of sampled data points (implicitly `TRUE` if `with_replacement = TRUE`).
seed	numeric value of 0 to 2^52 Seed for the random number generator. If `NULL` (default), a random seed value between 0 and 10000 is picked.

Value

Expr

Examples

```
df = pl$DataFrame(a = 1:4)
df$select(pl$col("a")$sample(fraction = 1, with_replacement = TRUE, seed = 1L))
df$select(pl$col("a")$sample(fraction = 2, with_replacement = TRUE, seed = 1L))
df$select(pl$col("a")$sample(n = 2, with_replacement = FALSE, seed = 1L))
```

Expr_search_sorted *Where to inject element(s) to maintain sorting*

Description

Find indices where elements should be inserted to maintain order.

Usage

```
Expr_search_sorted(element)
```

Arguments

element	Element to insert. Can be an Expr or something coercible to an Expr.

Details

This function looks up where to insert element to keep self column sorted. It is assumed the column is already sorted in ascending order (otherwise this leads to wrong results).

Value

Expr

Examples

```
df = pl$DataFrame(a = c(1, 3, 4, 4, 6))
df

# in which row should 5 be inserted in order to not break the sort?
# (value is 0-indexed)
df$select(
  zero = pl$col("a")$search_sorted(0),
  three = pl$col("a")$search_sorted(3),
  five = pl$col("a")$search_sorted(5)
)
```

Expr_set_sorted *Flag an Expr as "sorted"*

Description

This enables downstream code to use fast paths for sorted arrays. WARNING: this doesn't check whether the data is actually sorted, you have to ensure of that yourself.

Usage

```
Expr_set_sorted(..., descending = FALSE)
```

Arguments

...	Ignored.
descending	Sort the columns in descending order.

Value

Expr

Examples

```
# correct use flag something correctly as ascendingly sorted
s = pl$select(pl$lit(1:4)$set_sorted()$alias("a"))$get_column("a")
s$flags

# incorrect use, flag something as not sorted ascendingly
s2 = pl$select(pl$lit(c(1, 3, 2, 4))$set_sorted()$alias("a"))$get_column("a")
s2$sort()
s2$flags # returns TRUE while it's not actually sorted
```

Expr_shift *Shift values by the given number of indices*

Description

Shift values by the given number of indices

Usage

```
Expr_shift(n = 1, fill_value = NULL)
```

Arguments

n	Number of indices to shift forward. If a negative value is passed, values are shifted in the opposite direction instead.
fill_value	Fill the resulting null values with this value. Accepts expression input. Non-expression inputs are parsed as literals.

Value

Expr

Examples

```
pl$DataFrame(a = c(1, 2, 4, 5, 8))$
  with_columns(
  pl$col("a")$shift(-2)$alias("shift-2"),
  pl$col("a")$shift(2)$alias("shift+2")
)
```

Expr_shrink_dtype *Shrink numeric columns to the minimal required datatype*

Description

Shrink to the dtype needed to fit the extrema of this Series. This can be used to reduce memory pressure.

Usage

```
Expr_shrink_dtype()
```

Value

Expr

Examples

```
df = pl$DataFrame(
  a = 1:3,
  b = c(1, 2, 3)
)
df

df$with_columns(pl$all()$shrink_dtype()$name$suffix("_shrunk"))
```

Expr_shuffle *Shuffle values*

Description

Shuffle values

Usage

```
Expr_shuffle(seed = NULL)
```

Arguments

seed	numeric value of 0 to 2^52 Seed for the random number generator. If NULL (default), a random seed value between 0 and 10000 is picked.

Value

Expr

Examples

```
pl$DataFrame(a = 1:4)$with_columns(shuff = pl$col("a")$shuffle(seed = 1))
```

Expr_sign *Get the sign of elements*

Description

Get the sign of elements

Usage

```
Expr_sign()
```

Value

Expr

Examples

```
pl$DataFrame(a = c(.9, -3, -0, 0, 4, NA_real_))$
  with_columns(sign = pl$col("a")$sign())
```

Expr_sin — *Compute sine*

Description

Compute sine

Usage

```
Expr_sin()
```

Value

Expr

Examples

```
pl$DataFrame(a = c(0, pi / 2, pi, NA_real_))$
  with_columns(sine = pl$col("a")$sin())
```

Expr_sinh — *Compute hyperbolic sine*

Description

Compute hyperbolic sine

Usage

```
Expr_sinh()
```

Value

Expr

Examples

```
pl$DataFrame(a = c(-1, asinh(0.5), 0, 1, NA_real_))$
  with_columns(sinh = pl$col("a")$sinh())
```

Expr_skew *Skewness*

Description

Compute the sample skewness of a data set.

Usage

```
Expr_skew(bias = TRUE)
```

Arguments

bias	If FALSE, then the calculations are corrected for statistical bias.

Details

For normally distributed data, the skewness should be about zero. For uni-modal continuous distributions, a skewness value greater than zero means that there is more weight in the right tail of the distribution.

Value

Expr

Examples

```
df = pl$DataFrame(list(a = c(1:3, 2:1)))
df$select(pl$col("a")$skew())
```

Expr_slice *Get a slice of an Expr*

Description

Performing a slice of length 1 on a subset of columns will recycle this value in those columns but will not change the number of rows in the data. See examples.

Usage

```
Expr_slice(offset, length = NULL)
```

Arguments

offset	Numeric or expression, zero-indexed. Indicates where to start the slice. A negative value is one-indexed and starts from the end.
length	Maximum number of elements contained in the slice. Default is full data.

Value

Expr

Examples

```
# as head
pl$DataFrame(list(a = 0:100))$select(
  pl$all()$slice(0, 6)
)

# as tail
pl$DataFrame(list(a = 0:100))$select(
  pl$all()$slice(-6, 6)
)

pl$DataFrame(list(a = 0:100))$select(
  pl$all()$slice(80)
)

# recycling
as_polars_df(mtcars)$with_columns(pl$col("mpg")$slice(0, 1)$first())
```

Expr_sort *Sort an Expr*

Description

Sort this column. If used in a groupby context, the groups are sorted.

Usage

```
Expr_sort(..., descending = FALSE, nulls_last = FALSE)
```

Arguments

`...`	Ignored.
`descending`	A logical. If `TRUE`, sort in descending order.
`nulls_last`	A logical. If `TRUE`, place `null` values last insead of first.

Value

Expr

Examples

```
pl$DataFrame(a = c(6, 1, 0, NA, Inf, NaN))$
  with_columns(sorted = pl$col("a")$sort())
```

Expr_sort_by — *Sort Expr by order of others*

Description

Sort this column by the ordering of another column, or multiple other columns. If used in a groupby context, the groups are sorted.

Usage

```
Expr_sort_by(
  by,
  ...,
  descending = FALSE,
  nulls_last = FALSE,
  multithreaded = TRUE,
  maintain_order = FALSE
)
```

Arguments

`by`	One expression or a list of expressions and/or strings (interpreted as column names).
`...`	Ignored.
`descending`	A logical. If `TRUE`, sort in descending order.
`nulls_last`	A logical. If `TRUE`, place `null` values last insead of first.
`multithreaded`	A logical. If `TRUE`, sort using multiple threads.
`maintain_order`	A logical to indicate whether the order should be maintained if elements are equal.

Value

Expr

Examples

```
df = pl$DataFrame(
  group = c("a", "a", "a", "b", "b", "b"),
  value1 = c(98, 1, 3, 2, 99, 100),
  value2 = c("d", "f", "b", "e", "c", "a")
)

# by one column/expression
df$with_columns(
  sorted = pl$col("group")$sort_by("value1")
)
```

```
# by two columns/expressions
df$with_columns(
  sorted = pl$col("group")$sort_by(
    list("value2", pl$col("value1")),
    descending = c(TRUE, FALSE)
  )
)

# by some expression
df$with_columns(
  sorted = pl$col("group")$sort_by(pl$col("value1")$sort(descending = TRUE))
)
```

`Expr_sqrt` *Compute the square root of the elements*

Description

Compute the square root of the elements

Usage

```
Expr_sqrt()
```

Value

Expr

Examples

```
pl$DataFrame(a = -1:3)$with_columns(a_sqrt = pl$col("a")$sqrt())
```

`Expr_std` *Get standard deviation*

Description

Get standard deviation

Usage

```
Expr_std(ddof = 1)
```

Arguments

`ddof`	An integer representing "Delta Degrees of Freedom": the divisor used in the calculation is `N - ddof`, where `N` represents the number of elements. By default ddof is `1`.

Value

Expr

Examples

```
pl$select(pl$lit(1:5)$std())
```

Expr_sub *Substract two expressions*

Description

Method equivalent of subtraction operator `expr - other`.

Usage

```
Expr_sub(other)
```

Arguments

`other`	Numeric literal or expression value.

Value

Expr

See Also

- Arithmetic operators

Examples

```
df = pl$DataFrame(x = 0:4)

df$with_columns(
  `x-2` = pl$col("x")$sub(2),
  `x-expr` = pl$col("x")$sub(pl$col("x")$cum_sum())
)
```

Expr_sum — *Get sum value*

Description

Get sum value

Usage

```
Expr_sum()
```

Details

The dtypes Int8, UInt8, Int16 and UInt16 are cast to Int64 before summing to prevent overflow issues.

Value

Expr

Examples

```
pl$DataFrame(x = c(1L, NA, 2L))$
  with_columns(sum = pl$col("x")$sum())
```

Expr_tail — *Get the last n elements*

Description

Get the last n elements

Usage

```
Expr_tail(n = 10)
```

Arguments

n	Number of elements to take.

Value

Expr

Examples

```
pl$DataFrame(x = 1:11)$select(pl$col("x")$tail(3))
```

Expr_tan — *Compute tangent*

Description

Compute tangent

Usage

```
Expr_tan()
```

Value

Expr

Examples

```
pl$DataFrame(a = c(0, pi / 2, pi, NA_real_))$
  with_columns(tangent = pl$col("a")$tan())
```

Expr_tanh — *Compute hyperbolic tangent*

Description

Compute hyperbolic tangent

Usage

```
Expr_tanh()
```

Value

Expr

Examples

```
pl$DataFrame(a = c(-1, atanh(0.5), 0, 1, NA_real_))$
  with_columns(tanh = pl$col("a")$tanh())
```

Expr_to_physical — *Cast an Expr to its physical representation*

Description

The following DataTypes will be converted:

- Date -> Int32
- Datetime -> Int64
- Time -> Int64
- Duration -> Int64
- Categorical -> UInt32
- List(inner) -> List(physical of inner) Other data types will be left unchanged.

Usage

```
Expr_to_physical()
```

Value

Expr

Examples

```
pl$DataFrame(
  list(vals = c("a", "x", NA, "a", "b"))
)$with_columns(
  pl$col("vals")$cast(pl$Categorical()),
  pl$col("vals")
  $cast(pl$Categorical())
  $to_physical()
  $alias("vals_physical")
)
```

Expr_to_r — *Convert an Expr to R output*

Description

This is mostly useful to debug an expression. It evaluates the Expr in an empty DataFrame and return the first Series to R.

Usage

```
Expr_to_r(
  df = NULL,
  i = 0,
  ...,
  int64_conversion = polars_options()$int64_conversion
)
```

Arguments

`df` If `NULL` (default), it evaluates the Expr in an empty DataFrame. Otherwise, provide a DataFrame that the Expr should be evaluated in.

`i` Numeric column to extract. Default is zero (which gives the first column).

`...` Any args pased to `as.data.frame()`.

`int64_conversion`
How should Int64 values be handled when converting a polars object to R?

- `"double"` (default) converts the integer values to double.
- `"bit64"` uses `bit64::as.integer64()` to do the conversion (requires the package `bit64` to be attached).
- `"string"` converts Int64 values to character.

Value

R object

Examples

```
pl$lit(1:3)$to_r()
```

Expr_to_series *Convert Literal to Series*

Description

Collect an expression based on literals into a Series.

Usage

```
Expr_to_series()
```

Value

Series

Examples

```
pl$lit(1:5)$to_series()
```

Expr_top_k *Top k values*

Description

Return the k largest elements. This has time complexity: $O(n + k logn - \frac{k}{2})$

Usage

```
Expr_top_k(k)
```

Arguments

k	Number of top values to get.

Value

Expr

Examples

```
pl$DataFrame(a = c(6, 1, 0, NA, Inf, NaN))$select(pl$col("a")$top_k(5))
```

Expr_unique *Get unique values*

Description

Get unique values

Usage

```
Expr_unique(maintain_order = FALSE)
```

Arguments

maintain_order	If TRUE, the unique values are returned in order of appearance.

Value

Expr

Examples

```
as_polars_df(iris)$select(pl$col("Species")$unique())
```

Expr_unique_counts *Count unique values*

Description

Return a count of the unique values in the order of appearance. This method differs from `$value_counts()` in that it does not return the values, only the counts and it might be faster.

Usage

```
Expr_unique_counts()
```

Value

Expr

Examples

```
as_polars_df(iris)$select(pl$col("Species")$unique_counts())
```

Expr_upper_bound *Find the upper bound of a DataType*

Description

Find the upper bound of a DataType

Usage

```
Expr_upper_bound()
```

Value

Expr

Examples

```
pl$DataFrame(
  x = c(1, 2, 3), y = -2:0,
  schema = list(x = pl$Float64, y = pl$Int32)
)$
  select(pl$all()$upper_bound())
```

Expr_value_counts *Value counts*

Description

Count all unique values and create a struct mapping value to count.

Usage

```
Expr_value_counts(..., sort = FALSE, parallel = FALSE, name, normalize = FALSE)
```

Arguments

`...`	Ignored.
`sort`	Ensure the output is sorted from most values to least.
`parallel`	Better to turn this off in the aggregation context, as it can lead to contention.
`name`	Give the resulting count column a specific name. The default is `"count"` if `normalize = FALSE` and `"proportion"` if `normalize = TRUE`.
`normalize`	If `TRUE`, it gives relative frequencies of the unique values instead of their count.

Value

Expr

Examples

```
df = as_polars_df(iris)
df$select(pl$col("Species")$value_counts())$unnest()
df$select(pl$col("Species")$value_counts(normalize = TRUE))$unnest()
```

Expr_var *Get variance*

Description

Get variance

Usage

```
Expr_var(ddof = 1)
```

Arguments

`ddof`	An integer representing "Delta Degrees of Freedom": the divisor used in the calculation is `N - ddof`, where `N` represents the number of elements. By default ddof is `1`.

Value

Expr

Examples

```
pl$select(pl$lit(1:5)$var())
```

Expr_when_then_otherwise

Make a when-then-otherwise expression

Description

`when-then-otherwise` is similar to R `ifelse()`. Always initiated by a `pl$when(<condition>)$then(<value if conditi` and optionally followed by chaining one or more `$when(<condition>)$then(<value if condition>)` statements.

Usage

```
pl_when(...)

When_then(statement)

Then_when(...)

Then_otherwise(statement)

ChainedWhen_then(statement)

ChainedThen_when(...)

ChainedThen_otherwise(statement)
```

Arguments

`...`	Expr or something coercible to an Expr that returns a boolian each row.
`statement`	Expr or something coercible to an Expr value to insert in `$then()` or `$otherwise()`. A character vector is parsed as column names.

Details

Chained when-then operations should be read like `if, else if, else if, ...` in R, not as `if, if, if, ...`, i.e. the first condition that evaluates to `true` will be picked.

If none of the conditions are `true`, an optional `$otherwise(<value if all statements are false>)` can be appended at the end. If not appended, and none of the conditions are `true`, `null` will be returned.

`RPolarsThen` objects and `RPolarsChainedThen` objects (returned by `$then()`) stores the same methods as Expr.

Value

- pl$when() returns a When object
- <When>$then() returns a Then object
- <Then>$when() returns a ChainedWhen object
- <ChainedWhen>$then() returns a ChainedThen object
- $otherwise() returns an Expr object.

Examples

```
df = pl$DataFrame(foo = c(1, 3, 4), bar = c(3, 4, 0))

# Add a column with the value 1, where column "foo" > 2 and the value -1
# where it isn't.
df$with_columns(
  val = pl$when(pl$col("foo") > 2)$then(1)$otherwise(-1)
)

# With multiple when-then chained:
df$with_columns(
  val = pl$when(pl$col("foo") > 2)
  $then(1)
  $when(pl$col("bar") > 2)
  $then(4)
  $otherwise(-1)
)

# The `$otherwise` at the end is optional.
# If left out, any rows where none of the `$when()` expressions are evaluated to `true`,
# are set to `null`
df$with_columns(
  val = pl$when(pl$col("foo") > 2)$then(1)
)

# Pass multiple predicates, each of which must be met:
df$with_columns(
  val = pl$when(
    pl$col("bar") > 0,
    pl$col("foo") %% 2 != 0
  )
  $then(99)
  $otherwise(-1)
)

# In `$then()`, a character vector is parsed as column names
df$with_columns(baz = pl$when(pl$col("foo") %% 2 == 1)$then("bar"))

# So use `pl$lit()` to insert a string
df$with_columns(baz = pl$when(pl$col("foo") %% 2 == 1)$then(pl$lit("bar")))
```

Expr_xor — *Apply logical XOR on two expressions*

Description

Combine two boolean expressions with XOR.

Usage

```
Expr_xor(other)
```

Arguments

other	numeric or string value; accepts expression input.

Value

Expr

Examples

```
pl$lit(TRUE)$xor(pl$lit(FALSE))
```

ExprArr_all — *Evaluate whether all boolean values in an array are true*

Description

Evaluate whether all boolean values in an array are true

Usage

```
ExprArr_all()
```

Value

Expr

Examples

```
df = pl$DataFrame(
  values = list(c(TRUE, TRUE), c(FALSE, TRUE), c(FALSE, FALSE), c(NA, NA)),
  schema = list(values = pl$Array(pl$Boolean, 2))
)
df$with_columns(all = pl$col("values")$arr$all())
```

ExprArr_any — *Evaluate whether any boolean values in an array are true*

Description

Evaluate whether any boolean values in an array are true

Usage

```
ExprArr_any()
```

Value

Expr

Examples

```
df = pl$DataFrame(
  values = list(c(TRUE, TRUE), c(FALSE, TRUE), c(FALSE, FALSE), c(NA, NA)),
  schema = list(values = pl$Array(pl$Boolean, 2))
)
df$with_columns(any = pl$col("values")$arr$any())
```

ExprArr_arg_max — *Get the index of the maximal value in an array*

Description

Get the index of the maximal value in an array

Usage

```
ExprArr_arg_max()
```

Value

Expr

Examples

```
df = pl$DataFrame(
  values = list(1:2, 2:1),
  schema = list(values = pl$Array(pl$Int32, 2))
)
df$with_columns(
  arg_max = pl$col("values")$arr$arg_max()
)
```

ExprArr_arg_min — *Get the index of the minimal value in an array*

Description

Get the index of the minimal value in an array

Usage

```
ExprArr_arg_min()
```

Value

Expr

Examples

```
df = pl$DataFrame(
  values = list(1:2, 2:1),
  schema = list(values = pl$Array(pl$Int32, 2))
)
df$with_columns(
  arg_min = pl$col("values")$arr$arg_min()
)
```

ExprArr_contains — *Check if array contains a given value*

Description

Check if array contains a given value

Usage

```
ExprArr_contains(item)
```

Arguments

item	Expr or something coercible to an Expr. Strings are *not* parsed as columns.

Value

Expr

Examples

```
df = pl$DataFrame(
  values = list(0:2, 4:6, c(NA_integer_, NA_integer_, NA_integer_)),
  item = c(0L, 4L, 2L),
  schema = list(values = pl$Array(pl$Float64, 3))
)
df$with_columns(
  with_expr = pl$col("values")$arr$contains(pl$col("item")),
  with_lit = pl$col("values")$arr$contains(1)
)
```

ExprArr_get *Get the value by index in an array*

Description

This allows to extract one value per array only.

Usage

```
ExprArr_get(index, ..., null_on_oob = TRUE)
```

Arguments

index	An Expr or something coercible to an Expr, that must return a single index. Values are 0-indexed (so index 0 would return the first item of every sub-array) and negative values start from the end (index -1 returns the last item).
...	Ignored.
null_on_oob	If TRUE, return null if an index is out of bounds. Otherwise, raise an error.

Value

Expr

Examples

```
df = pl$DataFrame(
  values = list(c(1, 2), c(3, 4), c(NA_real_, 6)),
  idx = c(1, NA, 3),
  schema = list(values = pl$Array(pl$Float64, 2))
)
df$with_columns(
  using_expr = pl$col("values")$arr$get("idx"),
  val_0 = pl$col("values")$arr$get(0),
  val_minus_1 = pl$col("values")$arr$get(-1),
  val_oob = pl$col("values")$arr$get(10)
)
```

ExprArr_join — *Join elements of an array*

Description

Join all string items in a sub-array and place a separator between them. This only works on columns of type `list[str]`.

Usage

```
ExprArr_join(separator, ignore_nulls = FALSE)
```

Arguments

`separator`	String to separate the items with. Can be an Expr. Strings are *not* parsed as columns.
`ignore_nulls`	If `FALSE` (default), null values are propagated: if the row contains any null values, the output is null.

Value

Expr

Examples

```
df = pl$DataFrame(
  values = list(c("a", "b", "c"), c("x", "y", "z"), c("e", NA, NA)),
  separator = c("-", "+", "/"),
  schema = list(values = pl$Array(pl$String, 3))
)
df$with_columns(
  join_with_expr = pl$col("values")$arr$join(pl$col("separator")),
  join_with_lit = pl$col("values")$arr$join(" "),
  join_ignore_null = pl$col("values")$arr$join(" ", ignore_nulls = TRUE)
)
```

ExprArr_max — *Find the maximum value in an array*

Description

Find the maximum value in an array

Usage

```
ExprArr_max()
```

Details

This method is only available with the "nightly" feature. See polars_info() for more details.

Value

Expr

Examples

```
df = pl$DataFrame(
  values = list(c(1, 2), c(3, 4), c(NA_real_, NA_real_)),
  schema = list(values = pl$Array(pl$Float64, 2))
)
df$with_columns(max = pl$col("values")$arr$max())
```

ExprArr_median *Find the median in an array*

Description

Find the median in an array

Usage

```
ExprArr_median()
```

Value

Expr

Examples

```
df = pl$DataFrame(
  values = list(c(2, 1, 4), c(8.4, 3.2, 1)),
  schema = list(values = pl$Array(pl$Float64, 3))
)
df$with_columns(median = pl$col("values")$arr$median())
```

ExprArr_min — *Find the minimum value in an array*

Description

Find the minimum value in an array

Usage

```
ExprArr_min()
```

Details

This method is only available with the "nightly" feature. See polars_info() for more details.

Value

Expr

Examples

```
df = pl$DataFrame(
  values = list(c(1, 2), c(3, 4), c(NA_real_, NA_real_)),
  schema = list(values = pl$Array(pl$Float64, 2))
)
df$with_columns(min = pl$col("values")$arr$min())
```

ExprArr_reverse — *Reverse values in an array*

Description

Reverse values in an array

Usage

```
ExprArr_reverse()
```

Value

Expr

Examples

```
df = pl$DataFrame(
  values = list(c(1, 2), c(3, 4), c(NA_real_, 6)),
  schema = list(values = pl$Array(pl$Float64, 2))
)
df$with_columns(reverse = pl$col("values")$arr$reverse())
```

ExprArr_shift — *Shift array values by* n *indices*

Description

Shift array values by n indices

Usage

```
ExprArr_shift(n = 1)
```

Arguments

n	Number of indices to shift forward. If a negative value is passed, values are shifted in the opposite direction instead.

Value

Expr

Examples

```
df = pl$DataFrame(
  values = list(1:3, c(2L, NA_integer_, 5L)),
  idx = 1:2,
  schema = list(values = pl$Array(pl$Int32, 3))
)
df$with_columns(
  shift_by_expr = pl$col("values")$arr$shift(pl$col("idx")),
  shift_by_lit = pl$col("values")$arr$shift(2)
)
```

ExprArr_sort — *Sort values in an array*

Description

Sort values in an array

Usage

```
ExprArr_sort(descending = FALSE, nulls_last = FALSE)
```

Arguments

descending	A logical. If TRUE, sort in descending order.
nulls_last	A logical. If TRUE, place null values last insead of first.

Examples

```
df = pl$DataFrame(
  values = list(c(2, 1), c(3, 4), c(NA_real_, 6)),
  schema = list(values = pl$Array(pl$Float64, 2))
)
df$with_columns(sort = pl$col("values")$arr$sort(nulls_last = TRUE))
```

ExprArr_std *Find the standard deviation in an array*

Description

Find the standard deviation in an array

Usage

```
ExprArr_std(ddof = 1)
```

Arguments

ddof	Delta Degrees of Freedom: the divisor used in the calculation is N - ddof, where N represents the number of elements. By default ddof is 1.

Value

Expr

Examples

```
df = pl$DataFrame(
  values = list(c(2, 1, 4), c(8.4, 3.2, 1)),
  schema = list(values = pl$Array(pl$Float64, 3))
)
df$with_columns(std = pl$col("values")$arr$std())
```

ExprArr_sum *Sum all elements in an array*

Description

Sum all elements in an array

Usage

```
ExprArr_sum()
```

Value

Expr

Examples

```
df = pl$DataFrame(
  values = list(c(1, 2), c(3, 4), c(NA_real_, 6)),
  schema = list(values = pl$Array(pl$Float64, 2))
)
df$with_columns(sum = pl$col("values")$arr$sum())
```

ExprArr_to_list *Convert an Array column into a List column with the same inner data type*

Description

Convert an Array column into a List column with the same inner data type

Usage

```
ExprArr_to_list()
```

Value

Expr of data type List

Examples

```
df = pl$DataFrame(
  a = list(c(1, 2), c(3, 4)),
  schema = list(a = pl$Array(pl$Int8, 2))
)

df$with_columns(
  list = pl$col("a")$arr$to_list()
)
```

ExprArr_to_struct *Convert array to struct*

Description

Convert array to struct

Usage

```
ExprArr_to_struct(fields = NULL)
```

Arguments

`fields`	If the name and number of the desired fields is known in advance, a list of field names can be given, which will be assigned by index. Otherwise, to dynamically assign field names, a custom R function that takes an R double and outputs a string value can be used. If `NULL` (default), fields will be `field_0`, `field_1` ... `field_n`.

Value

Expr

Examples

```
df = pl$DataFrame(
  values = list(1:3, c(2L, NA_integer_, 5L)),
  schema = list(values = pl$Array(pl$Int32, 3))
)
df$with_columns(
  struct = pl$col("values")$arr$to_struct()
)

# pass a custom function that will name all fields by adding a prefix
df2 = df$with_columns(
  pl$col("values")$arr$to_struct(
    fields = \(idx) paste0("col_", idx)
  )
)
df2

df2$unnest()
```

ExprArr_unique — *Get unique values in an array*

Description

Get unique values in an array

Usage

```
ExprArr_unique(maintain_order = FALSE)
```

Arguments

`maintain_order`	If `TRUE`, the unique values are returned in order of appearance.

Value

Expr

Examples

```
df = pl$DataFrame(
  values = list(c(1, 1, 2), c(4, 4, 4), c(NA_real_, 6, 7)),
  schema = list(values = pl$Array(pl$Float64, 3))
)
df$with_columns(unique = pl$col("values")$arr$unique())
```

ExprArr_var — *Find the variance in an array*

Description

Find the variance in an array

Usage

```
ExprArr_var(ddof = 1)
```

Arguments

`ddof`	Delta Degrees of Freedom: the divisor used in the calculation is N - ddof, where N represents the number of elements. By default ddof is 1.

Value

Expr

Examples

```
df = pl$DataFrame(
  values = list(c(2, 1, 4), c(8.4, 3.2, 1)),
  schema = list(values = pl$Array(pl$Float64, 3))
)
df$with_columns(var = pl$col("values")$arr$var())
```

ExprBin_contains *Check if binaries contain a binary substring*

Description

Check if binaries contain a binary substring

Usage

```
ExprBin_contains(literal)
```

Arguments

literal	The binary substring to look for.

Value

Expr returning a Boolean

Examples

```
colors = pl$DataFrame(
  name = c("black", "yellow", "blue"),
  code = as_polars_series(c("x00x00x00", "xffxffx00", "x00x00xff"))$cast(pl$Binary),
  lit = as_polars_series(c("x00", "xffx00", "xffxff"))$cast(pl$Binary)
)

colors$select(
  "name",
  contains_with_lit = pl$col("code")$bin$contains("xff"),
  contains_with_expr = pl$col("code")$bin$contains(pl$col("lit"))
)
```

ExprBin_decode *Decode values using the provided encoding*

Description

Decode values using the provided encoding

Usage

```
ExprBin_decode(encoding, ..., strict = TRUE)
```

Arguments

encoding	A character, "hex" or "base64". The encoding to use.
...	Ignored.
strict	Raise an error if the underlying value cannot be decoded, otherwise mask out with a null value.

Value

Expr of data type String.

Examples

```
df = pl$DataFrame(
  name = c("black", "yellow", "blue"),
  code_hex = as_polars_series(c("000000", "ffff00", "0000ff"))$cast(pl$Binary),
  code_base64 = as_polars_series(c("AAAA", "//8A", "AAD/"))$cast(pl$Binary)
)

df$with_columns(
  decoded_hex = pl$col("code_hex")$bin$decode("hex"),
  decoded_base64 = pl$col("code_base64")$bin$decode("base64")
)

# Set `strict = FALSE` to set invalid values to `null` instead of raising an error.
df = pl$DataFrame(
  colors = as_polars_series(c("000000", "ffff00", "invalid_value"))$cast(pl$Binary)
)
df$select(pl$col("colors")$bin$decode("hex", strict = FALSE))
```

ExprBin_encode — *Encode a value using the provided encoding*

Description

Encode a value using the provided encoding

Usage

```
ExprBin_encode(encoding)
```

Arguments

encoding	A character, "hex" or "base64". The encoding to use.

Value

Expr of data type String.

Examples

```
df = pl$DataFrame(
  name = c("black", "yellow", "blue"),
  code = as_polars_series(
    c("000000", "ffff00", "0000ff")
  )$cast(pl$Binary)$bin$decode("hex")
)

df$with_columns(encoded = pl$col("code")$bin$encode("hex"))
```

ExprBin_ends_with — *Check if string values end with a binary substring*

Description

Check if string values end with a binary substring

Usage

```
ExprBin_ends_with(suffix)
```

Arguments

suffix	Suffix substring.

Value

Expr returning a Boolean

Examples

```
colors = pl$DataFrame(
  name = c("black", "yellow", "blue"),
  code = as_polars_series(c("x00x00x00", "xffxffx00", "x00x00xff"))$cast(pl$Binary),
  suffix = as_polars_series(c("x00", "xffx00", "xffxff"))$cast(pl$Binary)
)

colors$select(
  "name",
  ends_with_lit = pl$col("code")$bin$ends_with("xff"),
  ends_with_expr = pl$col("code")$bin$ends_with(pl$col("suffix"))
)
```

ExprBin_size *Get the size of binary values in the given unit*

Description

Get the size of binary values in the given unit

Usage

```
ExprBin_size(unit = "b")
```

Arguments

`unit`	Scale the returned size to the given unit. Can be `"b"`, `"kb"`, `"mb"`, `"gb"`, `"tb"`, or their full names (`"kilobytes"`, etc.).

Value

Expr of data type UInt or Float.

Examples

```
df = pl$DataFrame(
  name = c("black", "yellow", "blue"),
  code_hex = as_polars_series(c("000000", "ffff00", "0000ff"))$cast(pl$Binary)
)

df$with_columns(
  n_bytes = pl$col("code_hex")$bin$size(),
  n_kilobytes = pl$col("code_hex")$bin$size("kb")
)
```

ExprBin_starts_with *Check if values start with a binary substring*

Description

Check if values start with a binary substring

Usage

```
ExprBin_starts_with(sub)
```

Arguments

sub	Prefix substring.

Value

Expr returing a Boolean

Examples

```
colors = pl$DataFrame(
  name = c("black", "yellow", "blue"),
  code = as_polars_series(c("x00x00x00", "xffxffx00", "x00x00xff"))$cast(pl$Binary),
  prefix = as_polars_series(c("x00", "xffx00", "xffxff"))$cast(pl$Binary)
)

colors$select(
  "name",
  starts_with_lit = pl$col("code")$bin$starts_with("xff"),
  starts_with_expr = pl$col("code")$bin$starts_with(pl$col("prefix"))
)
```

ExprCat_get_categories *Get the categories stored in this data type*

Description

Get the categories stored in this data type

Usage

```
ExprCat_get_categories()
```

Value

A polars DataFrame with the categories for each categorical Series.

Examples

```
df = pl$DataFrame(
  cats = factor(c("z", "z", "k", "a", "b")),
  vals = factor(c(3, 1, 2, 2, 3))
)
df

df$select(
  pl$col("cats")$cat$get_categories()
)
df$select(
  pl$col("vals")$cat$get_categories()
)
```

`ExprCat_set_ordering` *Set Ordering*

Description

Determine how this categorical series should be sorted.

Usage

```
ExprCat_set_ordering(ordering)
```

Arguments

`ordering`	string either 'physical' or 'lexical' • `"physical"`: use the physical representation of the categories to determine the order (default). • `"lexical"`: use the string values to determine the order.

Value

An Expr of datatype Categorical

Examples

```
df = pl$DataFrame(
  cats = factor(c("z", "z", "k", "a", "b")),
  vals = c(3, 1, 2, 2, 3)
)

# sort by the string value of categories
df$with_columns(
  pl$col("cats")$cat$set_ordering("lexical")
)$sort("cats", "vals")
```

```
# sort by the underlying value of categories
df$with_columns(
  pl$col("cats")$cat$set_ordering("physical")
)$sort("cats", "vals")
```

ExprDT_cast_time_unit *cast_time_unit*

Description

Cast the underlying data to another time unit. This may lose precision. The corresponding global timepoint will stay unchanged +/- precision.

Usage

```
ExprDT_cast_time_unit(tu = c("ns", "us", "ms"))
```

Arguments

tu	string option either 'ns', 'us', or 'ms'

Value

Expr of i64

Examples

```
df = pl$DataFrame(
  date = pl$datetime_range(
    start = as.Date("2001-1-1"),
    end = as.Date("2001-1-3"),
    interval = "1d1s"
  )
)
df$select(
  pl$col("date"),
  pl$col("date")$dt$cast_time_unit()$alias("cast_time_unit_ns"),
  pl$col("date")$dt$cast_time_unit(tu = "ms")$alias("cast_time_unit_ms")
)
```

ExprDT_combine *Combine Date and Time*

Description

If the underlying expression is a Datetime then its time component is replaced, and if it is a Date then a new Datetime is created by combining the two values.

Usage

```
ExprDT_combine(time, time_unit = "us")
```

Arguments

time	The number of epoch since or before (if negative) the Date. Can be an Expr or a PTime.
time_unit	Unit of time. One of "ms", "us" (default) or "ns".

Value

Date/Datetime expr

Examples

```
df = pl$DataFrame(
  dtm = c(
    ISOdatetime(2022, 12, 31, 10, 30, 45),
    ISOdatetime(2023, 7, 5, 23, 59, 59)
  ),
  dt = c(ISOdate(2022, 10, 10), ISOdate(2022, 7, 5)),
  tm = c(pl$time(1, 2, 3, 456000), pl$time(7, 8, 9, 101000))
)$explode("tm")

df

df$select(
  d1 = pl$col("dtm")$dt$combine(pl$col("tm")),
  s2 = pl$col("dt")$dt$combine(pl$col("tm")),
  d3 = pl$col("dt")$dt$combine(pl$time(4, 5, 6))
)
```

ExprDT_convert_time_zone

Convert to given time zone for an expression of type Datetime.

Description

If converting from a time-zone-naive datetime, then conversion will happen as if converting from UTC, regardless of your system's time zone.

Usage

```
ExprDT_convert_time_zone(time_zone)
```

Arguments

time_zone	String time zone from `base::OlsonNames()`

Value

Expr of i64

Examples

```
df = pl$DataFrame(
  date = pl$datetime_range(
    as.POSIXct("2020-03-01", tz = "UTC"),
    as.POSIXct("2020-05-01", tz = "UTC"),
    "1mo1s"
  )
)

df$select(
  "date",
  London = pl$col("date")$dt$convert_time_zone("Europe/London")
)
```

ExprDT_day

Day

Description

Extract day from underlying Date representation. Applies to Date and Datetime columns. Returns the day of month starting from 1. The return value ranges from 1 to 31. (The last day of month differs by months.)

Usage

```
ExprDT_day()
```

Value

Expr of day as UInt32

Examples

```
df = pl$DataFrame(
  date = pl$date_range(
    as.Date("2020-12-25"),
    as.Date("2021-1-05"),
    interval = "1d",
    time_zone = "GMT"
  )
)
df$with_columns(
  pl$col("date")$dt$day()$alias("day")
)
```

ExprDT_epoch *Epoch*

Description

Get the time passed since the Unix EPOCH in the give time unit.

Usage

```
ExprDT_epoch(time_unit = "us")
```

Arguments

time_unit	Time unit, one of "ns", "us", "ms", "s" or "d".

Value

Expr with datatype Int64

Examples

```
df = pl$DataFrame(date = pl$date_range(as.Date("2001-1-1"), as.Date("2001-1-3")))

df$with_columns(
  epoch_ns = pl$col("date")$dt$epoch(),
  epoch_s = pl$col("date")$dt$epoch(time_unit = "s")
)
```

ExprDT_hour *Hour*

Description

Extract hour from underlying Datetime representation. Applies to Datetime columns. Returns the hour number from 0 to 23.

Usage

```
ExprDT_hour()
```

Value

Expr of hour as UInt32

Examples

```
df = pl$DataFrame(
  date = pl$datetime_range(
    as.Date("2020-12-25"),
    as.Date("2021-1-05"),
    interval = "1d2h",
    time_zone = "GMT"
  )
)
df$with_columns(
  pl$col("date")$dt$hour()$alias("hour")
)
```

ExprDT_is_leap_year *Determine whether the year of the underlying date is a leap year*

Description

Determine whether the year of the underlying date is a leap year

Usage

```
ExprDT_is_leap_year()
```

Value

An Expr of datatype Bool

Examples

```
df = pl$DataFrame(date = as.Date(c("2000-01-01", "2001-01-01", "2002-01-01")))

df$with_columns(
  leap_year = pl$col("date")$dt$is_leap_year()
)
```

ExprDT_iso_year *Iso-Year*

Description

Extract ISO year from underlying Date representation. Applies to Date and Datetime columns. Returns the year number in the ISO standard. This may not correspond with the calendar year.

Usage

```
ExprDT_iso_year()
```

Value

Expr of iso_year as Int32

Examples

```
df = pl$DataFrame(
  date = pl$date_range(
    as.Date("2020-12-25"),
    as.Date("2021-1-05"),
    interval = "1d",
    time_zone = "GMT"
  )
)
df$with_columns(
  pl$col("date")$dt$year()$alias("year"),
  pl$col("date")$dt$iso_year()$alias("iso_year")
)
```

ExprDT_microsecond *Extract microseconds from underlying Datetime representation.*

Description

Applies to Datetime columns.

Usage

```
ExprDT_microsecond()
```

Value

Expr of data type Int32

Examples

```
df = pl$DataFrame(
  datetime = as.POSIXct(
    c(
      "1978-01-01 01:01:01",
      "2024-10-13 05:30:14.500",
      "2065-01-01 10:20:30.06"
    ),
    "UTC"
  )
)

df$with_columns(
  microsecond = pl$col("datetime")$dt$microsecond()
)
```

ExprDT_millisecond *Extract milliseconds from underlying Datetime representation*

Description

Applies to Datetime columns.

Usage

```
ExprDT_millisecond()
```

Value

Expr of data type Int32

Examples

```
df = pl$DataFrame(
  datetime = as.POSIXct(
    c(
      "1978-01-01 01:01:01",
      "2024-10-13 05:30:14.500",
      "2065-01-01 10:20:30.06"
    ),
    "UTC"
  )
)

df$with_columns(
  millisecond = pl$col("datetime")$dt$millisecond()
)
```

ExprDT_minute *Minute*

Description

Extract minutes from underlying Datetime representation. Applies to Datetime columns. Returns the minute number from 0 to 59.

Usage

```
ExprDT_minute()
```

Value

Expr of minute as UInt32

Examples

```
df = pl$DataFrame(
  date = pl$datetime_range(
    as.Date("2020-12-25"),
    as.Date("2021-1-05"),
    interval = "1d5s",
    time_zone = "GMT"
  )
)
df$with_columns(
  pl$col("date")$dt$minute()$alias("minute")
)
```

ExprDT_month *Month*

Description

Extract month from underlying Date representation. Applies to Date and Datetime columns. Returns the month number starting from 1. The return value ranges from 1 to 12.

Usage

```
ExprDT_month()
```

Value

Expr of month as UInt32

Examples

```
df = pl$DataFrame(
  date = pl$date_range(
    as.Date("2020-12-25"),
    as.Date("2021-1-05"),
    interval = "1d",
    time_zone = "GMT"
  )
)
df$with_columns(
  pl$col("date")$dt$month()$alias("month")
)
```

ExprDT_nanosecond *Extract nanoseconds from underlying Datetime representation*

Description

Applies to Datetime columns.

Usage

```
ExprDT_nanosecond()
```

Value

Expr of data type Int32

Examples

```
df = pl$DataFrame(
  datetime = as.POSIXct(
    c(
      "1978-01-01 01:01:01",
      "2024-10-13 05:30:14.500",
      "2065-01-01 10:20:30.06"
    ),
    "UTC"
  )
)

df$with_columns(
  nanosecond = pl$col("datetime")$dt$nanosecond()
)
```

`ExprDT_offset_by` *Offset By*

Description

Offset this date by a relative time offset. This differs from `pl$col("foo_datetime_tu") + value_tu` in that it can take months and leap years into account. Note that only a single minus sign is allowed in the `by` string, as the first character.

Usage

```
ExprDT_offset_by(by)
```

Arguments

`by`	optional string encoding duration see details.

Details

The `by` are created with the the following string language:

- 1ns # 1 nanosecond
- 1us # 1 microsecond
- 1ms # 1 millisecond
- 1s # 1 second
- 1m # 1 minute
- 1h # 1 hour
- 1d # 1 day
- 1w # 1 calendar week
- 1mo # 1 calendar month

- 1y # 1 calendar year
- 1i # 1 index count

These strings can be combined:

- 3d12h4m25s # 3 days, 12 hours, 4 minutes, and 25 seconds

Value

Date/Datetime expr

Examples

```
df = pl$DataFrame(
  dates = pl$date_range(
    as.Date("2000-1-1"),
    as.Date("2005-1-1"),
    "1y"
  )
)
df$select(
  pl$col("dates")$dt$offset_by("1y")$alias("date_plus_1y"),
  pl$col("dates")$dt$offset_by("-1y2mo")$alias("date_min")
)

# the "by" argument also accepts expressions
df = pl$DataFrame(
  dates = pl$datetime_range(
    as.POSIXct("2022-01-01", tz = "GMT"),
    as.POSIXct("2022-01-02", tz = "GMT"),
    interval = "6h", time_unit = "ms", time_zone = "GMT"
  )$to_r(),
  offset = c("1d", "-2d", "1mo", NA, "1y")
)

df

df$with_columns(new_dates = pl$col("dates")$dt$offset_by(pl$col("offset")))
```

ExprDT_ordinal_day *Ordinal Day*

Description

Extract ordinal day from underlying Date representation. Applies to Date and Datetime columns. Returns the day of year starting from 1. The return value ranges from 1 to 366. (The last day of year differs by years.)

Usage

```
ExprDT_ordinal_day()
```

Value

Expr of ordinal_day as UInt32

Examples

```
df = pl$DataFrame(
  date = pl$date_range(
    as.Date("2020-12-25"),
    as.Date("2021-1-05"),
    interval = "1d",
    time_zone = "GMT"
  )
)
df$with_columns(
  pl$col("date")$dt$ordinal_day()$alias("ordinal_day")
)
```

ExprDT_quarter *Quarter*

Description

Extract quarter from underlying Date representation. Applies to Date and Datetime columns. Returns the quarter ranging from 1 to 4.

Usage

```
ExprDT_quarter()
```

Value

Expr of quarter as UInt32

Examples

```
df = pl$DataFrame(
  date = pl$date_range(
    as.Date("2020-12-25"),
    as.Date("2021-1-05"),
    interval = "1d",
    time_zone = "GMT"
  )
)
df$with_columns(
  pl$col("date")$dt$quarter()$alias("quarter")
)
```

ExprDT_replace_time_zone

Replace time zone

Description

Cast time zone for a Series of type Datetime. This is different from `$convert_time_zone()` as it will also modify the underlying timestamp. Use to correct a wrong time zone annotation. This will change the corresponding global timepoint.

Usage

```
ExprDT_replace_time_zone(
  time_zone,
  ...,
  ambiguous = "raise",
  non_existent = "raise"
)
```

Arguments

`time_zone`	`NULL` or string time zone from `base::OlsonNames()`
`...`	Ignored.
`ambiguous`	Determine how to deal with ambiguous datetimes: • `"raise"` (default): throw an error • `"earliest"`: use the earliest datetime • `"latest"`: use the latest datetime • `"null"`: return a null value
`non_existent`	Determine how to deal with non-existent datetimes: • `"raise"` (default): throw an error • `"null"`: return a null value

Value

Expr of i64

Examples

```
df1 = pl$DataFrame(
  london_timezone = pl$datetime_range(
    as.POSIXct("2020-03-01", tz = "UTC"),
    as.POSIXct("2020-07-01", tz = "UTC"),
    "1mo1s"
  )$dt$convert_time_zone("Europe/London")
)
```

```
df1$select(
  "london_timezone",
 London_to_Amsterdam = pl$col("london_timezone")$dt$replace_time_zone("Europe/Amsterdam")
)

# You can use `ambiguous` to deal with ambiguous datetimes:
dates = c(
  "2018-10-28 01:30",
  "2018-10-28 02:00",
  "2018-10-28 02:30",
  "2018-10-28 02:00"
)
df2 = pl$DataFrame(
  ts = as_polars_series(dates)$str$strptime(pl$Datetime("us")),
  ambiguous = c("earliest", "earliest", "latest", "latest")
)

df2$with_columns(
  ts_localized = pl$col("ts")$dt$replace_time_zone(
    "Europe/Brussels",
    ambiguous = pl$col("ambiguous")
  )
)
```

`ExprDT_round` *Round datetime*

Description

Divide the date/datetime range into buckets. Each date/datetime in the first half of the interval is mapped to the start of its bucket. Each date/datetime in the second half of the interval is mapped to the end of its bucket.

Usage

```
ExprDT_round(every)
```

Arguments

`every`	Either an Expr or a string indicating a column name or a duration (see Details).

Details

The `every` and `offset` argument are created with the the following string language:

- 1ns # 1 nanosecond
- 1us # 1 microsecond
- 1ms # 1 millisecond
- 1s # 1 second

- 1m # 1 minute
- 1h # 1 hour
- 1d # 1 day
- 1w # 1 calendar week
- 1mo # 1 calendar month
- 1y # 1 calendar year These strings can be combined:
  - 3d12h4m25s # 3 days, 12 hours, 4 minutes, and 25 seconds

Value

Date/Datetime expr

Examples

```
t1 = as.POSIXct("3040-01-01", tz = "GMT")
t2 = t1 + as.difftime(25, units = "secs")
s = pl$datetime_range(t1, t2, interval = "2s", time_unit = "ms")

df = pl$DataFrame(datetime = s)$with_columns(
  pl$col("datetime")$dt$round("4s")$alias("rounded_4s")
)
df
```

`ExprDT_second` *Extract seconds from underlying Datetime representation*

Description

Applies to Datetime columns. Returns the integer second number from 0 to 59, or a floating point number from 0 < 60 if `fractional=TRUE` that includes any milli/micro/nanosecond component.

Usage

```
ExprDT_second(fractional = FALSE)
```

Arguments

`fractional`	A logical. Whether to include the fractional component of the second.

Value

Expr of data type Int8 or Float64

Examples

```
df = pl$DataFrame(
  datetime = as.POSIXct(
    c(
      "1978-01-01 01:01:01",
      "2024-10-13 05:30:14.500",
      "2065-01-01 10:20:30.06"
    ),
    "UTC"
  )
)

df$with_columns(
  second = pl$col("datetime")$dt$second(),
  second_fractional = pl$col("datetime")$dt$second(fractional = TRUE)
)
```

ExprDT_strftime *strftime*

Description

Format Date/Datetime with a formatting rule. See chrono strftime/strptime <https://docs.rs/chrono/latest/chro

Usage

```
ExprDT_strftime(format)
```

Arguments

format	string format very much like in R passed to chrono

Value

Date/Datetime expr

Examples

```
pl$lit(as.POSIXct("2021-01-02 12:13:14", tz = "GMT"))$dt$strftime("this is the year: %Y")$to_r()
```

ExprDT_time *Extract time from a Datetime Series*

Description

This only works on Datetime Series, it will error on Date Series.

Usage

```
ExprDT_time()
```

Value

A Time Expr

Examples

```
df = pl$DataFrame(dates = pl$datetime_range(
  as.Date("2000-1-1"),
  as.Date("2000-1-2"),
  "1h"
))

df$with_columns(times = pl$col("dates")$dt$time())
```

ExprDT_timestamp *timestamp*

Description

Return a timestamp in the given time unit.

Usage

```
ExprDT_timestamp(tu = c("ns", "us", "ms"))
```

Arguments

tu	string option either 'ns', 'us', or 'ms'

Value

Expr of i64

Examples

```
df = pl$DataFrame(
  date = pl$datetime_range(
    start = as.Date("2001-1-1"),
    end = as.Date("2001-1-3"),
    interval = "1d1s"
  )
)
df$select(
  pl$col("date"),
  pl$col("date")$dt$timestamp()$alias("timestamp_ns"),
  pl$col("date")$dt$timestamp(tu = "ms")$alias("timestamp_ms")
)
```

ExprDT_total_days *Days*

Description

Extract the days from a Duration type.

Usage

```
ExprDT_total_days()
```

Value

Expr of i64

Examples

```
df = pl$DataFrame(
  date = pl$datetime_range(
    start = as.Date("2020-3-1"),
    end = as.Date("2020-5-1"),
    interval = "1mo1s"
  )
)
df$select(
  pl$col("date"),
  diff_days = pl$col("date")$diff()$dt$total_days()
)
```

ExprDT_total_hours *Hours*

Description

Extract the hours from a Duration type.

Usage

```
ExprDT_total_hours()
```

Value

Expr of i64

Examples

```
df = pl$DataFrame(
  date = pl$date_range(
    start = as.Date("2020-1-1"),
    end = as.Date("2020-1-4"),
    interval = "1d"
  )
)
df$select(
  pl$col("date"),
  diff_hours = pl$col("date")$diff()$dt$total_hours()
)
```

ExprDT_total_microseconds *microseconds*

Description

Extract the microseconds from a Duration type.

Usage

```
ExprDT_total_microseconds()
```

Value

Expr of i64

Examples

```
df = pl$DataFrame(date = pl$datetime_range(
  start = as.POSIXct("2020-1-1", tz = "GMT"),
  end = as.POSIXct("2020-1-1 00:00:01", tz = "GMT"),
  interval = "1ms"
))
df$select(
  pl$col("date"),
  diff_microsec = pl$col("date")$diff()$dt$total_microseconds()
)
```

ExprDT_total_milliseconds *milliseconds*

Description

Extract the milliseconds from a Duration type.

Usage

```
ExprDT_total_milliseconds()
```

Value

Expr of i64

Examples

```
df = pl$DataFrame(date = pl$datetime_range(
  start = as.POSIXct("2020-1-1", tz = "GMT"),
  end = as.POSIXct("2020-1-1 00:00:01", tz = "GMT"),
  interval = "1ms"
))
df$select(
  pl$col("date"),
  diff_millisec = pl$col("date")$diff()$dt$total_milliseconds()
)
```

ExprDT_total_minutes *Minutes*

Description

Extract the minutes from a Duration type.

Usage

```
ExprDT_total_minutes()
```

Value

Expr of i64

Examples

```
df = pl$DataFrame(
  date = pl$date_range(
    start = as.Date("2020-1-1"),
    end = as.Date("2020-1-4"),
    interval = "1d"
  )
)
df$select(
  pl$col("date"),
  diff_minutes = pl$col("date")$diff()$dt$total_minutes()
)
```

ExprDT_total_nanoseconds *nanoseconds*

Description

Extract the nanoseconds from a Duration type.

Usage

```
ExprDT_total_nanoseconds()
```

Value

Expr of i64

Examples

```
df = pl$DataFrame(date = pl$datetime_range(
  start = as.POSIXct("2020-1-1", tz = "GMT"),
  end = as.POSIXct("2020-1-1 00:00:01", tz = "GMT"),
  interval = "1ms"
))
df$select(
  pl$col("date"),
  diff_nanosec = pl$col("date")$diff()$dt$total_nanoseconds()
)
```

ExprDT_total_seconds *Seconds*

Description

Extract the seconds from a Duration type.

Usage

```
ExprDT_total_seconds()
```

Value

Expr of i64

Examples

```
df = pl$DataFrame(date = pl$datetime_range(
  start = as.POSIXct("2020-1-1", tz = "GMT"),
  end = as.POSIXct("2020-1-1 00:04:00", tz = "GMT"),
  interval = "1m"
))
df$select(
  pl$col("date"),
  diff_sec = pl$col("date")$diff()$dt$total_seconds()
)
```

ExprDT_truncate *Truncate datetime*

Description

Divide the date/datetime range into buckets. Each date/datetime is mapped to the start of its bucket.

Usage

```
ExprDT_truncate(every)
```

Arguments

every	Either an Expr or a string indicating a column name or a duration (see Details).

Details

The `every` and `offset` argument are created with the the following string language:

- 1ns # 1 nanosecond
- 1us # 1 microsecond
- 1ms # 1 millisecond
- 1s # 1 second
- 1m # 1 minute
- 1h # 1 hour
- 1d # 1 day
- 1w # 1 calendar week
- 1mo # 1 calendar month
- 1y # 1 calendar year These strings can be combined:
  - 3d12h4m25s # 3 days, 12 hours, 4 minutes, and 25 seconds

Value

Date/Datetime expr

Examples

```
t1 = as.POSIXct("3040-01-01", tz = "GMT")
t2 = t1 + as.difftime(25, units = "secs")
s = pl$datetime_range(t1, t2, interval = "2s", time_unit = "ms")

df = pl$DataFrame(datetime = s)$with_columns(
  pl$col("datetime")$dt$truncate("4s")$alias("truncated_4s")
)
df
```

ExprDT_week *Week*

Description

Extract the week from the underlying Date representation. Applies to Date and Datetime columns. Returns the ISO week number starting from 1. The return value ranges from 1 to 53. (The last week of year differs by years.)

Usage

```
ExprDT_week()
```

Value

Expr of week as UInt32

Examples

```
df = pl$DataFrame(
  date = pl$date_range(
    as.Date("2020-12-25"),
    as.Date("2021-1-05"),
    interval = "1d",
    time_zone = "GMT"
  )
)
df$with_columns(
  pl$col("date")$dt$week()$alias("week")
)
```

ExprDT_weekday *Weekday*

Description

Extract the week day from the underlying Date representation. Applies to Date and Datetime columns. Returns the ISO weekday number where monday = 1 and sunday = 7

Usage

```
ExprDT_weekday()
```

Value

Expr of weekday as UInt32

Examples

```
df = pl$DataFrame(
  date = pl$date_range(
    as.Date("2020-12-25"),
    as.Date("2021-1-05"),
    interval = "1d",
    time_zone = "GMT"
  )
)
df$with_columns(
  pl$col("date")$dt$weekday()$alias("weekday")
)
```

ExprDT_with_time_unit *with_time_unit*

Description

Set time unit of a Series of dtype Datetime or Duration. This does not modify underlying data, and should be used to fix an incorrect time unit. The corresponding global timepoint will change.

Usage

```
ExprDT_with_time_unit(tu = c("ns", "us", "ms"))
```

Arguments

tu	string option either 'ns', 'us', or 'ms'

Value

Expr of i64

Examples

```
df = pl$DataFrame(
  date = pl$datetime_range(
    start = as.Date("2001-1-1"),
    end = as.Date("2001-1-3"),
    interval = "1d1s"
  )
)
df$select(
  pl$col("date"),
  pl$col("date")$dt$with_time_unit()$alias("with_time_unit_ns"),
  pl$col("date")$dt$with_time_unit(tu = "ms")$alias("with_time_unit_ms")
)
```

ExprDT_year *Year*

Description

Extract year from underlying Date representation. Applies to Date and Datetime columns. Returns the year number in the calendar date.

Usage

```
ExprDT_year()
```

Value

Expr of Year as Int32

Examples

```
df = pl$DataFrame(
  date = pl$date_range(
    as.Date("2020-12-25"),
    as.Date("2021-1-05"),
    interval = "1d",
    time_zone = "GMT"
  )
)
df$with_columns(
  pl$col("date")$dt$year()$alias("year"),
  pl$col("date")$dt$iso_year()$alias("iso_year")
)
```

ExprList_all *Evaluate whether all boolean values in a list are true*

Description

Evaluate whether all boolean values in a list are true

Usage

```
ExprList_all()
```

Value

Expr

Examples

```
df = pl$DataFrame(
  list(a = list(c(TRUE, TRUE), c(FALSE, TRUE), c(FALSE, FALSE), NA, c()))
)
df$with_columns(all = pl$col("a")$list$all())
```

ExprList_any *Evaluate whether any boolean values in a list are true*

Description

Evaluate whether any boolean values in a list are true

Usage

```
ExprList_any()
```

Value

Expr

Examples

```
df = pl$DataFrame(
  list(a = list(c(TRUE, TRUE), c(FALSE, TRUE), c(FALSE, FALSE), NA, c()))
)
df$with_columns(any = pl$col("a")$list$any())
```

ExprList_arg_max *Get the index of the maximal value in list*

Description

Get the index of the maximal value in list

Usage

```
ExprList_arg_max()
```

Value

Expr

Examples

```
df = pl$DataFrame(list(s = list(1:2, 2:1)))
df$with_columns(
  arg_max = pl$col("s")$list$arg_max()
)
```

ExprList_arg_min *Get the index of the minimal value in list*

Description

Get the index of the minimal value in list

Usage

```
ExprList_arg_min()
```

Value

Expr

Examples

```
df = pl$DataFrame(list(s = list(1:2, 2:1)))
df$with_columns(
  arg_min = pl$col("s")$list$arg_min()
)
```

ExprList_concat *Concat two list variables*

Description

Concat two list variables

Usage

```
ExprList_concat(other)
```

Arguments

other	Values to concat with. Can be an Expr or something coercible to an Expr.

Value

Expr

Examples

```
df = pl$DataFrame(
  a = list("a", "x"),
  b = list(c("b", "c"), c("y", "z"))
)
df$with_columns(
  conc_to_b = pl$col("a")$list$concat(pl$col("b")),
  conc_to_lit_str = pl$col("a")$list$concat(pl$lit("some string")),
  conc_to_lit_list = pl$col("a")$list$concat(pl$lit(list("hello", c("hello", "world"))))
)
```

ExprList_contains *Check if list contains a given value*

Description

Check if list contains a given value

Usage

```
ExprList_contains(item)
```

Arguments

item	Expr or something coercible to an Expr. Strings are *not* parsed as columns.

Value

Expr

Examples

```
df = pl$DataFrame(
  a = list(3:1, NULL, 1:2),
  item = 0:2
)
df$with_columns(
  with_expr = pl$col("a")$list$contains(pl$col("item")),
  with_lit = pl$col("a")$list$contains(1)
)
```

ExprList_diff — *Compute difference between list values*

Description

This computes the first discrete difference between shifted items of every list. The parameter `n` gives the interval between items to subtract, e.g `n = 2` the output will be the difference between the 1st and the 3rd value, the 2nd and 4th value, etc.

Usage

```
ExprList_diff(n = 1, null_behavior = c("ignore", "drop"))
```

Arguments

`n`	Number of slots to shift. If negative, then it starts from the end.
`null_behavior`	How to handle `null` values. Either `"ignore"` (default) or `"drop"`.

Value

Expr

Examples

```
df = pl$DataFrame(list(s = list(1:4, c(10L, 2L, 1L))))
df$with_columns(diff = pl$col("s")$list$diff(2))

# negative value starts shifting from the end
df$with_columns(diff = pl$col("s")$list$diff(-2))
```

ExprList_eval — *Run any polars expression on the list values*

Description

Run any polars expression on the list values

Usage

```
ExprList_eval(expr, parallel = FALSE)
```

Arguments

`expr`	Expression to run. Note that you can select an element with `pl$element()`, `pl$first()`, and more. See Examples.
`parallel`	Run all expression parallel. Don't activate this blindly. Parallelism is worth it if there is enough work to do per thread. This likely should not be used in the `$group_by()` context, because we already do parallel execution per group.

Value

Expr

Examples

```
df = pl$DataFrame(
  a = list(c(1, 8, 3), c(3, 2), c(NA, NA, 1)),
  b = list(c("R", "is", "amazing"), c("foo", "bar"), "text")
)

df

# standardize each value inside a list, using only the values in this list
df$select(
  a_stand = pl$col("a")$list$eval(
    (pl$element() - pl$element()$mean()) / pl$element()$std()
  )
)

# count characters for each element in list. Since column "b" is list[str],
# we can apply all `$str` functions on elements in the list:
df$select(
  b_len_chars = pl$col("b")$list$eval(
    pl$element()$str$len_chars()
  )
)

# concat strings in each list
df$select(
  pl$col("b")$list$eval(pl$element()$str$join(" "))$list$first()
)
```

`ExprList_explode` *Returns a column with a separate row for every list element*

Description

Returns a column with a separate row for every list element

Usage

```
ExprList_explode()
```

Value

Expr

Examples

```
df = pl$DataFrame(a = list(c(1, 2, 3), c(4, 5, 6)))
df$select(pl$col("a")$list$explode())
```

ExprList_first *Get the first value in a list*

Description

Get the first value in a list

Usage

```
ExprList_first()
```

Value

Expr

Examples

```
df = pl$DataFrame(list(a = list(3:1, NULL, 1:2)))
df$with_columns(
  first = pl$col("a")$list$first()
)
```

ExprList_gather *Get several values by index in a list*

Description

This allows to extract several values per list. To extract a single value by index, use `$list$get()`.

Usage

```
ExprList_gather(index, null_on_oob = FALSE)
```

Arguments

index	An Expr or something coercible to an Expr, that can return several single indices. Values are 0-indexed (so index 0 would return the first item of every sublist) and negative values start from the end (index `-1` returns the last item). If the index is out of bounds, it will return a `null`. Strings are parsed as column names.
null_on_oob	If `TRUE`, return `null` if an index is out of bounds. Otherwise, raise an error.

Value

Expr

Examples

```
df = pl$DataFrame(
  a = list(c(3, 2, 1), 1, c(1, 2)),
  idx = list(0:1, integer(), c(1L, 999L))
)
df$with_columns(
  gathered = pl$col("a")$list$gather("idx", null_on_oob = TRUE)
)

df$with_columns(
  gathered = pl$col("a")$list$gather(2, null_on_oob = TRUE)
)

# by some column name, must cast to an Int/Uint type to work
df$with_columns(
 gathered = pl$col("a")$list$gather(pl$col("a")$cast(pl$List(pl$UInt64)), null_on_oob = TRUE)
)
```

ExprList_gather_every *Gather every nth element in a list*

Description

Gather every nth element in a list

Usage

```
ExprList_gather_every(n, offset = 0)
```

Arguments

n	Positive integer.
offset	Starting index.

Value

Expr

Examples

```
df = pl$DataFrame(
  a = list(1:5, 6:8, 9:12),
  n = c(2, 1, 3),
  offset = c(0, 1, 0)
)

df$with_columns(
  gather_every = pl$col("a")$list$gather_every(pl$col("n"), offset = pl$col("offset"))
)
```

ExprList_get *Get the value by index in a list*

Description

This allows to extract one value per list only. To extract several values by index, use `$list$gather()`.

Usage

```
ExprList_get(index, ..., null_on_oob = TRUE)
```

Arguments

`index`	An Expr or something coercible to an Expr, that must return a single index. Values are 0-indexed (so index 0 would return the first item of every sublist) and negative values start from the end (index `-1` returns the last item).
`...`	Ignored.
`null_on_oob`	If `TRUE`, return `null` if an index is out of bounds. Otherwise, raise an error.

Value

Expr

Examples

```
df = pl$DataFrame(
  values = list(c(2, 2, NA), c(1, 2, 3), NA_real_, NULL),
  idx = c(1, 2, NA, 3)
)
df$with_columns(
  using_expr = pl$col("values")$list$get("idx"),
  val_0 = pl$col("values")$list$get(0),
  val_minus_1 = pl$col("values")$list$get(-1),
  val_oob = pl$col("values")$list$get(10)
)
```

ExprList_head — *Get the first* n *values of a list*

Description

Get the first n values of a list

Usage

```
ExprList_head(n = 5L)
```

Arguments

n	Number of values to return for each sublist. Can be an Expr. Strings are parsed as column names.

Value

Expr

Examples

```
df = pl$DataFrame(
  s = list(1:4, c(10L, 2L, 1L)),
  n = 1:2
)
df$with_columns(
  head_by_expr = pl$col("s")$list$head("n"),
  head_by_lit = pl$col("s")$list$head(2)
)
```

ExprList_join — *Join elements of a list*

Description

Join all string items in a sublist and place a separator between them. This only works on columns of type `list[str]`.

Usage

```
ExprList_join(separator, ignore_nulls = FALSE)
```

Arguments

separator	String to separate the items with. Can be an Expr. Strings are *not* parsed as columns.
ignore_nulls	If FALSE (default), null values are propagated: if the row contains any null values, the output is null.

Value

Expr

Examples

```
df = pl$DataFrame(
  s = list(c("a", "b", "c"), c("x", "y"), c("e", NA)),
  separator = c("-", "+", "/")
)
df$with_columns(
  join_with_expr = pl$col("s")$list$join(pl$col("separator")),
  join_with_lit = pl$col("s")$list$join(" "),
  join_ignore_null = pl$col("s")$list$join(" ", ignore_nulls = TRUE)
)
```

ExprList_last *Get the last value in a list*

Description

Get the last value in a list

Usage

```
ExprList_last()
```

Value

Expr

Examples

```
df = pl$DataFrame(list(a = list(3:1, NULL, 1:2)))
df$with_columns(
  last = pl$col("a")$list$last()
)
```

ExprList_len — *Get the length of each list*

Description

Return the number of elements in each list. Null values are counted in the total.

Usage

```
ExprList_len()
```

Value

Expr

Examples

```
df = pl$DataFrame(list(list_of_strs = list(c("a", "b", NA), "c")))
df$with_columns(len_list = pl$col("list_of_strs")$list$len())
```

ExprList_max — *Find the maximum value in a list*

Description

Find the maximum value in a list

Usage

```
ExprList_max()
```

Value

Expr

Examples

```
df = pl$DataFrame(values = list(c(1, 2, 3, NA), c(2, 3), NA_real_))
df$with_columns(max = pl$col("values")$list$max())
```

ExprList_mean — *Compute the mean value of a list*

Description

Compute the mean value of a list

Usage

```
ExprList_mean()
```

Value

Expr

Examples

```
df = pl$DataFrame(values = list(c(1, 2, 3, NA), c(2, 3), NA_real_))
df$with_columns(mean = pl$col("values")$list$mean())
```

ExprList_min — *Find the minimum value in a list*

Description

Find the minimum value in a list

Usage

```
ExprList_min()
```

Value

Expr

Examples

```
df = pl$DataFrame(values = list(c(1, 2, 3, NA), c(2, 3), NA_real_))
df$with_columns(min = pl$col("values")$list$min())
```

ExprList_n_unique *Get the number of unique values in a list*

Description

Get the number of unique values in a list

Usage

```
ExprList_n_unique()
```

Value

Expr

Examples

```
df = pl$DataFrame(values = list(c(2, 2, NA), c(1, 2, 3), NA_real_))
df$with_columns(unique = pl$col("values")$list$n_unique())
```

ExprList_reverse *Reverse values in a list*

Description

Reverse values in a list

Usage

```
ExprList_reverse()
```

Value

Expr

Examples

```
df = pl$DataFrame(values = list(c(1, 2, 3, NA), c(2, 3), NA_real_))
df$with_columns(reverse = pl$col("values")$list$reverse())
```

ExprList_sample *Sample from this list*

Description

Sample from this list

Usage

```
ExprList_sample(
  n = NULL,
  ...,
  fraction = NULL,
  with_replacement = FALSE,
  shuffle = FALSE,
  seed = NULL
)
```

Arguments

n	Number of items to return. Cannot be used with `fraction`.
...	Ignored.
fraction	Fraction of items to return. Cannot be used with `n`. Can be larger than 1 if `with_replacement` is `TRUE`.
with_replacement	If `TRUE` (default), allow values to be sampled more than once.
shuffle	Shuffle the order of sampled data points (implicitly `TRUE` if `with_replacement = TRUE`).
seed	numeric value of 0 to 2^52 Seed for the random number generator. If `NULL` (default), a random seed value between 0 and 10000 is picked.

Value

Expr

Examples

```
df = pl$DataFrame(
  values = list(1:3, NA_integer_, c(NA_integer_, 3L), 5:7),
  n = c(1, 1, 1, 2)
)

df$with_columns(
  sample = pl$col("values")$list$sample(n = pl$col("n"), seed = 1)
)
```

ExprList_set_difference

Get the difference of two list variables

Description

This returns the "asymmetric difference", meaning only the elements of the first list that are not in the second list. To get all elements that are in only one of the two lists, use `$set_symmetric_difference()`.

Usage

```
ExprList_set_difference(other)
```

Arguments

`other`	Other list variable. Can be an Expr or something coercible to an Expr.

Details

Note that the datatypes inside the list must have a common supertype. For example, the first column can be `list[i32]` and the second one can be `list[i8]` because it can be cast to `list[i32]`. However, the second column cannot be e.g `list[f32]`.

Value

Expr

Examples

```
df = pl$DataFrame(
  a = list(1:3, NA_integer_, c(NA_integer_, 3L), 5:7),
  b = list(2:4, 3L, c(3L, 4L, NA_integer_), c(6L, 8L))
)

df$with_columns(difference = pl$col("a")$list$set_difference("b"))
```

ExprList_set_intersection

Get the intersection of two list variables

Description

Get the intersection of two list variables

Usage

```
ExprList_set_intersection(other)
```

Arguments

other	Other list variable. Can be an Expr or something coercible to an Expr.

Details

Note that the datatypes inside the list must have a common supertype. For example, the first column can be `list[i32]` and the second one can be `list[i8]` because it can be cast to `list[i32]`. However, the second column cannot be e.g `list[f32]`.

Value

Expr

Examples

```
df = pl$DataFrame(
  a = list(1:3, NA_integer_, c(NA_integer_, 3L), 5:7),
  b = list(2:4, 3L, c(3L, 4L, NA_integer_), c(6L, 8L))
)

df$with_columns(intersection = pl$col("a")$list$set_intersection("b"))
```

ExprList_set_symmetric_difference

Get the symmetric difference of two list variables

Description

This returns all elements that are in only one of the two lists. To get only elements that are in the first list but not in the second one, use `$set_difference()`.

Usage

```
ExprList_set_symmetric_difference(other)
```

Arguments

other	Other list variable. Can be an Expr or something coercible to an Expr.

Details

Note that the datatypes inside the list must have a common supertype. For example, the first column can be `list[i32]` and the second one can be `list[i8]` because it can be cast to `list[i32]`. However, the second column cannot be e.g `list[f32]`.

Value

Expr

Examples

```
df = pl$DataFrame(
  a = list(1:3, NA_integer_, c(NA_integer_, 3L), 5:7),
  b = list(2:4, 3L, c(3L, 4L, NA_integer_), c(6L, 8L))
)

df$with_columns(
  symmetric_difference = pl$col("a")$list$set_symmetric_difference("b")
)
```

`ExprList_set_union` *Get the union of two list variables*

Description

Get the union of two list variables

Usage

```
ExprList_set_union(other)
```

Arguments

`other`	Other list variable. Can be an Expr or something coercible to an Expr.

Details

Note that the datatypes inside the list must have a common supertype. For example, the first column can be `list[i32]` and the second one can be `list[i8]` because it can be cast to `list[i32]`. However, the second column cannot be e.g `list[f32]`.

Value

Expr

Examples

```
df = pl$DataFrame(
  a = list(1:3, NA_integer_, c(NA_integer_, 3L), 5:7),
  b = list(2:4, 3L, c(3L, 4L, NA_integer_), c(6L, 8L))
)

df$with_columns(union = pl$col("a")$list$set_union("b"))
```

ExprList_shift *Shift list values by* n *indices*

Description

Shift list values by n indices

Usage

```
ExprList_shift(n = 1)
```

Arguments

n	Number of indices to shift forward. If a negative value is passed, values are shifted in the opposite direction instead.

Value

Expr

Examples

```
df = pl$DataFrame(
  s = list(1:4, c(10L, 2L, 1L)),
  idx = 1:2
)
df$with_columns(
  shift_by_expr = pl$col("s")$list$shift(pl$col("idx")),
  shift_by_lit = pl$col("s")$list$shift(2)
)
```

ExprList_slice *Slice list*

Description

This extracts length values at most, starting at index offset. This can return less than length values if length is larger than the number of values.

Usage

```
ExprList_slice(offset, length = NULL)
```

Arguments

`offset`	Start index. Negative indexing is supported. Can be an Expr. Strings are parsed as column names.
`length`	Length of the slice. If `NULL` (default), the slice is taken to the end of the list. Can be an Expr. Strings are parsed as column names.

Value

Expr

Examples

```
df = pl$DataFrame(
  s = list(1:4, c(10L, 2L, 1L)),
  idx_off = 1:2,
  len = c(4, 1)
)
df$with_columns(
  slice_by_expr = pl$col("s")$list$slice("idx_off", "len"),
  slice_by_lit = pl$col("s")$list$slice(2, 3)
)
```

ExprList_sort *Sort values in a list*

Description

Sort values in a list

Usage

```
ExprList_sort(descending = FALSE)
```

Arguments

`descending`	Sort values in descending order

Value

Expr

Examples

```
df = pl$DataFrame(values = list(c(NA, 2, 1, 3), c(Inf, 2, 3, NaN), NA_real_))
df$with_columns(sort = pl$col("values")$list$sort())
```

ExprList_sum — *Sum all elements in a list*

Description

Sum all elements in a list

Usage

```
ExprList_sum()
```

Value

Expr

Examples

```
df = pl$DataFrame(values = list(c(1, 2, 3, NA), c(2, 3), NA_real_))
df$with_columns(sum = pl$col("values")$list$sum())
```

ExprList_tail — *Get the last* n *values of a list*

Description

Get the last n values of a list

Usage

```
ExprList_tail(n = 5L)
```

Arguments

n	Number of values to return for each sublist. Can be an Expr. Strings are parsed as column names.

Value

Expr

Examples

```
df = pl$DataFrame(
  s = list(1:4, c(10L, 2L, 1L)),
  n = 1:2
)
df$with_columns(
  tail_by_expr = pl$col("s")$list$tail("n"),
  tail_by_lit = pl$col("s")$list$tail(2)
)
```

ExprList_to_struct *Convert a Series of type* List *to* Struct

---

Description

Convert a Series of type `List` to `Struct`

Usage

```
ExprList_to_struct(
  n_field_strategy = c("first_non_null", "max_width"),
  fields = NULL,
  upper_bound = 0
)
```

Arguments

`n_field_strategy`
: Strategy to determine the number of fields of the struct. If `"first_non_null"` (default), set number of fields equal to the length of the first non zero-length list. If `"max_width"`, the number of fields is the maximum length of a list.

`fields`
: If the name and number of the desired fields is known in advance, a list of field names can be given, which will be assigned by index. Otherwise, to dynamically assign field names, a custom R function that takes an R double and outputs a string value can be used. If `NULL` (default), fields will be `field_0`, `field_1` ... `field_n`.

`upper_bound`
: A `LazyFrame` needs to know the schema at all time. The caller therefore must provide an `upper_bound` of struct fields that will be set. If set incorrectly, downstream operation may fail. For instance an `all()$sum()` expression will look in the current schema to determine which columns to select. When operating on a `DataFrame`, the schema does not need to be tracked or pre-determined, as the result will be eagerly evaluated, so you can leave this parameter unset.

Value

Expr

Examples

```
df = pl$DataFrame(list(a = list(1:2, 1:3)))

# this discards the third value of the second list as the struct length is
# determined based on the length of the first non-empty list
df$with_columns(
  struct = pl$col("a")$list$to_struct()
)

# we can use "max_width" to keep all values
df$with_columns(
  struct = pl$col("a")$list$to_struct(n_field_strategy = "max_width")
)

# pass a custom function that will name all fields by adding a prefix
df2 = df$with_columns(
  pl$col("a")$list$to_struct(
    fields = \(idx) paste0("col_", idx)
  )
)
df2

df2$unnest()

df2$to_list()
```

ExprList_unique *Get unique values in a list*

Description

Get unique values in a list

Usage

```
ExprList_unique(maintain_order = FALSE)
```

Arguments

`maintain_order` Maintain order of data. This requires more work.

Value

Expr

Examples

```
df = pl$DataFrame(values = list(c(2, 2, NA), c(1, 2, 3), NA_real_))
df$with_columns(unique = pl$col("values")$list$unique())
```

ExprMeta_eq — *Check if two expressions are equivalent*

Description

Indicate if this expression is the same as another expression. See also the counterpart `$meta$neq()`.

Usage

```
ExprMeta_eq(other)
```

Arguments

`other`	Expr to compare with

Value

A logical value

Examples

```
# three naive expression literals
e1 = pl$lit(40) + 2
e2 = pl$lit(42)
e3 = pl$lit(40) + 2

# e1 and e3 are identical expressions
e1$meta$eq(e3)

# when evaluated, e1 and e2 are equal
e1$eq(e2)$to_r()

# however, on the meta-level, e1 and e2 are NOT identical expressions
e1$meta$eq(e2)
```

ExprMeta_has_multiple_outputs — *Indicate if an expression has multiple outputs*

Description

Indicate if an expression has multiple outputs

Usage

```
ExprMeta_has_multiple_outputs()
```

Value

Boolean

Examples

```
e = (pl$col("alice") + pl$col("eve"))$alias("bob")
e$meta$has_multiple_outputs()

# pl$all() select multiple cols to modify them, so it has multiple outputs
pl$all()$meta$has_multiple_outputs()
```

ExprMeta_is_regex_projection *Indicate if an expression uses a regex projection*

Description

Indicate if an expression uses a regex projection

Usage

```
ExprMeta_is_regex_projection()
```

Value

Boolean

Examples

```
pl$col("^Sepal.*$")$meta$is_regex_projection()
pl$col("Sepal.Length")$meta$is_regex_projection()
```

ExprMeta_neq *Check if two expressions are different*

Description

Indicate if this expression is different from another expression. See also the counterpart `$meta$eq()`.

Usage

```
ExprMeta_neq(other)
```

Arguments

other	Expr to compare with

Value

A logical value

Examples

```
# three naive expression literals
e1 = pl$lit(40) + 2
e2 = pl$lit(42)
e3 = pl$lit(40) + 2

# e1 and e3 are identical expressions
e1$meta$neq(e3)

# when evaluated, e1 and e2 are equal
e1$neq(e2)$to_r()

# however, on the meta-level, e1 and e2 are different
e1$meta$neq(e2)
```

ExprMeta_output_name *Get the column name that this expression would produce*

Description

It may not always be possible to determine the output name as that can depend on the schema of the context; in that case this will raise an error if `raise_if_undetermined` is `TRUE` (the default), or return `NA` otherwise.

Usage

```
ExprMeta_output_name(..., raise_if_undetermined = TRUE)
```

Arguments

`...` Ignored.

`raise_if_undetermined` If `TRUE` (default), raise an error if the output name cannot be determined. Otherwise, return `NA`.

Value

A character vector

Examples

```
e = pl$col("foo") * pl$col("bar")
e$meta$output_name()

e_filter = pl$col("foo")$filter(pl$col("bar") == 13)
e_filter$meta$output_name()

e_sum_over = pl$sum("foo")$over("groups")
e_sum_over$meta$output_name()

e_sum_slice = pl$sum("foo")$slice(pl$len() - 10, pl$col("bar"))
e_sum_slice$meta$output_name()

pl$len()$meta$output_name()

pl$col("*")$meta$output_name(raise_if_undetermined = FALSE)
```

ExprMeta_pop *Pop*

Description

Pop the latest expression and return the input(s) of the popped expression.

Usage

```
ExprMeta_pop()
```

Value

A list of expressions which in most cases will have a unit length. This is not the case when an expression has multiple inputs, for instance in a `$fold()` expression.

Examples

```
e1 = pl$lit(40) + 2
e2 = pl$lit(42)$sum()

e1
e1$meta$pop()

e2
e2$meta$pop()
```

ExprMeta_root_names *Get the root column names*

Description

This returns the names of input columns. Use `$meta$output_name()` to get the name of output column.

Usage

```
ExprMeta_root_names()
```

Value

A character vector

Examples

```
e = (pl$col("alice") + pl$col("eve"))$alias("bob")
e$meta$root_names()
```

ExprMeta_tree_format *Format an expression as a tree*

Description

Format an expression as a tree

Usage

```
ExprMeta_tree_format(return_as_string = FALSE)
```

Arguments

`return_as_string`
: Return the tree as a character vector? If `FALSE` (default), the tree is printed in the console.

Value

If `return_as_string` is `TRUE`, a character vector describing the tree.

If `return_as_string` is `FALSE`, prints the tree in the console but doesn't return any value.

Examples

```
my_expr = (pl$col("foo") * pl$col("bar"))$sum()$over(pl$col("ham")) / 2
my_expr$meta$tree_format()
```

ExprMeta_undo_aliases *Undo any renaming operation*

Description

This removes any renaming operation like `$alias()` or `$name$keep()`. Polars uses the "leftmost rule" to determine naming, meaning that the first element of the expression will be used to name the output.

Usage

```
ExprMeta_undo_aliases()
```

Value

Expr with aliases undone

Examples

```
e = (pl$col("alice") + pl$col("eve"))$alias("bob")
e$meta$output_name()
e$meta$undo_aliases()$meta$output_name()
```

ExprName_keep *Keep the original root name of the expression.*

Description

Keep the original root name of the expression.

Usage

```
ExprName_keep()
```

Value

Expr

Examples

```
pl$DataFrame(list(alice = 1:3))$select(pl$col("alice")$alias("bob")$name$keep())
```

ExprName_prefix *Add a prefix to a column name*

Description

Add a prefix to a column name

Usage

```
ExprName_prefix(prefix)
```

Arguments

prefix	Prefix to be added to column name(s)

Value

Expr

See Also

$suffix() to add a suffix

Examples

```
dat = as_polars_df(mtcars)

dat$select(
  pl$col("mpg"),
  pl$col("mpg")$name$prefix("name_"),
  pl$col("cyl", "drat")$name$prefix("bar_")
)
```

ExprName_prefix_fields *Add a prefix to all fields name of a struct*

Description

Add a prefix to all fields name of a struct

Usage

```
ExprName_prefix_fields(prefix)
```

Arguments

prefix	Prefix to add to the field name.

Value

Expr

Examples

```
df = pl$DataFrame(a = 1, b = 2)$select(
  pl$struct(pl$all())$alias("my_struct")
)

df$with_columns(pl$col("my_struct")$name$prefix_fields("col_"))$unnest()
```

ExprName_suffix *Add a suffix to a column name*

Description

Add a suffix to a column name

Usage

```
ExprName_suffix(suffix)
```

Arguments

suffix	Suffix to be added to column name(s)

Value

Expr

See Also

$prefix() to add a prefix

Examples

```
dat = as_polars_df(mtcars)

dat$select(
  pl$col("mpg"),
  pl$col("mpg")$name$suffix("_foo"),
  pl$col("cyl", "drat")$name$suffix("_bar")
)
```

ExprName_suffix_fields

Add a suffix to all fields name of a struct

Description

Add a suffix to all fields name of a struct

Usage

```
ExprName_suffix_fields(suffix)
```

Arguments

suffix	Suffix to add to the field name.

Value

Expr

Examples

```
df = pl$DataFrame(a = 1, b = 2)$select(
  pl$struct(pl$all())$alias("my_struct")
)

df$with_columns(pl$col("my_struct")$name$suffix_fields("_post"))$unnest()
```

ExprName_to_lowercase

Make the root column name lowercase

Description

Due to implementation constraints, this method can only be called as the last expression in a chain.

Usage

```
ExprName_to_lowercase()
```

Value

Expr

Examples

```
pl$DataFrame(Alice = 1:3)$with_columns(pl$col("Alice")$name$to_lowercase())
```

ExprName_to_uppercase *Make the root column name uppercase*

Description

Due to implementation constraints, this method can only be called as the last expression in a chain.

Usage

```
ExprName_to_uppercase()
```

Value

Expr

Examples

```
pl$DataFrame(Alice = 1:3)$with_columns(pl$col("Alice")$name$to_uppercase())
```

ExprStr_contains *Check if string contains a substring that matches a pattern*

Description

Check if string contains a substring that matches a pattern

Usage

```
ExprStr_contains(pattern, ..., literal = FALSE, strict = TRUE)
```

Arguments

`pattern`	A character or something can be coerced to a string Expr of a valid regex pattern, compatible with the regex crate.
`...`	Ignored.
`literal`	Logical. If `TRUE` (default), treat `pattern` as a literal string, not as a regular expression.
`strict`	Logical. If `TRUE` (default), raise an error if the underlying pattern is not a valid regex, otherwise mask out with a null value.

Details

To modify regular expression behaviour (such as case-sensitivity) with flags, use the inline `(?iLmsuxU)` syntax. See the regex crate's section on grouping and flags for additional information about the use of inline expression modifiers.

Value

Expr of Boolean data type

See Also

- `$str$start_with()`: Check if string values start with a substring.
- `$str$ends_with()`: Check if string values end with a substring.
- `$str$find()`: Return the index position of the first substring matching a pattern.

Examples

```
# The inline `(?i)` syntax example
pl$DataFrame(s = c("AAA", "aAa", "aaa"))$with_columns(
  default_match = pl$col("s")$str$contains("AA"),
  insensitive_match = pl$col("s")$str$contains("(?i)AA")
)

df = pl$DataFrame(txt = c("Crab", "cat and dog", "rab$bit", NA))
df$with_columns(
  regex = pl$col("txt")$str$contains("cat|bit"),
  literal = pl$col("txt")$str$contains("rab$", literal = TRUE)
)
```

ExprStr_contains_any *Use the aho-corasick algorithm to find matches*

Description

This function determines if any of the patterns find a match.

Usage

```
ExprStr_contains_any(patterns, ..., ascii_case_insensitive = FALSE)
```

Arguments

`patterns`	Character vector or something can be coerced to strings Expr of a valid regex pattern, compatible with the regex crate.
`...`	Ignored.
`ascii_case_insensitive`	Enable ASCII-aware case insensitive matching. When this option is enabled, searching will be performed without respect to case for ASCII letters (a-z and A-Z) only.

Value

Expr of Boolean data type

See Also

- <Expr>strcontains()

Examples

```
df = pl$DataFrame(
  lyrics = c(
    "Everybody wants to rule the world",
    "Tell me what you want, what you really really want",
    "Can you feel the love tonight"
  )
)

df$with_columns(
  contains_any = pl$col("lyrics")$str$contains_any(c("you", "me"))
)
```

ExprStr_count_matches *Count all successive non-overlapping regex matches*

Description

Count all successive non-overlapping regex matches

Usage

```
ExprStr_count_matches(pattern, ..., literal = FALSE)
```

Arguments

pattern	A character or something can be coerced to a string Expr of a valid regex pattern, compatible with the regex crate.
...	Ignored.
literal	Logical. If TRUE (default), treat pattern as a literal string, not as a regular expression.

Value

Expr of data type UInt32. Returns null if the original value is null.

Examples

```
df = pl$DataFrame(foo = c("12 dbc 3xy", "cat\\w", "1zy3\\d\\d", NA))

df$with_columns(
  count_digits = pl$col("foo")$str$count_matches(r"(\d)"),
  count_slash_d = pl$col("foo")$str$count_matches(r"(\d)", literal = TRUE)
)
```

ExprStr_decode — *Decode a value using the provided encoding*

Description

Decode a value using the provided encoding

Usage

```
ExprStr_decode(encoding, ..., strict = TRUE)
```

Arguments

encoding	Either 'hex' or 'base64'.
...	Not used currently.
strict	If TRUE (default), raise an error if the underlying value cannot be decoded. Otherwise, replace it with a null value.

Value

String array with values decoded using provided encoding

Examples

```
df = pl$DataFrame(strings = c("foo", "bar", NA))
df$select(pl$col("strings")$str$encode("hex"))
df$with_columns(
  pl$col("strings")$str$encode("base64")$alias("base64"), # notice DataType is not encoded
   pl$col("strings")$str$encode("hex")$alias("hex") # ... and must restored with cast
)$with_columns(
   pl$col("base64")$str$decode("base64")$alias("base64_decoded")$cast(pl$String),
   pl$col("hex")$str$decode("hex")$alias("hex_decoded")$cast(pl$String)
)
```

ExprStr_encode — *Encode a value using the provided encoding*

Description

Encode a value using the provided encoding

Usage

```
ExprStr_encode(encoding)
```

Arguments

encoding Either 'hex' or 'base64'.

Value

String array with values encoded using provided encoding

Examples

```
df = pl$DataFrame(strings = c("foo", "bar", NA))
df$select(pl$col("strings")$str$encode("hex"))
df$with_columns(
  pl$col("strings")$str$encode("base64")$alias("base64"), # notice DataType is not encoded
   pl$col("strings")$str$encode("hex")$alias("hex") # ... and must restored with cast
)$with_columns(
  pl$col("base64")$str$decode("base64")$alias("base64_decoded")$cast(pl$String),
  pl$col("hex")$str$decode("hex")$alias("hex_decoded")$cast(pl$String)
)
```

ExprStr_ends_with *Check if string ends with a regex*

Description

Check if string values end with a substring.

Usage

```
ExprStr_ends_with(sub)
```

Arguments

sub Suffix substring or Expr.

Details

See also `$str$starts_with()` and `$str$contains()`.

Value

Expr of Boolean data type

Examples

```
df = pl$DataFrame(fruits = c("apple", "mango", NA))
df$select(
  pl$col("fruits"),
  pl$col("fruits")$str$ends_with("go")$alias("has_suffix")
)
```

ExprStr_extract *Extract the target capture group from provided patterns*

Description

Extract the target capture group from provided patterns

Usage

```
ExprStr_extract(pattern, group_index)
```

Arguments

pattern	A valid regex pattern. Can be an Expr or something coercible to an Expr. Strings are parsed as column names.
group_index	Index of the targeted capture group. Group 0 means the whole pattern, first group begin at index 1 (default).

Value

String array. Contains null if original value is null or regex capture nothing.

Examples

```
df = pl$DataFrame(
  a = c(
    "http://vote.com/ballon_dor?candidate=messi&ref=polars",
    "http://vote.com/ballon_dor?candidat=jorginho&ref=polars",
    "http://vote.com/ballon_dor?candidate=ronaldo&ref=polars"
  )
)
df$with_columns(
  extracted = pl$col("a")$str$extract(pl$lit(r"(candidate=(\w+))"), 1)
)
```

ExprStr_extract_all *Extract all matches for the given regex pattern*

Description

Extracts all matches for the given regex pattern. Extracts each successive non-overlapping regex match in an individual string as an array.

Usage

```
ExprStr_extract_all(pattern)
```

Arguments

pattern	A valid regex pattern

Value

List[String] array. Contain null if original value is null or regex capture nothing.

Examples

```
df = pl$DataFrame(foo = c("123 bla 45 asd", "xyz 678 910t"))
df$select(
  pl$col("foo")$str$extract_all(r"((\d+))")$alias("extracted_nrs")
)
```

ExprStr_extract_groups

Extract all capture groups for the given regex pattern

Description

Extract all capture groups for the given regex pattern

Usage

```
ExprStr_extract_groups(pattern)
```

Arguments

pattern	A character of a valid regular expression pattern containing at least one capture group, compatible with the regex crate.

Details

All group names are strings. If your pattern contains unnamed groups, their numerical position is converted to a string. See examples.

Value

Expr of data type Struct with fields of data type String.

Examples

```
df = pl$DataFrame(
  url = c(
    "http://vote.com/ballon_dor?candidate=messi&ref=python",
    "http://vote.com/ballon_dor?candidate=weghorst&ref=polars",
    "http://vote.com/ballon_dor?error=404&ref=rust"
  )
)
```

```
pattern = r"(candidate=(?<candidate>\w+)&ref=(?<ref>\w+))"

df$with_columns(
  captures = pl$col("url")$str$extract_groups(pattern)
)$unnest("captures")

# If the groups are unnamed, their numerical position (as a string) is used:

pattern = r"(candidate=(\w+)&ref=(\w+))"

df$with_columns(
  captures = pl$col("url")$str$extract_groups(pattern)
)$unnest("captures")
```

`ExprStr_extract_many` *Use the aho-corasick algorithm to extract matches*

Description

Use the aho-corasick algorithm to extract matches

Usage

```
ExprStr_extract_many(
  patterns,
  ...,
  ascii_case_insensitive = FALSE,
  overlapping = FALSE
)
```

Arguments

`patterns`	String patterns to search. This can be an Expr or something coercible to an Expr. Strings are parsed as column names.
`...`	Ignored.
`ascii_case_insensitive`	Enable ASCII-aware case insensitive matching. When this option is enabled, searching will be performed without respect to case for ASCII letters (a-z and A-Z) only.
`overlapping`	Whether matches can overlap.

Value

Expr: Series of dtype String.

Examples

```
df = pl$DataFrame(values = "discontent")
patterns = pl$lit(c("winter", "disco", "onte", "discontent"))

df$with_columns(
  matches = pl$col("values")$str$extract_many(patterns),
  matches_overlap = pl$col("values")$str$extract_many(patterns, overlapping = TRUE)
)

df = pl$DataFrame(
  values = c("discontent", "rhapsody"),
 patterns = list(c("winter", "disco", "onte", "discontent"), c("rhap", "ody", "coalesce"))
)

df$select(pl$col("values")$str$extract_many("patterns"))
```

ExprStr_find *Return the index position of the first substring matching a pattern*

Description

Return the index position of the first substring matching a pattern

Usage

```
ExprStr_find(pattern, ..., literal = FALSE, strict = TRUE)
```

Arguments

pattern	A character or something can be coerced to a string Expr of a valid regex pattern, compatible with the regex crate.
...	Ignored.
literal	Logical. If TRUE (default), treat pattern as a literal string, not as a regular expression.
strict	Logical. If TRUE (default), raise an error if the underlying pattern is not a valid regex, otherwise mask out with a null value.

Details

To modify regular expression behaviour (such as case-sensitivity) with flags, use the inline (?iLmsuxU) syntax. See the regex crate's section on grouping and flags for additional information about the use of inline expression modifiers.

Value

An Expr of data type UInt32

See Also

- `$str$start_with()`: Check if string values start with a substring.
- `$str$ends_with()`: Check if string values end with a substring.
- `$str$contains()`: Check if string contains a substring that matches a pattern.

Examples

```
pl$DataFrame(s = c("AAA", "aAa", "aaa"))$with_columns(
  default_match = pl$col("s")$str$find("Aa"),
  insensitive_match = pl$col("s")$str$find("(?i)Aa")
)
```

ExprStr_head — *Return the first n characters of each string*

Description

Return the first n characters of each string

Usage

```
ExprStr_head(n)
```

Arguments

n	Length of the slice (integer or expression). Strings are parsed as column names. Negative indexing is supported.

Details

The n input is defined in terms of the number of characters in the (UTF-8) string. A character is defined as a Unicode scalar value. A single character is represented by a single byte when working with ASCII text, and a maximum of 4 bytes otherwise.

When the n input is negative, `head()` returns characters up to the nth from the end of the string. For example, if `n = -3`, then all characters except the last three are returned.

If the length of the string has fewer than n characters, the full string is returned.

Value

Expr: Series of dtype String.

Examples

```
df = pl$DataFrame(
  s = c("pear", NA, "papaya", "dragonfruit"),
  n = c(3, 4, -2, -5)
)

df$with_columns(
  s_head_5 = pl$col("s")$str$head(5),
  s_head_n = pl$col("s")$str$head("n")
)
```

ExprStr_join — *Vertically concatenate the string values in the column to a single string value.*

Description

Vertically concatenate the string values in the column to a single string value.

Usage

```
ExprStr_join(delimiter = "", ..., ignore_nulls = TRUE)
```

Arguments

delimiter	The delimiter to insert between consecutive string values.
...	Ignored.
ignore_nulls	Ignore null values (default). If FALSE, null values will be propagated: if the column contains any null values, the output is null.

Value

Expr of String concatenated

Examples

```
# concatenate a Series of strings to a single string
df = pl$DataFrame(foo = c(1, NA, 2))

df$select(pl$col("foo")$str$join("-"))

df$select(pl$col("foo")$str$join("-", ignore_nulls = FALSE))
```

ExprStr_json_decode *Parse string values as JSON.*

Description

Parse string values as JSON.

Usage

```
ExprStr_json_decode(dtype, infer_schema_length = 100)
```

Arguments

dtype	The dtype to cast the extracted value to. If NULL, the dtype will be inferred from the JSON value.
infer_schema_length	How many rows to parse to determine the schema. If NULL, all rows are used.

Details

Throw errors if encounter invalid json strings.

Value

Expr returning a struct

Examples

```
df = pl$DataFrame(
  json_val = c('{"a":1, "b": true}', NA, '{"a":2, "b": false}')
)
dtype = pl$Struct(pl$Field("a", pl$Int64), pl$Field("b", pl$Boolean))
df$select(pl$col("json_val")$str$json_decode(dtype))
```

ExprStr_json_path_match *Extract the first match of JSON string with the provided JSONPath expression*

Description

Extract the first match of JSON string with the provided JSONPath expression

Usage

```
ExprStr_json_path_match(json_path)
```

Arguments

`json_path`	A valid JSON path query string.

Details

Throw errors if encounter invalid JSON strings. All return value will be cast to String regardless of the original value.

Documentation on JSONPath standard can be found here: https://goessner.net/articles/JsonPath/.

Value

String array. Contain null if original value is null or the json_path return nothing.

Examples

```
df = pl$DataFrame(
  json_val = c('{"a":"1"}', NA, '{"a":2}', '{"a":2.1}', '{"a":true}')
)
df$select(pl$col("json_val")$str$json_path_match("$.a"))
```

ExprStr_len_bytes *Get the number of bytes in strings*

Description

Get length of the strings as UInt32 (as number of bytes). Use `$str$len_chars()` to get the number of characters.

Usage

```
ExprStr_len_bytes()
```

Details

If you know that you are working with ASCII text, `lengths` will be equivalent, and faster (returns length in terms of the number of bytes).

Value

Expr of u32

Examples

```
pl$DataFrame(
  s = c("Café", NA, "345", "æøå")
)$select(
  pl$col("s"),
  pl$col("s")$str$len_bytes()$alias("lengths"),
  pl$col("s")$str$len_chars()$alias("n_chars")
)
```

ExprStr_len_chars *Get the number of characters in strings*

Description

Get length of the strings as UInt32 (as number of characters). Use `$str$len_bytes()` to get the number of bytes.

Usage

```
ExprStr_len_chars()
```

Details

If you know that you are working with ASCII text, `lengths` will be equivalent, and faster (returns length in terms of the number of bytes).

Value

Expr of u32

Examples

```
pl$DataFrame(
  s = c("Café", NA, "345", "æøå")
)$select(
  pl$col("s"),
  pl$col("s")$str$len_bytes()$alias("lengths"),
  pl$col("s")$str$len_chars()$alias("n_chars")
)
```

ExprStr_pad_end *Left justify strings*

Description

Return the string left justified in a string of length `width`.

Usage

```
ExprStr_pad_end(width, fillchar = " ")
```

Arguments

`width`	Justify left to this length.
`fillchar`	Fill with this ASCII character.

Details

Padding is done using the specified `fillchar`. The original string is returned if `width` is less than or equal to `len(s)`.

Value

Expr of String

Examples

```
df = pl$DataFrame(a = c("cow", "monkey", NA, "hippopotamus"))
df$select(pl$col("a")$str$pad_end(8, "*"))
```

ExprStr_pad_start *Right justify strings*

Description

Return the string right justified in a string of length `width`.

Usage

```
ExprStr_pad_start(width, fillchar = " ")
```

Arguments

`width`	Justify right to this length.
`fillchar`	Fill with this ASCII character.

Details

Padding is done using the specified `fillchar`. The original string is returned if `width` is less than or equal to `len(s)`.

Value

Expr of String

Examples

```
df = pl$DataFrame(a = c("cow", "monkey", NA, "hippopotamus"))
df$select(pl$col("a")$str$pad_start(8, "*"))
```

ExprStr_replace *Replace first matching regex/literal substring with a new string value*

Description

Replace first matching regex/literal substring with a new string value

Usage

```
ExprStr_replace(pattern, value, ..., literal = FALSE, n = 1L)
```

Arguments

`pattern`	A character or something can be coerced to a string Expr of a valid regex pattern, compatible with the regex crate.
`value`	A character or an Expr of string that will replace the matched substring.
`...`	Ignored.
`literal`	Logical. If `TRUE` (default), treat `pattern` as a literal string, not as a regular expression.
`n`	A number of matches to replace. Note that regex replacement with `n > 1` not yet supported, so raise an error if `n > 1` and `pattern` includes regex pattern and `literal = FALSE`.

Details

To modify regular expression behaviour (such as case-sensitivity) with flags, use the inline `(?iLmsuxU)` syntax. See the regex crate's section on grouping and flags for additional information about the use of inline expression modifiers.

Value

Expr of String type

Capture groups

The dollar sign ($) is a special character related to capture groups. To refer to a literal dollar sign, use $$ instead or set `literal` to `TRUE`.

See Also

- `<Expr>$str$replace_all()`

Examples

```
df = pl$DataFrame(id = 1L:2L, text = c("123abc", "abc456"))
df$with_columns(pl$col("text")$str$replace(r"(abc\b)", "ABC"))

# Capture groups are supported.
# Use `${1}` in the value string to refer to the first capture group in the pattern,
# `${2}` to refer to the second capture group, and so on.
# You can also use named capture groups.
df = pl$DataFrame(word = c("hat", "hut"))
df$with_columns(
  positional = pl$col("word")$str$replace("h(.)t", "b${1}d"),
  named = pl$col("word")$str$replace("h(?<vowel>.)t", "b${vowel}d")
)

# Apply case-insensitive string replacement using the `(?i)` flag.
df = pl$DataFrame(
  city = "Philadelphia",
  season = c("Spring", "Summer", "Autumn", "Winter"),
  weather = c("Rainy", "Sunny", "Cloudy", "Snowy")
)
df$with_columns(
  pl$col("weather")$str$replace("(?i)foggy|rainy|cloudy|snowy", "Sunny")
)
```

ExprStr_replace_all *Replace all matching regex/literal substrings with a new string value*

Description

Replace all matching regex/literal substrings with a new string value

Usage

```
ExprStr_replace_all(pattern, value, ..., literal = FALSE)
```

Arguments

pattern	A character or something can be coerced to a string Expr of a valid regex pattern, compatible with the regex crate.
value	A character or an Expr of string that will replace the matched substring.
...	Ignored.
literal	Logical. If TRUE (default), treat pattern as a literal string, not as a regular expression.

Details

To modify regular expression behaviour (such as case-sensitivity) with flags, use the inline (?iLmsuxU) syntax. See the regex crate's section on grouping and flags for additional information about the use of inline expression modifiers.

Value

Expr of String type

Capture groups

The dollar sign ($) is a special character related to capture groups. To refer to a literal dollar sign, use $$ instead or set literal to TRUE.

See Also

- <Expr>strreplace()

Examples

```
df = pl$DataFrame(id = 1L:2L, text = c("abcabc", "123a123"))
df$with_columns(pl$col("text")$str$replace_all("a", "-"))

# Capture groups are supported.
# Use `${1}` in the value string to refer to the first capture group in the pattern,
# `${2}` to refer to the second capture group, and so on.
# You can also use named capture groups.
df = pl$DataFrame(word = c("hat", "hut"))
df$with_columns(
  positional = pl$col("word")$str$replace_all("h(.)t", "b${1}d"),
  named = pl$col("word")$str$replace_all("h(?<vowel>.)t", "b${vowel}d")
)

# Apply case-insensitive string replacement using the `(?i)` flag.
df = pl$DataFrame(
  city = "Philadelphia",
  season = c("Spring", "Summer", "Autumn", "Winter"),
  weather = c("Rainy", "Sunny", "Cloudy", "Snowy")
)
df$with_columns(
  pl$col("weather")$str$replace_all(
```

```
    "(?i)foggy|rainy|cloudy|snowy", "Sunny"
  )
)
```

ExprStr_replace_many *Use the aho-corasick algorithm to replace many matches*

Description

This function replaces several matches at once.

Usage

```
ExprStr_replace_many(patterns, replace_with, ascii_case_insensitive = FALSE)
```

Arguments

patterns	String patterns to search. Can be an Expr.
replace_with	A vector of strings used as replacements. If this is of length 1, then it is applied to all matches. Otherwise, it must be of same length as the patterns argument.
ascii_case_insensitive	Enable ASCII-aware case insensitive matching. When this option is enabled, searching will be performed without respect to case for ASCII letters (a-z and A-Z) only.

Value

Expr

Examples

```
df = pl$DataFrame(
  lyrics = c(
    "Everybody wants to rule the world",
    "Tell me what you want, what you really really want",
    "Can you feel the love tonight"
  )
)

# a replacement of length 1 is applied to all matches
df$with_columns(
  remove_pronouns = pl$col("lyrics")$str$replace_many(c("you", "me"), "")
)

# if there are more than one replacement, the patterns and replacements are
# matched
df$with_columns(
  fake_pronouns = pl$col("lyrics")$str$replace_many(c("you", "me"), c("foo", "bar"))
)
```

ExprStr_reverse *Returns string values in reversed order*

Description

Returns string values in reversed order

Usage

```
ExprStr_reverse()
```

Value

Expr

Examples

```
df = pl$DataFrame(text = c("foo", "bar", NA))
df$with_columns(reversed = pl$col("text")$str$reverse())
```

ExprStr_slice *Create subslices of the string values of a String Series*

Description

Create subslices of the string values of a String Series

Usage

```
ExprStr_slice(offset, length = NULL)
```

Arguments

offset	Start index. Negative indexing is supported.
length	Length of the slice. If NULL (default), the slice is taken to the end of the string.

Value

Expr: Series of dtype String.

Examples

```
df = pl$DataFrame(s = c("pear", NA, "papaya", "dragonfruit"))
df$with_columns(
  pl$col("s")$str$slice(-3)$alias("s_sliced")
)
```

ExprStr_split — *Split the string by a substring*

Description

Split the string by a substring

Usage

```
ExprStr_split(by, inclusive = FALSE)
```

Arguments

by	Substring to split by. Can be an Expr.
inclusive	If TRUE, include the split character/string in the results.

Value

List of String type

Examples

```
df = pl$DataFrame(s = c("foo bar", "foo-bar", "foo bar baz"))
df$select(pl$col("s")$str$split(by = " "))

df = pl$DataFrame(
  s = c("foo^bar", "foo_bar", "foo*bar*baz"),
  by = c("_", "_", "*")
)
df
df$select(pl$col("s")$str$split(by = pl$col("by"))$alias("split"))
```

ExprStr_split_exact — *Split the string by a substring using* n *splits*

Description

This results in a struct of n+1 fields. If it cannot make n splits, the remaining field elements will be null.

Usage

```
ExprStr_split_exact(by, n, inclusive = FALSE)
```

Arguments

by	Substring to split by.
n	Number of splits to make.
inclusive	If TRUE, include the split character/string in the results.

Value

Struct where each of n+1 fields is of String type

Examples

```
df = pl$DataFrame(s = c("a_1", NA, "c", "d_4"))
df$with_columns(
  split = pl$col("s")$str$split_exact(by = "_", 1),
  split_inclusive = pl$col("s")$str$split_exact(by = "_", 1, inclusive = TRUE)
)
```

ExprStr_splitn *Split the string by a substring, restricted to returning at most* n *items*

Description

If the number of possible splits is less than n-1, the remaining field elements will be null. If the number of possible splits is n-1 or greater, the last (nth) substring will contain the remainder of the string.

Usage

```
ExprStr_splitn(by, n)
```

Arguments

by	Substring to split by.
n	Number of splits to make.

Value

Struct where each of n fields is of String type

Examples

```
df = pl$DataFrame(s = c("a_1", NA, "c", "d_4_e"))
df$with_columns(
  s1 = pl$col("s")$str$splitn(by = "_", 1),
  s2 = pl$col("s")$str$splitn(by = "_", 2),
  s3 = pl$col("s")$str$splitn(by = "_", 3)
)
```

ExprStr_starts_with *Check if string starts with a regex*

Description

Check if string values starts with a substring.

Usage

```
ExprStr_starts_with(sub)
```

Arguments

sub	Prefix substring or Expr.

Details

See also `$str$contains()` and `$str$ends_with()`.

Value

Expr of Boolean data type

Examples

```
df = pl$DataFrame(fruits = c("apple", "mango", NA))
df$select(
  pl$col("fruits"),
  pl$col("fruits")$str$starts_with("app")$alias("has_suffix")
)
```

ExprStr_strip_chars *Strip leading and trailing characters*

Description

Remove leading and trailing characters.

Usage

```
ExprStr_strip_chars(matches = NULL)
```

Arguments

matches	The set of characters to be removed. All combinations of this set of characters will be stripped. If `NULL` (default), all whitespace is removed instead. This can be an Expr.

Details

This function will not strip any chars beyond the first char not matched. `strip_chars()` removes characters at the beginning and the end of the string. Use `strip_chars_start()` and `strip_chars_end()` to remove characters only from left and right respectively.

Value

Expr of String lowercase chars

Examples

```
df = pl$DataFrame(foo = c(" hello", "\tworld"))
df$select(pl$col("foo")$str$strip_chars())
df$select(pl$col("foo")$str$strip_chars(" hel rld"))
```

ExprStr_strip_chars_end

Strip trailing characters

Description

Remove trailing characters.

Usage

```
ExprStr_strip_chars_end(matches = NULL)
```

Arguments

`matches`	The set of characters to be removed. All combinations of this set of characters will be stripped. If `NULL` (default), all whitespace is removed instead. This can be an Expr.

Details

This function will not strip any chars beyond the first char not matched. `strip_chars_end()` removes characters at the end of the string only. Use `strip_chars()` and `strip_chars_start()` to remove characters from the left and right or only from the left respectively.

Value

Expr of String lowercase chars

Examples

```
df = pl$DataFrame(foo = c(" hello", "\tworld"))
df$select(pl$col("foo")$str$strip_chars_end(" hel\trld"))
df$select(pl$col("foo")$str$strip_chars_end("rldhel\t "))
```

ExprStr_strip_chars_start

Strip leading characters

Description

Remove leading characters.

Usage

```
ExprStr_strip_chars_start(matches = NULL)
```

Arguments

matches	The set of characters to be removed. All combinations of this set of characters will be stripped. If NULL (default), all whitespace is removed instead. This can be an Expr.

Details

This function will not strip any chars beyond the first char not matched. `strip_chars_start()` removes characters at the beginning of the string only. Use `strip_chars()` and `strip_chars_end()` to remove characters from the left and right or only from the right respectively.

Value

Expr of String lowercase chars

Examples

```
df = pl$DataFrame(foo = c(" hello", "\tworld"))
df$select(pl$col("foo")$str$strip_chars_start(" hel rld"))
```

ExprStr_strptime

Convert a String column into a Date/Datetime/Time column.

Description

Similar to the `strptime()` function.

Usage

```
ExprStr_strptime(
  dtype,
  format = NULL,
  ...,
  strict = TRUE,
  exact = TRUE,
  cache = TRUE,
  ambiguous = "raise"
)
```

Arguments

dtype	The data type to convert into. Can be either pl$Date, pl$Datetime(), or pl$Time.
format	Format to use for conversion. Refer to the chrono crate documentation for the full specification. Example: "%Y-%m-%d %H:%M:%S". If NULL (default), the format is inferred from the data. Notice that time zone %Z is not supported and will just ignore timezones. Numeric time zones like %z or %:z are supported.
...	Not used.
strict	If TRUE (default), raise an error if a single string cannot be parsed. If FALSE, produce a polars null.
exact	If TRUE (default), require an exact format match. If FALSE, allow the format to match anywhere in the target string. Conversion to the Time type is always exact. Note that using exact = FALSE introduces a performance penalty - cleaning your data beforehand will almost certainly be more performant.
cache	Use a cache of unique, converted dates to apply the datetime conversion.
ambiguous	Determine how to deal with ambiguous datetimes: • "raise" (default): throw an error • "earliest": use the earliest datetime • "latest": use the latest datetime • "null": return a null value

Details

When parsing a Datetime the column precision will be inferred from the format string, if given, e.g.: "%F %T%.3f" => pl$Datetime("ms"). If no fractional second component is found then the default is "us" (microsecond).

Value

Expr of Date, Datetime or Time type

See Also

- <Expr>strto_date()
- <Expr>strto_datetime()
- <Expr>strto_time()

Examples

```
# Dealing with a consistent format
s = as_polars_series(c("2020-01-01 01:00Z", "2020-01-01 02:00Z"))

s$str$strptime(pl$Datetime(), "%Y-%m-%d %H:%M%#z")

# Auto infer format
s$str$strptime(pl$Datetime())

# Datetime with timezone is interpreted as UTC timezone
as_polars_series("2020-01-01T01:00:00+09:00")$str$strptime(pl$Datetime())

# Dealing with different formats.
s = as_polars_series(
  c(
    "2021-04-22",
    "2022-01-04 00:00:00",
    "01/31/22",
    "Sun Jul  8 00:34:60 2001"
  ),
  "date"
)

s$to_frame()$select(
  pl$coalesce(
    pl$col("date")$str$strptime(pl$Date, "%F", strict = FALSE),
    pl$col("date")$str$strptime(pl$Date, "%F %T", strict = FALSE),
    pl$col("date")$str$strptime(pl$Date, "%D", strict = FALSE),
    pl$col("date")$str$strptime(pl$Date, "%c", strict = FALSE)
  )
)

# Ignore invalid time
s = as_polars_series(
  c(
    "2023-01-01 11:22:33 -0100",
    "2023-01-01 11:22:33 +0300",
    "invalid time"
  )
)

s$str$strptime(
  pl$Datetime("ns"),
  format = "%Y-%m-%d %H:%M:%S %z",
  strict = FALSE
```

```
)
```

`ExprStr_tail` *Return the last n characters of each string*

Description

Return the last n characters of each string

Usage

```
ExprStr_tail(n)
```

Arguments

n	Length of the slice (integer or expression). Strings are parsed as column names. Negative indexing is supported.

Details

The n input is defined in terms of the number of characters in the (UTF-8) string. A character is defined as a Unicode scalar value. A single character is represented by a single byte when working with ASCII text, and a maximum of 4 bytes otherwise.

When the n input is negative, `tail()` returns characters starting from the nth from the beginning of the string. For example, if `n = -3`, then all characters except the first three are returned.

If the length of the string has fewer than n characters, the full string is returned.

Value

Expr: Series of dtype String.

Examples

```
df = pl$DataFrame(
  s = c("pear", NA, "papaya", "dragonfruit"),
  n = c(3, 4, -2, -5)
)

df$with_columns(
  s_tail_5 = pl$col("s")$str$tail(5),
  s_tail_n = pl$col("s")$str$tail("n")
)
```

ExprStr_to_date *Convert a String column into a Date column*

Description

Convert a String column into a Date column

Usage

```
ExprStr_to_date(format = NULL, ..., strict = TRUE, exact = TRUE, cache = TRUE)
```

Arguments

format	Format to use for conversion. Refer to the chrono crate documentation for the full specification. Example: `"%Y-%m-%d %H:%M:%S"`. If `NULL` (default), the format is inferred from the data. Notice that time zone `%Z` is not supported and will just ignore timezones. Numeric time zones like `%z` or `%:z` are supported.
...	Not used.
strict	If `TRUE` (default), raise an error if a single string cannot be parsed. If `FALSE`, produce a polars `null`.
exact	If `TRUE` (default), require an exact format match. If `FALSE`, allow the format to match anywhere in the target string. Conversion to the Time type is always exact. Note that using `exact = FALSE` introduces a performance penalty - cleaning your data beforehand will almost certainly be more performant.
cache	Use a cache of unique, converted dates to apply the datetime conversion.

Value

Expr of Date type

See Also

- `<Expr>$str$strptime()`

Examples

```
s = as_polars_series(c("2020/01/01", "2020/02/01", "2020/03/01"))

s$str$to_date()

# by default, this errors if some values cannot be converted
s = as_polars_series(c("2020/01/01", "2020 02 01", "2020-03-01"))
try(s$str$to_date())
s$str$to_date(strict = FALSE)
```

ExprStr_to_datetime *Convert a String column into a Datetime column*

Description

Convert a String column into a Datetime column

Usage

```
ExprStr_to_datetime(
  format = NULL,
  ...,
  time_unit = NULL,
  time_zone = NULL,
  strict = TRUE,
  exact = TRUE,
  cache = TRUE,
  ambiguous = "raise"
)
```

Arguments

format	Format to use for conversion. Refer to the chrono crate documentation for the full specification. Example: `"%Y-%m-%d %H:%M:%S"`. If `NULL` (default), the format is inferred from the data. Notice that time zone `%Z` is not supported and will just ignore timezones. Numeric time zones like `%z` or `%:z` are supported.
...	Not used.
time_unit	Unit of time for the resulting Datetime column. If `NULL` (default), the time unit is inferred from the format string if given, e.g.: `"%F %T%.3f"` => `pl$Datetime("ms")`. If no fractional second component is found, the default is `"us"` (microsecond).
time_zone	for the resulting Datetime column.
strict	If `TRUE` (default), raise an error if a single string cannot be parsed. If `FALSE`, produce a polars `null`.
exact	If `TRUE` (default), require an exact format match. If `FALSE`, allow the format to match anywhere in the target string. Note that using `exact = FALSE` introduces a performance penalty - cleaning your data beforehand will almost certainly be more performant.
cache	Use a cache of unique, converted dates to apply the datetime conversion.
ambiguous	Determine how to deal with ambiguous datetimes: • `"raise"` (default): throw an error • `"earliest"`: use the earliest datetime • `"latest"`: use the latest datetime • `"null"`: return a null value

Value

Expr of Datetime type

See Also

- `<Expr>$str$strptime()`

Examples

```
s = as_polars_series(c("2020-01-01 01:00Z", "2020-01-01 02:00Z"))

s$str$to_datetime("%Y-%m-%d %H:%M%#z")
s$str$to_datetime(time_unit = "ms")
```

ExprStr_to_integer *Convert a String column into an Int64 column with base radix*

Description

Convert a String column into an Int64 column with base radix

Usage

```
ExprStr_to_integer(..., base = 10L, strict = TRUE)
```

Arguments

`...`	Ignored.
`base`	A positive integer or expression which is the base of the string we are parsing. Characters are parsed as column names. Default: `10L`.
`strict`	A logical. If `TRUE` (default), parsing errors or integer overflow will raise an error. If `FALSE`, silently convert to `null`.

Value

Expression of data type `Int64`.

Examples

```
df = pl$DataFrame(bin = c("110", "101", "010", "invalid"))
df$with_columns(
  parsed = pl$col("bin")$str$to_integer(base = 2, strict = FALSE)
)

df = pl$DataFrame(hex = c("fa1e", "ff00", "cafe", NA))
df$with_columns(
  parsed = pl$col("hex")$str$to_integer(base = 16, strict = TRUE)
)
```

ExprStr_to_lowercase *Convert a string to lowercase*

Description

Transform to lowercase variant.

Usage

```
ExprStr_to_lowercase()
```

Value

Expr of String lowercase chars

Examples

```
pl$lit(c("A", "b", "c", "1", NA))$str$to_lowercase()$to_series()
```

ExprStr_to_time *Convert a String column into a Time column*

Description

Convert a String column into a Time column

Usage

```
ExprStr_to_time(format = NULL, ..., strict = TRUE, cache = TRUE)
```

Arguments

format	Format to use for conversion. Refer to the chrono crate documentation for the full specification. Example: `"%Y-%m-%d %H:%M:%S"`. If `NULL` (default), the format is inferred from the data. Notice that time zone `%Z` is not supported and will just ignore timezones. Numeric time zones like `%z` or `%:z` are supported.
...	Not used.
strict	If `TRUE` (default), raise an error if a single string cannot be parsed. If `FALSE`, produce a polars `null`.
cache	Use a cache of unique, converted dates to apply the datetime conversion.

Value

Expr of Time type

See Also

- <Expr>strstrptime()

Examples

```
s = as_polars_series(c("01:00", "02:00", "03:00"))

s$str$to_time("%H:%M")
```

ExprStr_to_titlecase *Convert a string to titlecase*

Description

Transform to titlecase variant.

Usage

```
ExprStr_to_titlecase()
```

Details

This method is only available with the "nightly" feature. See polars_info() for more details.

Value

Expr of String titlecase chars

Examples

```
pl$lit(c("hello there", "HI, THERE", NA))$str$to_titlecase()$to_series()
```

ExprStr_to_uppercase *Convert a string to uppercase*

Description

Transform to uppercase variant.

Usage

```
ExprStr_to_uppercase()
```

Value

Expr of String uppercase chars

Examples

```
pl$lit(c("A", "b", "c", "1", NA))$str$to_uppercase()$to_series()
```

ExprStr_zfill *Fills the string with zeroes.*

Description

Add zeroes to a string until it reaches n characters. If the number of characters is already greater than n, the string is not modified.

Usage

```
ExprStr_zfill(alignment)
```

Arguments

alignment	Fill the value up to this length. This can be an Expr or something coercible to an Expr. Strings are parsed as column names.

Details

Return a copy of the string left filled with ASCII '0' digits to make a string of length width.

A leading sign prefix ('+'/'-') is handled by inserting the padding after the sign character rather than before. The original string is returned if width is less than or equal to len(s).

Value

Expr

Examples

```
some_floats_expr = pl$lit(c(0, 10, -5, 5))

# cast to String and ljust alignment = 5, and view as R char vector
some_floats_expr$cast(pl$String)$str$zfill(5)$to_r()

# cast to int and the to utf8 and then ljust alignment = 5, and view as R
# char vector
some_floats_expr$cast(pl$Int64)$cast(pl$String)$str$zfill(5)$to_r()
```

ExprStruct_field *Retrieve one of the fields of this Struct as a new Series*

Description

Retrieve one of the fields of this Struct as a new Series

Usage

```
ExprStruct_field(name)
```

Arguments

name	Name of the field.

Value

Expr of datatype Struct

Examples

```
df = pl$DataFrame(
  aaa = c(1, 2),
  bbb = c("ab", "cd"),
  ccc = c(TRUE, NA),
  ddd = list(c(1, 2), 3)
)$select(
  pl$struct(pl$all())$alias("struct_col")
)
# struct field into a new Series
df$select(
  pl$col("struct_col")$struct$field("bbb"),
  pl$col("struct_col")$struct$field("ddd")
)
```

ExprStruct_rename_fields *Rename the fields of the struct*

Description

Rename the fields of the struct

Usage

```
ExprStruct_rename_fields(names)
```

Arguments

names	Vector or list of strings given in the same order as the struct's fields. Providing fewer names will drop the latter fields. If too many names are given, the extra names are ignored.

Value

Expr of datatype Struct

Examples

```
df = pl$DataFrame(
  aaa = 1:2,
  bbb = c("ab", "cd"),
  ccc = c(TRUE, NA),
  ddd = list(1:2, 3L)
)$select(
  pl$struct(pl$all())$alias("struct_col")
)$select(
  pl$col("struct_col")$struct$rename_fields(c("www", "xxx", "yyy", "zzz"))
)
df$unnest()
```

ExprStruct_with_fields

Add or overwrite fields of this struct

Description

This is similar to `$with_columns()` on `DataFrame`. Use `pl$field()` to quickly select a field in a `$struct$with_fields()` context.

Usage

```
ExprStruct_with_fields(...)
```

Arguments

...	Field(s) to add. Accepts expression input. Strings are parsed as column names, other non-expression inputs are parsed as literals.

Value

An `Expr` of data type Struct.

Examples

```
df = pl$DataFrame(x = c(1, 4, 9), y = c(4, 9, 16), multiply = c(10, 2, 3))$
  with_columns(coords = pl$struct(c("x", "y")))$
  select("coords", "multiply")

df

df = df$with_columns(
  pl$col("coords")$struct$with_fields(
    pl$field("x")$sqrt(),
    y_mul = pl$field("y") * pl$col("multiply")
  )
)

df

df$unnest("coords")
```

`global_rpool_cap` *Get/set global R session pool capacity (DEPRECATED)*

Description

Deprecated. Use polars_options() to get, and pl$set_options() to set.

Usage

```
pl_get_global_rpool_cap()

pl_set_global_rpool_cap(n)
```

Arguments

`n`	Integer, the capacity limit R sessions to process R code.

Details

Background R sessions communicate via polars arrow IPC (series/vectors) or R serialize + shared memory buffers via the rust crate `ipc-channel`. Multi-process communication has overhead because all data must be serialized/de-serialized and sent via buffers. Using multiple R sessions will likely only give a speed-up in a `low io - high cpu` scenario. Native polars query syntax runs in threads and have no overhead. Polars has as default double as many thread workers as cores. If any worker are queuing for or using R sessions, other workers can still continue any native polars parts as much as possible.

Value

`polars_options()$rpool_cap` returns the capacity ("limit") of co-running external R sessions / processes. `polars_options()$rpool_active` is the number of R sessions are already spawned in the pool. `rpool_cap` is the limit of new R sessions to spawn. Anytime a polars thread worker needs a background R session specifically to run R code embedded in a query via `$map_batches(..., in_background = TRUE)` or `$map_elements(..., in_background = TRUE)`, it will obtain any R session idling in rpool, or spawn a new R session (process) if `capacity` is not already reached. If `capacity` is already reached, the thread worker will sleep and in a R job queue until an R session is idle.

Examples

```
default = polars_options()$rpool_cap |> print()
options(polars.rpool_cap = 8)
polars_options()$rpool_cap
options(polars.rpool_cap = default)
polars_options()$rpool_cap
```

GroupBy_agg *Aggregate over a GroupBy*

Description

Aggregate a DataFrame over a groupby

Usage

```
GroupBy_agg(...)
```

Arguments

`...`	exprs to aggregate over. ... args can also be passed wrapped in a list `$agg(list(e1,e2,e3))`

Value

aggregated DataFrame

Examples

```
pl$DataFrame(
  foo = c("one", "two", "two", "one", "two"),
  bar = c(5, 3, 2, 4, 1)
)$group_by("foo")$agg(
  pl$col("bar")$sum()$name$suffix("_sum"),
  pl$col("bar")$mean()$alias("bar_tail_sum")
)
```

GroupBy_class — *Operations on Polars grouped DataFrame*

Description

The GroupBy class in R, is just another interface on top of the DataFrame in rust polars. Groupby does not use the rust api for `<DataFrame>$group_by()` + `$agg()` because the groupby-struct is a reference to a DataFrame and that reference will share lifetime with its parent DataFrame.

Details

There is no way to expose lifetime limited objects via extendr currently (might be quirky anyhow with R GC). Instead the inputs for the `group_by` are just stored on R side, until also `agg` is called. Which will end up in a self-owned DataFrame object and all is fine. groupby aggs are performed via the rust polars LazyGroupBy methods, see DataFrame.groupby_agg method.

Active bindings

columns:
`$columns` returns a character vector with the column names.

Examples

```
as_polars_df(mtcars)$group_by("cyl")$agg(
  pl$col("mpg")$sum()
)
```

GroupBy_first — *GroupBy First*

Description

Reduce the groups to the first value.

Usage

```
GroupBy_first()
```

Value

aggregated DataFrame

Examples

```
df = pl$DataFrame(
  a = c(1, 2, 2, 3, 4, 5),
  b = c(0.5, 0.5, 4, 10, 13, 14),
  c = c(TRUE, TRUE, TRUE, FALSE, FALSE, TRUE),
  d = c("Apple", "Orange", "Apple", "Apple", "Banana", "Banana")
)
df$group_by("d", maintain_order = TRUE)$first()
```

GroupBy_last *GroupBy Last*

Description

Reduce the groups to the last value.

Usage

```
GroupBy_last()
```

Value

aggregated DataFrame

Examples

```
df = pl$DataFrame(
  a = c(1, 2, 2, 3, 4, 5),
  b = c(0.5, 0.5, 4, 10, 13, 14),
  c = c(TRUE, TRUE, TRUE, FALSE, FALSE, TRUE),
  d = c("Apple", "Orange", "Apple", "Apple", "Banana", "Banana")
)
df$group_by("d", maintain_order = TRUE)$last()
```

GroupBy_max *GroupBy Max*

Description

Reduce the groups to the maximum value.

Usage

```
GroupBy_max()
```

Value

aggregated DataFrame

Examples

```
df = pl$DataFrame(
  a = c(1, 2, 2, 3, 4, 5),
  b = c(0.5, 0.5, 4, 10, 13, 14),
  c = c(TRUE, TRUE, TRUE, FALSE, FALSE, TRUE),
  d = c("Apple", "Orange", "Apple", "Apple", "Banana", "Banana")
)
df$group_by("d", maintain_order = TRUE)$max()
```

GroupBy_mean *GroupBy Mean*

Description

Reduce the groups to the mean value.

Usage

```
GroupBy_mean()
```

Value

aggregated DataFrame

Examples

```
df = pl$DataFrame(
  a = c(1, 2, 2, 3, 4, 5),
  b = c(0.5, 0.5, 4, 10, 13, 14),
  c = c(TRUE, TRUE, TRUE, FALSE, FALSE, TRUE),
  d = c("Apple", "Orange", "Apple", "Apple", "Banana", "Banana")
)
df$group_by("d", maintain_order = TRUE)$mean()
```

GroupBy_median — *GroupBy Median*

Description

Reduce the groups to the median value.

Usage

```
GroupBy_median()
```

Value

aggregated DataFrame

Examples

```
df = pl$DataFrame(
  a = c(1, 2, 2, 3, 4, 5),
  b = c(0.5, 0.5, 4, 10, 13, 14),
  c = c(TRUE, TRUE, TRUE, FALSE, FALSE, TRUE),
  d = c("Apple", "Orange", "Apple", "Apple", "Banana", "Banana")
)
df$group_by("d", maintain_order = TRUE)$median()
```

GroupBy_min — *GroupBy Min*

Description

Reduce the groups to the minimum value.

Usage

```
GroupBy_min()
```

Value

aggregated DataFrame

Examples

```
df = pl$DataFrame(
  a = c(1, 2, 2, 3, 4, 5),
  b = c(0.5, 0.5, 4, 10, 13, 14),
  c = c(TRUE, TRUE, TRUE, FALSE, FALSE, TRUE),
  d = c("Apple", "Orange", "Apple", "Apple", "Banana", "Banana")
)
df$group_by("d", maintain_order = TRUE)$min()
```

GroupBy_null_count *GroupBy null count*

Description

Create a new DataFrame that shows the null counts per column.

Usage

```
GroupBy_null_count()
```

Value

DataFrame

Examples

```
x = mtcars
x[1:10, 3:5] = NA
pl$DataFrame(x)$group_by("cyl")$null_count()
```

GroupBy_quantile *Quantile*

Description

Aggregate the columns in the DataFrame to their quantile value.

Usage

```
GroupBy_quantile(quantile, interpolation = "nearest")
```

Arguments

quantile	numeric Quantile between 0.0 and 1.0.
interpolation	string Interpolation method: "nearest", "higher", "lower", "midpoint", or "linear".

Value

GroupBy

Examples

```
as_polars_df(mtcars)$lazy()$quantile(.4)$collect()
```

GroupBy_shift — *Shift the values by a given period*

Description

Shift the values by a given period

Usage

```
GroupBy_shift(n = 1, fill_value = NULL)
```

Arguments

n	Number of indices to shift forward. If a negative value is passed, values are shifted in the opposite direction instead.
fill_value	Fill the resulting null values with this value. Accepts expression input. Non-expression inputs are parsed as literals.

Value

GroupBy

Examples

```
as_polars_df(mtcars)$group_by("cyl")$shift(2)
```

GroupBy_std — *GroupBy Std*

Description

Reduce the groups to the standard deviation value.

Usage

```
GroupBy_std()
```

Value

aggregated DataFrame

Examples

```
df = pl$DataFrame(
  a = c(1, 2, 2, 3, 4, 5),
  b = c(0.5, 0.5, 4, 10, 13, 14),
  c = c(TRUE, TRUE, TRUE, FALSE, FALSE, TRUE),
  d = c("Apple", "Orange", "Apple", "Apple", "Banana", "Banana")
)
df$group_by("d", maintain_order = TRUE)$std()
```

GroupBy_sum *GroupBy Sum*

Description

Reduce the groups to the sum value.

Usage

```
GroupBy_sum()
```

Value

aggregated DataFrame

Examples

```
df = pl$DataFrame(
  a = c(1, 2, 2, 3, 4, 5),
  b = c(0.5, 0.5, 4, 10, 13, 14),
  c = c(TRUE, TRUE, TRUE, FALSE, FALSE, TRUE),
  d = c("Apple", "Orange", "Apple", "Apple", "Banana", "Banana")
)
df$group_by("d", maintain_order = TRUE)$sum()
```

GroupBy_ungroup *GroupBy_ungroup*

Description

Revert the group by operation.

Usage

```
GroupBy_ungroup()
```

Value

DataFrame

Examples

```
gb = as_polars_df(mtcars)$group_by("cyl")
gb

gb$ungroup()
```

GroupBy_var *GroupBy Var*

Description

Reduce the groups to the variance value.

Usage

```
GroupBy_var()
```

Value

aggregated DataFrame

Examples

```
df = pl$DataFrame(
  a = c(1, 2, 2, 3, 4, 5),
  b = c(0.5, 0.5, 4, 10, 13, 14),
  c = c(TRUE, TRUE, TRUE, FALSE, FALSE, TRUE),
  d = c("Apple", "Orange", "Apple", "Apple", "Banana", "Banana")
)
df$group_by("d", maintain_order = TRUE)$var()
```

---

head.RPolarsDataFrame *Return the first or the last* n *parts of an object*

Description

They are equivalent to `$head()` and `$tail()` methods.

Usage

```
## S3 method for class 'RPolarsDataFrame'
head(x, n = 6L, ...)

## S3 method for class 'RPolarsLazyFrame'
head(x, n = 6L, ...)

## S3 method for class 'RPolarsDataFrame'
tail(x, n = 6L, ...)

## S3 method for class 'RPolarsLazyFrame'
tail(x, n = 6L, ...)
```

Arguments

x	A polars object
n	An integer vector of length 1. Note that negative values are not supported for if x is a LazyFrame.
...	Ignored

Value

A polars object of the same class as x

See Also

- <DataFrame>$head()
- <LazyFrame>$head()
- <DataFrame>$tail()
- <LazyFrame>$tail()
- <LazyFrame>$fetch()

Examples

```
df = pl$DataFrame(foo = 1:5, bar = 6:10, ham = letters[1:5])
lf = df$lazy()

head(df, 2)
tail(df, 2)

head(lf, 2)
tail(lf, 2)

head(df, -2)
tail(df, -2)
```

infer_nanoarrow_schema.RPolarsDataFrame

Infer nanoarrow schema from a Polars object

Description

Infer nanoarrow schema from a Polars object

Usage

```
## S3 method for class 'RPolarsDataFrame'
infer_nanoarrow_schema(x, ..., compat_level = FALSE)

## S3 method for class 'RPolarsSeries'
infer_nanoarrow_schema(x, ..., compat_level = FALSE)
```

Arguments

`x`	A polars object
`...`	Ignored
`compat_level`	Use a specific compatibility level when exporting Polars' internal data structures. This can be: • an integer indicating the compatibility version (currently only 0 for oldest and 1 for newest); • a logical value with `TRUE` for the newest version and `FALSE` for the oldest version.

Examples

```
library(nanoarrow)

pl_df = as_polars_df(mtcars)$select("mpg", "cyl")
pl_s = as_polars_series(letters)

infer_nanoarrow_schema(pl_df)
infer_nanoarrow_schema(pl_s)
```

is_polars_df — *Test if the object is a polars DataFrame*

Description

This function tests if the object is a polars DataFrame.

Usage

```
is_polars_df(x)
```

Arguments

x	An object

Value

A logical value

Examples

```
is_polars_df(mtcars)

is_polars_df(as_polars_df(mtcars))
```

is_polars_dtype — *Test if the object a polars DataType*

Description

Test if the object a polars DataType

Usage

```
is_polars_dtype(x, include_unknown = FALSE)
```

Arguments

x	An object
include_unknown	If FALSE (default), pl$Unknown is considered as an invalid datatype.

Value

A logical value

Examples

```
is_polars_dtype(pl$Int64)
is_polars_dtype(mtcars)
is_polars_dtype(pl$Unknown)
is_polars_dtype(pl$Unknown, include_unknown = TRUE)
```

---

is_polars_lf *Test if the object is a polars LazyFrame*

Description

This function tests if the object is a polars LazyFrame.

Usage

```
is_polars_lf(x)
```

Arguments

x	An object

Value

A logical value

Examples

```
is_polars_lf(mtcars)

is_polars_lf(as_polars_lf(mtcars))
```

---

is_polars_series *Test if the object is a polars Series*

Description

This function tests if the object is a polars Series.

Usage

```
is_polars_series(x)
```

Arguments

x	An object

Value

A logical value

Examples

```
is_polars_series(1:3)

is_polars_series(as_polars_series(1:3))
```

---

knit_print.RPolarsDataFrame

knit print polars DataFrame

Description

Mimics Python Polars' NotebookFormatter for HTML outputs.

Usage

```
## S3 method for class 'RPolarsDataFrame'
knit_print(x, ...)
```

Arguments

x	a polars DataFrame to knit_print
...	additional arguments, not used

Details

Outputs HTML tables if the output format is HTML and the document's `df_print` option is not `"default"` or `"tibble"`.

Or, the output format can be enforced with R's `options` function as follows:

- `options(polars.df_knitr_print = "default")` for the default print method.
- `options(polars.df_knitr_print = "html")` for the HTML table.

Value

invisible x or NULL

LazyFrame_cast — *Cast LazyFrame column(s) to the specified dtype*

Description

This allows to convert all columns to a datatype or to convert only specific columns. Contrarily to the Python implementation, it is not possible to convert all columns of a specific datatype to another datatype.

Usage

```
LazyFrame_cast(dtypes, ..., strict = TRUE)
```

Arguments

`dtypes`	Either a datatype or a list where the names are column names and the values are the datatypes to convert to.
`...`	Ignored.
`strict`	If `TRUE` (default), throw an error if a cast could not be done (for instance, due to an overflow). Otherwise, return `null`.

Value

A LazyFrame

Examples

```
lf = pl$LazyFrame(
  foo = 1:3,
  bar = c(6, 7, 8),
  ham = as.Date(c("2020-01-02", "2020-03-04", "2020-05-06"))
)

# Cast only some columns
lf$cast(list(foo = pl$Float32, bar = pl$UInt8))$collect()

# Cast all columns to the same type
lf$cast(pl$String)$collect()
```

LazyFrame_class *Inner workings of the LazyFrame-class*

Description

The LazyFrame-class is simply two environments of respectively the public and private methods/function calls to the polars rust side. The instantiated LazyFrame-object is an externalptr to a lowlevel rust polars LazyFrame object. The pointer address is the only statefullness of the LazyFrame object on the R side. Any other state resides on the rust side. The S3 method .DollarNames.RPolarsLazyFrame exposes all public $foobar()-methods which are callable onto the object.

Most methods return another LazyFrame-class instance or similar which allows for method chaining. This class system in lack of a better name could be called "environment classes" and is the same class system extendr provides, except here there is both a public and private set of methods. For implementation reasons, the private methods are external and must be called from .pr$LazyFrame$methodname(). Also, all private methods must take any self as an argument, thus they are pure functions. Having the private methods as pure functions solved/simplified self-referential complications.

DataFrame and LazyFrame can both be said to be a Frame. To convert use <DataFrame>$lazy() and <LazyFrame>$collect(). You can also create a LazyFrame directly with pl$LazyFrame(). This is quite similar to the lazy-collect syntax of the dplyr package to interact with database connections such as SQL variants. Most SQL databases would be able to perform the same optimizations as polars such predicate pushdown and projection pushdown. However polars can interact and optimize queries with both SQL DBs and other data sources such parquet files simultaneously.

Active bindings

columns:
$columns returns a character vector with the column names.

dtypes:
$dtypes returns a unnamed list with the data type of each column.

schema:
$schema returns a named list with the data type of each column.

width:
$width returns the number of columns in the LazyFrame.

Conversion to R data types considerations

When converting Polars objects, such as DataFrames to R objects, for example via the as.data.frame() generic function, each type in the Polars object is converted to an R type. In some cases, an error may occur because the conversion is not appropriate. In particular, there is a high possibility of an error when converting a Datetime type without a time zone. A Datetime type without a time zone in Polars is converted to the POSIXct type in R, which takes into account the time zone in which the R session is running (which can be checked with the Sys.timezone() function). In this case, if ambiguous times are included, a conversion error will occur. In such cases, change

the session time zone using `Sys.setenv(TZ = "UTC")` and then perform the conversion, or use the `$dt$replace_time_zone()` method on the Datetime type column to explicitly specify the time zone before conversion.

```
# Due to daylight savings, clocks were turned forward 1 hour on Sunday, March 8, 2020, 2:00:00 am
# so this particular date-time doesn't exist
non_existent_time = as_polars_series("2020-03-08 02:00:00")$str$strptime(pl$Datetime(), "%F %T")

withr::with_timezone(
  "America/New_York",
  {
    tryCatch(
     # This causes an error due to the time zone (the `TZ` env var is affected).
      as.vector(non_existent_time),
      error = function(e) e
    )
  }
)
#> <error: in $to_vector(): in to_r: ComputeError(ErrString("datetime '2020-03-08 02:00:00' is non-exis

withr::with_timezone(
  "America/New_York",
  {
    # This is safe.
    as.vector(non_existent_time$dt$replace_time_zone("UTC"))
  }
)
#> [1] "2020-03-08 02:00:00 UTC"
```

Examples

```
# see all exported methods
ls(.pr$env$RPolarsLazyFrame)

# see all private methods (not intended for regular use)
ls(.pr$LazyFrame)


## Practical example ##
# First writing R iris dataset to disk, to illustrte a difference
temp_filepath = tempfile()
write.csv(iris, temp_filepath, row.names = FALSE)

# Following example illustrates 2 ways to obtain a LazyFrame

# The-Okay-way: convert an in-memory DataFrame to LazyFrame

# eager in-mem R data.frame
Rdf = read.csv(temp_filepath)
```

```
# eager in-mem polars DataFrame
Pdf = as_polars_df(Rdf)

# lazy frame starting from in-mem DataFrame
Ldf_okay = Pdf$lazy()

# The-Best-Way:  LazyFrame created directly from a data source is best...
Ldf_best = pl$scan_csv(temp_filepath)

# ... as if to e.g. filter the LazyFrame, that filtering also caleld predicate will be
# pushed down in the executation stack to the csv_reader, and thereby only bringing into
# memory the rows matching to filter.
# apply filter:
filter_expr = pl$col("Species") == "setosa" # get only rows where Species is setosa
Ldf_okay = Ldf_okay$filter(filter_expr) # overwrite LazyFrame with new
Ldf_best = Ldf_best$filter(filter_expr)

# the non optimized plans are similar, on entire in-mem csv, apply filter
Ldf_okay$explain(optimized = FALSE)
Ldf_best$explain(optimized = FALSE)

# NOTE For Ldf_okay, the full time to load csv alrady paid when creating Rdf and Pdf

# The optimized plan are quite different, Ldf_best will read csv and perform filter simultaneously
Ldf_okay$explain()
Ldf_best$explain()


# To acquire result in-mem use $colelct()
Pdf_okay = Ldf_okay$collect()
Pdf_best = Ldf_best$collect()


# verify tables would be the same
all.equal(
  Pdf_okay$to_data_frame(),
  Pdf_best$to_data_frame()
)

# a user might write it as a one-liner like so:
Pdf_best2 = pl$scan_csv(temp_filepath)$filter(pl$col("Species") == "setosa")
```

`LazyFrame_clear` *Create an empty or n-row null-filled copy of the LazyFrame*

Description

Returns a n-row null-filled LazyFrame with an identical schema. `n` can be greater than the current number of rows in the LazyFrame.

Usage

```
LazyFrame_clear(n = 0)
```

Arguments

n	Number of (null-filled) rows to return in the cleared frame.

Value

A n-row null-filled LazyFrame with an identical schema

Examples

```
df = pl$LazyFrame(
  a = c(NA, 2, 3, 4),
  b = c(0.5, NA, 2.5, 13),
  c = c(TRUE, TRUE, FALSE, NA)
)

df$clear()

df$clear(n = 5)
```

LazyFrame_clone *Clone a LazyFrame*

Description

This makes a very cheap deep copy/clone of an existing LazyFrame. Rarely useful as LazyFrames are nearly 100% immutable. Any modification of a LazyFrame should lead to a clone anyways, but this can be useful when dealing with attributes (see examples).

Usage

```
LazyFrame_clone()
```

Value

A LazyFrame

Examples

```
df1 = as_polars_lf(iris)

# Make a function to take a LazyFrame, add an attribute, and return a LazyFrame
give_attr = function(data) {
  attr(data, "created_on") = "2024-01-29"
  data
}
```

```
df2 = give_attr(df1)

# Problem: the original LazyFrame also gets the attribute while it shouldn't!
attributes(df1)

# Use $clone() inside the function to avoid that
give_attr = function(data) {
  data = data$clone()
  attr(data, "created_on") = "2024-01-29"
  data
}
df1 = as_polars_lf(iris)
df2 = give_attr(df1)

# now, the original LazyFrame doesn't get this attribute
attributes(df1)
```

`LazyFrame_collect` *Collect a query into a DataFrame*

Description

`$collect()` performs the query on the LazyFrame. It returns a DataFrame

Usage

```
LazyFrame_collect(
  ...,
  type_coercion = TRUE,
  predicate_pushdown = TRUE,
  projection_pushdown = TRUE,
  simplify_expression = TRUE,
  slice_pushdown = TRUE,
  comm_subplan_elim = TRUE,
  comm_subexpr_elim = TRUE,
  cluster_with_columns = TRUE,
  streaming = FALSE,
  no_optimization = FALSE,
  collect_in_background = FALSE
)
```

Arguments

`...`	Ignored.
`type_coercion`	Logical. Coerce types such that operations succeed and run on minimal required memory.
`predicate_pushdown`	Logical. Applies filters as early as possible at scan level.

`projection_pushdown`
: Logical. Select only the columns that are needed at the scan level.

`simplify_expression`
: Logical. Various optimizations, such as constant folding and replacing expensive operations with faster alternatives.

`slice_pushdown`
: Logical. Only load the required slice from the scan level. Don't materialize sliced outputs (e.g. `join$head(10)`).

`comm_subplan_elim`
: Logical. Will try to cache branching subplans that occur on self-joins or unions.

`comm_subexpr_elim`
: Logical. Common subexpressions will be cached and reused.

`cluster_with_columns`
: Combine sequential independent calls to `with_columns()`.

`streaming`
: Logical. Run parts of the query in a streaming fashion (this is in an alpha state).

`no_optimization`
: Logical. Sets the following parameters to `FALSE`: `predicate_pushdown`, `projection_pushdown`, `slice_pushdown`, `comm_subplan_elim`, `comm_subexpr_elim`, `cluster_with_columns`.

`collect_in_background`
: Logical. Detach this query from R session. Computation will start in background. Get a handle which later can be converted into the resulting DataFrame. Useful in interactive mode to not lock R session.

Details

Note: use `$fetch(n)` if you want to run your query on the first `n` rows only. This can be a huge time saver in debugging queries.

Value

A `DataFrame`

See Also

- `$fetch()` - fast limited query check
- `$profile()` - same as `$collect()` but also returns a table with each operation profiled.
- `$collect_in_background()` - non-blocking collect returns a future handle. Can also just be used via `$collect(collect_in_background = TRUE)`.
- `$sink_parquet()` streams query to a parquet file.
- `$sink_ipc()` streams query to a arrow file.

Examples

```
as_polars_lf(iris)$filter(pl$col("Species") == "setosa")$collect()
```

LazyFrame_collect_in_background

Collect a query in background

Description

This doesn't block the R session as it calls `$collect()` in a a detached thread. This can also be used via `$collect(collect_in_background = TRUE)`.

Usage

```
LazyFrame_collect_in_background()
```

Details

This function immediately returns an RThreadHandle. Use `<RPolarsRThreadHandle>$is_finished()` to see if done. Use `<RPolarsRThreadHandle>$join()` to wait and get the final result.

It is useful to not block the R session while query executes. If you use `<Expr>$map_batches()` or `<Expr>$map_elements()` to run R functions in the query, then you must pass `in_background = TRUE` in `$map_batches()` (or `$map_elements()`). Otherwise, `$collect_in_background()` will fail because the main R session is not available for polars execution. See also examples below.

Value

RThreadHandle, a future-like thread handle for the task

Examples

```
# Some expression which does contain a map
expr = pl$col("mpg")$map_batches(
  \(x) {
    Sys.sleep(.1)
    x * 0.43
  },
  in_background = TRUE # set TRUE if collecting in background queries with $map or $apply
)$alias("kml")

# return is immediately a handle to another thread.
handle = as_polars_lf(mtcars)$with_columns(expr)$collect_in_background()

# ask if query is done
if (!handle$is_finished()) print("not done yet")

# get result, blocking until polars query is done
df = handle$join()
df
```

LazyFrame_drop *Drop columns of a LazyFrame*

Description

Drop columns of a LazyFrame

Usage

```
LazyFrame_drop(..., strict = TRUE)
```

Arguments

...	Characters of column names to drop. Passed to `pl$col()`.
strict	Validate that all column names exist in the schema and throw an exception if a column name does not exist in the schema.

Value

LazyFrame

Examples

```
as_polars_lf(mtcars)$drop(c("mpg", "hp"))$collect()

# equivalent
as_polars_lf(mtcars)$drop("mpg", "hp")$collect()
```

LazyFrame_drop_nulls *Drop nulls (missing values)*

Description

Drop all rows that contain nulls (which correspond to `NA` in R).

Usage

```
LazyFrame_drop_nulls(subset = NULL)
```

Arguments

subset	A character vector with the names of the column(s) for which nulls are considered. If `NULL` (default), use all columns.

Value

LazyFrame

Examples

```
tmp = mtcars
tmp[1:3, "mpg"] = NA
tmp[4, "hp"] = NA
tmp = pl$LazyFrame(tmp)

# number of rows in `tmp` before dropping nulls
tmp$collect()$height

tmp$drop_nulls()$collect()$height
tmp$drop_nulls("mpg")$collect()$height
tmp$drop_nulls(c("mpg", "hp"))$collect()$height
```

LazyFrame_explain *Create a string representation of the query plan*

Description

The query plan is read from bottom to top. When `optimized = FALSE`, the query as it was written by the user is shown. This is not what Polars runs. Instead, it applies optimizations that are displayed by default by `$explain()`. One classic example is the predicate pushdown, which applies the filter as early as possible (i.e. at the bottom of the plan).

Usage

```
LazyFrame_explain(
  ...,
  format = "plain",
  optimized = TRUE,
  type_coercion = TRUE,
  predicate_pushdown = TRUE,
  projection_pushdown = TRUE,
  simplify_expression = TRUE,
  slice_pushdown = TRUE,
  comm_subplan_elim = TRUE,
  comm_subexpr_elim = TRUE,
  cluster_with_columns = TRUE,
  streaming = FALSE
)
```

Arguments

`...`	Ignored.
`format`	The format to use for displaying the logical plan. Must be either `"plain"` (default) or `"tree"`.
`optimized`	Return an optimized query plan. If `TRUE` (default), the subsequent optimization flags control which optimizations run.

type_coercion Logical. Coerce types such that operations succeed and run on minimal required memory.

predicate_pushdown
Logical. Applies filters as early as possible at scan level.

projection_pushdown
Logical. Select only the columns that are needed at the scan level.

simplify_expression
Logical. Various optimizations, such as constant folding and replacing expensive operations with faster alternatives.

slice_pushdown Logical. Only load the required slice from the scan level. Don't materialize sliced outputs (e.g. `join$head(10)`).

comm_subplan_elim
Logical. Will try to cache branching subplans that occur on self-joins or unions.

comm_subexpr_elim
Logical. Common subexpressions will be cached and reused.

cluster_with_columns
Combine sequential independent calls to `with_columns()`.

streaming Logical. Run parts of the query in a streaming fashion (this is in an alpha state).

Value

A character value containing the query plan.

Examples

```
lazy_frame = as_polars_lf(iris)

# Prepare your query
lazy_query = lazy_frame$sort("Species")$filter(pl$col("Species") != "setosa")

# This is the query that was written by the user, without any optimizations
# (use cat() for better printing)
lazy_query$explain(optimized = FALSE) |> cat()

# This is the query after `polars` optimizes it: instead of sorting first and
# then filtering, it is faster to filter first and then sort the rest.
lazy_query$explain() |> cat()

# Also possible to see this as tree format
lazy_query$explain(format = "tree") |> cat()
```

LazyFrame_explode *Explode columns containing a list of values*

Description

This will take every element of a list column and add it on an additional row.

Usage

```
LazyFrame_explode(...)
```

Arguments

...	Column(s) to be exploded as individual Into<Expr> or list/vector of Into<Expr>. In a handful of places in rust-polars, only the plain variant Expr::Column is accepted. This is currenly one of such places. Therefore pl$col("name") and pl$all() is allowed, not pl$col("name")$alias("newname"). "name" is implicitly converted to pl$col("name").

Details

Only columns of DataType List or Array can be exploded.

Named expressions like $explode(a = pl$col("b")) will not implicitly trigger $alias("a") here, due to only variant Expr::Column is supported in rust-polars.

Value

LazyFrame

Examples

```
df = pl$LazyFrame(
  letters = c("aa", "aa", "bb", "cc"),
  numbers = list(1, c(2, 3), c(4, 5), c(6, 7, 8)),
  numbers_2 = list(0, c(1, 2), c(3, 4), c(5, 6, 7)) # same structure as numbers
)
df

# explode a single column, append others
df$explode("numbers")$collect()

# explode two columns of same nesting structure, by names or the common dtype
# "List(Float64)"
df$explode("numbers", "numbers_2")$collect()
df$explode(pl$col(pl$List(pl$Float64)))$collect()
```

LazyFrame_fetch *Fetch* n *rows of a LazyFrame*

Description

This is similar to $collect() but limit the number of rows to collect. It is mostly useful to check that a query works as expected.

Usage

```
LazyFrame_fetch(
  n_rows = 500,
  ...,
  type_coercion = TRUE,
  predicate_pushdown = TRUE,
  projection_pushdown = TRUE,
  simplify_expression = TRUE,
  slice_pushdown = TRUE,
  comm_subplan_elim = TRUE,
  comm_subexpr_elim = TRUE,
  cluster_with_columns = TRUE,
  streaming = FALSE,
  no_optimization = FALSE
)
```

Arguments

`n_rows` Integer. Maximum number of rows to fetch.

`...` Ignored.

`type_coercion` Logical. Coerce types such that operations succeed and run on minimal required memory.

`predicate_pushdown` Logical. Applies filters as early as possible at scan level.

`projection_pushdown` Logical. Select only the columns that are needed at the scan level.

`simplify_expression` Logical. Various optimizations, such as constant folding and replacing expensive operations with faster alternatives.

`slice_pushdown` Logical. Only load the required slice from the scan level. Don't materialize sliced outputs (e.g. `join$head(10)`).

`comm_subplan_elim` Logical. Will try to cache branching subplans that occur on self-joins or unions.

`comm_subexpr_elim` Logical. Common subexpressions will be cached and reused.

`cluster_with_columns` Combine sequential independent calls to `with_columns()`.

`streaming` Logical. Run parts of the query in a streaming fashion (this is in an alpha state).

`no_optimization` Logical. Sets the following parameters to `FALSE`: `predicate_pushdown`, `projection_pushdown`, `slice_pushdown`, `comm_subplan_elim`, `comm_subexpr_elim`, `cluster_with_columns`.

Details

`$fetch()` does not guarantee the final number of rows in the DataFrame output. It only guarantees that `n` rows are used at the beginning of the query. Filters, join operations and a lower number of rows available in the scanned file influence the final number of rows.

Value

A DataFrame of maximum n_rows

See Also

- `$collect()` - regular collect.
- `$profile()` - same as `$collect()` but also returns a table with each operation profiled.
- `$collect_in_background()` - non-blocking collect returns a future handle. Can also just be used via `$collect(collect_in_background = TRUE)`.
- `$sink_parquet()` streams query to a parquet file.
- `$sink_ipc()` streams query to a arrow file.

Examples

```
# fetch 3 rows
as_polars_lf(iris)$fetch(3)

# this fetch-query returns 4 rows, because we started with 3 and appended one
# row in the query (see section 'Details')
as_polars_lf(iris)$
  select(pl$col("Species")$append("flora gigantica, alien"))$
  fetch(3)
```

LazyFrame_fill_nan *Fill floating point NaN value with a fill value*

Description

Fill floating point NaN value with a fill value

Usage

```
LazyFrame_fill_nan(value)
```

Arguments

`value`	Value used to fill `NaN` values.

Value

LazyFrame

Examples

```
df = pl$LazyFrame(
  a = c(1.5, 2, NaN, 4),
  b = c(1.5, NaN, NaN, 4)
)
df$fill_nan(99)$collect()
```

LazyFrame_fill_null *Fill nulls*

Description

Fill null values (which correspond to NA in R) using the specified value or strategy.

Usage

```
LazyFrame_fill_null(fill_value)
```

Arguments

fill_value	Value to fill nulls with.

Value

LazyFrame

Examples

```
df = pl$LazyFrame(
  a = c(1.5, 2, NA, 4),
  b = c(1.5, NA, NA, 4)
)
df$fill_null(99)$collect()
```

LazyFrame_filter *Apply filter to LazyFrame*

Description

Filter rows with an Expression defining a boolean column. Multiple expressions are combined with & (AND). This is equivalent to dplyr::filter().

Usage

```
LazyFrame_filter(...)
```

Arguments

...	Polars expressions which will evaluate to a boolean.

Details

Rows where the condition returns NA are dropped.

Value

A new `LazyFrame` object with add/modified column.

Examples

```
lf = as_polars_lf(iris)

lf$filter(pl$col("Species") == "setosa")$collect()

# This is equivalent to
# lf$filter(pl$col("Sepal.Length") > 5 & pl$col("Petal.Width") < 1)
lf$filter(pl$col("Sepal.Length") > 5, pl$col("Petal.Width") < 1)
```

`LazyFrame_first` *Get the first row of a LazyFrame*

Description

Get the first row of a LazyFrame

Usage

```
LazyFrame_first()
```

Value

A LazyFrame with one row

Examples

```
as_polars_lf(mtcars)$first()$collect()
```

`LazyFrame_gather_every` *Take every nth row in the LazyFrame*

Description

Take every nth row in the LazyFrame

Usage

```
LazyFrame_gather_every(n, offset = 0)
```

Arguments

n	Gather every n-th row.
offset	Starting index.

Value

A LazyFrame

Examples

```
lf = pl$LazyFrame(a = 1:4, b = 5:8)
lf$gather_every(2)$collect()

lf$gather_every(2, offset = 1)$collect()
```

LazyFrame_group_by *Group a LazyFrame*

Description

This doesn't modify the data but only stores information about the group structure. This structure can then be used by several functions (`$agg()`, `$filter()`, etc.).

Usage

```
LazyFrame_group_by(..., maintain_order = polars_options()$maintain_order)
```

Arguments

...	Column(s) to group by. Accepts expression input. Characters are parsed as column names.
maintain_order	Ensure that the order of the groups is consistent with the input data. This is slower than a default group by. Setting this to `TRUE` blocks the possibility to run on the streaming engine. The default value can be changed with `options(polars.maintain_order = TRUE)`.

Value

LazyGroupBy (a LazyFrame with special groupby methods like `$agg()`)

Examples

```
lf = pl$LazyFrame(
  a = c("a", "b", "a", "b", "c"),
  b = c(1, 2, 1, 3, 3),
  c = c(5, 4, 3, 2, 1)
)

lf$group_by("a")$agg(pl$col("b")$sum())$collect()

# Set `maintain_order = TRUE` to ensure the order of the groups is consistent with the input.
lf$group_by("a", maintain_order = TRUE)$agg(pl$col("c"))$collect()

# Group by multiple columns by passing a list of column names.
lf$group_by(c("a", "b"))$agg(pl$max("c"))$collect()

# Or pass some arguments to group by multiple columns in the same way.
# Expressions are also accepted.
lf$group_by("a", pl$col("b") %/% 2)$agg(
  pl$col("c")$mean()
)$collect()

# The columns will be renamed to the argument names.
lf$group_by(d = "a", e = pl$col("b") %/% 2)$agg(
  pl$col("c")$mean()
)$collect()
```

`LazyFrame_group_by_dynamic`

Group based on a date/time or integer column

Description

If you have a time series `<t_0, t_1, ..., t_n>`, then by default the windows created will be:

- (t_0 - period, t_0]
- (t_1 - period, t_1]
- ...
- (t_n - period, t_n]

whereas if you pass a non-default offset, then the windows will be:

- (t_0 + offset, t_0 + offset + period]
- (t_1 + offset, t_1 + offset + period]
- ...
- (t_n + offset, t_n + offset + period]

Usage

```
LazyFrame_group_by_dynamic(
  index_column,
  ...,
  every,
  period = NULL,
  offset = NULL,
  include_boundaries = FALSE,
  closed = "left",
  label = "left",
  group_by = NULL,
  start_by = "window"
)
```

Arguments

`index_column` Column used to group based on the time window. Often of type Date/Datetime. This column must be sorted in ascending order (or, if by is specified, then it must be sorted in ascending order within each group). In case of a rolling group by on indices, dtype needs to be either Int32 or Int64. Note that Int32 gets temporarily cast to Int64, so if performance matters use an Int64 column.

`...` Ignored.

`every` Interval of the window.

`period` A character representing the length of the window, must be non-negative. See the `Polars duration string language` section for details.

`offset` A character representing the offset of the window, or `NULL` (default). If `NULL`, `-period` is used. See the `Polars duration string language` section for details.

`include_boundaries` Add two columns `"_lower_boundary"` and `"_upper_boundary"` columns that show the boundaries of the window. This will impact performance because it's harder to parallelize.

`closed` Define which sides of the temporal interval are closed (inclusive). This can be either `"left"`, `"right"`, `"both"` or `"none"`.

`label` Define which label to use for the window:

- `"left"`: lower boundary of the window
- `"right"`: upper boundary of the window
- `"datapoint"`: the first value of the index column in the given window. If you don't need the label to be at one of the boundaries, choose this option for maximum performance.

`group_by` Also group by this column/these columns.

`start_by` The strategy to determine the start of the first window by:

- `"window"`: start by taking the earliest timestamp, truncating it with `every`, and then adding `offset`. Note that weekly windows start on Monday.
- `"datapoint"`: start from the first encountered data point.

- a day of the week (only takes effect if `every` contains `"w"`): `"monday"` starts the window on the Monday before the first data point, etc.

Details

In case of a rolling operation on an integer column, the windows are defined by:

- "1i" # length 1
- "10i" # length 10

Value

A LazyGroupBy object

See Also

- `<LazyFrame>$rolling()`

Examples

```
lf = pl$LazyFrame(
  time = pl$datetime_range(
    start = strptime("2021-12-16 00:00:00", format = "%Y-%m-%d %H:%M:%S", tz = "UTC"),
    end = strptime("2021-12-16 03:00:00", format = "%Y-%m-%d %H:%M:%S", tz = "UTC"),
    interval = "30m"
  ),
  n = 0:6
)
lf$collect()

# get the sum in the following hour relative to the "time" column
lf$group_by_dynamic("time", every = "1h")$agg(
  vals = pl$col("n"),
  sum = pl$col("n")$sum()
)$collect()

# using "include_boundaries = TRUE" is helpful to see the period considered
lf$group_by_dynamic("time", every = "1h", include_boundaries = TRUE)$agg(
  vals = pl$col("n")
)$collect()

# in the example above, the values didn't include the one *exactly* 1h after
# the start because "closed = 'left'" by default.
# Changing it to "right" includes values that are exactly 1h after. Note that
# the value at 00:00:00 now becomes included in the interval [23:00:00 - 00:00:00],
# even if this interval wasn't there originally
lf$group_by_dynamic("time", every = "1h", closed = "right")$agg(
  vals = pl$col("n")
)$collect()
# To keep both boundaries, we use "closed = 'both'". Some values now belong to
# several groups:
lf$group_by_dynamic("time", every = "1h", closed = "both")$agg(
```

```
  vals = pl$col("n")
)$collect()

# Dynamic group bys can also be combined with grouping on normal keys
lf = lf$with_columns(
  groups = as_polars_series(c("a", "a", "a", "b", "b", "a", "a"))
)
lf$collect()

lf$group_by_dynamic(
  "time",
  every = "1h",
  closed = "both",
  group_by = "groups",
  include_boundaries = TRUE
)$agg(pl$col("n"))$collect()

# We can also create a dynamic group by based on an index column
lf = pl$LazyFrame(
  idx = 0:5,
  A = c("A", "A", "B", "B", "B", "C")
)$with_columns(pl$col("idx")$set_sorted())
lf$collect()

lf$group_by_dynamic(
  "idx",
  every = "2i",
  period = "3i",
  include_boundaries = TRUE,
  closed = "right"
)$agg(A_agg_list = pl$col("A"))$collect()
```

`LazyFrame_head` *Get the first* `n` *rows.*

Description

A shortcut for `$slice(0, n)`. Consider using the `$fetch()` method if you want to test your query. The `$fetch()` operation will load the first `n` rows at the scan level, whereas `$head()` is applied at the end.

Usage

```
LazyFrame_head(n = 5L)
```

Arguments

`n`	Number of rows to return.

Details

`$limit()` is an alias for `$head()`.

Value

A new `LazyFrame` object with applied filter.

Examples

```
lf = pl$LazyFrame(a = 1:6, b = 7:12)

lf$head()$collect()

lf$head(2)$collect()
```

LazyFrame_join *Join LazyFrames*

Description

This function can do both mutating joins (adding columns based on matching observations, for example with `how = "left"`) and filtering joins (keeping observations based on matching observations, for example with `how = "inner"`).

Usage

```
LazyFrame_join(
  other,
  on = NULL,
  how = "inner",
  ...,
  left_on = NULL,
  right_on = NULL,
  suffix = "_right",
  validate = "m:m",
  join_nulls = FALSE,
  allow_parallel = TRUE,
  force_parallel = FALSE,
  coalesce = NULL
)
```

Arguments

`other`	LazyFrame to join with.
`on`	Either a vector of column names or a list of expressions and/or strings. Use `left_on` and `right_on` if the column names to match on are different between the two DataFrames.

how — One of the following methods: "inner", "left", "right", "full", "semi", "anti", "cross".

... — Ignored.

left_on, right_on — Same as on but only for the left or the right DataFrame. They must have the same length.

suffix — Suffix to add to duplicated column names.

validate — Checks if join is of specified type:

- "m:m" (default): many-to-many, doesn't perform any checks;
- "1:1": one-to-one, check if join keys are unique in both left and right datasets;
- "1:m": one-to-many, check if join keys are unique in left dataset
- "m:1": many-to-one, check if join keys are unique in right dataset

Note that this is currently not supported by the streaming engine, and is only supported when joining by single columns.

join_nulls — Join on null values. By default null values will never produce matches.

allow_parallel — Allow the physical plan to optionally evaluate the computation of both DataFrames up to the join in parallel.

force_parallel — Force the physical plan to evaluate the computation of both DataFrames up to the join in parallel.

coalesce — Coalescing behavior (merging of join columns).

- NULL: join specific.
- TRUE: Always coalesce join columns.
- FALSE: Never coalesce join columns.

Value

LazyFrame

Examples

```
# inner join by default
df1 = pl$LazyFrame(list(key = 1:3, payload = c("f", "i", NA)))
df2 = pl$LazyFrame(list(key = c(3L, 4L, 5L, NA_integer_)))
df1$join(other = df2, on = "key")

# cross join
df1 = pl$LazyFrame(x = letters[1:3])
df2 = pl$LazyFrame(y = 1:4)
df1$join(other = df2, how = "cross")

# use "validate" to ensure join keys are not duplicated
df1 = pl$LazyFrame(x = letters[1:5], y = 1:5)
df2 = pl$LazyFrame(x = c("a", letters[1:4]), y2 = 6:10)

# this throws an error because there are two keys in df2 that match the key
```

```
# in df1
tryCatch(
  df1$join(df2, on = "x", validate = "1:1")$collect(),
  error = function(e) print(e)
)
```

LazyFrame_join_asof *Perform joins on nearest keys*

Description

This is similar to a left-join except that we match on nearest key rather than equal keys.

Usage

```
LazyFrame_join_asof(
  other,
  ...,
  left_on = NULL,
  right_on = NULL,
  on = NULL,
  by_left = NULL,
  by_right = NULL,
  by = NULL,
  strategy = c("backward", "forward", "nearest"),
  suffix = "_right",
  tolerance = NULL,
  allow_parallel = TRUE,
  force_parallel = FALSE,
  coalesce = TRUE
)
```

Arguments

`other` LazyFrame

`...` Not used, blocks use of further positional arguments

`left_on`, `right_on`
: Same as `on` but only for the left or the right DataFrame. They must have the same length.

`on` Either a vector of column names or a list of expressions and/or strings. Use `left_on` and `right_on` if the column names to match on are different between the two DataFrames.

`by_left`, `by_right`
: Same as `by` but only for the left or the right table. They must have the same length.

`by` Join on these columns before performing asof join. Either a vector of column names or a list of expressions and/or strings. Use `left_by` and `right_by` if the column names to match on are different between the two tables.

`strategy` Strategy for where to find match:

- "backward" (default): search for the last row in the right table whose `on` key is less than or equal to the left key.
- "forward": search for the first row in the right table whose `on` key is greater than or equal to the left key.
- "nearest": search for the last row in the right table whose value is nearest to the left key. String keys are not currently supported for a nearest search.

`suffix` Suffix to add to duplicated column names.

`tolerance` Numeric tolerance. By setting this the join will only be done if the near keys are within this distance. If an asof join is done on columns of dtype "Date", "Datetime", "Duration" or "Time", use the Polars duration string language. About the language, see the `Polars duration string language` section for details.

There may be a circumstance where R types are not sufficient to express a numeric tolerance. In that case, you can use the expression syntax like `tolerance = pl$lit(42)$cast(pl$Uint64)`

`allow_parallel` Allow the physical plan to optionally evaluate the computation of both DataFrames up to the join in parallel.

`force_parallel` Force the physical plan to evaluate the computation of both DataFrames up to the join in parallel.

`coalesce` Coalescing behavior (merging of `on` / `left_on` / `right_on` columns):

- `TRUE`: Always coalesce join columns;
- `FALSE`: Never coalesce join columns. Note that joining on any other expressions than `col` will turn off coalescing.

Details

Both tables (DataFrames or LazyFrames) must be sorted by the asof_join key.

Polars duration string language

Polars duration string language is a simple representation of durations. It is used in many Polars functions that accept durations.

It has the following format:

- 1ns (1 nanosecond)
- 1us (1 microsecond)
- 1ms (1 millisecond)
- 1s (1 second)
- 1m (1 minute)
- 1h (1 hour)
- 1d (1 calendar day)

- 1w (1 calendar week)
- 1mo (1 calendar month)
- 1q (1 calendar quarter)
- 1y (1 calendar year)

Or combine them: "3d12h4m25s" # 3 days, 12 hours, 4 minutes, and 25 seconds

By "calendar day", we mean the corresponding time on the next day (which may not be 24 hours, due to daylight savings). Similarly for "calendar week", "calendar month", "calendar quarter", and "calendar year".

Examples

```
#
# create two LazyFrame to join asof
gdp = pl$LazyFrame(
  date = as.Date(c("2015-1-1", "2016-1-1", "2017-5-1", "2018-1-1", "2019-1-1")),
  gdp = c(4321, 4164, 4411, 4566, 4696),
  group = c("b", "a", "a", "b", "b")
)

pop = pl$LazyFrame(
  date = as.Date(c("2016-5-12", "2017-5-12", "2018-5-12", "2019-5-12")),
  population = c(82.19, 82.66, 83.12, 83.52),
  group = c("b", "b", "a", "a")
)

# optional make sure tables are already sorted with "on" join-key
gdp = gdp$sort("date")
pop = pop$sort("date")


# Left-join_asof LazyFrame pop with gdp on "date"
# Look backward in gdp to find closest matching date
pop$join_asof(gdp, on = "date", strategy = "backward")$collect()

# .... and forward
pop$join_asof(gdp, on = "date", strategy = "forward")$collect()

# join by a group: "only look within groups"
pop$join_asof(gdp, on = "date", by = "group", strategy = "backward")$collect()

# only look 2 weeks and 2 days back
pop$join_asof(gdp, on = "date", strategy = "backward", tolerance = "2w2d")$collect()

# only look 11 days back (numeric tolerance depends on polars type, <date> is in days)
pop$join_asof(gdp, on = "date", strategy = "backward", tolerance = 11)$collect()
```

LazyFrame_join_where *Perform a join based on one or multiple (in)equality predicates*

Description

This performs an inner join, so only rows where all predicates are true are included in the result, and a row from either LazyFrame may be included multiple times in the result.

Note that the row order of the input LazyFrames is not preserved.

Usage

```
LazyFrame_join_where(other, ..., suffix = "_right")
```

Arguments

other	LazyFrame to join with.
...	(In)Equality condition to join the two tables on. When a column name occurs in both tables, the proper suffix must be applied in the predicate. For example, if both tables have a column "x" that you want to use in the conditions, you must refer to the column of the right table as "x<suffix>".
suffix	Suffix to append to columns with a duplicate name.

Value

A LazyFrame

Examples

```
east = pl$LazyFrame(
  id = c(100, 101, 102),
  dur = c(120, 140, 160),
  rev = c(12, 14, 16),
  cores = c(2, 8, 4)
)

west = pl$LazyFrame(
  t_id = c(404, 498, 676, 742),
  time = c(90, 130, 150, 170),
  cost = c(9, 13, 15, 16),
  cores = c(4, 2, 1, 4)
)

east$join_where(
  west,
  pl$col("dur") < pl$col("time"),
  pl$col("rev") < pl$col("cost")
)$collect()
```

LazyFrame_last *Get the last row of a LazyFrame*

Description

Aggregate the columns in the LazyFrame to their maximum value.

Usage

```
LazyFrame_last()
```

Value

A LazyFrame with one row

Examples

```
as_polars_lf(mtcars)$last()$collect()
```

LazyFrame_max *Max*

Description

Aggregate the columns in the LazyFrame to their maximum value.

Usage

```
LazyFrame_max()
```

Value

A LazyFrame with one row

Examples

```
as_polars_lf(mtcars)$max()$collect()
```

LazyFrame_mean *Mean*

Description

Aggregate the columns in the LazyFrame to their mean value.

Usage

```
LazyFrame_mean()
```

Value

A LazyFrame with one row

Examples

```
as_polars_lf(mtcars)$mean()$collect()
```

LazyFrame_median *Median*

Description

Aggregate the columns in the LazyFrame to their median value.

Usage

```
LazyFrame_median()
```

Value

A LazyFrame with one row

Examples

```
as_polars_lf(mtcars)$median()$collect()
```

LazyFrame_min *Min*

Description

Aggregate the columns in the LazyFrame to their minimum value.

Usage

```
LazyFrame_min()
```

Value

A LazyFrame with one row

Examples

```
as_polars_lf(mtcars)$min()$collect()
```

LazyFrame_print *print LazyFrame internal method*

Description

can be used i the middle of a method chain

Usage

```
LazyFrame_print(x)
```

Arguments

x	LazyFrame

Value

self

Examples

```
as_polars_lf(iris)$print()
```

LazyFrame_profile *Collect and profile a lazy query.*

Description

This will run the query and return a list containing the materialized DataFrame and a DataFrame that contains profiling information of each node that is executed.

Usage

```
LazyFrame_profile(
  type_coercion = TRUE,
  predicate_pushdown = TRUE,
  projection_pushdown = TRUE,
  simplify_expression = TRUE,
  slice_pushdown = TRUE,
  comm_subplan_elim = TRUE,
  comm_subexpr_elim = TRUE,
  cluster_with_columns = TRUE,
  streaming = FALSE,
  no_optimization = FALSE,
  collect_in_background = FALSE,
  show_plot = FALSE,
  truncate_nodes = 0
)
```

Arguments

`type_coercion` Logical. Coerce types such that operations succeed and run on minimal required memory.

`predicate_pushdown` Logical. Applies filters as early as possible at scan level.

`projection_pushdown` Logical. Select only the columns that are needed at the scan level.

`simplify_expression` Logical. Various optimizations, such as constant folding and replacing expensive operations with faster alternatives.

`slice_pushdown` Logical. Only load the required slice from the scan level. Don't materialize sliced outputs (e.g. `join$head(10)`).

`comm_subplan_elim` Logical. Will try to cache branching subplans that occur on self-joins or unions.

`comm_subexpr_elim` Logical. Common subexpressions will be cached and reused.

`cluster_with_columns` Combine sequential independent calls to `with_columns()`.

streaming Logical. Run parts of the query in a streaming fashion (this is in an alpha state).

no_optimization
Logical. Sets the following parameters to FALSE: predicate_pushdown, projection_pushdown, slice_pushdown, comm_subplan_elim, comm_subexpr_elim, cluster_with_columns.

collect_in_background
Logical. Detach this query from R session. Computation will start in background. Get a handle which later can be converted into the resulting DataFrame. Useful in interactive mode to not lock R session.

show_plot Show a Gantt chart of the profiling result

truncate_nodes Truncate the label lengths in the Gantt chart to this number of characters. If 0 (default), do not truncate.

Details

The units of the timings are microseconds.

Value

List of two DataFrames: one with the collected result, the other with the timings of each step. If show_graph = TRUE, then the plot is also stored in the list.

See Also

- $collect() - regular collect.
- $fetch() - fast limited query check
- $collect_in_background() - non-blocking collect returns a future handle. Can also just be used via $collect(collect_in_background = TRUE).
- $sink_parquet() streams query to a parquet file.
- $sink_ipc() streams query to a arrow file.

Examples

```
## Simplest use case
pl$LazyFrame()$select(pl$lit(2) + 2)$profile()

## Use $profile() to compare two queries

# -1-  map each Species-group with native polars, takes ~120us only
as_polars_lf(iris)$
  sort("Sepal.Length")$
  group_by("Species", maintain_order = TRUE)$
  agg(pl$col(pl$Float64)$first() + 5)$
  profile()

# -2-  map each Species-group of each numeric column with an R function, takes ~7000us (slow!)

# some R function, prints `.` for each time called by polars
r_func = \(s) {
  cat(".")
```

```
  s$to_r()[1] + 5
}

as_polars_lf(iris)$
  sort("Sepal.Length")$
  group_by("Species", maintain_order = TRUE)$
  agg(pl$col(pl$Float64)$map_elements(r_func))$
  profile()
```

LazyFrame_quantile *Quantile*

Description

Aggregate the columns in the DataFrame to a unique quantile value. Use `$describe()` to specify several quantiles.

Usage

```
LazyFrame_quantile(quantile, interpolation = "nearest")
```

Arguments

`quantile`	Numeric of length 1 between 0 and 1.
`interpolation`	One of `"nearest"`, `"higher"`, `"lower"`, `"midpoint"`, or `"linear"`.

Value

LazyFrame

Examples

```
as_polars_lf(mtcars)$quantile(.4)$collect()
```

LazyFrame_rename *Rename column names of a LazyFrame*

Description

Rename column names of a LazyFrame

Usage

```
LazyFrame_rename(...)
```

Arguments

... One of the following:

- Key value pairs that map from old name to new name, like `old_name = "new_name"`.
- As above but with params wrapped in a list
- An R function that takes the old names character vector as input and returns the new names character vector.

Details

If existing names are swapped (e.g. `A` points to `B` and `B` points to `A`), polars will block projection and predicate pushdowns at this node.

Value

LazyFrame

Examples

```
lf = pl$LazyFrame(
  foo = 1:3,
  bar = 6:8,
  ham = letters[1:3]
)

lf$rename(foo = "apple")$collect()

lf$rename(
  \(column_name) paste0("c", substr(column_name, 2, 100))
)$collect()
```

LazyFrame_reverse *Reverse*

Description

Reverse the LazyFrame (the last row becomes the first one, etc.).

Usage

```
LazyFrame_reverse()
```

Value

LazyFrame

Examples

```
as_polars_lf(mtcars)$reverse()$collect()
```

LazyFrame_rolling — *Create rolling groups based on a date/time or integer column*

Description

If you have a time series `<t_0, t_1, ..., t_n>`, then by default the windows created will be:

- (t_0 - period, t_0]
- (t_1 - period, t_1]
- ...
- (t_n - period, t_n]

whereas if you pass a non-default offset, then the windows will be:

- (t_0 + offset, t_0 + offset + period]
- (t_1 + offset, t_1 + offset + period]
- ...
- (t_n + offset, t_n + offset + period]

Usage

```
LazyFrame_rolling(
  index_column,
  ...,
  period,
  offset = NULL,
  closed = "right",
  group_by = NULL
)
```

Arguments

`index_column`	Column used to group based on the time window. Often of type Date/Datetime. This column must be sorted in ascending order (or, if `by` is specified, then it must be sorted in ascending order within each group). In case of a rolling group by on indices, dtype needs to be either Int32 or Int64. Note that Int32 gets temporarily cast to Int64, so if performance matters use an Int64 column.
`...`	Ignored.
`period`	A character representing the length of the window, must be non-negative. See the `Polars duration string language` section for details.
`offset`	A character representing the offset of the window, or `NULL` (default). If `NULL`, `-period` is used. See the `Polars duration string language` section for details.
`closed`	Define which sides of the temporal interval are closed (inclusive). This can be either `"left"`, `"right"`, `"both"` or `"none"`.
`group_by`	Also group by this column/these columns.

Details

In case of a rolling operation on an integer column, the windows are defined by:

- "1i" # length 1
- "10i" # length 10

Value

A LazyGroupBy object

Polars duration string language

Polars duration string language is a simple representation of durations. It is used in many Polars functions that accept durations.

It has the following format:

- 1ns (1 nanosecond)
- 1us (1 microsecond)
- 1ms (1 millisecond)
- 1s (1 second)
- 1m (1 minute)
- 1h (1 hour)
- 1d (1 calendar day)
- 1w (1 calendar week)
- 1mo (1 calendar month)
- 1q (1 calendar quarter)
- 1y (1 calendar year)

Or combine them: `"3d12h4m25s"` # 3 days, 12 hours, 4 minutes, and 25 seconds

By "calendar day", we mean the corresponding time on the next day (which may not be 24 hours, due to daylight savings). Similarly for "calendar week", "calendar month", "calendar quarter", and "calendar year".

See Also

- `<LazyFrame>$group_by_dynamic()`

Examples

```
dates = c(
  "2020-01-01 13:45:48",
  "2020-01-01 16:42:13",
  "2020-01-01 16:45:09",
  "2020-01-02 18:12:48",
  "2020-01-03 19:45:32",
  "2020-01-08 23:16:43"
```

```
)

df = pl$LazyFrame(dt = dates, a = c(3, 7, 5, 9, 2, 1))$with_columns(
  pl$col("dt")$str$strptime(pl$Datetime())$set_sorted()
)

df$rolling(index_column = "dt", period = "2d")$agg(
  sum_a = pl$sum("a"),
  min_a = pl$min("a"),
  max_a = pl$max("a")
)$collect()
```

`LazyFrame_select` *Select and modify columns of a LazyFrame*

Description

Similar to `dplyr::mutate()`. However, it discards unmentioned columns (like `.()` in `data.table`).

Usage

```
LazyFrame_select(...)
```

Arguments

`...`	Columns to keep. Those can be expressions (e.g `pl$col("a")`), column names (e.g `"a"`), or list containing expressions or column names (e.g `list(pl$col("a"))`).

Value

A LazyFrame

Examples

```
as_polars_lf(iris)$select(
  pl$col("Sepal.Length")$abs()$alias("abs_SL"),
  (pl$col("Sepal.Length") + 2)$alias("add_2_SL")
)
```

LazyFrame_select_seq *Select and modify columns of a LazyFrame*

Description

Similar to `dplyr::mutate()`. However, it discards unmentioned columns (like `.()` in `data.table`).

This will run all expression sequentially instead of in parallel. Use this when the work per expression is cheap. Otherwise, `$select()` should be preferred.

Usage

```
LazyFrame_select_seq(...)
```

Arguments

`...`	Columns to keep. Those can be expressions (e.g `pl$col("a")`), column names (e.g `"a"`), or list containing expressions or column names (e.g `list(pl$col("a"))`).

Value

A LazyFrame

Examples

```
as_polars_lf(iris)$select_seq(
  pl$col("Sepal.Length")$abs()$alias("abs_SL"),
  (pl$col("Sepal.Length") + 2)$alias("add_2_SL")
)
```

LazyFrame_serialize *Serialize the logical plan of this LazyFrame to a file or string in JSON format*

Description

Note that not all LazyFrames can be serialized. For example, LazyFrames that contain UDFs such as `$map_elements()` cannot be serialized.

Usage

```
LazyFrame_serialize()
```

Value

A character of the JSON representation of the logical plan

See Also

- pl$deserialize_lf()

Examples

```
lf = pl$LazyFrame(a = 1:3)$sum()
json = lf$serialize()
json

# The logical plan can later be deserialized back into a LazyFrame.
pl$deserialize_lf(json)$collect()
```

LazyFrame_shift *Shift a LazyFrame*

Description

Shift the values by a given period. If the period (n) is positive, then n rows will be inserted at the top of the DataFrame and the last n rows will be discarded. Vice-versa if the period is negative. In the end, the total number of rows of the DataFrame doesn't change.

Usage

```
LazyFrame_shift(n = 1, fill_value = NULL)
```

Arguments

n	Number of indices to shift forward. If a negative value is passed, values are shifted in the opposite direction instead.
fill_value	Fill the resulting null values with this value. Accepts expression input. Non-expression inputs are parsed as literals.

Value

LazyFrame

Examples

```
lf = pl$LazyFrame(a = 1:4, b = 5:8)

lf$shift(2)$collect()

lf$shift(-2)$collect()

lf$shift(-2, fill_value = 100)$collect()
```

LazyFrame_sink_csv *Stream the output of a query to a CSV file*

Description

This writes the output of a query directly to a CSV file without collecting it in the R session first. This is useful if the output of the query is still larger than RAM as it would crash the R session if it was collected into R.

Usage

```
LazyFrame_sink_csv(
  path,
  ...,
  include_bom = FALSE,
  include_header = TRUE,
  separator = ",",
  line_terminator = "\n",
  quote_char = "\"",
  batch_size = 1024,
  datetime_format = NULL,
  date_format = NULL,
  time_format = NULL,
  float_precision = NULL,
  null_values = "",
  quote_style = "necessary",
  maintain_order = TRUE,
  type_coercion = TRUE,
  predicate_pushdown = TRUE,
  projection_pushdown = TRUE,
  simplify_expression = TRUE,
  slice_pushdown = TRUE,
  no_optimization = FALSE
)
```

Arguments

`path`	A character. File path to which the file should be written.
`...`	Ignored.
`include_bom`	Whether to include UTF-8 BOM (byte order mark) in the CSV output.
`include_header`	Whether to include header in the CSV output.
`separator`	Separate CSV fields with this symbol.
`line_terminator`	String used to end each row.
`quote_char`	Byte to use as quoting character.

batch_size
: Number of rows that will be processed per thread.

datetime_format
: A format string, with the specifiers defined by the chrono Rust crate. If no format specified, the default fractional-second precision is inferred from the maximum timeunit found in the frame's Datetime cols (if any).

date_format
: A format string, with the specifiers defined by the chrono Rust crate.

time_format
: A format string, with the specifiers defined by the chrono Rust crate.

float_precision
: Number of decimal places to write, applied to both Float32 and Float64 datatypes.

null_values
: A string representing null values (defaulting to the empty string).

quote_style
: Determines the quoting strategy used.

- `"necessary"` (default): This puts quotes around fields only when necessary. They are necessary when fields contain a quote, delimiter or record terminator. Quotes are also necessary when writing an empty record (which is indistinguishable from a record with one empty field). This is the default.
- `"always"`: This puts quotes around every field.
- `"non_numeric"`: This puts quotes around all fields that are non-numeric. Namely, when writing a field that does not parse as a valid float or integer, then quotes will be used even if they aren't strictly necessary.
- `"never"`: This never puts quotes around fields, even if that results in invalid CSV data (e.g. by not quoting strings containing the separator).

maintain_order
: Maintain the order in which data is processed. Setting this to `FALSE` will be slightly faster.

type_coercion
: Logical. Coerce types such that operations succeed and run on minimal required memory.

predicate_pushdown
: Logical. Applies filters as early as possible at scan level.

projection_pushdown
: Logical. Select only the columns that are needed at the scan level.

simplify_expression
: Logical. Various optimizations, such as constant folding and replacing expensive operations with faster alternatives.

slice_pushdown
: Logical. Only load the required slice from the scan level. Don't materialize sliced outputs (e.g. `join$head(10)`).

no_optimization
: Logical. Sets the following parameters to `FALSE`: `predicate_pushdown`, `projection_pushdown`, `slice_pushdown`, `comm_subplan_elim`, `comm_subexpr_elim`, `cluster_with_columns`.

Value

Invisibly returns the input LazyFrame

Examples

```
# sink table 'mtcars' from mem to CSV
tmpf = tempfile()
as_polars_lf(mtcars)$sink_csv(tmpf)

# stream a query end-to-end
tmpf2 = tempfile()
pl$scan_csv(tmpf)$select(pl$col("cyl") * 2)$sink_csv(tmpf2)

# load parquet directly into a DataFrame / memory
pl$scan_csv(tmpf2)$collect()
```

LazyFrame_sink_ipc *Stream the output of a query to an Arrow IPC file*

Description

This writes the output of a query directly to an Arrow IPC file without collecting it in the R session first. This is useful if the output of the query is still larger than RAM as it would crash the R session if it was collected into R.

Usage

```
LazyFrame_sink_ipc(
  path,
  ...,
  compression = c("zstd", "lz4", "uncompressed"),
  maintain_order = TRUE,
  type_coercion = TRUE,
  predicate_pushdown = TRUE,
  projection_pushdown = TRUE,
  simplify_expression = TRUE,
  slice_pushdown = TRUE,
  no_optimization = FALSE
)
```

Arguments

path	A character. File path to which the file should be written.
...	Ignored.
compression	NULL or a character of the compression method, "uncompressed" or "lz4" or "zstd". NULL is equivalent to "uncompressed". Choose "zstd" for good compression performance. Choose "lz4" for fast compression/decompression.
maintain_order	Maintain the order in which data is processed. Setting this to FALSE will be slightly faster.
type_coercion	Logical. Coerce types such that operations succeed and run on minimal required memory.

predicate_pushdown
: Logical. Applies filters as early as possible at scan level.

projection_pushdown
: Logical. Select only the columns that are needed at the scan level.

simplify_expression
: Logical. Various optimizations, such as constant folding and replacing expensive operations with faster alternatives.

slice_pushdown
: Logical. Only load the required slice from the scan level. Don't materialize sliced outputs (e.g. `join$head(10)`).

no_optimization
: Logical. Sets the following parameters to `FALSE`: `predicate_pushdown`, `projection_pushdown`, `slice_pushdown`, `comm_subplan_elim`, `comm_subexpr_elim`, `cluster_with_columns`.

Value

Invisibly returns the input LazyFrame

Examples

```
# sink table 'mtcars' from mem to ipc
tmpf = tempfile()
as_polars_lf(mtcars)$sink_ipc(tmpf)

# stream a query end-to-end (not supported yet, https://github.com/pola-rs/polars/issues/1040)
# tmpf2 = tempfile()
# pl$scan_ipc(tmpf)$select(pl$col("cyl") * 2)$sink_ipc(tmpf2)

# load ipc directly into a DataFrame / memory
# pl$scan_ipc(tmpf2)$collect()
```

LazyFrame_sink_ndjson *Stream the output of a query to a JSON file*

Description

This writes the output of a query directly to a JSON file without collecting it in the R session first. This is useful if the output of the query is still larger than RAM as it would crash the R session if it was collected into R.

Usage

```
LazyFrame_sink_ndjson(
  path,
  ...,
  maintain_order = TRUE,
  type_coercion = TRUE,
  predicate_pushdown = TRUE,
```

```
  projection_pushdown = TRUE,
  simplify_expression = TRUE,
  slice_pushdown = TRUE,
  no_optimization = FALSE
)
```

Arguments

`path` A character. File path to which the file should be written.

`...` Ignored.

`maintain_order` Maintain the order in which data is processed. Setting this to `FALSE` will be slightly faster.

`type_coercion` Logical. Coerce types such that operations succeed and run on minimal required memory.

`predicate_pushdown` Logical. Applies filters as early as possible at scan level.

`projection_pushdown` Logical. Select only the columns that are needed at the scan level.

`simplify_expression` Logical. Various optimizations, such as constant folding and replacing expensive operations with faster alternatives.

`slice_pushdown` Logical. Only load the required slice from the scan level. Don't materialize sliced outputs (e.g. `join$head(10)`).

`no_optimization` Logical. Sets the following parameters to `FALSE`: `predicate_pushdown`, `projection_pushdown`, `slice_pushdown`, `comm_subplan_elim`, `comm_subexpr_elim`, `cluster_with_columns`.

Value

Invisibly returns the input LazyFrame

Examples

```
# sink table 'mtcars' from mem to JSON
tmpf = tempfile(fileext = ".json")
as_polars_lf(mtcars)$sink_ndjson(tmpf)

# load parquet directly into a DataFrame / memory
pl$scan_ndjson(tmpf)$collect()
```

LazyFrame_sink_parquet

Stream the output of a query to a Parquet file

Description

This writes the output of a query directly to a Parquet file without collecting it in the R session first. This is useful if the output of the query is still larger than RAM as it would crash the R session if it was collected into R.

Usage

```
LazyFrame_sink_parquet(
  path,
  ...,
  compression = "zstd",
  compression_level = 3,
  statistics = TRUE,
  row_group_size = NULL,
  data_page_size = NULL,
  maintain_order = TRUE,
  type_coercion = TRUE,
  predicate_pushdown = TRUE,
  projection_pushdown = TRUE,
  simplify_expression = TRUE,
  slice_pushdown = TRUE,
  no_optimization = FALSE
)
```

Arguments

`path` A character. File path to which the file should be written.

`...` Ignored.

`compression` String. The compression method. One of:

- "lz4": fast compression/decompression.
- "uncompressed"
- "snappy": this guarantees that the parquet file will be compatible with older parquet readers.
- "gzip"
- "lzo"
- "brotli"
- "zstd": good compression performance.

`compression_level` `NULL` or Integer. The level of compression to use. Only used if method is one of 'gzip', 'brotli', or 'zstd'. Higher compression means smaller files on disk:

- "gzip": min-level: 0, max-level: 10.
- "brotli": min-level: 0, max-level: 11.
- "zstd": min-level: 1, max-level: 22.

`statistics` Whether statistics should be written to the Parquet headers. Possible values:

- `TRUE`: enable default set of statistics (default)
- `FALSE`: disable all statistics
- `"full"`: calculate and write all available statistics.
- A named list where all values must be `TRUE` or `FALSE`, e.g. `list(min = TRUE, max = FALSE)`. Statistics available are `"min"`, `"max"`, `"distinct_count"`, `"null_count"`.

`row_group_size` `NULL` or Integer. Size of the row groups in number of rows. If `NULL` (default), the chunks of the DataFrame are used. Writing in smaller chunks may reduce memory pressure and improve writing speeds.

`data_page_size` Size of the data page in bytes. If `NULL` (default), it is set to 1024^2 bytes. will be ~1MB.

`maintain_order` Maintain the order in which data is processed. Setting this to `FALSE` will be slightly faster.

`type_coercion` Logical. Coerce types such that operations succeed and run on minimal required memory.

`predicate_pushdown` Logical. Applies filters as early as possible at scan level.

`projection_pushdown` Logical. Select only the columns that are needed at the scan level.

`simplify_expression` Logical. Various optimizations, such as constant folding and replacing expensive operations with faster alternatives.

`slice_pushdown` Logical. Only load the required slice from the scan level. Don't materialize sliced outputs (e.g. `join$head(10)`).

`no_optimization` Logical. Sets the following parameters to `FALSE`: `predicate_pushdown`, `projection_pushdown`, `slice_pushdown`, `comm_subplan_elim`, `comm_subexpr_elim`, `cluster_with_columns`.

Value

Invisibly returns the input LazyFrame

Examples

```
# sink table 'mtcars' from mem to parquet
tmpf = tempfile()
as_polars_lf(mtcars)$sink_parquet(tmpf)

# stream a query end-to-end
tmpf2 = tempfile()
pl$scan_parquet(tmpf)$select(pl$col("cyl") * 2)$sink_parquet(tmpf2)
```

```
# load parquet directly into a DataFrame / memory
pl$scan_parquet(tmpf2)$collect()
```

LazyFrame_slice *Slice*

Description

Get a slice of the LazyFrame.

Usage

```
LazyFrame_slice(offset, length = NULL)
```

Arguments

`offset`	Start index, can be a negative value. This is 0-indexed, so `offset = 1` doesn't include the first row.
`length`	Length of the slice. If `NULL` (default), all rows starting at the offset will be selected.

Value

A LazyFrame

Examples

```
as_polars_lf(mtcars)$slice(2, 4)$collect()
as_polars_lf(mtcars)$slice(30)$collect()
mtcars[2:6, ]
```

LazyFrame_sort *Sort the LazyFrame by the given columns*

Description

Sort the LazyFrame by the given columns

Usage

```
LazyFrame_sort(
  by,
  ...,
  descending = FALSE,
  nulls_last = FALSE,
  maintain_order = FALSE,
  multithreaded = TRUE
)
```

Arguments

by	Column(s) to sort by. Can be character vector of column names, a list of Expr(s) or a list with a mix of Expr(s) and column names.
...	More columns to sort by as above but provided one Expr per argument.
descending	Logical. Sort in descending order (default is FALSE). This must be either of length 1 or a logical vector of the same length as the number of Expr(s) specified in by and ....
nulls_last	A logical or logical vector of the same length as the number of columns. If TRUE, place null values last insead of first.
maintain_order	Whether the order should be maintained if elements are equal. If TRUE, streaming is not possible and performance might be worse since this requires a stable search.
multithreaded	A logical. If TRUE, sort using multiple threads.

Value

LazyFrame

Examples

```
df = mtcars
df$mpg[1] = NA
df = pl$LazyFrame(df)
df$sort("mpg")$collect()
df$sort("mpg", nulls_last = TRUE)$collect()
df$sort("cyl", "mpg")$collect()
df$sort(c("cyl", "mpg"))$collect()
df$sort(c("cyl", "mpg"), descending = TRUE)$collect()
df$sort(c("cyl", "mpg"), descending = c(TRUE, FALSE))$collect()
df$sort(pl$col("cyl"), pl$col("mpg"))$collect()
```

LazyFrame_sql *Execute a SQL query against the LazyFrame*

Description

The calling frame is automatically registered as a table in the SQL context under the name "self". All DataFrames and LazyFrames found in the envir are also registered, using their variable name. More control over registration and execution behaviour is available by the SQLContext object.

Usage

```
LazyFrame_sql(query, ..., table_name = NULL, envir = parent.frame())
```

Arguments

query	A character of the SQL query to execute.
...	Ignored.
table_name	NULL (default) or a character of an explicit name for the table that represents the calling frame (the alias "self" will always be registered/available).
envir	The environment to search for polars DataFrames/LazyFrames.

Details

This functionality is considered **unstable**, although it is close to being considered stable. It may be changed at any point without it being considered a breaking change.

Value

LazyFrame

See Also

- SQLContext

Examples

```
lf1 = pl$LazyFrame(a = 1:3, b = 6:8, c = c("z", "y", "x"))
lf2 = pl$LazyFrame(a = 3:1, d = c(125, -654, 888))

# Query the LazyFrame using SQL:
lf1$sql("SELECT c, b FROM self WHERE a > 1")$collect()

# Join two LazyFrames:
lf1$sql(
  "
SELECT self.*, d
FROM self
INNER JOIN lf2 USING (a)
WHERE a > 1 AND b < 8
"
)$collect()

# Apply SQL transforms (aliasing "self" to "frame") and subsequently
# filter natively (you can freely mix SQL and native operations):
lf1$sql(
  query = r"(
SELECT
 a,
MOD(a, 2) == 0 AS a_is_even,
(b::float / 2) AS 'b/2',
CONCAT_WS(':', c, c, c) AS c_c_c
FROM frame
ORDER BY a
)",
```

```
  table_name = "frame"
)$filter(!pl$col("c_c_c")$str$starts_with("x"))$collect()
```

LazyFrame_std *Std*

Description

Aggregate the columns of this LazyFrame to their standard deviation values.

Usage

```
LazyFrame_std(ddof = 1)
```

Arguments

ddof	Delta Degrees of Freedom: the divisor used in the calculation is N - ddof, where N represents the number of elements. By default ddof is 1.

Value

A LazyFrame with one row

Examples

```
as_polars_lf(mtcars)$std()$collect()
```

LazyFrame_sum *Sum*

Description

Aggregate the columns of this LazyFrame to their sum values.

Usage

```
LazyFrame_sum()
```

Value

A LazyFrame with one row

Examples

```
as_polars_lf(mtcars)$sum()$collect()
```

LazyFrame_tail *Get the last* n *rows.*

Description

Get the last n rows.

Usage

```
LazyFrame_tail(n = 5L)
```

Arguments

n	Number of rows to return.

Value

A new LazyFrame object with applied filter.

See Also

<LazyFrame>$head()

Examples

```
lf = pl$LazyFrame(a = 1:6, b = 7:12)

lf$tail()$collect()

lf$tail(2)$collect()
```

LazyFrame_to_dot *Plot the query plan*

Description

This only returns the "dot" output that can be passed to other packages, such as DiagrammeR::grViz().

Usage

```
LazyFrame_to_dot(
  ...,
  optimized = TRUE,
  type_coercion = TRUE,
  predicate_pushdown = TRUE,
  projection_pushdown = TRUE,
  simplify_expression = TRUE,
  slice_pushdown = TRUE,
  comm_subplan_elim = TRUE,
  comm_subexpr_elim = TRUE,
  cluster_with_columns = TRUE,
  streaming = FALSE
)
```

Arguments

`...`	Not used..
`optimized`	Optimize the query plan.
`type_coercion`	Logical. Coerce types such that operations succeed and run on minimal required memory.
`predicate_pushdown`	Logical. Applies filters as early as possible at scan level.
`projection_pushdown`	Logical. Select only the columns that are needed at the scan level.
`simplify_expression`	Logical. Various optimizations, such as constant folding and replacing expensive operations with faster alternatives.
`slice_pushdown`	Logical. Only load the required slice from the scan level. Don't materialize sliced outputs (e.g. `join$head(10)`).
`comm_subplan_elim`	Logical. Will try to cache branching subplans that occur on self-joins or unions.
`comm_subexpr_elim`	Logical. Common subexpressions will be cached and reused.
`cluster_with_columns`	Combine sequential independent calls to `with_columns()`.
`streaming`	Logical. Run parts of the query in a streaming fashion (this is in an alpha state).

Value

A character vector

Examples

```
lf = pl$LazyFrame(
  a = c("a", "b", "a", "b", "b", "c"),
```

```
  b = 1:6,
  c = 6:1
)

query = lf$group_by("a", maintain_order = TRUE)$agg(
  pl$all()$sum()
)$sort(
  "a"
)

query$to_dot() |> cat()

# You could print the graph by using DiagrammeR for example, with
# query$to_dot() |> DiagrammeR::grViz().
```

`LazyFrame_unique` *Drop duplicated rows*

Description

Drop duplicated rows

Usage

```
LazyFrame_unique(subset = NULL, ..., keep = "any", maintain_order = FALSE)
```

Arguments

`subset`	A character vector with the names of the column(s) to use to identify duplicates. If `NULL` (default), use all columns.
`...`	Not used.
`keep`	Which of the duplicate rows to keep: • `"any"` (default): Does not give any guarantee of which row is kept. This allows more optimizations. • `"first"`: Keep first unique row. • `"last"`: Keep last unique row. • `"none"`: Don't keep duplicate rows.
`maintain_order`	Keep the same order as the original data. Setting this to `TRUE` makes it more expensive to compute and blocks the possibility to run on the streaming engine.

Value

LazyFrame

Examples

```
df = pl$LazyFrame(
  x = sample(10, 100, rep = TRUE),
  y = sample(10, 100, rep = TRUE)
)
df$collect()$height

df$unique()$collect()$height
df$unique(subset = "x")$collect()$height

df$unique(keep = "last")

# only keep unique rows
df$unique(keep = "none")
```

LazyFrame_unnest *Unnest the Struct columns of a LazyFrame*

Description

Unnest the Struct columns of a LazyFrame

Usage

```
LazyFrame_unnest(...)
```

Arguments

...	Names of the struct columns to unnest. This doesn't accept Expr. If nothing is provided, then all columns of datatype Struct are unnested.

Value

A LazyFrame where some or all columns of datatype Struct are unnested.

Examples

```
lf = pl$LazyFrame(
  a = 1:5,
  b = c("one", "two", "three", "four", "five"),
  c = 6:10
)$
  select(
  pl$struct("b"),
  pl$struct(c("a", "c"))$alias("a_and_c")
)
lf$collect()

# by default, all struct columns are unnested
```

```
lf$unnest()$collect()

# we can specify specific columns to unnest
lf$unnest("a_and_c")$collect()
```

`LazyFrame_unpivot` *Unpivot a Frame from wide to long format*

Description

Unpivot a Frame from wide to long format

Usage

```
LazyFrame_unpivot(
  on = NULL,
  ...,
  index = NULL,
  variable_name = NULL,
  value_name = NULL
)
```

Arguments

`on`	Values to use as identifier variables. If `value_vars` is empty all columns that are not in `id_vars` will be used.
`...`	Not used.
`index`	Columns to use as identifier variables.
`variable_name`	Name to give to the new column containing the names of the melted columns. Defaults to "variable".
`value_name`	Name to give to the new column containing the values of the melted columns. Defaults to `"value"`.

Details

Optionally leaves identifiers set.

This function is useful to massage a Frame into a format where one or more columns are identifier variables (id_vars), while all other columns, considered measured variables (value_vars), are "unpivoted" to the row axis, leaving just two non-identifier columns, 'variable' and 'value'.

Value

A LazyFrame

Examples

```
lf = pl$LazyFrame(
  a = c("x", "y", "z"),
  b = c(1, 3, 5),
  c = c(2, 4, 6)
)
lf$unpivot(index = "a", on = c("b", "c"))$collect()
```

LazyFrame_var *Var*

Description

Aggregate the columns of this LazyFrame to their variance values.

Usage

```
LazyFrame_var(ddof = 1)
```

Arguments

ddof	Delta Degrees of Freedom: the divisor used in the calculation is N - ddof, where N represents the number of elements. By default ddof is 1.

Value

A LazyFrame with one row

Examples

```
as_polars_lf(mtcars)$var()$collect()
```

LazyFrame_with_columns *Select and modify columns of a LazyFrame*

Description

Add columns or modify existing ones with expressions. This is the equivalent of `dplyr::mutate()` as it keeps unmentioned columns (unlike `$select()`).

Usage

```
LazyFrame_with_columns(...)
```

Arguments

...	Any expressions or string column name, or same wrapped in a list. If first and only element is a list, it is unwrapped as a list of args.

Value

A LazyFrame

Examples

```
as_polars_lf(iris)$with_columns(
  pl$col("Sepal.Length")$abs()$alias("abs_SL"),
  (pl$col("Sepal.Length") + 2)$alias("add_2_SL")
)

# same query
l_expr = list(
  pl$col("Sepal.Length")$abs()$alias("abs_SL"),
  (pl$col("Sepal.Length") + 2)$alias("add_2_SL")
)
as_polars_lf(iris)$with_columns(l_expr)

as_polars_lf(iris)$with_columns(
  pl$col("Sepal.Length")$abs(), # not named expr will keep name "Sepal.Length"
  SW_add_2 = (pl$col("Sepal.Width") + 2)
)
```

LazyFrame_with_columns_seq

Select and modify columns of a LazyFrame

Description

Add columns or modify existing ones with expressions. This is the equivalent of `dplyr::mutate()` as it keeps unmentioned columns (unlike `$select()`).

This will run all expression sequentially instead of in parallel. Use this when the work per expression is cheap. Otherwise, `$with_columns()` should be preferred.

Usage

```
LazyFrame_with_columns_seq(...)
```

Arguments

...	Any expressions or string column name, or same wrapped in a list. If first and only element is a list, it is unwrapped as a list of args.

Value

A LazyFrame

Examples

```
as_polars_lf(iris)$with_columns_seq(
  pl$col("Sepal.Length")$abs()$alias("abs_SL"),
  (pl$col("Sepal.Length") + 2)$alias("add_2_SL")
)

# same query
l_expr = list(
  pl$col("Sepal.Length")$abs()$alias("abs_SL"),
  (pl$col("Sepal.Length") + 2)$alias("add_2_SL")
)
as_polars_lf(iris)$with_columns_seq(l_expr)

as_polars_lf(iris)$with_columns_seq(
  pl$col("Sepal.Length")$abs(), # not named expr will keep name "Sepal.Length"
  SW_add_2 = (pl$col("Sepal.Width") + 2)
)
```

LazyFrame_with_context

Add an external context to the computation graph

Description

This allows expressions to also access columns from DataFrames or LazyFrames that are not part of this one.

Usage

```
LazyFrame_with_context(other)
```

Arguments

other	Data/LazyFrame to have access to. This can be a list of DataFrames and LazyFrames.

Value

A LazyFrame

Examples

```
lf = pl$LazyFrame(a = c(1, 2, 3), b = c("a", "c", NA))
lf_other = pl$LazyFrame(c = c("foo", "ham"))

lf$with_context(lf_other)$select(
  pl$col("b") + pl$col("c")$first()
)$collect()

# Fill nulls with the median from another lazyframe:
train_lf = pl$LazyFrame(
  feature_0 = c(-1.0, 0, 1), feature_1 = c(-1.0, 0, 1)
)
test_lf = pl$LazyFrame(
  feature_0 = c(-1.0, NA, 1), feature_1 = c(-1.0, 0, 1)
)

test_lf$with_context(train_lf$select(pl$all()$name$suffix("_train")))$select(
  pl$col("feature_0")$fill_null(pl$col("feature_0_train")$median())
)$collect()
```

LazyFrame_with_row_index

Add a column for row indices

Description

Add a new column at index 0 that counts the rows

Usage

```
LazyFrame_with_row_index(name, offset = NULL)
```

Arguments

name	string name of the created column
offset	positive integer offset for the start of the counter

Value

A new LazyFrame with a counter column in front

Examples

```
df = as_polars_lf(mtcars)

# by default, the index starts at 0 (to mimic the behavior of Python Polars)
df$with_row_index("idx")

# but in R, we use a 1-index
df$with_row_index("idx", offset = 1)
```

LazyGroupBy_agg *LazyGroupBy_agg*

Description

aggregate a polar_lazy_group_by

Usage

```
LazyGroupBy_agg(...)
```

Arguments

`...`	exprs to aggregate over. ... args can also be passed wrapped in a list `$agg(list(e1,e2,e3))`

Value

A new `LazyFrame` object.

Examples

```
lgb = pl$DataFrame(
  foo = c("one", "two", "two", "one", "two"),
  bar = c(5, 3, 2, 4, 1)
)$
  lazy()$
  group_by("foo")


print(lgb)

lgb$
  agg(
  pl$col("bar")$sum()$name$suffix("_sum"),
  pl$col("bar")$mean()$alias("bar_tail_sum")
)
```

LazyGroupBy_class *Operations on Polars grouped LazyFrame*

Description

This class comes from `<LazyFrame>$group_by()`, etc.

Active bindings

columns:
`$columns` returns a character vector with the column names.

Examples

```
as_polars_lf(mtcars)$group_by("cyl")$agg(
  pl$col("mpg")$sum()
)
```

LazyGroupBy_head *LazyGroupBy_head*

Description

get n rows of head of group

Usage

```
LazyGroupBy_head(n = 1L)
```

Arguments

n	integer number of rows to get

Value

A new LazyFrame object.

LazyGroupBy_print *LazyGroupBy_print*

Description

prints opaque groupby, not much to show

Usage

```
LazyGroupBy_print()
```

Value

invisible self

LazyGroupBy_tail *LazyGroupBy_tail*

Description

get n tail rows of group

Usage

```
LazyGroupBy_tail(n = 1L)
```

Arguments

n	integer number of rows to get

Value

A new LazyFrame object.

LazyGroupBy_ungroup *LazyGroupBy_ungroup*

Description

Revert the group by operation.

Usage

```
LazyGroupBy_ungroup()
```

Value

A new LazyFrame object.

Examples

```
lf = as_polars_lf(mtcars)
lf

lgb = lf$group_by("cyl")
lgb

lgb$ungroup()
```

length.RPolarsDataFrame *Get the length*

Description

Get the length

Usage

```
## S3 method for class 'RPolarsDataFrame'
length(x)

## S3 method for class 'RPolarsLazyFrame'
length(x)

## S3 method for class 'RPolarsSeries'
length(x)
```

Arguments

x	A DataFrame, LazyFrame, or Series

max.RPolarsDataFrame *Compute the maximum value*

Description

Compute the maximum value

Usage

```
## S3 method for class 'RPolarsDataFrame'
max(x, ...)

## S3 method for class 'RPolarsLazyFrame'
max(x, ...)

## S3 method for class 'RPolarsSeries'
max(x, ...)
```

Arguments

x	A DataFrame, LazyFrame, or Series
...	Not used.

mean.RPolarsDataFrame *Compute the mean*

Description

Compute the mean

Usage

```
## S3 method for class 'RPolarsDataFrame'
mean(x, ...)

## S3 method for class 'RPolarsLazyFrame'
mean(x, ...)

## S3 method for class 'RPolarsSeries'
mean(x, ...)
```

Arguments

x	A DataFrame, LazyFrame, or Series
...	Not used.

median.RPolarsDataFrame *Compute the median*

Description

Compute the median

Usage

```
## S3 method for class 'RPolarsDataFrame'
median(x, ...)

## S3 method for class 'RPolarsLazyFrame'
median(x, ...)

## S3 method for class 'RPolarsSeries'
median(x, ...)
```

Arguments

x	A DataFrame, LazyFrame, or Series
...	Not used.

min.RPolarsDataFrame *Compute the minimum value*

Description

Compute the minimum value

Usage

```
## S3 method for class 'RPolarsDataFrame'
min(x, ...)

## S3 method for class 'RPolarsLazyFrame'
min(x, ...)

## S3 method for class 'RPolarsSeries'
min(x, ...)
```

Arguments

x	A DataFrame, LazyFrame, or Series
...	Not used.

na.omit.RPolarsLazyFrame *Drop missing values*

Description

Drop missing values

Usage

```
## S3 method for class 'RPolarsLazyFrame'
na.omit(object, subset = NULL, ...)

## S3 method for class 'RPolarsDataFrame'
na.omit(object, subset = NULL, ...)
```

Arguments

object	A DataFrame or LazyFrame
subset	Character vector of column names to drop missing values from.
...	Not used.

Examples

```
df = as_polars_df(data.frame(a = c(NA, 2:10), b = c(1, NA, 3:10)))$lazy()
na.omit(df)
na.omit(df, subset = "a")
na.omit(df, subset = c("a", "b"))
```

---

names.RPolarsDataFrame *Get the column names*

Description

Get the column names

Usage

```
## S3 method for class 'RPolarsDataFrame'
names(x)

## S3 method for class 'RPolarsLazyFrame'
names(x)

## S3 method for class 'RPolarsLazyGroupBy'
names(x)

## S3 method for class 'RPolarsGroupBy'
names(x)
```

Arguments

x	A DataFrame or LazyFrame

---

pl_all *New Expr referring to all columns*

Description

Not to mix up with `Expr_object$all()` which is a 'reduce Boolean columns by AND' method.

Usage

```
pl_all(name = NULL)
```

Arguments

name	Character vector indicating on which columns the AND operation should be applied.

Value

Boolean literal

Examples

```
test = pl$DataFrame(col_1 = c(TRUE, TRUE), col_2 = c(TRUE, FALSE))
test

# here, the first `$all()` selects all columns, and the second `$all()` checks
# whether all values are true in each column
test$with_columns(pl$all()$all())
```

---

pl_all_horizontal *Apply the AND logical rowwise*

Description

Apply the AND logical rowwise

Usage

```
pl_all_horizontal(...)
```

Arguments

...	Columns to concatenate into a single string column. Accepts expressions. Strings are parsed as column names, other non-expression inputs are parsed as literals.

Value

Expr

Examples

```
df = pl$DataFrame(
  a = c(TRUE, FALSE, NA, NA),
  b = c(TRUE, FALSE, NA, NA),
  c = c(TRUE, FALSE, NA, TRUE)
)
df

df$with_columns(
  pl$all_horizontal("a", "b", "c")$alias("all")
)

# drop rows that have at least one missing value
# == keep rows that only have non-missing values
df$filter(
  pl$all_horizontal(pl$all()$is_not_null())
)
```

pl_any_horizontal *Apply the OR logical rowwise*

Description

Apply the OR logical rowwise

Usage

```
pl_any_horizontal(...)
```

Arguments

...	Columns to concatenate into a single string column. Accepts expressions. Strings are parsed as column names, other non-expression inputs are parsed as literals.

Value

Expr

Examples

```
df = pl$DataFrame(
  a = c(FALSE, FALSE, NA, NA),
  b = c(TRUE, FALSE, NA, NA),
  c = c(TRUE, FALSE, NA, TRUE)
)
df

df$with_columns(
  pl$any_horizontal("a", "b", "c")$alias("any")
)

# drop rows that only have missing values == keep rows that have at least one
# non-missing value
df$filter(
  pl$any_horizontal(pl$all()$is_not_null())
)
```

pl_approx_n_unique *Approximate count of unique values*

Description

This function is syntactic sugar for `pl$col(...)$approx_n_unique()`, and uses the HyperLogLog++ algorithm for cardinality estimation.

Usage

```
pl_approx_n_unique(...)
```

Arguments

...	Characters indicating the column names, passed to `pl$col()`. See `?pl_col` for details.

Value

Expr

See Also

- `<Expr>$approx_n_unique()`

Examples

```
df = pl$DataFrame(
  a = c(1, 8, 1),
  b = c(4, 5, 2),
  c = c("foo", "bar", "foo")
)

df$select(pl$approx_n_unique("a"))

df$select(pl$approx_n_unique("b", "c"))
```

---

pl_arg_sort_by *Return the row indices that would sort the columns*

Description

Return the row indices that would sort the columns

Usage

```
pl_arg_sort_by(
  ...,
  descending = FALSE,
  nulls_last = FALSE,
  multithreaded = TRUE,
  maintain_order = FALSE
)
```

Arguments

...	Column(s) to arg sort by. Can be Expr(s) or something coercible to Expr(s). Strings are parsed as column names.
descending	Logical. Sort in descending order (default is FALSE). This must be either of length 1 or a logical vector of the same length as the number of Expr(s) specified in by and ....
nulls_last	A logical or logical vector of the same length as the number of columns. If TRUE, place null values last insead of first.
multithreaded	A logical. If TRUE, sort using multiple threads.
maintain_order	Whether the order should be maintained if elements are equal. If TRUE, streaming is not possible and performance might be worse since this requires a stable search.

Value

Expr

See Also

$arg_sort() to find the row indices that would sort an Expr.

Examples

```
df = pl$DataFrame(
  a = c(0, 1, 1, 0),
  b = c(3, 2, 3, 2)
)

df$with_columns(
  arg_sort_a = pl$arg_sort_by("a"),
  arg_sort_ab = pl$arg_sort_by(c("a", "b"), descending = TRUE)
)

# we can also pass Expr
df$with_columns(
  arg_sort_a = pl$arg_sort_by(pl$col("a") * -1)
)
```

---

pl_arg_where *Return indices that match a condition*

Description

Return indices that match a condition

Usage

```
pl_arg_where(condition)
```

Arguments

`condition`	An Expr that gives a boolean.

Value

Expr

Examples

```
df = pl$DataFrame(a = c(1, 2, 3, 4, 5))
df$select(
  pl$arg_where(pl$col("a") %% 2 == 0)
)
```

---

pl_coalesce *Coalesce*

Description

Folds the expressions from left to right, keeping the first non-null value.

Usage

```
pl_coalesce(...)
```

Arguments

`...`	is a: If one arg: • Series or Expr, same as `column$sum()` • string, same as `pl$col(column)$sum()` • numeric, same as `pl$lit(column)$sum()` • list of strings(column names) or expressions to add up as expr1 + expr2 + expr3 + ... If several args, then wrapped in a list and handled as above.

Value

Expr

Examples

```
df = pl$DataFrame(
  a = NA_real_,
  b = c(1L, 4L, NA_real_, NA_real_),
  c = c(2:4, NA_real_)
)

# use coalesce to get first non Null value for each row, otherwise insert 99.9
df$with_columns(
  pl$coalesce("a", "b", "c", 99.9)$alias("d")
)
```

`pl_col` *Create an expression representing column(s) in a dataframe*

Description

Create an expression representing column(s) in a dataframe

Usage

```
pl_col(...)
```

Arguments

`...` One of the following:

- character vectors
  - Single wildcard `"*"` has a special meaning: check the examples.
- RPolarsDataTypes
- a list of RPolarsDataTypes

Value

Expr of a column or columns

Examples

```
# a single column by a character
pl$col("foo")

# multiple columns by characters
pl$col("foo", "bar")

# multiple columns by RPolarsDataTypes
pl$col(pl$Float64, pl$String)

# Single `"*"` is converted to a wildcard expression
pl$col("*")
```

```
# multiple character vectors and a list of RPolarsDataTypes are also allowed
pl$col(c("foo", "bar"), "baz")
pl$col("foo", c("bar", "baz"))
pl$col(list(pl$Float64, pl$String))

# there are some special notations for selecting columns
df = pl$DataFrame(foo = 1:3, bar = 4:6, baz = 7:9)

## select all columns with a wildcard `"*"`
df$select(pl$col("*"))

## select multiple columns by a regular expression
## starts with `^` and ends with `$`
df$select(pl$col(c("^ba.*$")))
```

`pl_concat` *Concat polars objects*

Description

Concat polars objects

Usage

```
pl_concat(
  ...,
 how = c("vertical", "vertical_relaxed", "horizontal", "diagonal", "diagonal_relaxed"),
  rechunk = FALSE,
  parallel = TRUE
)
```

Arguments

`...`	Either individual unpacked args or args wrapped in list(). Args can be eager as DataFrame, Series and R vectors, or lazy as LazyFrame and Expr. The first element determines the output of `$concat()`: if the first element is lazy, a LazyFrame is returned; otherwise, a DataFrame is returned (note that if the first element is eager, all other elements have to be eager to avoid implicit collect).
`how`	Bind direction. Can be "vertical" (like `rbind()`), "horizontal" (like `cbind()`), or "diagonal". For `"vertical"` and `"diagonal"`, adding the suffix `"_relaxed"` will cast columns to their shared supertypes. For example, if we try to vertically concatenate two columns of types `i32` and `f64`, using `how = "vertical_relaxed"` will cast the column of type `i32` to `f64` beforehand.
`rechunk`	Perform a rechunk at last.
`parallel`	Only used for LazyFrames. If `TRUE` (default), lazy computations may be executed in parallel.

Details

Categorical columns/Series must have been constructed while global string cache enabled. See pl$enable_string_cache().

Value

DataFrame, Series, LazyFrame or Expr

Examples

```
# vertical
l_ver = lapply(1:10, function(i) {
  l_internal = list(
    a = 1:5,
    b = letters[1:5]
  )
  pl$DataFrame(l_internal)
})
pl$concat(l_ver, how = "vertical")

# horizontal
l_hor = lapply(1:10, function(i) {
  l_internal = list(
    1:5,
    letters[1:5]
  )
  names(l_internal) = paste0(c("a", "b"), i)
  pl$DataFrame(l_internal)
})
pl$concat(l_hor, how = "horizontal")

# diagonal
pl$concat(l_hor, how = "diagonal")

# if two columns don't share the same type, concat() will error unless we use
# `how = "vertical_relaxed"`:
test = pl$DataFrame(x = 1L) # i32
test2 = pl$DataFrame(x = 1.0) # f64

pl$concat(test, test2, how = "vertical_relaxed")
```

---

pl_concat_list *Concat the arrays in a Series dtype List in linear time.*

Description

Folds the expressions from left to right, keeping the first non-null value.

Usage

```
pl_concat_list(exprs)
```

Arguments

exprs	list of Into, strings interpreted as column names

Value

Expr

Examples

```
# Create lagged columns and collect them into a list. This mimics a rolling window.
df = pl$DataFrame(A = c(1, 2, 9, 2, 13))
df$with_columns(lapply(
  0:2,
  \(i) pl$col("A")$shift(i)$alias(paste0("A_lag_", i))
))$select(
  pl$concat_list(lapply(2:0, \(i) pl$col(paste0("A_lag_", i))))$alias(
    "A_rolling"
  )
)

# concat Expr a Series and an R obejct
pl$concat_list(list(
  pl$lit(1:5),
  as_polars_series(5:1),
  rep(0L, 5)
))$alias("alice")$to_series()
```

---

pl_concat_str *Horizontally concatenate columns into a single string column*

Description

Horizontally concatenate columns into a single string column

Usage

```
pl_concat_str(..., separator = "", ignore_nulls = FALSE)
```

Arguments

...	Columns to concatenate into a single string column. Accepts expressions. Strings are parsed as column names, other non-expression inputs are parsed as literals. Non-String columns are cast to String

separator	String that will be used to separate the values of each column.
ignore_nulls	If FALSE (default), null values are propagated: if the row contains any null values, the output is null.

Value

Expr

Examples

```
df = pl$DataFrame(
  a = 1:3,
  b = c("dogs", "cats", NA),
  c = c("play", "swim", "walk")
)

df$with_columns(
  pl$concat_str(
    pl$col("a") * 2L, "b", "c", pl$lit("!"),
    separator = " "
  )$alias("full_sentence")
)

df$with_columns(
  pl$concat_str(
    pl$col("a") * 2L, "b", "c", pl$lit("!"),
    separator = " ",
    ignore_nulls = TRUE
  )$alias("full_sentence")
)
```

---

pl_corr *Correlation*

Description

Calculates the correlation between two columns

Usage

```
pl_corr(a, b, method = "pearson", propagate_nans = FALSE)
```

Arguments

a	One column name or Expr or anything convertible Into via pl$col().
b	Another column name or Expr or anything convertible Into via pl$col().
method	str One of 'pearson' or 'spearman'
propagate_nans	bool Used only when calculating the spearman rank correlation. If True any NaN encountered will lead to NaN in the output. Defaults to False where NaN are regarded as larger than any finite number and thus lead to the highest rank.

Value

Expr for the computed correlation

Examples

```
lf = as_polars_lf(data.frame(a = c(1, 8, 3), b = c(4, 5, 2)))
lf$select(pl$corr("a", "b", method = "spearman"))$collect()
```

---

pl_count — *Return the number of non-null values in the column.*

Description

This function is syntactic sugar for `pl$col(...)$count()`.

Usage

```
pl_count(...)
```

Arguments

`...`	Characters indicating the column names, passed to `pl$col()`. See `?pl_col` for details.

Details

Calling this function without any arguments returns the number of rows in the context. This way of using the function is deprecated. Please use `pl$len()` instead.

Value

Expression of data type UInt32

See Also

- `pl$len()`
- `<Expr>$count()`

Examples

```
df = pl$DataFrame(
  a = c(1, 2, NA),
  b = c(3, NA, NA),
  c = c("foo", "bar", "foo")
)

df$select(pl$count("a"))

df$select(pl$count(c("b", "c")))
```

pl_cov — *Covariance*

Description

Calculates the covariance between two columns / expressions.

Usage

```
pl_cov(a, b, ddof = 1)
```

Arguments

a	One column name or Expr or anything convertible Into via `pl$col()`.
b	Another column name or Expr or anything convertible Into via `pl$col()`.
ddof	integer Delta Degrees of Freedom: the divisor used in the calculation is N - ddof, where N represents the number of elements. By default ddof is 1.

Value

Expr for the computed covariance

Examples

```
lf = as_polars_lf(data.frame(a = c(1, 8, 3), b = c(4, 5, 2)))
lf$select(pl$cov("a", "b"))$collect()
pl$cov(c(1, 8, 3), c(4, 5, 2))$to_r()
```

pl_DataFrame — *Create a new polars DataFrame*

Description

Create a new polars DataFrame

Usage

```
pl_DataFrame(..., make_names_unique = TRUE, schema = NULL)
```

Arguments

`...` One of the following:

- mixed vectors and/or Series of equal length
- a list of mixed vectors and Series of equal length (Deprecated, please use `as_polars_df()` instead).

Columns will be named as of named arguments or alternatively by names of Series or given a placeholder name.

`make_names_unique` If `TRUE` (default), any duplicated names will be prefixed a running number.

`schema` A named list that will be used to convert a variable to a specific DataType. Same as `schema_overrides` of `as_polars_df()`.

Value

DataFrame

See Also

- `as_polars_df()`

Examples

```
pl$DataFrame(
  a = c(1, 2, 3, 4, 5),
  b = 1:5,
  c = letters[1:5],
  d = list(1:1, 1:2, 1:3, 1:4, 1:5)
) # directly from vectors
```

---

pl_date *Create a Date expression*

Description

Create a Date expression

Usage

```
pl_date(year, month, day)
```

Arguments

`year` An Expr or something coercible to an Expr, that must return an integer. Strings are parsed as column names. Floats are cast to integers.

`month` An Expr or something coercible to an Expr, that must return an integer between 1 and 12. Strings are parsed as column names. Floats are cast to integers.

`day` An Expr or something coercible to an Expr, that must return an integer between 1 and 31. Strings are parsed as column names. Floats are cast to integers.

Value

An Expr of type Date

See Also

- pl$datetime()
- pl$time()

Examples

```
df = pl$DataFrame(year = 2019:2021, month = 9:11, day = 10:12)

df$with_columns(
  date_from_cols = pl$date("year", "month", "day"),
  date_from_lit = pl$date(2020, 3, 5),
  date_from_mix = pl$date("year", 3, 5)
)

# floats are coerced to integers
df$with_columns(
  date_floats = pl$date(2018.8, 5.3, 1)
)

# if date can't be constructed, it returns null
df$with_columns(
  date_floats = pl$date(pl$lit("abc"), -2, 1)
)
```

---

pl_date_range *Generate a date range*

Description

If both `start` and end are passed as the Date types (not Datetime), and the `interval` granularity is no finer than `"1d"`, the returned range is also of type Date. All other permutations return a Datetime.

Usage

```
pl_date_range(start, end, interval = "1d", ..., closed = "both")
```

Arguments

`start`	Lower bound of the date range. Something that can be coerced to a Date or a Datetime expression. See examples for details.
`end`	Upper bound of the date range. Something that can be coerced to a Date or a Datetime expression. See examples for details.

`interval`	Interval of the range periods, specified as a difftime object or using the Polars duration string language. See the `Polars duration string language` section for details.
`...`	Ignored.
`closed`	Define which sides of the range are closed (inclusive). One of the followings: `"both"` (default), `"left"`, `"right"`, `"none"`.

Value

An Expr of data type Date or Datetime

Polars duration string language

Polars duration string language is a simple representation of durations. It is used in many Polars functions that accept durations.

It has the following format:

- 1ns (1 nanosecond)
- 1us (1 microsecond)
- 1ms (1 millisecond)
- 1s (1 second)
- 1m (1 minute)
- 1h (1 hour)
- 1d (1 calendar day)
- 1w (1 calendar week)
- 1mo (1 calendar month)
- 1q (1 calendar quarter)
- 1y (1 calendar year)

Or combine them: `"3d12h4m25s"` # 3 days, 12 hours, 4 minutes, and 25 seconds

By "calendar day", we mean the corresponding time on the next day (which may not be 24 hours, due to daylight savings). Similarly for "calendar week", "calendar month", "calendar quarter", and "calendar year".

See Also

`pl$date_ranges()` to create a simple Series of data type list(Date) based on column values.

Examples

```
# Using Polars duration string to specify the interval:
pl$date_range(as.Date("2022-01-01"), as.Date("2022-03-01"), "1mo") |>
  as_polars_series("date")

# Using `difftime` object to specify the interval:
pl$date_range(
```

```
  as.Date("1985-01-01"),
  as.Date("1985-01-10"),
  as.difftime(2, units = "days")
) |>
  as_polars_series("date")
```

`pl_date_ranges` *Generate a list containing a date range*

Description

If both `start` and `end` are passed as the Date types (not Datetime), and the `interval` granularity is no finer than `"1d"`, the returned range is also of type Date. All other permutations return a Datetime.

Usage

```
pl_date_ranges(start, end, interval = "1d", ..., closed = "both")
```

Arguments

`start`	Lower bound of the date range. Something that can be coerced to a Date or a Datetime expression. See examples for details.
`end`	Upper bound of the date range. Something that can be coerced to a Date or a Datetime expression. See examples for details.
`interval`	Interval of the range periods, specified as a difftime object or using the Polars duration string language. See the `Polars duration string language` section for details.
`...`	Ignored.
`closed`	Define which sides of the range are closed (inclusive). One of the followings: `"both"` (default), `"left"`, `"right"`, `"none"`.

Value

An Expr of data type List(Date) or List(Datetime)

Polars duration string language

Polars duration string language is a simple representation of durations. It is used in many Polars functions that accept durations.

It has the following format:

- 1ns (1 nanosecond)
- 1us (1 microsecond)
- 1ms (1 millisecond)
- 1s (1 second)

- 1m (1 minute)
- 1h (1 hour)
- 1d (1 calendar day)
- 1w (1 calendar week)
- 1mo (1 calendar month)
- 1q (1 calendar quarter)
- 1y (1 calendar year)

Or combine them: `"3d12h4m25s"` # 3 days, 12 hours, 4 minutes, and 25 seconds

By "calendar day", we mean the corresponding time on the next day (which may not be 24 hours, due to daylight savings). Similarly for "calendar week", "calendar month", "calendar quarter", and "calendar year".

See Also

`pl$date_range()` to create a simple Series of data type Date.

Examples

```
df = pl$DataFrame(
  start = as.Date(c("2022-01-01", "2022-01-02", NA)),
  end = as.Date("2022-01-03")
)

df$with_columns(
  date_range = pl$date_ranges("start", "end"),
  date_range_cr = pl$date_ranges("start", "end", closed = "right")
)

# provide a custom "end" value
df$with_columns(
  date_range_lit = pl$date_ranges("start", pl$lit(as.Date("2022-01-02")))
)
```

`pl_datetime` *Create a Datetime expression*

Description

Create a Datetime expression

Usage

```
pl_datetime(
  year,
  month,
  day,
  hour = NULL,
  minute = NULL,
  second = NULL,
  microsecond = NULL,
  ...,
  time_unit = "us",
  time_zone = NULL,
  ambiguous = "raise"
)
```

Arguments

`year`	An Expr or something coercible to an Expr, that must return an integer. Strings are parsed as column names. Floats are cast to integers.
`month`	An Expr or something coercible to an Expr, that must return an integer between 1 and 12. Strings are parsed as column names. Floats are cast to integers.
`day`	An Expr or something coercible to an Expr, that must return an integer between 1 and 31. Strings are parsed as column names. Floats are cast to integers.
`hour`	An Expr or something coercible to an Expr, that must return an integer between 0 and 23. Strings are parsed as column names. Floats are cast to integers.
`minute`	An Expr or something coercible to an Expr, that must return an integer between 0 and 59. Strings are parsed as column names. Floats are cast to integers.
`second`	An Expr or something coercible to an Expr, that must return an integer between 0 and 59. Strings are parsed as column names. Floats are cast to integers.
`microsecond`	An Expr or something coercible to an Expr, that must return an integer between 0 and 999,999. Strings are parsed as column names. Floats are cast to integers.
`...`	Not used.
`time_unit`	Unit of time. One of `"ms"`, `"us"` (default) or `"ns"`.
`time_zone`	Time zone string, as defined in `OlsonNames()`. Setting `timezone = "*"` will match any timezone, which can be useful to select all Datetime columns containing a timezone.
`ambiguous`	Determine how to deal with ambiguous datetimes: • `"raise"` (default): throw an error • `"earliest"`: use the earliest datetime • `"latest"`: use the latest datetime • `"null"`: return a null value

Value

An Expr of type Datetime

See Also

- pl$date()
- pl$time()

Examples

```
df = pl$DataFrame(
  year = 2019:2021,
  month = 9:11,
  day = 10:12,
  min = 55:57
)

df$with_columns(
  dt_from_cols = pl$datetime("year", "month", "day", minute = "min"),
  dt_from_lit = pl$datetime(2020, 3, 5, hour = 20:22),
  dt_from_mix = pl$datetime("year", 3, 5, second = 1)
)

# floats are coerced to integers
df$with_columns(
  dt_floats = pl$datetime(2018.8, 5.3, 1, second = 2.1)
)

# if datetime can't be constructed, it returns null
df$with_columns(
  dt_floats = pl$datetime(pl$lit("abc"), -2, 1)
)

# can control the time_unit
df$with_columns(
  dt_from_cols = pl$datetime("year", "month", "day", minute = "min", time_unit = "ms")
)
```

---

pl_datetime_range *Generate a datetime range*

Description

Generate a datetime range

Usage

```
pl_datetime_range(
  start,
  end,
  interval = "1d",
  ...,
```

```
  closed = "both",
  time_unit = NULL,
  time_zone = NULL
)
```

Arguments

`start`	Lower bound of the date range. Something that can be coerced to a Date or a Datetime expression. See examples for details.
`end`	Upper bound of the date range. Something that can be coerced to a Date or a Datetime expression. See examples for details.
`interval`	Interval of the range periods, specified as a difftime object or using the Polars duration string language. See the `Polars duration string language` section for details.
`...`	Ignored.
`closed`	Define which sides of the range are closed (inclusive). One of the followings: `"both"` (default), `"left"`, `"right"`, `"none"`.
`time_unit`	Time unit of the resulting the Datetime data type. One of `"ns"`, `"us"`, `"ms"` or `NULL`
`time_zone`	Time zone of the resulting Datetime data type.

Value

An Expr of data type Datetime

Polars duration string language

Polars duration string language is a simple representation of durations. It is used in many Polars functions that accept durations.

It has the following format:

- 1ns (1 nanosecond)
- 1us (1 microsecond)
- 1ms (1 millisecond)
- 1s (1 second)
- 1m (1 minute)
- 1h (1 hour)
- 1d (1 calendar day)
- 1w (1 calendar week)
- 1mo (1 calendar month)
- 1q (1 calendar quarter)
- 1y (1 calendar year)

Or combine them: `"3d12h4m25s"` # 3 days, 12 hours, 4 minutes, and 25 seconds

By "calendar day", we mean the corresponding time on the next day (which may not be 24 hours, due to daylight savings). Similarly for "calendar week", "calendar month", "calendar quarter", and "calendar year".

See Also

pl$datetime_ranges() to create a simple Series of data type list(Datetime) based on column values.

Examples

```
# Using Polars duration string to specify the interval:
pl$datetime_range(as.Date("2022-01-01"), as.Date("2022-03-01"), "1mo") |>
  as_polars_series("datetime")

# Using `difftime` object to specify the interval:
pl$datetime_range(
  as.Date("1985-01-01"),
  as.Date("1985-01-10"),
  as.difftime(1, units = "days") + as.difftime(12, units = "hours")
) |>
  as_polars_series("datetime")

# Specifying a time zone:
pl$datetime_range(
  as.Date("2022-01-01"),
  as.Date("2022-03-01"),
  "1mo",
  time_zone = "America/New_York"
) |>
  as_polars_series("datetime")
```

---

pl_datetime_ranges *Generate a list containing a datetime range*

Description

Generate a list containing a datetime range

Usage

```
pl_datetime_ranges(
  start,
  end,
  interval = "1d",
  ...,
  closed = "both",
  time_unit = NULL,
  time_zone = NULL
)
```

Arguments

`start`	Lower bound of the date range. Something that can be coerced to a Date or a Datetime expression. See examples for details.
`end`	Upper bound of the date range. Something that can be coerced to a Date or a Datetime expression. See examples for details.
`interval`	Interval of the range periods, specified as a difftime object or using the Polars duration string language. See the `Polars duration string language` section for details.
`...`	Ignored.
`closed`	Define which sides of the range are closed (inclusive). One of the followings: `"both"` (default), `"left"`, `"right"`, `"none"`.
`time_unit`	Time unit of the resulting the Datetime data type. One of `"ns"`, `"us"`, `"ms"` or `NULL`
`time_zone`	Time zone of the resulting Datetime data type.

Value

An Expr of data type list(Datetime)

Polars duration string language

Polars duration string language is a simple representation of durations. It is used in many Polars functions that accept durations.

It has the following format:

- 1ns (1 nanosecond)
- 1us (1 microsecond)
- 1ms (1 millisecond)
- 1s (1 second)
- 1m (1 minute)
- 1h (1 hour)
- 1d (1 calendar day)
- 1w (1 calendar week)
- 1mo (1 calendar month)
- 1q (1 calendar quarter)
- 1y (1 calendar year)

Or combine them: `"3d12h4m25s"` # 3 days, 12 hours, 4 minutes, and 25 seconds

By "calendar day", we mean the corresponding time on the next day (which may not be 24 hours, due to daylight savings). Similarly for "calendar week", "calendar month", "calendar quarter", and "calendar year".

See Also

`pl$datetime_range()` to create a simple Series of data type Datetime.

Examples

```
df = pl$DataFrame(
  start = as.POSIXct(c("2022-01-01 10:00", "2022-01-01 11:00", NA)),
  end = as.POSIXct("2022-01-01 12:00")
)

df$with_columns(
  dt_range = pl$datetime_ranges("start", "end", interval = "1h"),
  dt_range_cr = pl$datetime_ranges("start", "end", closed = "right", interval = "1h")
)

# provide a custom "end" value
df$with_columns(
  dt_range_lit = pl$datetime_ranges(
    "start", pl$lit(as.POSIXct("2022-01-01 11:00")),
    interval = "1h"
  )
)
```

---

pl_deserialize_lf *Read a logical plan from a JSON file to construct a LazyFrame*

Description

Read a logical plan from a JSON file to construct a LazyFrame

Usage

```
pl_deserialize_lf(json)
```

Arguments

`json`	A character of the JSON representation of the logical plan.

Value

LazyFrame

See Also

- `<LazyFrame>$serialize()`

Examples

```
lf = pl$LazyFrame(a = 1:3)$sum()
json = lf$serialize()
pl$deserialize_lf(json)$collect()
```

pl_disable_string_cache

Disable the global string cache

Description

Some functions (e.g joins) can be applied on Categorical series only allowed if using the global string cache is enabled. This function disables the string_cache. In general, you should use `pl$with_string_cache()` instead.

Usage

```
pl_disable_string_cache()
```

Value

This doesn't return any value.

See Also

`pl$using_string_cache` `pl$enable_string_cache` `pl$with_string_cache`

Examples

```
pl$enable_string_cache()
pl$using_string_cache()
pl$disable_string_cache()
pl$using_string_cache()
```

pl_dtypes

DataTypes (RPolarsDataType)

Description

`DataType` any polars type (ported so far)

Value

not applicable

Examples

```
print(ls(pl$dtypes))
pl$dtypes$Float64
pl$dtypes$String

pl$List(pl$List(pl$UInt64))

pl$Struct(pl$Field("CityNames", pl$String))

# The function changes type from Int32 to String
# Specifying the output DataType: String solves the problem
as_polars_series(1:4)$map_elements(\(x) letters[x], datatype = pl$dtypes$String)
```

`pl_duration` *Create polars Duration from distinct time components*

Description

Create polars Duration from distinct time components

Usage

```
pl_duration(
  ...,
  weeks = NULL,
  days = NULL,
  hours = NULL,
  minutes = NULL,
  seconds = NULL,
  milliseconds = NULL,
  microseconds = NULL,
  nanoseconds = NULL,
  time_unit = "us"
)
```

Arguments

`...`	Not used.
`weeks`	Number of weeks to add. Expr or something coercible to an Expr. Strings are parsed as column names. *Same thing for argument* `days` *to* `nanoseconds`.
`days`	Number of days to add.
`hours`	Number of hours to add.
`minutes`	Number of minutes to add.
`seconds`	Number of seconds to add.
`milliseconds`	Number of milliseconds to add.

microseconds	Number of microseconds to add.
nanoseconds	Number of nanoseconds to add.
time_unit	Time unit of the resulting expression.

Details

A duration represents a fixed amount of time. For example, `pl$duration(days = 1)` means "exactly 24 hours". By contrast, `Expr$dt$offset_by('1d')` means "1 calendar day", which could sometimes be 23 hours or 25 hours depending on Daylight Savings Time. For non-fixed durations such as "calendar month" or "calendar day", please use `Expr$dt$offset_by()` instead.

Value

Expr

Examples

```
test = pl$DataFrame(
  dt = c(
    "2022-01-01 00:00:00",
    "2022-01-02 00:00:00"
  ),
  add = 1:2
)$with_columns(
  pl$col("dt")$str$strptime(pl$Datetime("us"), format = NULL)
)

test$with_columns(
  (pl$col("dt") + pl$duration(weeks = "add"))$alias("add_weeks"),
  (pl$col("dt") + pl$duration(days = "add"))$alias("add_days"),
  (pl$col("dt") + pl$duration(seconds = "add"))$alias("add_seconds"),
  (pl$col("dt") + pl$duration(milliseconds = "add"))$alias("add_millis"),
  (pl$col("dt") + pl$duration(hours = "add"))$alias("add_hours")
)

# we can also pass an Expr
test$with_columns(
  (pl$col("dt") + pl$duration(weeks = pl$col("add") + 1))$alias("add_weeks"),
  (pl$col("dt") + pl$duration(days = pl$col("add") + 1))$alias("add_days"),
  (pl$col("dt") + pl$duration(seconds = pl$col("add") + 1))$alias("add_seconds"),
  (pl$col("dt") + pl$duration(milliseconds = pl$col("add") + 1))$alias("add_millis"),
  (pl$col("dt") + pl$duration(hours = pl$col("add") + 1))$alias("add_hours")
)
```

---

pl_element *an element in 'eval'-expr*

Description

Alias for an element in evaluated in an `eval` expression.

Usage

```
pl_element()
```

Value

Expr

Examples

```
pl$lit(1:5)$cumulative_eval(pl$element()$first() - pl$element()$last()**2)$to_r()
```

---

pl_enable_string_cache

Enable the global string cache

Description

Some functions (e.g joins) can be applied on Categorical series only allowed if using the global string cache is enabled. This function enables the string_cache. In general, you should use `pl$with_string_cache()` instead.

Usage

```
pl_enable_string_cache()
```

Value

This doesn't return any value.

See Also

`pl$using_string_cache` `pl$disable_string_cache` `pl$with_string_cache`

Examples

```
pl$enable_string_cache()
pl$using_string_cache()
pl$disable_string_cache()
pl$using_string_cache()
```

pl_field — *Quickly select a field in a Struct*

Description

This is syntactic sugar that should mostly be used in `$struct$with_fields()`. `pl$field("x")` is equivalent to `pl$col("my_struct")$struct$field("x")`.

Usage

```
pl_field(name)
```

Arguments

`name`	Name of the field to select.

Value

An Expr with the datatype from the selected field.

Examples

```
df = pl$DataFrame(x = c(1, 4, 9), y = c(4, 9, 16), multiply = c(10, 2, 3))$
  with_columns(coords = pl$struct(c("x", "y")))$
  select("coords", "multiply")

df

df = df$with_columns(
  pl$col("coords")$struct$with_fields(
    pl$field("x")$sqrt(),
    y_mul = pl$field("y") * pl$col("multiply")
  )
)

df

df$unnest("coords")
```

pl_Field_class — *Create Field*

Description

A Field is composed of a name and a data type. Fields are used in Structs-datatypes and Schemas to represent everything of the Series/Column except the raw values.

Usage

```
pl_Field(name, datatype)
```

Arguments

name	Field name
datatype	DataType

Value

An object of class "RPolarsRField" containing its name and its data type.

Active Bindings

datatype:
$datatype returns the data type of the Field.
$datatype = <RPolarsDataType> sets the data type of the Field.

name:
$name returns the name of the Field.
$name = "new_name" sets the name of the Field.

Examples

```
field = pl$Field("city_names", pl$String)

field
field$datatype
field$name

# Set the new data type
field$datatype = pl$Categorical()
field$datatype

# Set the new name
field$name = "CityPoPulations"
field
```

---

pl_first *Get the first value.*

Description

This function has different behavior depending on arguments:

- Missing -> Takes first column of a context.
- Character vectors -> Syntactic sugar for pl$col(...)$first().

Usage

```
pl_first(...)
```

Arguments

...	Characters indicating the column names (passed to `pl$col()`, see `?pl_col` for details), or empty. If empty (default), returns an expression to take the first column of the context instead.

Value

Expr

See Also

- `<Expr>$first()`

Examples

```
df = pl$DataFrame(
  a = c(1, 8, 3),
  b = c(4, 5, 2),
  c = c("foo", "bar", "foo")
)

df$select(pl$first())

df$select(pl$first("b"))

df$select(pl$first(c("a", "c")))
```

---

pl_fold *Accumulate over multiple columns horizontally with an R function*

Description

This allows one to do rowwise operations, starting with an initial value (`acc`). See `pl$reduce()` to do rowwise operations without this initial value.

Usage

```
pl_fold(acc, lambda, exprs)
```

Arguments

acc	an Expr or Into of the initial accumulator.
lambda	R function which takes two polars Series as input and return one.
exprs	Expressions to aggregate over. May also be a wildcard expression.

Value

An expression that will be applied rowwise

Examples

```
df = as_polars_df(mtcars)

# Make the row-wise sum of all columns
df$with_columns(
  pl$fold(
    acc = pl$lit(0),
    lambda = \(acc, x) acc + x,
    exprs = pl$col("*")
  )$alias("mpg_drat_sum_folded")
)
```

---

pl_from_epoch *Convert a Unix timestamp to date(time)*

Description

Depending on the `time_unit` provided, this function will return a different dtype:

- `time_unit = "d"` returns `pl$Date`
- `time_unit = "s"` returns `pl$Datetime("us")` (`pl$Datetime`'s default)
- `time_unit = "ms"` returns `pl$Datetime("ms")`
- `time_unit = "us"` returns `pl$Datetime("us")`
- `time_unit = "ns"` returns `pl$Datetime("ns")`

Usage

```
pl_from_epoch(column, time_unit = "s")
```

Arguments

`column`	An Expr from which integers will be parsed. If this is a float column, then the decimal part of the float will be ignored. Character are parsed as column names, but other literal values must be passed to `pl$lit()`.
`time_unit`	One of `"ns"`, `"us"`, `"ms"`, `"s"`, `"d"`

Value

Expr as Date or Datetime depending on the `time_unit`.

Examples

```
# pass an integer column
df = pl$DataFrame(timestamp = c(1666683077, 1666683099))
df$with_columns(
  timestamp_to_datetime = pl$from_epoch(pl$col("timestamp"), time_unit = "s")
)

# pass a literal
pl$from_epoch(pl$lit(c(1666683077, 1666683099)), time_unit = "s")$to_series()

# use different time_unit
df = pl$DataFrame(timestamp = c(12345, 12346))
df$with_columns(
  timestamp_to_date = pl$from_epoch(pl$col("timestamp"), time_unit = "d")
)
```

`pl_head` *Get the first* `n` *rows.*

Description

This function is syntactic sugar for `pl$col(...)$head(n)`.

Usage

```
pl_head(..., n = 10)
```

Arguments

`...`	Characters indicating the column names, passed to `pl$col()`. See `?pl_col` for details.
`n`	Number of rows to return.

Value

Expr

See Also

- `<Expr>$head()`

Examples

```
df = pl$DataFrame(
  a = c(1, 8, 3),
  b = c(4, 5, 2),
  c = c("foo", "bar", "foo")
)
```

```
df$select(pl$head("a"))

df$select(pl$head("a", "b", n = 2))
```

`pl_implode` *Aggregate all column values into a list.*

Description

This function is syntactic sugar for `pl$col(...)$implode()`.

Usage

```
pl_implode(...)
```

Arguments

`...`	Characters indicating the column names, passed to `pl$col()`. See `?pl_col` for details.

Value

Expr

Examples

```
as_polars_df(iris)$select(pl$implode("Species"))
```

`pl_int_range` *Generate a range of integers*

Description

Generate a range of integers

Usage

```
pl_int_range(start = 0, end = NULL, step = 1, ..., dtype = pl$Int64)
```

Arguments

`start`	Start of the range (inclusive). Defaults to 0.
`end`	End of the range (exclusive). If `NULL` (default), the value of `start` is used and `start` is set to 0.
`step`	Step size of the range.
`...`	Not used.
`dtype`	Data type of the range.

Value

An Expr with the data type specified in `dtype` (default is `Int64`).

See Also

`pl$int_ranges()` to generate a range of integers for each row of the input columns.

Examples

```
pl$int_range(0, 3) |>
  as_polars_series()

# "end" can be omitted for shorter syntax
pl$int_range(3) |>
  as_polars_series()

# custom data type
pl$int_range(3, dtype = pl$Int16) |>
  as_polars_series()

# one can use pl$int_range() and pl$len() to create an index column
df = pl$DataFrame(a = c(1, 3, 5), b = c(2, 4, 6))
df$select(
  index = pl$int_range(pl$len(), dtype = pl$UInt32),
  pl$all()
)
```

---

pl_int_ranges *Generate a range of integers for each row of the input columns*

Description

Generate a range of integers for each row of the input columns

Usage

```
pl_int_ranges(start = 0, end = NULL, step = 1, ..., dtype = pl$Int64)
```

Arguments

`start`	Start of the range (inclusive). Defaults to 0.
`end`	End of the range (exclusive). If `NULL` (default), the value of `start` is used and `start` is set to 0.
`step`	Step size of the range.
`...`	Not used.
`dtype`	Data type of the range.

Value

An Expr with the data type List(dtype) (with Int64 as default of dtype).

See Also

pl$int_range() to generate a single range of integers.

Examples

```
df = pl$DataFrame(start = c(1, -1), end = c(3, 2))

df$with_columns(int_range = pl$int_ranges("start", "end"))

df$with_columns(int_range = pl$int_ranges("start", "end", dtype = pl$Int16))
```

---

pl_is_schema *check if schema*

Description

check if schema

Usage

```
pl_is_schema(x)
```

Arguments

x	object to test if schema

Value

bool

Examples

```
pl$is_schema(as_polars_df(iris)$schema)
pl$is_schema(list("alice", "bob"))
```

`pl_last` *Get the last value.*

Description

This function has different behavior depending on the input type:

- Missing -> Takes last column of a context.
- Character vectors -> Syntactic sugar for `pl$col(...)$last()`.

Usage

```
pl_last(...)
```

Arguments

`...`	Characters indicating the column names (passed to `pl$col()`, see `?pl_col` for details), or empty. If empty (default), returns an expression to take the last column of the context instead.

Value

Expr

See Also

- `<Expr>$last()`

Examples

```
df = pl$DataFrame(
  a = c(1, 8, 3),
  b = c(4, 5, 2),
  c = c("foo", "bar", "baz")
)

df$select(pl$last())

df$select(pl$last("a"))

df$select(pl$last(c("b", "c")))
```

pl_LazyFrame *Create new LazyFrame*

Description

This is simply a convenience function to create `LazyFrames` in a quick way. It is a wrapper around `pl$DataFrame()$lazy()`. Note that this should only be used for making examples and quick demonstrations.

Usage

```
pl_LazyFrame(...)
```

Arguments

`...`	Anything that is accepted by `pl$DataFrame()`

Value

LazyFrame

Examples

```
pl$LazyFrame(
  a = c(1, 2, 3, 4, 5),
  b = 1:5,
  c = letters[1:5],
  d = list(1:1, 1:2, 1:3, 1:4, 1:5)
) # directly from vectors

# from a list of vectors or data.frame
pl$LazyFrame(list(
  a = c(1, 2, 3, 4, 5),
  b = 1:5,
  c = letters[1:5],
  d = list(1L, 1:2, 1:3, 1:4, 1:5)
))

# custom schema
pl$LazyFrame(
  iris,
  schema = list(Sepal.Length = pl$Float32, Species = pl$String)
)$collect()
```

pl_len — *Return the number of rows in the context.*

Description

This is similar to `COUNT(*)` in SQL.

Usage

```
pl_len()
```

Value

Expression of data type UInt32

See Also

- `<Expr>$count()`

Examples

```
df = pl$DataFrame(
  a = c(1, 2, NA),
  b = c(3, NA, NA),
  c = c("foo", "bar", "foo")
)

df$select(pl$len())
```

pl_lit — *Create a literal value*

Description

Create a literal value

Usage

```
pl_lit(x)
```

Arguments

x	A vector of any length

Details

`pl$lit(NULL)` translates into a polars `null`.

Value

Expr

Examples

```
# values to literal, explicit `pl$lit(42)` implicit `+ 2`
pl$col("some_column") / pl$lit(42) + 2

# vector to literal explicitly via Series and back again
# R vector to expression and back again
pl$select(pl$lit(as_polars_series(1:4)))$to_list()[[1L]]

# r vector to literal and back r vector
pl$lit(1:4)$to_r()

# r vector to literal to dataframe
pl$select(pl$lit(1:4))

# r vector to literal to Series
pl$lit(1:4)$to_series()

# vectors to literal implicitly
(pl$lit(2) + 1:4) / 4:1
```

---

pl_max *Get the maximum value.*

Description

Syntactic sugar for `pl$col(...)$max()`.

Usage

```
pl_max(...)
```

Arguments

...	Characters indicating the column names, passed to `pl$col()`. See `?pl_col` for details.

Value

Expr

See Also

- `<Expr>$max()`
- `pl$max_horizontal()`

Examples

```
df = pl$DataFrame(
  num_1 = c(1, 8, 3),
  num_2 = c(4, 5, 2),
  chr_1 = c("foo", "bar", "foo")
)

df$select(pl$max("num_1"))

# Get the maximum value of multiple columns.
df$select(pl$max(r"(^num_\d+$)"))

df$select(pl$max("num_1", "num_2"))
```

---

pl_max_horizontal *Get the maximum value rowwise*

Description

Get the maximum value rowwise

Usage

```
pl_max_horizontal(...)
```

Arguments

...	Columns to concatenate into a single string column. Accepts expressions. Strings are parsed as column names, other non-expression inputs are parsed as literals.

Value

Expr

Examples

```
df = pl$DataFrame(
  a = NA_real_,
  b = c(2:1, NA_real_, NA_real_),
  c = c(1:2, NA_real_, Inf)
)
df$with_columns(
  pl$max_horizontal("a", "b", "c", 99.9)$alias("max")
)
```

pl_mean — *Get the mean value.*

Description

This function is syntactic sugar for `pl$col(...)$mean()`.

Usage

```
pl_mean(...)
```

Arguments

`...`	Characters indicating the column names, passed to `pl$col()`. See `?pl_col` for details.

Value

Expr

See Also

- `<Expr>$mean()`
- `pl$mean_horizontal()`

Examples

```
df = pl$DataFrame(
  a = c(1, 8, 3),
  b = c(4, 5, 2),
  c = c("foo", "bar", "foo")
)

df$select(pl$mean("a"))

df$select(pl$mean("a", "b"))
```

pl_mean_horizontal — *Compute the mean rowwise*

Description

Compute the mean rowwise

Usage

```
pl_mean_horizontal(...)
```

Arguments

...	Columns to concatenate into a single string column. Accepts expressions. Strings are parsed as column names, other non-expression inputs are parsed as literals.

Value

Expr

Examples

```
df = pl$DataFrame(
  a = c(1, 8, 3, 6, 7),
  b = c(4, 5, NA_real_, Inf, NaN)
)

df$with_columns(
  pl$mean_horizontal("a", "b")$alias("mean"),
  pl$mean_horizontal("a", "b", 5)$alias("mean_with_lit")
)
```

---

pl_median *Get the median value.*

Description

This function is syntactic sugar for `pl$col(...)$median()`.

Usage

```
pl_median(...)
```

Arguments

...	Characters indicating the column names, passed to `pl$col()`. See `?pl_col` for details.

Value

Expr

See Also

- `<Expr>$median()`

Examples

```
df = pl$DataFrame(
  a = c(1, 8, 3),
  b = c(4, 5, 2),
  c = c("foo", "bar", "foo")
)

df$select(pl$median("a"))

df$select(pl$median("a", "b"))
```

`pl_mem_address` *Get Memory Address*

Description

Get underlying mem address a rust object (via ExtPtr). Expert use only.

Usage

```
pl_mem_address(robj)
```

Arguments

`robj`	an R object

Details

Does not give meaningful answers for regular R objects.

Value

String of mem address

Examples

```
pl$mem_address(pl$Series(values = 1:3))
```

pl_min *Get the minimum value.*

Description

Syntactic sugar for `pl$col(...)$min()`.

Usage

```
pl_min(...)
```

Arguments

...	Characters indicating the column names, passed to `pl$col()`. See `?pl_col` for details.

Value

Expr

See Also

- `<Expr>$min()`
- `pl$min_horizontal()`

Examples

```
df = pl$DataFrame(
  num_1 = c(1, 8, 3),
  num_2 = c(4, 5, 2),
  chr_1 = c("foo", "bar", "foo")
)

df$select(pl$min("num_1"))

# Get the minimum value of multiple columns.
df$select(pl$min(r"(^num_\d+$)"))

df$select(pl$min("num_1", "num_2"))
```

pl_min_horizontal *Get the minimum value rowwise*

Description

Get the minimum value rowwise

Usage

```
pl_min_horizontal(...)
```

Arguments

...	Columns to concatenate into a single string column. Accepts expressions. Strings are parsed as column names, other non-expression inputs are parsed as literals.

Value

Expr

Examples

```
df = pl$DataFrame(
  a = NA_real_,
  b = c(2:1, NA_real_, NA_real_),
  c = c(1:2, NA_real_, -Inf)
)
df$with_columns(
  pl$min_horizontal("a", "b", "c", 99.9)$alias("min")
)
```

pl_n_unique *Count unique values.*

Description

This function is syntactic sugar for `pl$col(...)$n_unique()`.

Usage

```
pl_n_unique(...)
```

Arguments

...	Characters indicating the column names, passed to `pl$col()`. See `?pl_col` for details.

Value

Expr

See Also

- <Expr>$n_unique()

Examples

```
df = pl$DataFrame(
  a = c(1, 8, 1),
  b = c(4, 5, 2),
  c = c("foo", "bar", "foo")
)

df$select(pl$n_unique("a"))

df$select(pl$n_unique("b", "c"))
```

---

pl_pl *The complete polars public API.*

Description

pl-object is a environment of all public functions and class constructors. Public functions are not exported as a normal package as it would be huge namespace collision with base:: and other functions. All object-methods are accessed with object$method() via the new class functions.

Having all functions in an namespace is similar to the rust- and python- polars api.

Usage

```
pl
```

Format

An object of class pl_polars_env (inherits from environment) of length 109.

Details

If someone do not particularly like the letter combination pl, they are free to bind the environment to another variable name as simon_says = pl or even do attach(pl)

Value

not applicable

Examples

```
# how to use polars via `pl`
pl$col("colname")$sum() / pl$lit(42L) # expression ~ chain-method / literal-expression

# show all public functions, RPolarsDataTypes, classes and methods
pl$show_all_public_functions()
pl$show_all_public_methods()
```

---

pl_PTime *Store Time in R*

Description

Store Time in R

Usage

```
pl_PTime(x, tu = c("s", "ms", "us", "ns"), format = "%H:%M:%S")
```

Arguments

x	an integer or double vector of n epochs since midnight OR a char vector of char times passed to as.POSIXct converted to seconds.
tu	timeunit either "s","ms","us","ns"
format	a format string passed to as.POSIXct format via ...

Details

PTime should probably be replaced with package nanotime or similar.

base R is missing encoding of Time since midnight "s" "ms", "us" and "ns". The latter "ns" is the standard for the polars Time type.

Use PTime to convert R doubles and integers and use as input to polars functions which needs a time.

Loosely inspired by data.table::ITime which is i32 only. PTime must support polars native timeunit is nanoseconds. The R double(float64) can imitate a i64 ns with full precision within the full range of 24 hours.

PTime does not have a time zone and always prints the time as is no matter local machine time zone.

An essential difference between R and polars is R prints POSIXct/lt without a timezone in local time. Polars prints Datetime without a timezone label as is (GMT). For POSIXct/lt taged with a timexone(tzone) and Datetime with a timezone(tz) the behavior is the same conversion is intuitive.

It appears behavior of R timezones is subject to change a bit in R 4.3.0, see polars unit test test-expr_datetime.R/"pl$date_range Date lazy/eager".

Value

a PTime vector either double or integer, with class "PTime" and attribute "tu" being either "s","ms","us" or "ns"

Examples

```
# make PTime in all time units
pl$PTime(runif(5) * 3600 * 24 * 1E0, tu = "s")
pl$PTime(runif(5) * 3600 * 24 * 1E3, tu = "ms")
pl$PTime(runif(5) * 3600 * 24 * 1E6, tu = "us")
pl$PTime(runif(5) * 3600 * 24 * 1E9, tu = "ns")
pl$PTime("23:59:59")


as_polars_series(pl$PTime(runif(5) * 3600 * 24 * 1E0, tu = "s"))
pl$lit(pl$PTime("23:59:59"))$to_series()

pl$lit(pl$PTime("23:59:59"))$to_r()
```

---

pl_raw_list *Polars raw list*

Description

Create an "rpolars_raw_list", which is an R list where all elements must be an R raw or `NULL`.

Usage

```
pl_raw_list(...)

## S3 method for class 'rpolars_raw_list'
x[index]

## S3 method for class 'rpolars_raw_list'
as.list(x, ...)
```

Arguments

`...`	Elements
`x`	A `rpolars_raw_list` object created with `pl$raw_list()`
`index`	Elements to select

Details

In R, raw can contain a binary sequence of bytes, and the length is the number of bytes. In polars a Series of DataType Binary is more like a vector of vectors of bytes where missing values are allowed, similar to how `NA`s can be present in vectors.

To ensure correct round-trip conversion, r-polars uses an R list where any elements must be raw or `NULL` (encoded as missing), and the S3 class is `c("rpolars_raw_list","list")`.

Value

An R list where any elements must be raw, and the S3 class is `c("rpolars_raw_list","list")`.

Examples

```
# create a rpolars_raw_list
raw_list = pl$raw_list(raw(1), raw(3), charToRaw("alice"), NULL)

# pass it to Series or lit
pl$Series(values = raw_list)
pl$lit(raw_list)

# convert polars bianry Series to rpolars_raw_list
pl$Series(values = raw_list)$to_r()


# NB: a plain list of raws yield a polars Series of DateType [list[Binary]]
# which is not the same
pl$Series(values = list(raw(1), raw(2)))

# to regular list, use as.list or unclass
as.list(raw_list)
# subsetting preserves class
pl$raw_list(NULL, raw(2), raw(3))[1:2]
# to regular list, use as.list or unclass
pl$raw_list(NULL, raw(2), raw(3)) |> as.list()
```

---

pl_read_csv *New DataFrame from CSV*

Description

New DataFrame from CSV

Usage

```
pl_read_csv(
  source,
  ...,
  has_header = TRUE,
  separator = ",",
  comment_prefix = NULL,
  quote_char = "\"",
  skip_rows = 0,
  dtypes = NULL,
  null_values = NULL,
  ignore_errors = FALSE,
  cache = FALSE,
```

```
  infer_schema_length = 100,
  n_rows = NULL,
  encoding = "utf8",
  low_memory = FALSE,
  rechunk = TRUE,
  skip_rows_after_header = 0,
  row_index_name = NULL,
  row_index_offset = 0,
  try_parse_dates = FALSE,
  eol_char = "\n",
  raise_if_empty = TRUE,
  truncate_ragged_lines = FALSE,
  reuse_downloaded = TRUE,
  include_file_paths = NULL
)
```

Arguments

`source` Path to a file or URL. It is possible to provide multiple paths provided that all CSV files have the same schema. It is not possible to provide several URLs.

`...` Ignored.

`has_header` Indicate if the first row of dataset is a header or not.If `FALSE`, column names will be autogenerated in the following format: `"column_x"` `x` being an enumeration over every column in the dataset starting at 1.

`separator` Single byte character to use as separator in the file.

`comment_prefix` A string, which can be up to 5 symbols in length, used to indicate the start of a comment line. For instance, it can be set to # or `//`.

`quote_char` Single byte character used for quoting. Set to `NULL` to turn off special handling and escaping of quotes.

`skip_rows` Start reading after a particular number of rows. The header will be parsed at this offset.

`dtypes` Named list of column names - dtypes or dtype - column names. This list is used while reading to overwrite dtypes. Supported types so far are:

- "Boolean" or "logical" for DataType::Boolean,
- "Categorical" or "factor" for DataType::Categorical,
- "Float32" or "double" for DataType::Float32,
- "Float64" or "float64" for DataType::Float64,
- "Int32" or "integer" for DataType::Int32,
- "Int64" or "integer64" for DataType::Int64,
- "String" or "character" for DataType::String,

`null_values` Values to interpret as `NA` values. Can be:

- a character vector: all values that match one of the values in this vector will be `NA`;
- a named list with column names and null values.

`ignore_errors` Keep reading the file even if some lines yield errors. You can also use `infer_schema_length = 0` to read all columns as UTF8 to check which values might cause an issue.

`cache` Cache the result after reading.

`infer_schema_length` Maximum number of rows to read to infer the column types. If set to 0, all columns will be read as UTF-8. If `NULL`, a full table scan will be done (slow).

`n_rows` Maximum number of rows to read.

`encoding` Either `"utf8"` or `"utf8-lossy"`. Lossy means that invalid UTF8 values are replaced with "?" characters.

`low_memory` Reduce memory usage (will yield a lower performance).

`rechunk` Reallocate to contiguous memory when all chunks / files are parsed.

`skip_rows_after_header` Parse the first row as headers, and then skip this number of rows.

`row_index_name` If not `NULL`, this will insert a row index column with the given name into the DataFrame.

`row_index_offset` Offset to start the row index column (only used if the name is set).

`try_parse_dates` Try to automatically parse dates. Most ISO8601-like formats can be inferred, as well as a handful of others. If this does not succeed, the column remains of data type `pl$String`.

`eol_char` Single byte end of line character (default: `\n`). When encountering a file with Windows line endings (`\r\n`), one can go with the default `\n`. The extra `\r` will be removed when processed.

`raise_if_empty` If `FALSE`, parsing an empty file returns an empty DataFrame or LazyFrame.

`truncate_ragged_lines` Truncate lines that are longer than the schema.

`reuse_downloaded` If `TRUE`(default) and a URL was provided, cache the downloaded files in session for an easy reuse.

`include_file_paths` Include the path of the source file(s) as a column with this name.

Value

DataFrame

pl_read_ipc *Read into a DataFrame from Arrow IPC (Feather v2) file*

Description

Read into a DataFrame from Arrow IPC (Feather v2) file

Usage

```
pl_read_ipc(
  source,
  ...,
  n_rows = NULL,
  memory_map = TRUE,
  row_index_name = NULL,
  row_index_offset = 0L,
  rechunk = FALSE,
  cache = TRUE
)
```

Arguments

source	A single character or a raw vector of Apache Arrow IPC file. You can use globbing with * to scan/read multiple files in the same directory (see examples).
...	Ignored.
n_rows	Maximum number of rows to read.
memory_map	A logical. If TRUE, try to memory map the file. This can greatly improve performance on repeated queries as the OS may cache pages. Only uncompressed Arrow IPC files can be memory mapped.
row_index_name	If not NULL, this will insert a row index column with the given name into the DataFrame.
row_index_offset	Offset to start the row index column (only used if the name is set).
rechunk	In case of reading multiple files via a glob pattern, rechunk the final DataFrame into contiguous memory chunks.
cache	Cache the result after reading.

Value

DataFrame

Examples

```
temp_dir = tempfile()
# Write a hive-style partitioned arrow file dataset
arrow::write_dataset(
  mtcars,
  temp_dir,
  partitioning = c("cyl", "gear"),
  format = "arrow",
  hive_style = TRUE
)
list.files(temp_dir, recursive = TRUE)

# Read the dataset
# Sinse hive-style partitioning is not supported,
# the `cyl` and `gear` columns are not contained in the result
pl$read_ipc(
  file.path(temp_dir, "**/*.arrow")
)

# Read a raw vector
arrow::arrow_table(
  foo = 1:5,
  bar = 6:10,
  ham = letters[1:5]
) |>
  arrow::write_to_raw(format = "file") |>
  pl$read_ipc()
```

---

pl_read_ndjson *New DataFrame from NDJSON*

Description

Read a file from path into a polars DataFrame.

Usage

```
pl_read_ndjson(
  source,
  ...,
  infer_schema_length = 100,
  batch_size = NULL,
  n_rows = NULL,
  low_memory = FALSE,
  rechunk = FALSE,
  row_index_name = NULL,
  row_index_offset = 0,
  ignore_errors = FALSE
)
```

Arguments

- `source` Path to a file or URL. It is possible to provide multiple paths provided that all NDJSON files have the same schema. It is not possible to provide several URLs.
- `...` Ignored.
- `infer_schema_length` Maximum number of rows to read to infer the column types. If set to 0, all columns will be read as UTF-8. If `NULL`, a full table scan will be done (slow).
- `batch_size` Number of rows that will be processed per thread.
- `n_rows` Maximum number of rows to read.
- `low_memory` Reduce memory usage (will yield a lower performance).
- `rechunk` Reallocate to contiguous memory when all chunks / files are parsed.
- `row_index_name` If not `NULL`, this will insert a row index column with the given name into the DataFrame.
- `row_index_offset` Offset to start the row index column (only used if the name is set).
- `ignore_errors` Keep reading the file even if some lines yield errors. You can also use `infer_schema_length = 0` to read all columns as UTF8 to check which values might cause an issue.

Value

A DataFrame

Examples

```
if (require("jsonlite", quietly = TRUE)) {
  ndjson_filename = tempfile()
  jsonlite::stream_out(iris, file(ndjson_filename), verbose = FALSE)
  pl$read_ndjson(ndjson_filename)
}
```

---

pl_read_parquet *Read a parquet file*

Description

Read a parquet file

Usage

```
pl_read_parquet(
  source,
  ...,
  n_rows = NULL,
  row_index_name = NULL,
  row_index_offset = 0L,
```

```
  parallel = c("auto", "columns", "row_groups", "none"),
  hive_partitioning = NULL,
  hive_schema = NULL,
  try_parse_hive_dates = TRUE,
  glob = TRUE,
  schema = NULL,
  rechunk = TRUE,
  low_memory = FALSE,
  storage_options = NULL,
  use_statistics = TRUE,
  cache = TRUE,
  include_file_paths = NULL,
  allow_missing_columns = FALSE
)
```

Arguments

`source` Path to a file. You can use globbing with * to scan/read multiple files in the same directory (see examples).

`...` Ignored.

`n_rows` Maximum number of rows to read.

`row_index_name` If not `NULL`, this will insert a row index column with the given name into the DataFrame.

`row_index_offset` Offset to start the row index column (only used if the name is set).

`parallel` This determines the direction of parallelism. `"auto"` will try to determine the optimal direction. Can be `"auto"`, `"columns"`, `"row_groups"`, `"prefiltered"`, or `"none"`. See 'Details'.

`hive_partitioning` Infer statistics and schema from Hive partitioned URL and use them to prune reads. If `NULL` (default), it is automatically enabled when a single directory is passed, and otherwise disabled.

`hive_schema` A list containing the column names and data types of the columns by which the data is partitioned, e.g. `list(a = pl$String, b = pl$Float32)`. If `NULL` (default), the schema of the Hive partitions is inferred.

`try_parse_hive_dates` Whether to try parsing hive values as date/datetime types.

`glob` Expand path given via globbing rules.

`schema` Specify the datatypes of the columns. The datatypes must match the datatypes in the file(s). If there are extra columns that are not in the file(s), consider also enabling `allow_missing_columns`.

`rechunk` In case of reading multiple files via a glob pattern, rechunk the final DataFrame into contiguous memory chunks.

`low_memory` Reduce memory usage (will yield a lower performance).

`storage_options`
: Experimental. List of options necessary to scan parquet files from different cloud storage providers (GCP, AWS, Azure, HuggingFace). See the 'Details' section.

`use_statistics`
: Use statistics in the parquet file to determine if pages can be skipped from reading.

`cache`
: Cache the result after reading.

`include_file_paths`
: Include the path of the source file(s) as a column with this name.

`allow_missing_columns`
: When reading a list of parquet files, if a column existing in the first file cannot be found in subsequent files, the default behavior is to raise an error. However, if `allow_missing_columns` is set to `TRUE`, a full-NULL column is returned instead of erroring for the files that do not contain the column.

Details

On parallel strategies:

The prefiltered strategy first evaluates the pushed-down predicates in parallel and determines a mask of which rows to read. Then, it parallelizes over both the columns and the row groups while filtering out rows that do not need to be read. This can provide significant speedups for large files (i.e. many row-groups) with a predicate that filters clustered rows or filters heavily. In other cases, prefiltered may slow down the scan compared other strategies.

The prefiltered settings falls back to auto if no predicate is given.

Connecting to cloud providers:

Polars supports scanning parquet files from different cloud providers. The cloud providers currently supported are AWS, GCP, and Azure. The supported keys to pass to the `storage_options` argument can be found here:

- aws
- gcp
- azure

Currently it is impossible to scan public parquet files from GCP without a valid service account. Be sure to always include a service account in the `storage_options` argument.

Scanning from HuggingFace:

It is possible to scan data stored on HuggingFace using a path starting with `hf://`. The `hf://` path format is defined as `hf://BUCKET/REPOSITORY@REVISION/PATH`, where:

- BUCKET is one of datasets or spaces
- REPOSITORY is the location of the repository. this is usually in the format of username/repo_name. A branch can also be optionally specified by appending `@branch`.
- REVISION is the name of the branch (or commit) to use. This is optional and defaults to main if not given.
- PATH is a file or directory path, or a glob pattern from the repository root.

A Hugging Face API key can be passed to access private locations using either of the following methods:

- Passing a token in storage_options to the scan function, e.g. `scan_parquet(..., storage_options = list(token =`
- Setting the HF_TOKEN environment variable, e.g. `Sys.setenv(HF_TOKEN = <your HF token>)`.

Value

DataFrame

Examples

```
# Write a Parquet file than we can then import as DataFrame
temp_file = withr::local_tempfile(fileext = ".parquet")
as_polars_df(mtcars)$write_parquet(temp_file)

pl$read_parquet(temp_file)

# Write a hive-style partitioned parquet dataset
temp_dir = withr::local_tempdir()
as_polars_df(mtcars)$write_parquet(temp_dir, partition_by = c("cyl", "gear"))
list.files(temp_dir, recursive = TRUE)

# If the path is a folder, Polars automatically tries to detect partitions
# and includes them in the output
pl$read_parquet(temp_dir)
```

---

pl_reduce *Accumulate over multiple columns horizontally with an R function*

Description

This allows one to do rowwise operations. See `pl$fold()` to do rowwise operations with an initial value.

Usage

```
pl_reduce(lambda, exprs)
```

Arguments

`lambda`	R function which takes two polars Series as input and return one.
`exprs`	Expressions to aggregate over. May also be a wildcard expression.

Value

An expression that will be applied rowwise

Examples

```
df = as_polars_df(mtcars)

# Make the row-wise sum of all columns
df$with_columns(
  pl$reduce(
    lambda = \(acc, x) acc + x,
    exprs = pl$col("*")
  )$alias("mpg_drat_sum_reduced")
)
```

---

pl_rolling_corr *Rolling correlation*

Description

Calculates the rolling correlation between two columns

Usage

```
pl_rolling_corr(a, b, window_size, min_periods = NULL, ddof = 1)
```

Arguments

a	One column name or Expr or anything convertible Into via `pl$col()`.
b	Another column name or Expr or anything convertible Into via `pl$col()`.
window_size	int The length of the window
min_periods	NULL or int The number of values in the window that should be non-null before computing a result. If NULL, it will be set equal to window size.
ddof	integer Delta Degrees of Freedom: the divisor used in the calculation is N - ddof, where N represents the number of elements. By default ddof is 1.

Value

Expr for the computed rolling correlation

Examples

```
lf = as_polars_lf(data.frame(a = c(1, 8, 3), b = c(4, 5, 2)))
lf$select(pl$rolling_corr("a", "b", window_size = 2))$collect()
```

pl_rolling_cov *Rolling covariance*

Description

Calculates the rolling covariance between two columns

Usage

```
pl_rolling_cov(a, b, window_size, min_periods = NULL, ddof = 1)
```

Arguments

a	One column name or Expr or anything convertible Into via `pl$col()`.
b	Another column name or Expr or anything convertible Into via `pl$col()`.
window_size	int The length of the window
min_periods	NULL or int The number of values in the window that should be non-null before computing a result. If NULL, it will be set equal to window size.
ddof	integer Delta Degrees of Freedom: the divisor used in the calculation is N - ddof, where N represents the number of elements. By default ddof is 1.

Value

Expr for the computed rolling covariance

Examples

```
lf = as_polars_lf(data.frame(a = c(1, 8, 3), b = c(4, 5, 2)))
lf$select(pl$rolling_cov("a", "b", window_size = 2))$collect()
```

pl_scan_csv *New LazyFrame from CSV*

Description

Read a file from path into a polars LazyFrame.

Usage

```
pl_scan_csv(
  source,
  ...,
  has_header = TRUE,
  separator = ",",
  comment_prefix = NULL,
  quote_char = "\"",
  skip_rows = 0,
  dtypes = NULL,
  null_values = NULL,
  ignore_errors = FALSE,
  cache = FALSE,
  infer_schema_length = 100,
  n_rows = NULL,
  encoding = "utf8",
  low_memory = FALSE,
  rechunk = TRUE,
  skip_rows_after_header = 0,
  row_index_name = NULL,
  row_index_offset = 0,
  try_parse_dates = FALSE,
  eol_char = "\n",
  raise_if_empty = TRUE,
  truncate_ragged_lines = FALSE,
  reuse_downloaded = TRUE,
  include_file_paths = NULL
)
```

Arguments

`source`	Path to a file or URL. It is possible to provide multiple paths provided that all CSV files have the same schema. It is not possible to provide several URLs.
`...`	Ignored.
`has_header`	Indicate if the first row of dataset is a header or not.If `FALSE`, column names will be autogenerated in the following format: `"column_x"` `x` being an enumeration over every column in the dataset starting at 1.
`separator`	Single byte character to use as separator in the file.
`comment_prefix`	A string, which can be up to 5 symbols in length, used to indicate the start of a comment line. For instance, it can be set to # or `//`.
`quote_char`	Single byte character used for quoting. Set to `NULL` to turn off special handling and escaping of quotes.
`skip_rows`	Start reading after a particular number of rows. The header will be parsed at this offset.
`dtypes`	Named list of column names - dtypes or dtype - column names. This list is used while reading to overwrite dtypes. Supported types so far are:

- "Boolean" or "logical" for DataType::Boolean,
- "Categorical" or "factor" for DataType::Categorical,
- "Float32" or "double" for DataType::Float32,
- "Float64" or "float64" for DataType::Float64,
- "Int32" or "integer" for DataType::Int32,
- "Int64" or "integer64" for DataType::Int64,
- "String" or "character" for DataType::String,

`null_values` Values to interpret as `NA` values. Can be:

- a character vector: all values that match one of the values in this vector will be `NA`;
- a named list with column names and null values.

`ignore_errors` Keep reading the file even if some lines yield errors. You can also use `infer_schema_length = 0` to read all columns as UTF8 to check which values might cause an issue.

`cache` Cache the result after reading.

`infer_schema_length` Maximum number of rows to read to infer the column types. If set to 0, all columns will be read as UTF-8. If `NULL`, a full table scan will be done (slow).

`n_rows` Maximum number of rows to read.

`encoding` Either `"utf8"` or `"utf8-lossy"`. Lossy means that invalid UTF8 values are replaced with "?" characters.

`low_memory` Reduce memory usage (will yield a lower performance).

`rechunk` Reallocate to contiguous memory when all chunks / files are parsed.

`skip_rows_after_header` Parse the first row as headers, and then skip this number of rows.

`row_index_name` If not `NULL`, this will insert a row index column with the given name into the DataFrame.

`row_index_offset` Offset to start the row index column (only used if the name is set).

`try_parse_dates` Try to automatically parse dates. Most ISO8601-like formats can be inferred, as well as a handful of others. If this does not succeed, the column remains of data type `pl$String`.

`eol_char` Single byte end of line character (default: `\n`). When encountering a file with Windows line endings (`\r\n`), one can go with the default `\n`. The extra `\r` will be removed when processed.

`raise_if_empty` If `FALSE`, parsing an empty file returns an empty DataFrame or LazyFrame.

`truncate_ragged_lines` Truncate lines that are longer than the schema.

`reuse_downloaded` If `TRUE`(default) and a URL was provided, cache the downloaded files in session for an easy reuse.

`include_file_paths` Include the path of the source file(s) as a column with this name.

Value

LazyFrame

Examples

```
my_file = tempfile()
write.csv(iris, my_file)
lazy_frame = pl$scan_csv(my_file)
lazy_frame$collect()
unlink(my_file)
```

---

pl_scan_ipc — *Lazily read from an Arrow IPC (Feather v2) file or multiple files via glob patterns*

Description

This allows the query optimizer to push down predicates and projections to the scan level, thereby potentially reducing memory overhead.

Usage

```
pl_scan_ipc(
  source,
  ...,
  n_rows = NULL,
  memory_map = TRUE,
  row_index_name = NULL,
  row_index_offset = 0L,
  rechunk = FALSE,
  cache = TRUE,
  hive_partitioning = NULL,
  hive_schema = NULL,
  try_parse_hive_dates = TRUE,
  include_file_paths = NULL
)
```

Arguments

source	Path to a file. You can use globbing with * to scan/read multiple files in the same directory (see examples).
...	Ignored.
n_rows	Maximum number of rows to read.
memory_map	A logical. If TRUE, try to memory map the file. This can greatly improve performance on repeated queries as the OS may cache pages. Only uncompressed Arrow IPC files can be memory mapped.

`row_index_name` If not `NULL`, this will insert a row index column with the given name into the DataFrame.

`row_index_offset`
Offset to start the row index column (only used if the name is set).

`rechunk` In case of reading multiple files via a glob pattern, rechunk the final DataFrame into contiguous memory chunks.

`cache` Cache the result after reading.

`hive_partitioning`
Infer statistics and schema from Hive partitioned URL and use them to prune reads. If `NULL` (default), it is automatically enabled when a single directory is passed, and otherwise disabled.

`hive_schema` A list containing the column names and data types of the columns by which the data is partitioned, e.g. `list(a = pl$String, b = pl$Float32)`. If `NULL` (default), the schema of the Hive partitions is inferred.

`try_parse_hive_dates`
Whether to try parsing hive values as date/datetime types.

`include_file_paths`
Character value indicating the column name that will include the path of the source file(s).

Details

Hive-style partitioning is not supported yet.

Value

LazyFrame

Examples

```
temp_dir = tempfile()
# Write a hive-style partitioned arrow file dataset
arrow::write_dataset(
  mtcars,
  temp_dir,
  partitioning = c("cyl", "gear"),
  format = "arrow",
  hive_style = TRUE
)
list.files(temp_dir, recursive = TRUE)

# If the path is a folder, Polars automatically tries to detect partitions
# and includes them in the output
pl$scan_ipc(temp_dir)$collect()

# We can also impose a schema to the partition
pl$scan_ipc(temp_dir, hive_schema = list(cyl = pl$String, gear = pl$Int32))$collect()
```

pl_scan_ndjson *New LazyFrame from NDJSON*

Description

Read a file from path into a polars LazyFrame.

Usage

```
pl_scan_ndjson(
  source,
  ...,
  infer_schema_length = 100,
  batch_size = NULL,
  n_rows = NULL,
  low_memory = FALSE,
  rechunk = FALSE,
  row_index_name = NULL,
  row_index_offset = 0,
  reuse_downloaded = TRUE,
  ignore_errors = FALSE
)
```

Arguments

`source` Path to a file or URL. It is possible to provide multiple paths provided that all NDJSON files have the same schema. It is not possible to provide several URLs.

`...` Ignored.

`infer_schema_length` Maximum number of rows to read to infer the column types. If set to 0, all columns will be read as UTF-8. If `NULL`, a full table scan will be done (slow).

`batch_size` Number of rows that will be processed per thread.

`n_rows` Maximum number of rows to read.

`low_memory` Reduce memory usage (will yield a lower performance).

`rechunk` Reallocate to contiguous memory when all chunks / files are parsed.

`row_index_name` If not `NULL`, this will insert a row index column with the given name into the DataFrame.

`row_index_offset` Offset to start the row index column (only used if the name is set).

`reuse_downloaded` If `TRUE`(default) and a URL was provided, cache the downloaded files in session for an easy reuse.

`ignore_errors` Keep reading the file even if some lines yield errors. You can also use `infer_schema_length = 0` to read all columns as UTF8 to check which values might cause an issue.

Value

A LazyFrame

Examples

```
if (require("jsonlite", quietly = TRUE)) {
  ndjson_filename = tempfile()
  jsonlite::stream_out(iris, file(ndjson_filename), verbose = FALSE)
  pl$scan_ndjson(ndjson_filename)$collect()
}
```

---

pl_scan_parquet *Scan a parquet file*

Description

Scan a parquet file

Usage

```
pl_scan_parquet(
  source,
  ...,
  n_rows = NULL,
  row_index_name = NULL,
  row_index_offset = 0L,
  parallel = c("auto", "columns", "row_groups", "none"),
  hive_partitioning = NULL,
  hive_schema = NULL,
  try_parse_hive_dates = TRUE,
  glob = TRUE,
  schema = NULL,
  rechunk = FALSE,
  low_memory = FALSE,
  storage_options = NULL,
  use_statistics = TRUE,
  cache = TRUE,
  include_file_paths = NULL,
  allow_missing_columns = FALSE
)
```

Arguments

source	Path to a file. You can use globbing with * to scan/read multiple files in the same directory (see examples).
...	Ignored.
n_rows	Maximum number of rows to read.

`row_index_name` If not `NULL`, this will insert a row index column with the given name into the DataFrame.

`row_index_offset`
Offset to start the row index column (only used if the name is set).

`parallel` This determines the direction of parallelism. `"auto"` will try to determine the optimal direction. Can be `"auto"`, `"columns"`, `"row_groups"`, `"prefiltered"`, or `"none"`. See 'Details'.

`hive_partitioning`
Infer statistics and schema from Hive partitioned URL and use them to prune reads. If `NULL` (default), it is automatically enabled when a single directory is passed, and otherwise disabled.

`hive_schema` A list containing the column names and data types of the columns by which the data is partitioned, e.g. `list(a = pl$String, b = pl$Float32)`. If `NULL` (default), the schema of the Hive partitions is inferred.

`try_parse_hive_dates`
Whether to try parsing hive values as date/datetime types.

`glob` Expand path given via globbing rules.

`schema` Specify the datatypes of the columns. The datatypes must match the datatypes in the file(s). If there are extra columns that are not in the file(s), consider also enabling `allow_missing_columns`.

`rechunk` In case of reading multiple files via a glob pattern, rechunk the final DataFrame into contiguous memory chunks.

`low_memory` Reduce memory usage (will yield a lower performance).

`storage_options`
Experimental. List of options necessary to scan parquet files from different cloud storage providers (GCP, AWS, Azure, HuggingFace). See the 'Details' section.

`use_statistics` Use statistics in the parquet file to determine if pages can be skipped from reading.

`cache` Cache the result after reading.

`include_file_paths`
Include the path of the source file(s) as a column with this name.

`allow_missing_columns`
When reading a list of parquet files, if a column existing in the first file cannot be found in subsequent files, the default behavior is to raise an error. However, if `allow_missing_columns` is set to `TRUE`, a full-NULL column is returned instead of erroring for the files that do not contain the column.

Details

On parallel strategies:

The prefiltered strategy first evaluates the pushed-down predicates in parallel and determines a mask of which rows to read. Then, it parallelizes over both the columns and the row groups while filtering out rows that do not need to be read. This can provide significant speedups for large files (i.e. many row-groups) with a predicate that filters clustered rows or filters heavily. In other cases, prefiltered may slow down the scan compared other strategies.

The prefiltered settings falls back to auto if no predicate is given.

Connecting to cloud providers:

Polars supports scanning parquet files from different cloud providers. The cloud providers currently supported are AWS, GCP, and Azure. The supported keys to pass to the `storage_options` argument can be found here:

- aws
- gcp
- azure

Currently it is impossible to scan public parquet files from GCP without a valid service account. Be sure to always include a service account in the `storage_options` argument.

Scanning from HuggingFace:

It is possible to scan data stored on HuggingFace using a path starting with `hf://`. The `hf://` path format is defined as `hf://BUCKET/REPOSITORY@REVISION/PATH`, where:

- BUCKET is one of datasets or spaces
- REPOSITORY is the location of the repository. this is usually in the format of username/repo_name. A branch can also be optionally specified by appending `@branch`.
- REVISION is the name of the branch (or commit) to use. This is optional and defaults to main if not given.
- PATH is a file or directory path, or a glob pattern from the repository root.

A Hugging Face API key can be passed to access private locations using either of the following methods:

- Passing a token in storage_options to the scan function, e.g. `scan_parquet(..., storage_options = list(token =`
- Setting the HF_TOKEN environment variable, e.g. `Sys.setenv(HF_TOKEN = <your HF token>)`.

Value

LazyFrame

Examples

```
# Write a Parquet file than we can then import as DataFrame
temp_file = withr::local_tempfile(fileext = ".parquet")
as_polars_df(mtcars)$write_parquet(temp_file)

pl$scan_parquet(temp_file)$collect()

# Write a hive-style partitioned parquet dataset
temp_dir = withr::local_tempdir()
as_polars_df(mtcars)$write_parquet(temp_dir, partition_by = c("cyl", "gear"))
list.files(temp_dir, recursive = TRUE)

# If the path is a folder, Polars automatically tries to detect partitions
# and includes them in the output
pl$scan_parquet(temp_dir)$collect()
```

pl_select — *Select from an empty DataFrame*

Description

`pl$select(...)` is a shorthand for `pl$DataFrame(list())$select(...)`

Usage

```
pl_select(...)
```

Arguments

`...`	Expressions

Value

a DataFrame

Examples

```
pl$select(
  pl$lit(1:4)$alias("ints"),
  pl$lit(letters[1:4])$alias("letters")
)
```

pl_Series — *Create new Series*

Description

This function is a simple way to convert R vectors to the Series class object. Internally, this function is a simple wrapper of `as_polars_series()`.

Usage

```
pl_Series(
  name = NULL,
  values = NULL,
  dtype = NULL,
  ...,
  strict = TRUE,
  nan_to_null = FALSE
)
```

Arguments

name	A character to use as the name of the Series, or NULL (default). Passed to the name argument in as_polars_series().
values	Object to convert into a polars Series. Passed to the x argument in as_polars_series().
dtype	One of polars data type or NULL. If not NULL, that data type is used to cast the Series created from the vector to a specific data type internally.
...	Ignored.
strict	A logical. If TRUE (default), throw an error if any value does not exactly match the given data type by the dtype argument. If FALSE, values that do not match the data type are cast to that data type or, if casting is not possible, set to null instead. Passed to the strict argument of the $cast() method internally.
nan_to_null	If TRUE, NaN values contained in the Series are replaced to null. Using the $fill_nan() method internally.

Details

Python Polars has a feature that automatically interprets something like polars.Series([1]) as polars.Series(values=[1]) if you specify Array like objects as the first argument. This feature is not available in R Polars, so something like pl$Series(1) will raise an error. You should use pl$Series(values = 1) or as_polars_series(1) instead.

Value

Series

See Also

- as_polars_series()

Examples

```
# Constructing a Series by specifying name and values positionally:
s = pl$Series("a", 1:3)
s

# Notice that the dtype is automatically inferred as a polars Int32:
s$dtype

# Constructing a Series with a specific dtype:
s2 = pl$Series(values = 1:3, name = "a", dtype = pl$Float32)
s2
```

pl_SQLContext *Initialise a new SQLContext*

Description

Create a new SQLContext and register the given LazyFrames.

Usage

```
pl_SQLContext(...)
```

Arguments

...	Name-value pairs of LazyFrame like objects to register.

Value

An SQLContext

Examples

```
ctx = pl$SQLContext(mtcars = mtcars)
ctx
```

pl_std *Get the standard deviation.*

Description

This function is syntactic sugar for `pl$col(...)$std(ddof)`.

Usage

```
pl_std(..., ddof = 1)
```

Arguments

...	Characters indicating the column names, passed to `pl$col()`. See `?pl_col` for details.
ddof	An integer representing "Delta Degrees of Freedom": the divisor used in the calculation is `N - ddof`, where `N` represents the number of elements. By default ddof is `1`.

Value

Expr

See Also

- <Expr>$std()

Examples

```
df = pl$DataFrame(
  a = c(1, 8, 3),
  b = c(4, 5, 2),
  c = c("foo", "bar", "foo")
)

df$select(pl$std("a"))

df$select(pl$std(c("a", "b")))
```

---

pl_struct *Collect columns into a struct column*

Description

Collect columns into a struct column

Usage

```
pl_struct(exprs, schema = NULL)
```

Arguments

exprs	Columns/Expressions to collect into a Struct.
schema	Optional schema named list that explicitly defines the struct field dtypes. Each name must match a column name wrapped in the struct. Can only be used to cast some or all dtypes, not to change the names. If NULL (default), columns datatype are not modified. Columns that do not exist are silently ignored and not included in the final struct.

Details

pl$struct() creates an Expr of DataType Struct().

Compared to the Python implementation, pl$struct() doesn't have the argument eager and always returns an Expr. Use $to_series() to return a Series.

Value

Expr with dtype Struct

Examples

```
# isolated expression to wrap all columns in a struct aliased 'my_struct'
pl$struct(pl$all())$alias("my_struct")

# wrap all column into on column/Series
df = pl$DataFrame(
  int = 1:2,
  str = c("a", "b"),
  bool = c(TRUE, NA),
  list = list(1:2, 3L)
)$select(
  pl$struct(pl$all())$alias("my_struct")
)

print(df)
print(df$schema) # returns a schema, a named list containing one element a Struct named my_struct

# wrap two columns in a struct and provide a schema to set all or some DataTypes by name
e1 = pl$struct(
  pl$col(c("int", "str")),
  schema = list(int = pl$Int64, str = pl$String)
)$alias("my_struct")
# same result as e.g. wrapping the columns in a struct and casting afterwards
e2 = pl$struct(
  list(pl$col("int"), pl$col("str"))
)$cast(
  pl$Struct(int = pl$Int64, str = pl$String)
)$alias("my_struct")

df = pl$DataFrame(
  int = 1:2,
  str = c("a", "b"),
  bool = c(TRUE, NA),
  list = list(1:2, 3L)
)

# verify equality in R
identical(df$select(e1)$to_list(), df$select(e2)$to_list())

df$select(e2)
df$select(e2)$to_data_frame()
```

`pl_sum` *Sum all values.*

Description

Syntactic sugar for `pl$col(...)$sum()`.

Usage

```
pl_sum(...)
```

Arguments

...	Characters indicating the column names, passed to `pl$col()`. See `?pl_col` for details.

Value

Expr

See Also

- `<Expr>$sum()`
- `pl$sum_horizontal()`

Examples

```
df = pl$DataFrame(col_a = 1:2, col_b = 3:4, c = 5:6)

df$select(pl$sum("col_a"))

# Sum multiple columns
df$select(pl$sum("col_a", "col_b"))

df$select(pl$sum("^col_.*$"))
```

---

pl_sum_horizontal *Compute the sum rowwise*

Description

Compute the sum rowwise

Usage

```
pl_sum_horizontal(...)
```

Arguments

...	Columns to concatenate into a single string column. Accepts expressions. Strings are parsed as column names, other non-expression inputs are parsed as literals.

Value

Expr

Examples

```
df = pl$DataFrame(
  a = NA_real_,
  b = c(3:4, NA_real_, NA_real_),
  c = c(1:2, NA_real_, -Inf)
)
df$with_columns(
  pl$sum_horizontal("a", "b", "c", 2)$alias("sum")
)
```

`pl_tail` *Get the last* `n` *rows.*

Description

This function is syntactic sugar for `pl$col(...)$tail(n)`.

Usage

```
pl_tail(..., n = 10)
```

Arguments

`...`	Characters indicating the column names, passed to `pl$col()`. See `?pl_col` for details.
`n`	Number of rows to return.

Value

Expr

See Also

- `<Expr>$tail()`

Examples

```
df = pl$DataFrame(
  a = c(1, 8, 3),
  b = c(4, 5, 2),
  c = c("foo", "bar", "foo")
)

df$select(pl$tail("a"))

df$select(pl$tail("a", "b", n = 2))
```

pl_thread_pool_size *Get the number of threads in the Polars thread pool.*

Description

The threadpool size can be overridden by setting the POLARS_MAX_THREADS environment variable before process start. It cannot be modified once polars is loaded. It is strongly recommended not to override this value as it will be set automatically by the engine.

Usage

```
pl_thread_pool_size()
```

Details

For compatibility with CRAN, the threadpool size is set to 2 by default. To disable this behavior and let the engine determine the threadpool size, one of the following ways can be used:

- Enable the disable_limit_max_threads feature of the library. This can be done by setting the feature flag when installing the package. See the installation vignette (vignette("install", "polars")) for details.
- Set the polars.limit_max_threads option to FALSE with the options() function. Same as setting the POLARS_MAX_THREADS environment variable, this option must be set before loading the package.

Value

The number of threads

Examples

```
pl$thread_pool_size()
```

pl_time *Create a Time expression*

Description

Create a Time expression

Usage

```
pl_time(hour = NULL, minute = NULL, second = NULL, microsecond = NULL)
```

Arguments

hour	An Expr or something coercible to an Expr, that must return an integer between 0 and 23. Strings are parsed as column names. Floats are cast to integers.
minute	An Expr or something coercible to an Expr, that must return an integer between 0 and 59. Strings are parsed as column names. Floats are cast to integers.
second	An Expr or something coercible to an Expr, that must return an integer between 0 and 59. Strings are parsed as column names. Floats are cast to integers.
microsecond	An Expr or something coercible to an Expr, that must return an integer between 0 and 999,999. Strings are parsed as column names. Floats are cast to integers.

Value

An Expr of type Time

See Also

- pl$datetime()
- pl$date()

Examples

```
df = pl$DataFrame(hour = 19:21, min = 9:11, sec = 10:12, micro = 1)

df$with_columns(
  time_from_cols = pl$time("hour", "min", "sec", "micro"),
  time_from_lit = pl$time(12, 3, 5),
  time_from_mix = pl$time("hour", 3, 5)
)

# floats are coerced to integers
df$with_columns(
  time_floats = pl$time(12.5, 5.3, 1)
)

# if time can't be constructed, it returns null
df$with_columns(
  time_floats = pl$time(pl$lit("abc"), -2, 1)
)
```

---

pl_using_string_cache *Check if the global string cache is enabled*

Description

This function simply checks if the global string cache is active.

Usage

```
pl_using_string_cache()
```

Value

A logical value

See Also

pl$with_string_cache pl$enable_enable_cache

Examples

```
pl$enable_string_cache()
pl$using_string_cache()
pl$disable_string_cache()
pl$using_string_cache()
```

---

pl_var *Get the variance.*

Description

This function is syntactic sugar for `pl$col(...)$var(ddof)`.

Usage

```
pl_var(..., ddof = 1)
```

Arguments

`...`	Characters indicating the column names, passed to `pl$col()`. See `?pl_col` for details.
`ddof`	An integer representing "Delta Degrees of Freedom": the divisor used in the calculation is `N - ddof`, where `N` represents the number of elements. By default ddof is `1`.

Value

Expr

See Also

- `<Expr>$var()`

Examples

```
df = pl$DataFrame(
  a = c(1, 8, 3),
  b = c(4, 5, 2),
  c = c("foo", "bar", "foo")
)

df$select(pl$var("a"))

df$select(pl$var("a", "b"))
```

`pl_with_string_cache` *Evaluate one or several expressions with global string cache*

Description

This function only temporarily enables the global string cache.

Usage

```
pl_with_string_cache(expr)
```

Arguments

`expr`	An Expr to evaluate while the string cache is enabled.

Value

return value of expression

See Also

`pl$using_string_cache` `pl$enable_enable_cache`

Examples

```
# activate string cache temporarily when constructing two DataFrame's
pl$with_string_cache({
  df1 = as_polars_df(head(iris, 2))
  df2 = as_polars_df(tail(iris, 2))
})
pl$concat(list(df1, df2))
```

polars_class_object *Any polars class object is made of this*

Description

One SEXP of Rtype: "externalptr" + a class attribute

Details

- `object$method()` calls are facilitated by a `$.ClassName`- s3method see 'R/after-wrappers.R'
- Code completion is facilitated by `.DollarNames.ClassName`-s3method see e.g. 'R/dataframe__frame.R'
- Implementation of property-methods as DataFrame_columns() and syntax checking is an extension to `$.ClassName` See function macro_add_syntax_check_to_class().

Value

not applicable

Examples

```
# all a polars object is only made of:
some_polars_object = as_polars_df(iris)
str(some_polars_object) # External Pointer tagged with a class attribute.

# All state is stored on rust side.

# The single exception from the rule is class "GroupBy", where objects also have
# two private attributes "groupby_input" and "maintain_order".
str(as_polars_df(iris)$group_by("Species"))
```

polars_code_completion_activate *Polars code completion*

Description

Polars code completion

Usage

```
polars_code_completion_activate(
  mode = c("auto", "rstudio", "native"),
  verbose = TRUE
)

polars_code_completion_deactivate()
```

Arguments

mode	One of "auto", "rstudio", or "native". Automatic mode picks "rstudio" if .Platform$GUI is "RStudio". "native" registers a custom line buffer completer with utils:::rc.getOption("custom.completer"). "rstudio" modifies RStudio code internal .DollarNames and function args completion, as the IDE does not behave well with utils:::rc.getOption("custom.completer").
verbose	Print message of what mode is started.

Details

Polars code completion has one implementation for a native terminal via utils:::rc.getOption("custom.completer") and one for Rstudio by intercepting Rstudio internal functions .rs.getCompletionsFunction & .rs.getCompletionsDollar in the loaded session environment tools:rstudio. Therefore, any error or slowness in the completion is likely to come from r-polars implementation.

Either completers will evaluate the full line-buffer to decide what methods are available. Pressing tab will literally evaluate left-hand-side with any following side. This works swiftly for the polars lazy API, but it can take some time for the eager API depending on the size of the data and of the query.

Examples

```
if (interactive()) {
  # activate completion
  polars_code_completion_activate()

  # method / property completion for chained expressions
  # add a $ and press tab to see methods of LazyFrame
  pl$LazyFrame(iris)

  # Arg + column-name completion
  # press tab inside group_by() to see args and/or column names.
  pl$LazyFrame(iris)$group_by()

  # deactivate like this or restart R session
  polars_code_completion_deactivate()
}
```

---

polars_duration_string

The Polars duration string language

Description

The Polars duration string language

Polars duration string language

Polars duration string language is a simple representation of durations. It is used in many Polars functions that accept durations.

It has the following format:

- 1ns (1 nanosecond)
- 1us (1 microsecond)
- 1ms (1 millisecond)
- 1s (1 second)
- 1m (1 minute)
- 1h (1 hour)
- 1d (1 calendar day)
- 1w (1 calendar week)
- 1mo (1 calendar month)
- 1q (1 calendar quarter)
- 1y (1 calendar year)

Or combine them: `"3d12h4m25s"` # 3 days, 12 hours, 4 minutes, and 25 seconds

By "calendar day", we mean the corresponding time on the next day (which may not be 24 hours, due to daylight savings). Similarly for "calendar week", "calendar month", "calendar quarter", and "calendar year".

---

polars_envvars *Get polars environment variables*

Description

Get polars environment variables

Usage

```
polars_envvars()
```

Details

The following envvars are available (in alphabetical order, with the default value in parenthesis):

- `POLARS_FMT_MAX_COLS` (`5`): Set the number of columns that are visible when displaying tables. If negative, all columns are displayed.
- `POLARS_FMT_MAX_ROWS` (`8`): Set the number of rows that are visible when displaying tables. If negative, all rows are displayed. This applies to both `DataFrame` and `Series`.
- `POLARS_FMT_STR_LEN` (`32`): Maximum number of characters to display;

- POLARS_FMT_TABLE_CELL_ALIGNMENT ("LEFT"): set the table cell alignment. Can be "LEFT", "CENTER", "RIGHT";
- POLARS_FMT_TABLE_CELL_LIST_LEN (3): Maximum number of elements of list variables to display;
- POLARS_FMT_TABLE_CELL_NUMERIC_ALIGNMENT ("LEFT"): Set the table cell alignment for numeric columns. Can be "LEFT", "CENTER", "RIGHT";
- POLARS_FMT_TABLE_DATAFRAME_SHAPE_BELOW ("0"): print the DataFrame shape information below the data when displaying tables. Can be "0" or "1".
- POLARS_FMT_TABLE_FORMATTING ("UTF8_FULL_CONDENSED"): Set table formatting style. Possible values:
  - "ASCII_FULL": ASCII, with all borders and lines, including row dividers.
  - "ASCII_FULL_CONDENSED": Same as ASCII_FULL, but with dense row spacing.
  - "ASCII_NO_BORDERS": ASCII, no borders.
  - "ASCII_BORDERS_ONLY": ASCII, borders only.
  - "ASCII_BORDERS_ONLY_CONDENSED": ASCII, borders only, dense row spacing.
  - "ASCII_HORIZONTAL_ONLY": ASCII, horizontal lines only.
  - "ASCII_MARKDOWN": ASCII, Markdown compatible.
  - "UTF8_FULL": UTF8, with all borders and lines, including row dividers.
  - "UTF8_FULL_CONDENSED": Same as UTF8_FULL, but with dense row spacing.
  - "UTF8_NO_BORDERS": UTF8, no borders.
  - "UTF8_BORDERS_ONLY": UTF8, borders only.
  - "UTF8_HORIZONTAL_ONLY": UTF8, horizontal lines only.
  - "NOTHING": No borders or other lines.
- POLARS_FMT_TABLE_HIDE_COLUMN_DATA_TYPES ("0"): Hide table column data types (i64, f64, str etc.). Can be "0" or "1".
- POLARS_FMT_TABLE_HIDE_COLUMN_NAMES ("0"): Hide table column names. Can be "0" or "1".
- POLARS_FMT_TABLE_HIDE_COLUMN_SEPARATOR ("0"): Hide the "---" separator between the column names and column types. Can be "0" or "1".
- POLARS_FMT_TABLE_HIDE_DATAFRAME_SHAPE_INFORMATION ("0"): Hide the DataFrame shape information when displaying tables. Can be "0" or "1".
- POLARS_FMT_TABLE_INLINE_COLUMN_DATA_TYPE ("0"): Moves the data type inline with the column name (to the right, in parentheses). Can be "0" or "1".
- POLARS_FMT_TABLE_ROUNDED_CORNERS ("0"): Apply rounded corners to UTF8-styled tables (only applies to UTF8 formats).
- POLARS_MAX_THREADS (<variable>): Maximum number of threads used to initialize the thread pool. The thread pool is locked once polars is loaded, so this envvar must be set before loading the package.
- POLARS_STREAMING_CHUNK_SIZE (<variable>): Chunk size used in the streaming engine. Integer larger than 1. By default, the chunk size is determined by the schema and size of the thread pool. For some datasets (esp. when you have large string elements) this can be too optimistic and lead to Out of Memory errors.

- POLARS_TABLE_WIDTH (<variable>): Set the maximum width of a table in characters.
- POLARS_VERBOSE ("0"): Enable additional verbose/debug logging.
- POLARS_WARN_UNSTABLE ("0"): Issue a warning when unstable functionality is used. Enabling this setting may help avoid functionality that is still evolving, potentially reducing maintenance burden from API changes and bugs. Can be "0" or "1".

The following configuration options are present in the Python API but currently cannot be changed in R: decimal separator, thousands separator, float precision, float formatting, trimming decimal zeros.

Value

polars_envvars() returns a named list where the names are the names of environment variables and values are their values.

Examples

```
polars_envvars()

pl$DataFrame(x = "This is a very very very long sentence.")

Sys.setenv(POLARS_FMT_STR_LEN = 50)
pl$DataFrame(x = "This is a very very very long sentence.")

# back to default
Sys.setenv(POLARS_FMT_STR_LEN = 32)
```

---

polars_info *Report information of the package*

Description

This function reports the following information:

- Package versions (the Polars R package version and the dependent Rust Polars crate version)
- Number of threads used by Polars
- Rust feature flags (See vignette("install", "polars") for details)
- Code completion mode: either "deactivated", "rstudio", or "native". See polars_code_completion_activate(

Usage

```
polars_info()
```

Value

A list with information of the package

Examples

```
polars_info()

polars_info()$versions

polars_info()$features$nightly
```

---

polars_options *Get and reset polars options*

Description

polars_options() returns a list of options for polars. Options can be set with options(). Note that **options must be prefixed with "polars."**, e.g to modify the option strictly_immutable you need to pass options(polars.strictly_immutable =). See below for a description of all options.

polars_options_reset() brings all polars options back to their default value.

Usage

```
polars_options()

polars_options_reset()
```

Details

The following options are available (in alphabetical order, with the default value in parenthesis):

- debug_polars (FALSE): Print additional information to debug Polars.
- do_not_repeat_call (FALSE): Do not print the call causing the error in error messages. The default is to show them.
- int64_conversion ("double"): How should Int64 values be handled when converting a polars object to R?
  - "double" converts the integer values to double.
  - "bit64" uses bit64::as.integer64() to do the conversion (requires the package bit64 to be attached).
  - "string" converts Int64 values to character.
- limit_max_threads (!polars_info()$features$disable_limit_max_threads): See ?pl_thread_pool_size for details. This option should be set before the package is loaded.
- maintain_order (FALSE): Default for the maintain_order argument in <LazyFrame>$group_by() and <DataFrame>$group_by().
- no_messages (FALSE): Hide messages.
- rpool_cap: The maximum number of R sessions that can be used to process R code in the background. See the section "About pool options" below.
- strictly_immutable (TRUE): Keep polars strictly immutable. Polars/arrow is in general pro "immutable objects". Immutability is also classic in R. To mimic the Python-polars API, set this to FALSE.

Value

polars_options() returns a named list where the names are option names and values are option values.

polars_options_reset() doesn't return anything.

About pool options

polars_options()$rpool_active indicates the number of R sessions already spawned in pool. polars_options()$rpool_cap indicates the maximum number of new R sessions that can be spawned. Anytime a polars thread worker needs a background R session specifically to run R code embedded in a query via $map_batches(..., in_background = TRUE) or $map_elements(..., in_background = TRUE), it will obtain any R session idling in rpool, or spawn a new R session (process) and add it to the rpool if rpool_cap is not already reached. If rpool_cap is already reached, the thread worker will sleep until an R session is idling.

Background R sessions communicate via polars arrow IPC (series/vectors) or R serialize + shared memory buffers via the rust crate ipc-channel. Multi-process communication has overhead because all data must be serialized/de-serialized and sent via buffers. Using multiple R sessions will likely only give a speed-up in a low io - high cpu scenario. Native polars query syntax runs in threads and have no overhead.

Examples

```
options(polars.maintain_order = TRUE, polars.strictly_immutable = FALSE)
polars_options()

# option checks are run when calling polars_options(), not when setting
# options
options(polars.maintain_order = 42, polars.int64_conversion = "foobar")
tryCatch(
  polars_options(),
  error = function(e) print(e)
)

# reset options to their default value
polars_options_reset()
```

---

print.RPolarsSeries *Print values*

Description

Print values

Usage

```
## S3 method for class 'RPolarsSeries'
print(x, ...)
```

Arguments

x	A Polars Series
...	Not used

RollingGroupBy_agg *Aggregate over a RollingGroupBy*

Description

Aggregate a DataFrame over a rolling window created with `$rolling()`.

Usage

```
RollingGroupBy_agg(...)
```

Arguments

...	Exprs to aggregate over. Those can also be passed wrapped in a list, e.g `$agg(list(e1,e2,e3))`.

Value

An aggregated DataFrame

Examples

```
df = pl$DataFrame(
 dt = c("2020-01-01", "2020-01-01", "2020-01-01", "2020-01-02", "2020-01-03", "2020-01-08"),
  a = c(3, 7, 5, 9, 2, 1)
)$with_columns(
  pl$col("dt")$str$strptime(pl$Date, format = NULL)$set_sorted()
)

df$rolling(index_column = "dt", period = "2d")$agg(
  pl$col("a"),
  pl$sum("a")$alias("sum_a"),
  pl$min("a")$alias("min_a"),
  pl$max("a")$alias("max_a")
)
```

RollingGroupBy_class *Operations on Polars DataFrame grouped by rolling windows*

Description

This class comes from <DataFrame>$rolling().

Examples

```
df = pl$DataFrame(
 dt = c("2020-01-01", "2020-01-01", "2020-01-01", "2020-01-02", "2020-01-03", "2020-01-08"),
  a = c(3, 7, 5, 9, 2, 1)
)$with_columns(
  pl$col("dt")$str$strptime(pl$Date, format = NULL)$set_sorted()
)

df$rolling(index_column = "dt", period = "2d")
```

RollingGroupBy_ungroup *Ungroup a RollingGroupBy object*

Description

Revert the $rolling() operation. Doing <DataFrame>$rolling(...)$ungroup() returns the original DataFrame.

Usage

```
RollingGroupBy_ungroup()
```

Value

DataFrame

Examples

```
df = pl$DataFrame(
 dt = c("2020-01-01", "2020-01-01", "2020-01-01", "2020-01-02", "2020-01-03", "2020-01-08"),
  a = c(3, 7, 5, 9, 2, 1)
)$with_columns(
  pl$col("dt")$str$strptime(pl$Date, format = NULL)$set_sorted()
)

df$rolling(index_column = "dt", period = "2d")$ungroup()
```

row.names.RPolarsDataFrame *Get the row names*

Description

Get the row names

Usage

```
## S3 method for class 'RPolarsDataFrame'
row.names(x)
```

Arguments

x	A Polars DataFrame

RThreadHandle_class *The RPolarsRThreadHandle class*

Description

A handle to some polars query running in a background thread.

Details

`<LazyFrame>$collect_in_background()` will execute a polars query detached from the R session and return an `RPolarsRThreadHandle` immediately. This `RPolarsRThreadHandle`-class has the methods `is_finished()` and `join()`.

NOTICE

The background thread cannot use the main R session, but can access the pool of extra R sessions to process R code embedded in polars query via `$map_batches(..., in_background = TRUE)` or `$map_elements(background=TRUE)`. Use `options(polars.rpool_cap = XX)` to limit number of parallel R sessions. Starting polars `<LazyFrame>$collect_in_background()` with e.g. some `$map_batches(..., in_background = FALSE)` will raise an Error as the main R session is not available to process the R part of the polars query. Native polars query does not need any R session.

See Also

- `<LazyFrame>$collect_in_background()`
- `<Expr>$map_batches()`
- `<Expr>$map_elements()`

Examples

```
prexpr = pl$col("mpg")$map_batches(\(x) {
  Sys.sleep(.1)
  x * 0.43
}, in_background = TRUE)$alias("kml")
handle = as_polars_lf(mtcars)$with_columns(prexpr)$collect_in_background()
if (!handle$is_finished()) print("not done yet")
df = handle$join() # get result
df
```

RThreadHandle_is_finished *Ask if RThreadHandle is finished?*

Description

Ask if RThreadHandle is finished?

Usage

```
RThreadHandle_is_finished()
```

Value

trinary value: TRUE if finished, FALSE if not, and NULL if the handle was exhausted with <RThreadHandle>$join().

RThreadHandle_join *Join a RThreadHandle*

Description

Join a RThreadHandle

Usage

```
RThreadHandle_join()
```

Details

method <RThreadHandle>$join(): will block until job is done and then return some value or raise an error from the thread. Calling <RThreadHandle>$join() a second time will raise an error because handle is already exhausted.

Value

return value from background thread

See Also

RThreadHandle_class

S3_arithmetic *Arithmetic operators for RPolars objects*

Description

Arithmetic operators for RPolars objects

Usage

```
## S3 method for class 'RPolarsExpr'
x + y

## S3 method for class 'RPolarsExpr'
x - y

## S3 method for class 'RPolarsExpr'
x * y

## S3 method for class 'RPolarsExpr'
x / y

## S3 method for class 'RPolarsExpr'
x ^ y

## S3 method for class 'RPolarsExpr'
x %% y

## S3 method for class 'RPolarsExpr'
x %/% y

## S3 method for class 'RPolarsSeries'
x + y

## S3 method for class 'RPolarsSeries'
x - y

## S3 method for class 'RPolarsSeries'
x * y

## S3 method for class 'RPolarsSeries'
x / y

## S3 method for class 'RPolarsSeries'
```

```
x ^ y

## S3 method for class 'RPolarsSeries'
x %% y

## S3 method for class 'RPolarsSeries'
x %/% y
```

Arguments

x, y	numeric type of RPolars objects or objects that can be coerced such. Only + can take strings.

Value

A Polars object the same type as the input.

See Also

- <Expr>$add()
- <Expr>$sub()
- <Expr>$mul()
- <Expr>$div()
- <Expr>$pow()
- <Expr>$mod()
- <Expr>$floor_div()
- <Series>$add()
- <Series>$sub()
- <Series>$mul()
- <Series>$div()
- <Series>$pow()
- <Series>$mod()
- <Series>$floor_div()

Examples

```
pl$lit(5) + 10
5 + pl$lit(10)
pl$lit(5) + pl$lit(10)
+pl$lit(1)

# This will not raise an error as it is not actually evaluated.
expr = pl$lit(5) + "10"
expr

# Will raise an error as it is evaluated.
```

```
tryCatch(
  expr$to_series(),
  error = function(e) e
)

as_polars_series(5) + 10
+as_polars_series(5)
-as_polars_series(5)
```

Series_add *Add Series*

Description

Method equivalent of addition operator `series + other`.

Usage

```
Series_add(other)
```

Arguments

`other`	Series like object of numeric or string values. Converted to Series by `as_polars_series()` in this method.

Value

Series

See Also

- Arithmetic operators

Examples

```
as_polars_series(1:3)$add(as_polars_series(11:13))
as_polars_series(1:3)$add(11:13)
as_polars_series(1:3)$add(1L)

as_polars_series("a")$add("-z")
```

Series_alias — *Change name of Series*

Description

Change name of Series

Usage

```
Series_alias(name)
```

Arguments

name	New name.

Value

Series

Examples

```
as_polars_series(1:3, name = "alice")$alias("bob")
```

Series_all — *Reduce Boolean Series with ALL*

Description

Reduce Boolean Series with ALL

Usage

```
Series_all()
```

Value

A logical value

Examples

```
as_polars_series(c(TRUE, TRUE, NA))$all()
```

Series_any — *Reduce boolean Series with ANY*

Description

Reduce boolean Series with ANY

Usage

```
Series_any()
```

Value

A logical value

Examples

```
as_polars_series(c(TRUE, FALSE, NA))$any()
```

Series_append — *Append two Series*

Description

Append two Series

Usage

```
Series_append(other, immutable = TRUE)
```

Arguments

other	Series to append.
immutable	Should the other Series be immutable? Default is TRUE.

Details

If immutable = FALSE, the Series object will not behave as immutable. This means that appending to this Series will affect any variable pointing to this memory location. This will break normal scoping rules of R. Setting immutable = FALSE is discouraged as it can have undesirable side effects and cloning Polars Series is a cheap operation.

Value

Series

Examples

```
# default immutable behavior, s_imut and s_imut_copy stay the same
s_imut = as_polars_series(1:3)
s_imut_copy = s_imut
s_new = s_imut$append(as_polars_series(1:3))
s_new

# the original Series didn't change
s_imut
s_imut_copy

# enabling mutable behavior requires setting a global option
withr::with_options(
  list(polars.strictly_immutable = FALSE),
  {
    s_mut = as_polars_series(1:3)
    s_mut_copy = s_mut
    s_new = s_mut$append(as_polars_series(1:3), immutable = FALSE)
    print(s_new)

    # the original Series also changed since it's mutable
    print(s_mut)
    print(s_mut_copy)
  }
)
```

Series_arg_max *Index of max value*

Description

Note that this is 0-indexed.

Usage

```
Series_arg_max()
```

Value

A numeric value

Examples

```
as_polars_series(c(5, 1))$arg_max()
```

Series_arg_min *Index of min value*

Description

Note that this is 0-indexed.

Usage

```
Series_arg_min()
```

Value

A numeric value

Examples

```
as_polars_series(c(5, 1))$arg_min()
```

Series_chunk_lengths *Lengths of Series memory chunks*

Description

Lengths of Series memory chunks

Usage

```
Series_chunk_lengths()
```

Value

Numeric vector. Output length is the number of chunks, and the sum of the output is equal to the length of the full Series.

Examples

```
chunked_series = c(as_polars_series(1:3), as_polars_series(1:10))
chunked_series$chunk_lengths()
```

Series_class *Inner workings of the Series-class*

Description

The `Series`-class is simply two environments of respectively the public and private methods/function calls to the polars rust side. The instantiated `Series`-object is an `externalptr` to a lowlevel rust polars Series object. The pointer address is the only statefullness of the Series object on the R side. Any other state resides on the rust side. The S3 method `.DollarNames.RPolarsSeries` exposes all public `$foobar()`-methods which are callable onto the object. Most methods return another `Series`-class instance or similar which allows for method chaining. This class system in lack of a better name could be called "environment classes" and is the same class system extendr provides, except here there is both a public and private set of methods. For implementation reasons, the private methods are external and must be called from `.pr$Series$methodname()`, also all private methods must take any self as an argument, thus they are pure functions. Having the private methods as pure functions solved/simplified self-referential complications.

Details

Check out the source code in R/Series_frame.R how public methods are derived from private methods. Check out extendr-wrappers.R to see the extendr-auto-generated methods. These are moved to .pr and converted into pure external functions in after-wrappers.R. In zzz.R (named zzz to be last file sourced) the extendr-methods are removed and replaced by any function prefixed `Series_`.

Active bindings

dtype:
`$dtype` returns the data type of the Series.

flags:
`$flags` returns a named list with flag names and their values.

Flags are used internally to avoid doing unnecessary computations, such as sorting a variable that we know is already sorted. The number of flags varies depending on the column type: columns of type `array` and `list` have the flags `SORTED_ASC`, `SORTED_DESC`, and `FAST_EXPLODE`, while other column types only have the former two.

- `SORTED_ASC` is set to `TRUE` when we sort a column in increasing order, so that we can use this information later on to avoid re-sorting it.
- `SORTED_DESC` is similar but applies to sort in decreasing order.

name:
`$name` returns the name of the Series.

shape:
`$shape` returns a numeric vector of length two with the number of length of the Series and width of the Series (always 1).

Expression methods

Series stores most of all Expr methods.

Some of these are stored in sub-namespaces.

arr:
`$arr` stores all array related methods.

bin:
`$bin` stores all binary related methods.

cat:
`$cat` stores all categorical related methods.

dt:
`$dt` stores all temporal related methods.

list:
`$list` stores all list related methods.

str:
`$str` stores all string related methods.

struct:
`$struct` stores all struct related methods and active bindings.

Active bindings specific to Series:

- `$struct$fields`: Returns a character vector of the fields in the struct.

Conversion to R data types considerations

When converting Polars objects, such as DataFrames to R objects, for example via the `as.data.frame()` generic function, each type in the Polars object is converted to an R type. In some cases, an error may occur because the conversion is not appropriate. In particular, there is a high possibility of an error when converting a Datetime type without a time zone. A Datetime type without a time zone in Polars is converted to the POSIXct type in R, which takes into account the time zone in which the R session is running (which can be checked with the `Sys.timezone()` function). In this case, if ambiguous times are included, a conversion error will occur. In such cases, change the session time zone using `Sys.setenv(TZ = "UTC")` and then perform the conversion, or use the `$dt$replace_time_zone()` method on the Datetime type column to explicitly specify the time zone before conversion.

```
# Due to daylight savings, clocks were turned forward 1 hour on Sunday, March 8, 2020, 2:00:00 am
# so this particular date-time doesn't exist
non_existent_time = as_polars_series("2020-03-08 02:00:00")$str$strptime(pl$Datetime(), "%F %T")

withr::with_timezone(
  "America/New_York",
  {
    tryCatch(
      # This causes an error due to the time zone (the `TZ` env var is affected).
```

```
      as.vector(non_existent_time),
      error = function(e) e
    )
  }
)
#> <error: in $to_vector(): in to_r: ComputeError(ErrString("datetime '2020-03-08 02:00:00' is non-exis

withr::with_timezone(
  "America/New_York",
  {
    # This is safe.
    as.vector(non_existent_time$dt$replace_time_zone("UTC"))
  }
)
#> [1] "2020-03-08 02:00:00 UTC"
```

Examples

```
# make a Series
s = as_polars_series(c(1:3, 1L))

# call an active binding
s$shape

# show flags
s$sort()$flags

# use Expr method
s$cos()

# use Expr method in subnamespaces
as_polars_series(list(3:1, 1:2, NULL))$list$first()
as_polars_series(c(1, NA, 2))$str$join("-")

s = pl$date_range(
  as.Date("2024-02-18"), as.Date("2024-02-24"),
  interval = "1d"
)$to_series()
s
s$dt$day()

# Other active bindings in subnamespaces
as_polars_series(data.frame(a = 1:2, b = 3:4))$struct$fields

# show all available methods for Series
pl$show_all_public_methods("RPolarsSeries")
```

Series_clear — *Create an empty or n-row null-filled copy of the Series*

Description

Returns a n-row null-filled Series with an identical schema. n can be greater than the current number of values in the Series.

Usage

```
Series_clear(n = 0)
```

Arguments

n	Number of (null-filled) rows to return in the cleared frame.

Value

A n-value null-filled Series with an identical schema

Examples

```
s = pl$Series(name = "a", values = 1:3)

s$clear()

s$clear(n = 5)
```

Series_clone — *Clone a Series*

Description

This makes a very cheap deep copy/clone of an existing Series. Rarely useful as Series are nearly 100% immutable. Any modification of a Series should lead to a clone anyways, but this can be useful when dealing with attributes (see examples).

Usage

```
Series_clone()
```

Value

Series

Examples

```
df1 = as_polars_series(1:10)

# Make a function to take a Series, add an attribute, and return a Series
give_attr = function(data) {
  attr(data, "created_on") = "2024-01-29"
  data
}
df2 = give_attr(df1)

# Problem: the original Series also gets the attribute while it shouldn't!
attributes(df1)

# Use $clone() inside the function to avoid that
give_attr = function(data) {
  data = data$clone()
  attr(data, "created_on") = "2024-01-29"
  data
}
df1 = as_polars_series(1:10)
df2 = give_attr(df1)

# now, the original Series doesn't get this attribute
attributes(df1)
```

`Series_div` *Divide Series*

Description

Method equivalent of division operator `series / other`.

Usage

```
Series_div(other)
```

Arguments

`other`	Series like object of numeric. Converted to Series by `as_polars_series()` in this method.

Value

Series

See Also

- Arithmetic operators

Examples

```
as_polars_series(1:3)$div(11:13)
as_polars_series(1:3)$div(as_polars_series(11:13))
as_polars_series(1:3)$div(1L)
```

`Series_equals` *Are two Series equal?*

Description

This checks whether two Series are equal in values and in their name.

Usage

```
Series_equals(other, null_equal = FALSE, strict = FALSE)
```

Arguments

`other`	Series to compare with.
`null_equal`	If `TRUE`, consider that null values are equal. Overridden by `strict`.
`strict`	If `TRUE`, do not allow similar DataType comparison. Overrides `null_equal`.

Value

A logical value

Examples

```
as_polars_series(1:4)$equals(as_polars_series(1:4))

# names are different
as_polars_series(1:4, "bob")$equals(as_polars_series(1:4))

# nulls are different by default
as_polars_series(c(1:4, NA))$equals(as_polars_series(c(1:4, NA)))
as_polars_series(c(1:4, NA))$equals(as_polars_series(c(1:4, NA)), null_equal = TRUE)

# datatypes are ignored by default
as_polars_series(1:4)$cast(pl$Int16)$equals(as_polars_series(1:4))
as_polars_series(1:4)$cast(pl$Int16)$equals(as_polars_series(1:4), strict = TRUE)
```

Series_floor_div *Floor Divide Series*

Description

Method equivalent of floor division operator `series %/% other`.

Usage

```
Series_floor_div(other)
```

Arguments

`other`	Series like object of numeric. Converted to Series by `as_polars_series()` in this method.

Value

Series

See Also

- Arithmetic operators

Examples

```
as_polars_series(1:3)$floor_div(11:13)
as_polars_series(1:3)$floor_div(as_polars_series(11:13))
as_polars_series(1:3)$floor_div(1L)
```

Series_is_numeric *Check if the Series is numeric*

Description

This checks whether the Series DataType is in `pl$numeric_dtypes`.

Usage

```
Series_is_numeric()
```

Value

A logical value

Examples

```
as_polars_series(1:4)$is_numeric()
as_polars_series(c("a", "b", "c"))$is_numeric()
pl$numeric_dtypes
```

`Series_is_sorted` *Check if the Series is sorted*

Description

Check if the Series is sorted

Usage

```
Series_is_sorted(descending = FALSE)
```

Arguments

`descending`	Check if the Series is sorted in descending order.

Value

A logical value

See Also

Use `$set_sorted()` to add a "sorted" flag to the Series that could be used for faster operations later on.

Examples

```
as_polars_series(1:4)$sort()$is_sorted()
```

`Series_item` *Return the element at the given index*

Description

Return the element at the given index

Usage

```
Series_item(index = NULL)
```

Arguments

`index`	Index of the item to return.

Value

A value of length 1

Examples

```
s1 = pl$Series(values = 1)

s1$item()

s2 = pl$Series(values = 9:7)

s2$cum_sum()$item(-1)
```

Series_len *Length of a Series*

Description

Length of a Series

Usage

```
Series_len()
```

Value

A numeric value

Examples

```
as_polars_series(1:10)$len()
```

Series_map_elements *Apply every value with an R fun*

Description

About as slow as regular non-vectorized R. Similar to using R sapply on a vector.

Usage

```
Series_map_elements(
  fun,
  datatype = NULL,
  strict_return_type = TRUE,
  allow_fail_eval = FALSE
)
```

Arguments

- `fun` r function, should take a single value as input and return one.
- `datatype` DataType of return value. Default NULL means same as input.
- `strict_return_type` bool, default TRUE: fail on wrong return type, FALSE: convert to polars Null
- `allow_fail_eval` bool, default FALSE: raise R fun error, TRUE: convert to polars Null

Value

Series

Examples

```
s = as_polars_series(letters[1:5], "ltrs")
f = \(x) paste(x, ":", as.integer(charToRaw(x)))
s$map_elements(f, pl$String)

# same as
as_polars_series(sapply(s$to_r(), f), s$name)
```

Series_max *Find the max of a Series*

Description

Find the max of a Series

Usage

```
Series_max()
```

Details

The Dtypes Int8, UInt8, Int16 and UInt16 are cast to Int64 before summing to prevent overflow issues.

Value

A numeric value

Examples

```
as_polars_series(c(1:2, NA, 3, 5))$max() # a NA is dropped always
as_polars_series(c(1:2, NA, 3, NaN, 4, Inf))$max() # NaN carries / poisons
as_polars_series(c(1:2, 3, Inf, 4, -Inf, 5))$max() # Inf-Inf is NaN
```

Series_mean — *Compute the mean of a Series*

Description

Compute the mean of a Series

Usage

```
Series_mean()
```

Details

The Dtypes Int8, UInt8, Int16 and UInt16 are cast to Int64 before summing to prevent overflow issues.

Value

A numeric value

Examples

```
as_polars_series(c(1:2, NA, 3, 5))$mean() # a NA is dropped always
as_polars_series(c(1:2, NA, 3, NaN, 4, Inf))$mean() # NaN carries / poisons
as_polars_series(c(1:2, 3, Inf, 4, -Inf, 5))$mean() # Inf-Inf is NaN
```

Series_median — *Compute the median of a Series*

Description

Compute the median of a Series

Usage

```
Series_median()
```

Details

The Dtypes Int8, UInt8, Int16 and UInt16 are cast to Int64 before summing to prevent overflow issues.

Value

A numeric value

Examples

```
as_polars_series(c(1:2, NA, 3, 5))$median() # a NA is dropped always
as_polars_series(c(1:2, NA, 3, NaN, 4, Inf))$median() # NaN carries / poisons
as_polars_series(c(1:2, 3, Inf, 4, -Inf, 5))$median() # Inf-Inf is NaN
```

Series_min *Find the min of a Series*

Description

Find the min of a Series

Usage

```
Series_min()
```

Details

The Dtypes Int8, UInt8, Int16 and UInt16 are cast to Int64 before summing to prevent overflow issues.

Value

A numeric value

Examples

```
as_polars_series(c(1:2, NA, 3, 5))$min() # a NA is dropped always
as_polars_series(c(1:2, NA, 3, NaN, 4, Inf))$min() # NaN carries / poisons
as_polars_series(c(1:2, 3, Inf, 4, -Inf, 5))$min() # Inf-Inf is NaN
```

Series_mod *Modulo Series*

Description

Method equivalent of modulo operator `series %% other`.

Usage

```
Series_mod(other)
```

Arguments

`other`	Series like object of numeric. Converted to Series by `as_polars_series()` in this method.

Value

Series

See Also

- Arithmetic operators

Examples

```
as_polars_series(1:4)$mod(2L)
as_polars_series(1:3)$mod(as_polars_series(11:13))
as_polars_series(1:3)$mod(1L)
```

Series_mul *Multiply Series*

Description

Method equivalent of multiplication operator `series * other`.

Usage

```
Series_mul(other)
```

Arguments

`other`	Series like object of numeric. Converted to Series by `as_polars_series()` in this method.

Value

Series

See Also

- Arithmetic operators

Examples

```
as_polars_series(1:3)$mul(11:13)
as_polars_series(1:3)$mul(as_polars_series(11:13))
as_polars_series(1:3)$mul(1L)
```

Series_n_chunks *Get the number of chunks that this Series contains.*

Description

Get the number of chunks that this Series contains.

Usage

```
Series_n_chunks()
```

Value

A numeric value

Examples

```
s = as_polars_series(1:3)
s$n_chunks()

# Concatenate Series with rechunk = TRUE
s2 = as_polars_series(4:6)
pl$concat(s, s2, rechunk = TRUE)$n_chunks()

# Concatenate Series with rechunk = FALSE
pl$concat(s, s2, rechunk = FALSE)$n_chunks()
```

Series_n_unique *Count unique values in Series*

Description

Count unique values in Series

Usage

```
Series_n_unique()
```

Value

A numeric value

Examples

```
as_polars_series(c(1, 2, 1, 4, 4, 1, 5))$n_unique()
```

Series_pow — *Power Series*

Description

Method equivalent of power operator `series ^ other`.

Usage

```
Series_pow(exponent)
```

Arguments

`exponent`	Series like object of numeric. Converted to Series by `as_polars_series()` in this method.

Value

Series

See Also

- Arithmetic operators

Examples

```
s = as_polars_series(1:4, name = "foo")

s$pow(3L)
```

Series_print — *Print Series*

Description

Print Series

Usage

```
Series_print()
```

Value

self

Examples

```
as_polars_series(1:3)
```

Series_rename — *Rename a series*

Description

Rename a series

Usage

```
Series_rename(name, in_place = FALSE)
```

Arguments

name	New name.
in_place	Rename in-place, which breaks immutability. If TRUE, you need to run options(polars.strictly_immu = FALSE) before, otherwise it will throw an error.

Value

Series

Examples

```
as_polars_series(1:4, "bob")$rename("alice")
```

Series_rep — *Duplicate and concatenate a series*

Description

Note that this function doesn't exist in Python Polars.

Usage

```
Series_rep(n, rechunk = TRUE)
```

Arguments

n	Number of times to repeat
rechunk	If TRUE (default), reallocate object in memory which can speed up some calculations. If FALSE, the Series will take less space in memory.

Value

Series

Examples

```
as_polars_series(1:2, "bob")$rep(3)
```

`Series_set_sorted` *Set a sorted flag on a Series*

Description

Set a sorted flag on a Series

Usage

```
Series_set_sorted(..., descending = FALSE, in_place = FALSE)
```

Arguments

`...`	Ignored.
`descending`	Sort the columns in descending order.
`in_place`	If `TRUE`, this will set the flag mutably and return `NULL`. Remember to use `options(polars.strictly_imm = FALSE)` before using this parameter, otherwise an error will occur. If `FALSE` (default), it will return a cloned Series with the flag.

Details

Use `$flags` to see the values of the sorted flags.

Value

A Series with a flag

Examples

```
s = as_polars_series(1:4)$set_sorted()
s$flags
```

Series_sort *Sort a Series*

Description

Sort a Series

Usage

```
Series_sort(
  ...,
  descending = FALSE,
  nulls_last = FALSE,
  multithreaded = TRUE,
  in_place = FALSE
)
```

Arguments

`...`	Ignored.
`descending`	A logical. If `TRUE`, sort in descending order.
`nulls_last`	A logical. If `TRUE`, place `null` values last insead of first.
`multithreaded`	A logical. If `TRUE`, sort using multiple threads.
`in_place`	If `TRUE`, this will set the flag mutably and return `NULL`. Remember to use `options(polars.strictly_imm = FALSE)` before using this parameter, otherwise an error will occur. If `FALSE` (default), it will return a cloned Series with the flag.

Value

Series

Examples

```
as_polars_series(c(1.5, NA, 1, NaN, Inf, -Inf))$sort()
as_polars_series(c(1.5, NA, 1, NaN, Inf, -Inf))$sort(nulls_last = TRUE)
```

Series_std — *Compute the standard deviation of a Series*

Description

Compute the standard deviation of a Series

Usage

```
Series_std(ddof = 1)
```

Arguments

ddof	Delta Degrees of Freedom: the divisor used in the calculation is N - ddof, where N represents the number of elements. By default ddof is 1.

Value

A numeric value

Examples

```
as_polars_series(1:10)$std()
```

Series_sub — *Subtract Series*

Description

Method equivalent of subtraction operator `series - other`.

Usage

```
Series_sub(other)
```

Arguments

other	Series like object of numeric. Converted to Series by `as_polars_series()` in this method.

Value

Series

See Also

- Arithmetic operators

Examples

```
as_polars_series(1:3)$sub(11:13)
as_polars_series(1:3)$sub(as_polars_series(11:13))
as_polars_series(1:3)$sub(1L)
1L - as_polars_series(1:3)
as_polars_series(1:3) - 1L
```

Series_sum *Compute the sum of a Series*

Description

Compute the sum of a Series

Usage

```
Series_sum()
```

Details

The Dtypes Int8, UInt8, Int16 and UInt16 are cast to Int64 before summing to prevent overflow issues.

Value

A numeric value

Examples

```
as_polars_series(c(1:2, NA, 3, 5))$sum() # a NA is dropped always
as_polars_series(c(1:2, NA, 3, NaN, 4, Inf))$sum() # NaN poisons the result
as_polars_series(c(1:2, 3, Inf, 4, -Inf, 5))$sum() # Inf-Inf is NaN
```

Series_to_frame *Convert Series to DataFrame*

Description

Convert Series to DataFrame

Usage

```
Series_to_frame()
```

Value

DataFrame

Examples

```
# default will be a DataFrame with empty name
as_polars_series(1:4)$to_frame()

as_polars_series(1:4, "bob")$to_frame()
```

Series_to_lit *Convert a Series to literal*

Description

Convert a Series to literal

Usage

```
Series_to_lit()
```

Value

Expr

Examples

```
as_polars_series(list(1:1, 1:2, 1:3, 1:4))$
  print()$
  to_lit()$
  list$len()$
  sum()$
  cast(pl$dtypes$Int8)$
  to_series()
```

Series_to_r *Convert Series to R vector or list*

Description

`$to_r()` automatically returns an R vector or list based on the Polars DataType. It is possible to force the output type by using `$to_vector()` or `$to_list()`.

Usage

```
Series_to_r(int64_conversion = polars_options()$int64_conversion)

Series_to_vector(int64_conversion = polars_options()$int64_conversion)

Series_to_list(int64_conversion = polars_options()$int64_conversion)
```

Arguments

`int64_conversion`

How should Int64 values be handled when converting a polars object to R?

- `"double"` (default) converts the integer values to double.
- `"bit64"` uses `bit64::as.integer64()` to do the conversion (requires the package `bit64` to be attached).
- `"string"` converts Int64 values to character.

Value

R list or vector

Conversion to R data types considerations

When converting Polars objects, such as DataFrames to R objects, for example via the `as.data.frame()` generic function, each type in the Polars object is converted to an R type. In some cases, an error may occur because the conversion is not appropriate. In particular, there is a high possibility of an error when converting a Datetime type without a time zone. A Datetime type without a time zone in Polars is converted to the POSIXct type in R, which takes into account the time zone in which the R session is running (which can be checked with the `Sys.timezone()` function). In this case, if ambiguous times are included, a conversion error will occur. In such cases, change the session time zone using `Sys.setenv(TZ = "UTC")` and then perform the conversion, or use the `$dt$replace_time_zone()` method on the Datetime type column to explicitly specify the time zone before conversion.

```
# Due to daylight savings, clocks were turned forward 1 hour on Sunday, March 8, 2020, 2:00:00 am
# so this particular date-time doesn't exist
non_existent_time = as_polars_series("2020-03-08 02:00:00")$str$strptime(pl$Datetime(), "%F %T")

withr::with_timezone(
  "America/New_York",
  {
    tryCatch(
     # This causes an error due to the time zone (the `TZ` env var is affected).
      as.vector(non_existent_time),
      error = function(e) e
    )
  }
)
#> <error: in $to_vector(): in to_r: ComputeError(ErrString("datetime '2020-03-08 02:00:00' is non-exis

withr::with_timezone(
  "America/New_York",
  {
    # This is safe.
    as.vector(non_existent_time$dt$replace_time_zone("UTC"))
  }
)
```

```
#> [1] "2020-03-08 02:00:00 UTC"
```

Examples

```
# Series with non-list type
series_vec = as_polars_series(letters[1:3])

series_vec$to_r() # as vector because Series DataType is not list (is String)
series_vec$to_list() # implicit call as.list(), convert to list
series_vec$to_vector() # implicit call unlist(), same as to_r() as already vector


# make a Series with nested lists
series_list = as_polars_series(
  list(
    list(c(1:5, NA_integer_)),
    list(1:2, NA_integer_)
  )
)
series_list

series_list$to_r() # as list because Series DataType is list
series_list$to_list() # implicit call as.list(), same as to_r() as already list
series_list$to_vector() # implicit call unlist(), append into a vector
```

Series_value_counts *Count the occurrences of unique values*

Description

Count the occurrences of unique values

Usage

```
Series_value_counts(
  ...,
  sort = TRUE,
  parallel = FALSE,
  name = "count",
  normalize = FALSE
)
```

Arguments

`...`	Ignored.
`sort`	Ensure the output is sorted from most values to least.
`parallel`	Better to turn this off in the aggregation context, as it can lead to contention.
`name`	Give the resulting count column a specific name. The default is `"count"` if `normalize = FALSE` and `"proportion"` if `normalize = TRUE`.
`normalize`	If `TRUE`, it gives relative frequencies of the unique values instead of their count.

Value

DataFrame

Examples

```
as_polars_series(iris$Species, name = "flower species")$value_counts()
```

Series_var *Compute the variance of a Series*

Description

Compute the variance of a Series

Usage

```
Series_var(ddof = 1)
```

Arguments

ddof	Delta Degrees of Freedom: the divisor used in the calculation is N - ddof, where N represents the number of elements. By default ddof is 1.

Value

A numeric value

Examples

```
as_polars_series(1:10)$var()
```

---

show_all_public_functions *show all public functions / objects*

Description

print any object(function, RPolarsDataType) available via `pl$`.

Usage

```
pl_show_all_public_functions()
```

Examples

```
pl$show_all_public_functions()
```

show_all_public_methods

show all public methods

Description

methods are listed by their Class

Usage

```
pl_show_all_public_methods(class_names = NULL)
```

Arguments

class_names	character vector of polars class names to show, Default NULL is all.

Examples

```
pl$show_all_public_methods()
```

SQLContext_class

Run SQL queries against DataFrame/LazyFrame data.

Description

Run SQL queries against DataFrame/LazyFrame data.

Examples

```
lf = pl$LazyFrame(a = 1:3, b = c("x", NA, "z"))

res = pl$SQLContext(frame = lf)$execute(
  "SELECT b, a*2 AS two_a FROM frame WHERE b IS NOT NULL"
)
res$collect()
```

SQLContext_execute *Execute SQL query against the registered data*

Description

Parse the given SQL query and execute it against the registered frame data.

Usage

```
SQLContext_execute(query)
```

Arguments

query	A character of the SQL query to execute.

Value

A LazyFrame

Examples

```
query = "SELECT * FROM mtcars WHERE cyl = 4"

pl$SQLContext(mtcars = mtcars)$execute(query)
```

SQLContext_register *Register a single data as a table*

Description

Register a single frame as a table, using the given name.

Usage

```
SQLContext_register(name, frame)
```

Arguments

name	A string name to register the frame as.
frame	A LazyFrame like object to register.

Details

If a table with the same name is already registered, it will be overwritten.

Value

Returns the SQLContext object invisibly.

Examples

```
ctx = pl$SQLContext()
ctx$register("mtcars", mtcars)

ctx$execute("SELECT * FROM mtcars LIMIT 5")$collect()
```

SQLContext_register_globals

Register all polars DataFrames/LazyFrames found in the environment

---

Description

Automatically maps variable names to table names.

Usage

```
SQLContext_register_globals(..., envir = parent.frame())
```

Arguments

`...`	Ignored.
`envir`	The environment to search for polars DataFrames/LazyFrames.

Details

If a table with the same name is already registered, it will be overwritten.

Value

Returns the SQLContext object invisibly.

See Also

- `<SQLContext>$register()`
- `<SQLContext>$register_many()`
- `<SQLContext>$unregister()`

Examples

```
df1 = pl$DataFrame(a = 1:3, b = c("x", NA, "z"))
df2 = pl$LazyFrame(a = 2:4, c = c("t", "w", "v"))

# Register frames directly from variables found in the current environment.
ctx = pl$SQLContext()$register_globals()
ctx$tables()

ctx$execute(
  "SELECT a, b, c FROM df1 LEFT JOIN df2 USING (a) ORDER BY a DESC"
)$collect()
```

SQLContext_register_many

Register multiple data as tables

Description

Register multiple frames as tables.

Usage

```
SQLContext_register_many(...)
```

Arguments

...	Name-value pairs of LazyFrame like objects to register.

Details

If a table with the same name is already registered, it will be overwritten.

Value

Returns the SQLContext object invisibly.

Examples

```
ctx = pl$SQLContext()
r_df = mtcars
pl_df = as_polars_df(mtcars)
pl_lf = as_polars_lf(mtcars)

ctx$register_many(r_df = r_df, pl_df = pl_df, pl_lf = pl_lf)

ctx$execute(
  "SELECT * FROM r_df
  UNION ALL
```

```
  SELECT * FROM pl_df
  UNION ALL
  SELECT * FROM pl_lf"
)$collect()
```

SQLContext_tables *List registered tables*

Description

Return a character vector of the registered table names.

Usage

```
SQLContext_tables()
```

Value

A character vector of the registered table names.

Examples

```
ctx = pl$SQLContext()
ctx$tables()
ctx$register("df1", mtcars)
ctx$tables()
ctx$register("df2", mtcars)
ctx$tables()
```

SQLContext_unregister *Unregister tables by name*

Description

Unregister tables by name.

Usage

```
SQLContext_unregister(names)
```

Arguments

names	A character vector of table names to unregister.

Value

Returns the SQLContext object invisibly.

Examples

```
# Initialise a new SQLContext and register the given tables.
ctx = pl$SQLContext(x = mtcars, y = mtcars, z = mtcars)
ctx$tables()

# Unregister some tables.
ctx$unregister(c("x", "y"))
ctx$tables()
```

---

sum.RPolarsDataFrame *Compute the sum*

Description

Compute the sum

Usage

```
## S3 method for class 'RPolarsDataFrame'
sum(x, ...)

## S3 method for class 'RPolarsLazyFrame'
sum(x, ...)

## S3 method for class 'RPolarsSeries'
sum(x, ...)
```

Arguments

x	A DataFrame, LazyFrame, or Series
...	Not used.

unique.RPolarsDataFrame

Drop duplicated rows

Description

Drop duplicated rows

Usage

```
## S3 method for class 'RPolarsDataFrame'
unique(x, incomparables = FALSE, subset = NULL, keep = "first", ...)

## S3 method for class 'RPolarsLazyFrame'
unique(x, incomparables = FALSE, subset = NULL, keep = "first", ...)
```

Arguments

x	A DataFrame or LazyFrame
incomparables	Not used.
subset	Character vector of column names to drop duplicated values from.
keep	Either "first", "last", or "none".
...	Not used.

Examples

```
df = pl$DataFrame(
  x = as.numeric(c(1, 1:5)),
  y = as.numeric(c(1, 1:5)),
  z = as.numeric(c(1, 1, 1:4))
)
unique(df)
```

Index

∗ **DataFrame_new**
LazyFrame_collect, 377
LazyFrame_collect_in_background, 379
∗ **DataFrame**
DataFrame_class, 33
DataFrame_describe, 37
DataFrame_drop_in_place, 39
DataFrame_drop_nulls, 39
DataFrame_dtype_strings, 40
DataFrame_equals, 40
DataFrame_estimated_size, 41
DataFrame_explode, 42
DataFrame_fill_null, 43
DataFrame_filter, 44
DataFrame_first, 45
DataFrame_get_column, 46
DataFrame_join, 53
DataFrame_last, 59
DataFrame_lazy, 59
DataFrame_max, 60
DataFrame_mean, 60
DataFrame_median, 61
DataFrame_min, 61
DataFrame_n_chunks, 62
DataFrame_null_count, 63
DataFrame_pivot, 65
DataFrame_quantile, 67
DataFrame_rechunk, 67
DataFrame_sample, 72
DataFrame_select, 73
DataFrame_sort, 76
DataFrame_std, 78
DataFrame_sum, 79
DataFrame_to_data_frame, 80
DataFrame_to_series, 85
DataFrame_to_struct, 86
DataFrame_transpose, 87
DataFrame_unpivot, 89
DataFrame_var, 91
DataFrame_with_columns, 91
DataFrame_with_row_index, 93
GroupBy_null_count, 363
knit_print.RPolarsDataFrame, 371
LazyFrame_first, 387
pl_select, 505
∗ **ExprDT**
ExprDT_cast_time_unit, 264
ExprDT_day, 266
ExprDT_hour, 268
ExprDT_iso_year, 269
ExprDT_minute, 271
ExprDT_month, 272
ExprDT_offset_by, 273
ExprDT_ordinal_day, 274
ExprDT_quarter, 275
ExprDT_replace_time_zone, 276
ExprDT_strftime, 279
ExprDT_timestamp, 280
ExprDT_week, 287
ExprDT_weekday, 287
ExprDT_with_time_unit, 288
ExprDT_year, 289
∗ **ExprStr**
ExprStr_decode, 324
ExprStr_encode, 324
ExprStr_ends_with, 325
ExprStr_extract, 326
ExprStr_extract_all, 326
ExprStr_json_decode, 332
ExprStr_json_path_match, 332
ExprStr_len_bytes, 333
ExprStr_len_chars, 334
ExprStr_pad_end, 335
ExprStr_pad_start, 335
ExprStr_slice, 340
ExprStr_split_exact, 341
ExprStr_splitn, 342

ExprStr_starts_with, 343
ExprStr_strip_chars, 343
ExprStr_to_lowercase, 352
ExprStr_to_titlecase, 353
ExprStr_to_uppercase, 353
ExprStr_zfill, 354
∗ **Expr_new**
pl_coalesce, 442
pl_concat_list, 445
∗ **Expr**
pl_element, 463
∗ **GroupBy**
GroupBy_first, 359
GroupBy_last, 360
GroupBy_max, 360
GroupBy_mean, 361
GroupBy_median, 362
GroupBy_min, 362
GroupBy_quantile, 363
GroupBy_std, 364
GroupBy_sum, 365
GroupBy_var, 366
∗ **LazyFrame_new**
DataFrame_lazy, 59
∗ **LazyFrame**
LazyFrame_class, 373
LazyFrame_collect, 377
LazyFrame_collect_in_background, 379
LazyFrame_explode, 382
LazyFrame_fetch, 383
LazyFrame_fill_null, 386
LazyFrame_filter, 386
LazyFrame_group_by, 388
LazyFrame_last, 399
LazyFrame_max, 399
LazyFrame_mean, 400
LazyFrame_median, 400
LazyFrame_min, 401
LazyFrame_print, 401
LazyFrame_profile, 402
LazyFrame_reverse, 405
LazyFrame_sort, 418
LazyFrame_std, 421
LazyFrame_sum, 421
LazyFrame_unpivot, 426
LazyFrame_var, 427
∗ **RThreadHandle**
RThreadHandle_is_finished, 526
RThreadHandle_join, 526
∗ **Series**
Series_class, 534
Series_map_elements, 542
∗ **api_object**
polars_class_object, 516
∗ **api**
pl_pl, 483
∗ **docs**
docs_translations, 117
∗ **functions**
pl_is_schema, 472
pl_raw_list, 485
show_all_public_functions, 557
show_all_public_methods, 558
∗ **options**
global_rpool_cap, 357
pl_disable_string_cache, 461
pl_enable_string_cache, 464
pl_using_string_cache, 513
pl_with_string_cache, 515
*.RPolarsExpr *(S3_arithmetic)*, 527
*.RPolarsSeries *(S3_arithmetic)*, 527
+.RPolarsExpr *(S3_arithmetic)*, 527
+.RPolarsSeries *(S3_arithmetic)*, 527
-.RPolarsExpr *(S3_arithmetic)*, 527
-.RPolarsSeries *(S3_arithmetic)*, 527
/.RPolarsExpr *(S3_arithmetic)*, 527
/.RPolarsSeries *(S3_arithmetic)*, 527
<DataFrame>$filter(), *17*
<DataFrame>$get_columns(), *84*
<DataFrame>$group_by(), *64*, *359*, *521*
<DataFrame>$group_by_dynamic(), *72*, *121*
<DataFrame>$head(), *367*
<DataFrame>$lazy(), *373*
<DataFrame>$n_chunks(), *68*
<DataFrame>$partition_by(), *48*
<DataFrame>$rechunk(), *62*
<DataFrame>$rolling(), *51*, *524*
<DataFrame>$select(), *17*
<DataFrame>$tail(), *367*
<DataFrame>$to_data_frame(), *21*
<DataFrame>$to_list(), *46*
<DataFrame>$to_raw_ipc(), *96*
<DataFrame>$write_ipc(), *85*
<Expr>$add(), *528*
<Expr>$approx_n_unique(), *440*

<Expr>$count(), *448*, *475*
<Expr>$div(), *159*, *528*
<Expr>$first(), *467*
<Expr>$floor_div(), *145*, *183*, *528*
<Expr>$head(), *469*
<Expr>$last(), *473*
<Expr>$map_batches(), *379*, *525*
<Expr>$map_elements(), *379*, *525*
<Expr>$max(), *476*
<Expr>$mean(), *478*
<Expr>$median(), *479*
<Expr>$min(), *481*
<Expr>$mod(), *159*, *528*
<Expr>$mul(), *528*
<Expr>$n_unique(), *483*
<Expr>$pow(), *528*
<Expr>$std(), *508*
<Expr>strcontains(), *323*
<Expr>strreplace(), *338*
<Expr>strreplace_all(), *337*
<Expr>strstrptime(), *349*, *351*, *353*
<Expr>strto_date(), *347*
<Expr>strto_datetime(), *347*
<Expr>strto_time(), *347*
<Expr>$sub(), *528*
<Expr>$sum(), *510*
<Expr>$tail(), *511*
<Expr>$var(), *514*
<LazyFrame>$collect(), *373*
<LazyFrame>$collect_in_background(), *525*
<LazyFrame>$fetch(), *367*
<LazyFrame>$filter(), *17*
<LazyFrame>$group_by(), *431*, *521*
<LazyFrame>$group_by_dynamic(), *407*
<LazyFrame>$head(), *367*, *422*
<LazyFrame>$rolling(), *391*
<LazyFrame>$select(), *17*
<LazyFrame>$serialize(), *460*
<LazyFrame>$tail(), *367*
<RPolarsRThreadHandle>$is_finished(), *379*
<RPolarsRThreadHandle>$join(), *379*
<RThreadHandle>$join(), *526*
<SQLContext>$register(), *560*
<SQLContext>$register_many(), *560*
<SQLContext>$unregister(), *560*
<Series>$add(), *528*
<Series>$div(), *528*
<Series>$floor_div(), *528*
<Series>$mod(), *528*
<Series>$mul(), *528*
<Series>$pow(), *528*
<Series>$sub(), *528*
?pl_col, *440*, *448*, *467*, *469*, *470*, *473*, *476*, *478*, *479*, *481*, *482*, *507*, *510*, *511*, *514*
?pl_thread_pool_size, *521*
[.RPolarsDataFrame, 17
[.RPolarsLazyFrame *([.RPolarsDataFrame)*, 17
[.RPolarsSeries *([.RPolarsDataFrame)*, 17
[.rpolars_raw_list *(pl_raw_list)*, 485
$agg(), *359*
$alias(), *317*
$arg_sort(), *441*
$cast(), *506*
$collect(), *27*, *385*, *403*
$collect_in_background(), *378*, *385*, *403*
$convert_time_zone(), *276*
$cut(), *195*
dtreplace_time_zone(), *20*, *22*, *34*, *81*, *83*, *374*, *535*, *555*
$fetch(), *27*, *378*, *392*, *403*
$fill_nan(), *506*
$flags, *550*
$fold(), *315*
$group_by(), *64*
$lazy(), *28*
$list$gather(), *297*
$list$get(), *295*
$map_batches(), *177*, *379*
$map_elements(), *379*, *409*
$meta$eq(), *313*
$meta$neq(), *312*
$meta$output_name(), *316*
$name$keep(), *317*
$prefix(), *319*
$profile(), *378*, *385*
$qcut(), *143*
$replace(), *200*
$replace_strict(), *199*
$set_difference(), *305*
$set_sorted(), *541*
$set_symmetric_difference(), *304*
$sink_ipc(), *378*, *385*, *403*

$sink_parquet(), *378*, *385*, *403*
strcontains(), *330*
strends_with(), *322*, *330*
strfind(), *322*
strstart_with(), *322*, *330*
$struct$with_fields(), *465*
$suffix(), *318*
$with_columns(), *356*
%/%.RPolarsExpr *(S3_arithmetic)*, 527
%/%.RPolarsSeries *(S3_arithmetic)*, 527
%%.RPolarsExpr *(S3_arithmetic)*, 527
%%.RPolarsSeries *(S3_arithmetic)*, 527
^.RPolarsExpr *(S3_arithmetic)*, 527
^.RPolarsSeries *(S3_arithmetic)*, 527

A Polars DataFrame, *23*, *31*
a polars Series, *28*, *30*
abs(n), *52*, *79*
agg *(GroupBy_agg)*, 358
apply *(Series_map_elements)*, 542
arg_unique *(Expr_arg_unique)*, 132
Arithmetic operators, *123*, *145*, *159*, *183*, *185*, *193*, *236*, *529*, *538*, *540*, *546*, *548*, *552*
as.character.RPolarsSeries, 18
as.data.frame(), *20*, *22*, *34*, *81*, *83*, *373*, *535*, *555*
as.data.frame.RPolarsDataFrame, 18
as.data.frame.RPolarsLazyFrame *(as.data.frame.RPolarsDataFrame)*, 18
as.list.rpolars_raw_list *(pl_raw_list)*, 485
as.matrix.RPolarsDataFrame, 21
as.matrix.RPolarsLazyFrame *(as.matrix.RPolarsDataFrame)*, 21
as.vector.RPolarsSeries, 21
as_arrow_table.RPolarsDataFrame, 22
as_nanoarrow_array_stream.RPolarsDataFrame, 23
as_nanoarrow_array_stream.RPolarsSeries *(as_nanoarrow_array_stream.RPolarsDataFrame)*, 23
as_polars_df, 24
as_polars_df(), *21*, *24*, *450*
as_polars_df(x, ...), *28*
as_polars_lf, 28
as_polars_lf(), *28*
as_polars_series, 28
as_polars_series(), *28*, *505*, *506*, *529*, *538*, *540*, *545*, *546*, *548*, *552*
as_polars_series(1), *506*
as_record_batch_reader.RPolarsDataFrame, 30

base::OlsonNames(), *266*, *276*
Binary, *485*

c.RPolarsSeries, 31
cast, *506*
Categorical, *104*, *143*, *195*
ChainedThen *(Expr_when_then_otherwise)*, 244
ChainedThen_otherwise *(Expr_when_then_otherwise)*, 244
ChainedThen_when *(Expr_when_then_otherwise)*, 244
ChainedWhen *(Expr_when_then_otherwise)*, 244
ChainedWhen_then *(Expr_when_then_otherwise)*, 244

data type, *33*, *34*, *373*, *466*, *534*
data type List, *255*
data.frame, *17*, *19*
DataFrame, *17*, *27*, *36*, *52*, *53*, *69*, *77*, *80*, *117*, *119*, *121*, *135*, *189*, *356*, *359*, *366*, *434–437*, *450*, *488*, *489*, *494*, *505*, *518*, *523*, *524*, *558*, *563*, *564*
DataFrame_cast, 32
DataFrame_class, 33
DataFrame_clear, 35
DataFrame_clone, 36
DataFrame_describe, 37
DataFrame_drop, 38
DataFrame_drop_in_place, 39
DataFrame_drop_nulls, 39
DataFrame_dtype_strings, 40
DataFrame_equals, 40
DataFrame_estimated_size, 41
DataFrame_explode, 42
DataFrame_fill_nan, 43
DataFrame_fill_null, 43
DataFrame_filter, 44
DataFrame_first, 45
DataFrame_gather_every, 45
DataFrame_get_column, 46

DataFrame_get_columns, 46
DataFrame_glimpse, 47
DataFrame_group_by, 48
DataFrame_group_by_dynamic, 49
DataFrame_head, 52
DataFrame_item, 53
DataFrame_join, 53
DataFrame_join_asof, 55
DataFrame_join_where, 58
DataFrame_last, 59
DataFrame_lazy, 59
DataFrame_limit *(*DataFrame_head*)*, 52
DataFrame_max, 60
DataFrame_mean, 60
DataFrame_median, 61
DataFrame_min, 61
DataFrame_n_chunks, 62
DataFrame_null_count, 63
DataFrame_partition_by, 64
DataFrame_pivot, 65
DataFrame_quantile, 67
DataFrame_rechunk, 67
DataFrame_rename, 69
DataFrame_reverse, 70
DataFrame_rolling, 70
DataFrame_sample, 72
DataFrame_select, 73
DataFrame_select_seq, 74
DataFrame_shift, 75
DataFrame_slice, 75
DataFrame_sort, 76
DataFrame_sql, 77
DataFrame_std, 78
DataFrame_sum, 79
DataFrame_tail, 79
DataFrame_to_data_frame, 80
DataFrame_to_dummies, 81
DataFrame_to_list, 82
DataFrame_to_raw_ipc, 84
DataFrame_to_series, 85
DataFrame_to_struct, 86
DataFrame_transpose, 87
DataFrame_unique, 88
DataFrame_unnest, 89
DataFrame_unpivot, 89
DataFrame_var, 91
DataFrame_with_columns, 91
DataFrame_with_columns_seq, 92
DataFrame_with_row_index, 93
DataFrame_write_csv, 94
DataFrame_write_ipc, 95
DataFrame_write_json, 96
DataFrame_write_ndjson, 97
DataFrame_write_parquet, 98
DataFrames, *20*, *22*, *34*, *64*, *77*, *81*, *83*, *373*, *419*, *420*, *535*, *555*, *560*
DataType, *466*
DataType_Array, 100
DataType_Categorical, 100
DataType_contains_categoricals, 101
DataType_contains_views, 102
DataType_Datetime, 102
DataType_Duration, 103
DataType_Enum, 104
DataType_is_array, 105
DataType_is_binary, 105
DataType_is_bool, 106
DataType_is_categorical, 106
DataType_is_enum, 107
DataType_is_float, 107
DataType_is_integer, 108
DataType_is_known, 108
DataType_is_list, 109
DataType_is_logical, 109
DataType_is_nested, 110
DataType_is_null, 110
DataType_is_numeric, 111
DataType_is_ord, 111
DataType_is_primitive, 112
DataType_is_signed_integer, 112
DataType_is_string, 113
DataType_is_struct, 113
DataType_is_temporal, 114
DataType_is_unsigned_integer, 114
DataType_List, 115
DataType_Struct, 115
Date, *207*, *209*, *212*, *214*, *216*, *220*, *222*, *224*
Datetime, *20*, *22*, *34*, *81*, *83*, *207*, *209*, *212*, *214*, *216*, *220*, *222*, *224*, *350*, *351*, *373*, *451–453*, *457*, *459*, *468*, *535*, *555*
difftime, *452*, *453*, *457*, *459*
dim.RPolarsDataFrame, 116
dim.RPolarsLazyFrame *(*dim.RPolarsDataFrame*)*, 116
dimnames.RPolarsDataFrame, 117

dimnames.RPolarsLazyFrame (dimnames.RPolarsDataFrame), 117
docs_translations, *31*, 117, *197*
dplyr::filter(), *44*, *386*
DynamicGroupBy_agg, 119
DynamicGroupBy_class, 121
DynamicGroupBy_ungroup, 121

element (pl_element), 463
exclude (Expr_exclude), 152
Expr, *123*, *125*, *145*, *147*, *148*, *158*, *161*, *175*, *176*, *183*, *184*, *186–189*, *193*, *202*, *236*, *244–246*, *249*, *255*, *259–261*, *270*, *272*, *278*, *297*, *321–323*, *325*, *329*, *336*, *338*, *343*, *346*, *349*, *351*, *352*, *356*, *440*, *443*, *452*, *453*, *457*, *459*, *467*, *469*, *470*, *473*, *476*, *478*, *479*, *481*, *483*, *507*, *510*, *511*, *514*, *535*, *554*
Expr_abs, 122
Expr_add, 122
Expr_agg_groups, 123
Expr_alias, 124
Expr_all, 124
Expr_and, 125
Expr_any, 126
Expr_append, 126
Expr_approx_n_unique, 127
Expr_arccos, 128
Expr_arccosh, 128
Expr_arcsin, 129
Expr_arcsinh, 129
Expr_arctan, 130
Expr_arctanh, 130
Expr_arg_max, 131
Expr_arg_min, 131
Expr_arg_sort, 132
Expr_arg_unique, 132
Expr_backward_fill, 133
Expr_bottom_k, 133
Expr_cast, 134
Expr_ceil, 135
Expr_class, 135
Expr_clip, 136
Expr_cos, 137
Expr_cosh, 137
Expr_count, 138
Expr_cum_count, 138
Expr_cum_max, 139
Expr_cum_min, 140
Expr_cum_prod, 140
Expr_cum_sum, 141
Expr_cumulative_eval, 142
Expr_cut, 142
Expr_diff, 144
Expr_div, 144
Expr_dot, 145
Expr_drop_nans, 146
Expr_drop_nulls, 146
Expr_entropy, 147
Expr_eq, 147, *148*
Expr_eq_missing, *147*, 148
Expr_ewm_mean, 149
Expr_ewm_std, 150
Expr_ewm_var, 151
Expr_exclude, 152
Expr_exp, 153
Expr_explode, 154
Expr_extend_constant, 154
Expr_fill_nan, 155
Expr_fill_null, 155
Expr_filter, 156
Expr_first, 157
Expr_flatten, 157
Expr_floor, 158
Expr_floor_div, 158
Expr_forward_fill, 159
Expr_gather, 160
Expr_gather_every, 160
Expr_gt, 161
Expr_gt_eq, 161
Expr_has_nulls, 162
Expr_hash, 162
Expr_head, 163
Expr_implode, 163
Expr_inspect, 164
Expr_interpolate, 164
Expr_is_between, 165
Expr_is_duplicated, 166
Expr_is_finite, 167
Expr_is_first_distinct, 167
Expr_is_in, 168
Expr_is_infinite, 168
Expr_is_last_distinct, 169
Expr_is_nan, 169
Expr_is_not_nan, 170

Expr_is_not_null, 170
Expr_is_null, 171
Expr_is_unique, 171
Expr_kurtosis, 172
Expr_last, 172
Expr_len *(*Expr_count*)*, 138
Expr_limit, 173
Expr_log, 173
Expr_log10, 174
Expr_lower_bound, 174
Expr_lt, 175
Expr_lt_eq, 175
Expr_map_batches, 176
Expr_map_elements, 178
Expr_max, 181
Expr_mean, 182
Expr_median, 182
Expr_min, 183
Expr_mod, 183
Expr_mode, 184
Expr_mul, 184
Expr_n_unique, 185
Expr_nan_max, 185
Expr_nan_min, 186
Expr_neq, 186, *187*
Expr_neq_missing, *186*, 187
Expr_not, 188
Expr_null_count, 188
Expr_or, 189
Expr_over, 189
Expr_pct_change, 191
Expr_peak_max, 192
Expr_peak_min, 192
Expr_pow, 193
Expr_product, 194
Expr_qcut, 194
Expr_quantile, 195
Expr_rank, 196
Expr_rechunk, 197
Expr_reinterpret, 198
Expr_rep, 198
Expr_repeat_by, 199
Expr_replace, 199
Expr_replace_strict, 200
Expr_reshape, 202
Expr_reverse, 203
Expr_rle, 203
Expr_rle_id, 204
Expr_rolling, 204
Expr_rolling_max, 206
Expr_rolling_max_by, 207
Expr_rolling_mean, 208
Expr_rolling_mean_by, 209
Expr_rolling_median, 210
Expr_rolling_median_by, 211
Expr_rolling_min, 213
Expr_rolling_min_by, 214
Expr_rolling_quantile, 215
Expr_rolling_quantile_by, 216
Expr_rolling_skew, 217
Expr_rolling_std, 218
Expr_rolling_std_by, 219
Expr_rolling_sum, 221
Expr_rolling_sum_by, 222
Expr_rolling_var, 223
Expr_rolling_var_by, 224
Expr_round, 225
Expr_sample, 226
Expr_search_sorted, 227
Expr_set_sorted, 228
Expr_shift, 228
Expr_shrink_dtype, 229
Expr_shuffle, 230
Expr_sign, 230
Expr_sin, 231
Expr_sinh, 231
Expr_skew, 232
Expr_slice, 232
Expr_sort, 233
Expr_sort_by, 234
Expr_sqrt, 235
Expr_std, 235
expr_str_strip_chars *(*ExprStr_strip_chars*)*, 343
expr_str_strip_chars_end *(*ExprStr_strip_chars_end*)*, 344
expr_str_strip_chars_start *(*ExprStr_strip_chars_start*)*, 345
expr_str_zfill *(*ExprStr_zfill*)*, 354
Expr_sub, 236
Expr_sum, 237
Expr_tail, 237
Expr_tan, 238
Expr_tanh, 238
Expr_to_physical, 239

Expr_to_r, 239
Expr_to_series, 240
Expr_top_k, 241
Expr_unique, 241
Expr_unique_counts, 242
Expr_upper_bound, 242
Expr_value_counts, 243
Expr_var, 243
Expr_when_then_otherwise, 244
Expr_xor, 246
ExprArr_all, 246
ExprArr_any, 247
ExprArr_arg_max, 247
ExprArr_arg_min, 248
ExprArr_contains, 248
ExprArr_get, 249
ExprArr_join, 250
ExprArr_max, 250
ExprArr_median, 251
ExprArr_min, 252
ExprArr_reverse, 252
ExprArr_shift, 253
ExprArr_sort, 253
ExprArr_std, 254
ExprArr_sum, 254
ExprArr_to_list, 255
ExprArr_to_struct, 256
ExprArr_unique, 257
ExprArr_var, 257
ExprBin_contains, 258
ExprBin_decode, 259
ExprBin_encode, 260
ExprBin_ends_with, 260
ExprBin_size, 261
ExprBin_starts_with, 262
ExprCat_get_categories, 262
ExprCat_set_ordering, 263
ExprDT_cast_time_unit, 264
ExprDT_combine, 265
ExprDT_convert_time_zone, 266
ExprDT_day, 266
ExprDT_epoch, 267
ExprDT_hour, 268
ExprDT_is_leap_year, 268
ExprDT_iso_year, 269
ExprDT_microsecond, 270
ExprDT_millisecond, 270
ExprDT_minute, 271
ExprDT_month, 272
ExprDT_nanosecond, 272
ExprDT_offset_by, 273
ExprDT_ordinal_day, 274
ExprDT_quarter, 275
ExprDT_replace_time_zone, 276
ExprDT_round, 277
ExprDT_second, 278
ExprDT_strftime, 279
ExprDT_time, 280
ExprDT_timestamp, 280
ExprDT_total_days, 281
ExprDT_total_hours, 282
ExprDT_total_microseconds, 282
ExprDT_total_milliseconds, 283
ExprDT_total_minutes, 284
ExprDT_total_nanoseconds, 284
ExprDT_total_seconds, 285
ExprDT_truncate, 286
ExprDT_week, 287
ExprDT_weekday, 287
ExprDT_with_time_unit, 288
ExprDT_year, 289
Expression, *17*, *351*, *448*, *475*
expression, *48*, *388*
Expressions, *505*
ExprList_all, 289
ExprList_any, 290
ExprList_arg_max, 290
ExprList_arg_min, 291
ExprList_concat, 291
ExprList_contains, 292
ExprList_diff, 293
ExprList_eval, 293
ExprList_explode, 294
ExprList_first, 295
ExprList_gather, 295
ExprList_gather_every, 296
ExprList_get, 297
ExprList_head, 298
ExprList_join, 298
ExprList_last, 299
ExprList_len, 300
ExprList_max, 300
ExprList_mean, 301
ExprList_min, 301
ExprList_n_unique, 302
ExprList_reverse, 302

ExprList_sample, 303
ExprList_set_difference, 304
ExprList_set_intersection, 304
ExprList_set_symmetric_difference, 305
ExprList_set_union, 306
ExprList_shift, 307
ExprList_slice, 307
ExprList_sort, 308
ExprList_sum, 309
ExprList_tail, 309
ExprList_to_struct, 310
ExprList_unique, 311
ExprMeta_eq, 312
ExprMeta_has_multiple_outputs, 312
ExprMeta_is_regex_projection, 313
ExprMeta_neq, 313
ExprMeta_output_name, 314
ExprMeta_pop, 315
ExprMeta_root_names, 316
ExprMeta_tree_format, 316
ExprMeta_undo_aliases, 317
ExprName_keep, 317
ExprName_prefix, 318
ExprName_prefix_fields, 318
ExprName_suffix, 319
ExprName_suffix_fields, 320
ExprName_to_lowercase, 320
ExprName_to_uppercase, 321
ExprStr_contains, 321
ExprStr_contains_any, 322
ExprStr_count_matches, 323
ExprStr_decode, 324
ExprStr_encode, 324
ExprStr_ends_with, 325
ExprStr_extract, 326
ExprStr_extract_all, 326
ExprStr_extract_groups, 327
ExprStr_extract_many, 328
ExprStr_find, 329
ExprStr_head, 330
ExprStr_join, 331
ExprStr_json_decode, 332
ExprStr_json_path_match, 332
ExprStr_len_bytes, 333
ExprStr_len_chars, 334
ExprStr_pad_end, 335
ExprStr_pad_start, 335
ExprStr_replace, 336
ExprStr_replace_all, 337
ExprStr_replace_many, 339
ExprStr_reverse, 340
ExprStr_slice, 340
ExprStr_split, 341
ExprStr_split_exact, 341
ExprStr_splitn, 342
ExprStr_starts_with, 343
ExprStr_strip_chars, 343
ExprStr_strip_chars_end, 344
ExprStr_strip_chars_start, 345
ExprStr_strptime, 345
ExprStr_tail, 348
ExprStr_to_date, 349
ExprStr_to_datetime, 350
ExprStr_to_integer, 351
ExprStr_to_lowercase, 352
ExprStr_to_time, 352
ExprStr_to_titlecase, 353
ExprStr_to_uppercase, 353
ExprStr_zfill, 354
ExprStruct_field, 355
ExprStruct_rename_fields, 355
ExprStruct_with_fields, 356

global_rpool_cap, 357
GroupBy, *48*, *50*
GroupBy_agg, 358
GroupBy_class, 359
GroupBy_first, 359
GroupBy_last, 360
GroupBy_max, 360
GroupBy_mean, 361
GroupBy_median, 362
GroupBy_min, 362
GroupBy_null_count, 363
GroupBy_quantile, 363
GroupBy_shift, 364
GroupBy_std, 364
GroupBy_sum, 365
GroupBy_ungroup, 365
GroupBy_var, 366

hash (Expr_hash), 162
head.RPolarsDataFrame, 366
head.RPolarsLazyFrame
(head.RPolarsDataFrame), 366

ifelse(), *244*

infer_nanoarrow_schema.RPolarsDataFrame, 368
infer_nanoarrow_schema.RPolarsSeries (infer_nanoarrow_schema.RPolarsDataFrame), 368
is_finished(), *525*
is_infinite (Expr_is_infinite), 168
is_nan (Expr_is_nan), 169
is_not_nan (Expr_is_not_nan), 170
is_polars_df, 369
is_polars_dtype, 369
is_polars_lf, 370
is_polars_series, 370

join(), *525*

knit_print.RPolarsDataFrame, 371

lapply(), *64*
lazy (DataFrame_lazy), 59
LazyFrame, *17*, *27*, *28*, *117*, *135*, *367*, *376*, *405*, *418*, *420*, *434–437*, *460*, *474*, *499*, *500*, *504*, *507*, *558*, *559*, *561*, *563*, *564*
LazyFrame_cast, 372
LazyFrame_class, 373
LazyFrame_clear, 375
LazyFrame_clone, 376
LazyFrame_collect, 377
LazyFrame_collect_in_background, 379
LazyFrame_drop, 380
LazyFrame_drop_nulls, 380
LazyFrame_explain, 381
LazyFrame_explode, 382
LazyFrame_fetch, 383
LazyFrame_fill_nan, 385
LazyFrame_fill_null, 386
LazyFrame_filter, 386
LazyFrame_first, 387
LazyFrame_gather_every, 387
LazyFrame_group_by, 388
LazyFrame_group_by_dynamic, 389
LazyFrame_head, 392
LazyFrame_join, 393
LazyFrame_join_asof, 395
LazyFrame_join_where, 398
LazyFrame_last, 399
LazyFrame_max, 399
LazyFrame_mean, 400
LazyFrame_median, 400
LazyFrame_min, 401
LazyFrame_print, 401
LazyFrame_profile, 402
LazyFrame_quantile, 404
LazyFrame_rename, 404
LazyFrame_reverse, 405
LazyFrame_rolling, 406
LazyFrame_select, 408
LazyFrame_select_seq, 409
LazyFrame_serialize, 409
LazyFrame_shift, 410
LazyFrame_sink_csv, 411
LazyFrame_sink_ipc, 413
LazyFrame_sink_ndjson, 414
LazyFrame_sink_parquet, 416
LazyFrame_slice, 418
LazyFrame_sort, 418
LazyFrame_sql, 419
LazyFrame_std, 421
LazyFrame_sum, 421
LazyFrame_tail, 422
LazyFrame_to_dot, 422
LazyFrame_unique, 424
LazyFrame_unnest, 425
LazyFrame_unpivot, 426
LazyFrame_var, 427
LazyFrame_with_columns, 427
LazyFrame_with_columns_seq, 428
LazyFrame_with_context, 429
LazyFrame_with_row_index, 430
LazyFrames, *77*, *419*, *420*, *560*
LazyGroupBy, *388*, *391*, *407*
LazyGroupBy_agg, 431
LazyGroupBy_class, 431
LazyGroupBy_head, 432
LazyGroupBy_print, 432
LazyGroupBy_tail, 433
LazyGroupBy_ungroup, 433
length.RPolarsDataFrame, 434
length.RPolarsLazyFrame (length.RPolarsDataFrame), 434
length.RPolarsSeries (length.RPolarsDataFrame), 434
list, *64*

matrix, *21*
max.RPolarsDataFrame, 434

max.RPolarsLazyFrame
(max.RPolarsDataFrame), 434
max.RPolarsSeries
(max.RPolarsDataFrame), 434
mean.RPolarsDataFrame, 435
mean.RPolarsLazyFrame
(mean.RPolarsDataFrame), 435
mean.RPolarsSeries
(mean.RPolarsDataFrame), 435
median.RPolarsDataFrame, 435
median.RPolarsLazyFrame
(median.RPolarsDataFrame), 435
median.RPolarsSeries
(median.RPolarsDataFrame), 435
min.RPolarsDataFrame, 436
min.RPolarsLazyFrame
(min.RPolarsDataFrame), 436
min.RPolarsSeries
(min.RPolarsDataFrame), 436

na.omit.RPolarsDataFrame
(na.omit.RPolarsLazyFrame), 436
na.omit.RPolarsLazyFrame, 436
names.RPolarsDataFrame, 437
names.RPolarsGroupBy
(names.RPolarsDataFrame), 437
names.RPolarsLazyFrame
(names.RPolarsDataFrame), 437
names.RPolarsLazyGroupBy
(names.RPolarsDataFrame), 437
Number of threads used by Polars, *520*

OlsonNames(), *102*, *455*
options(), *512*, *521*
otherwise (Expr_when_then_otherwise), 244

pl (pl_pl), 483
pl$all(), *124*
pl$arg_sort_by(), *132*
pl$col(), *38*, *64*, *380*, *440*, *448*, *467*, *469*, *470*, *473*, *476*, *478*, *479*, *481*, *482*, *507*, *510*, *511*, *514*
pl$date(), *456*, *513*
pl$date_range(), *454*
pl$date_ranges(), *452*
pl$Datetime(), *346*
pl$datetime(), *451*, *513*
pl$Datetime(ms), *346*, *350*, *468*
pl$Datetime(ns), *468*
pl$Datetime(us), *468*
pl$datetime_range(), *459*
pl$datetime_ranges(), *458*
pl$deserialize_lf(), *410*
pl$disable_string_cache, *464*
pl$enable_enable_cache, *514*, *515*
pl$enable_string_cache, *461*
pl$enable_string_cache(), *445*
pl$Field(), *115*
pl$field(), *356*
pl$fold(), *494*
pl$int_range(), *472*
pl$int_ranges(), *471*
pl$LazyFrame(), *373*
pl$len(), *448*
pl$lit(), *468*
pl$max_horizontal(), *476*
pl$mean_horizontal(), *478*
pl$min_horizontal(), *481*
pl$reduce(), *467*
pl$sum_horizontal(), *510*
pl$time(), *451*, *456*
pl$using_string_cache, *461*, *464*, *515*
pl$with_string_cache, *461*, *464*, *514*
pl_all, 437
pl_all_horizontal, 438
pl_any_horizontal, 439
pl_approx_n_unique, 439
pl_arg_sort_by, 440
pl_arg_where, 441
pl_coalesce, 442
pl_col, 443
pl_concat, 444
pl_concat_list, 445
pl_concat_str, 446
pl_corr, 447
pl_count, 448
pl_cov, 449
pl_DataFrame, 449
pl_date, 450
pl_date_range, 451
pl_date_ranges, 453
pl_Datetime (DataType_Datetime), 102
pl_datetime, 454
pl_datetime_range, 456
pl_datetime_ranges, 458
pl_deserialize_lf, 460

pl_disable_string_cache, 461
pl_dtypes, 461
pl_duration, 462
pl_element, 463
pl_enable_string_cache, 464
pl_Field (pl_Field_class), 465
pl_field, 465
pl_Field_class, 465
pl_first, 466
pl_fold, 467
pl_from_epoch, 468
pl_get_global_rpool_cap (global_rpool_cap), 357
pl_head, 469
pl_implode, 470
pl_int_range, 470
pl_int_ranges, 471
pl_is_schema, 472
pl_last, 473
pl_LazyFrame, 474
pl_len, 475
pl_lit, 475
pl_max, 476
pl_max_horizontal, 477
pl_mean, 478
pl_mean_horizontal, 478
pl_median, 479
pl_mem_address, 480
pl_min, 481
pl_min_horizontal, 482
pl_n_unique, 482
pl_pl, 483
pl_PTime, 484
pl_raw_list, 485
pl_read_csv, 486
pl_read_ipc, 489
pl_read_ndjson, 490
pl_read_parquet, 491
pl_reduce, 494
pl_rolling_corr, 495
pl_rolling_cov, 496
pl_scan_csv, 496
pl_scan_ipc, 499
pl_scan_ndjson, 501
pl_scan_parquet, 502
pl_select, 505
pl_Series, 505
pl_set_global_rpool_cap (global_rpool_cap), 357
pl_show_all_public_functions (show_all_public_functions), 557
pl_show_all_public_methods (show_all_public_methods), 558
pl_SQLContext, 507
pl_std, 507
pl_struct, 508
pl_sum, 509
pl_sum_horizontal, 510
pl_tail, 511
pl_thread_pool_size, 512
pl_time, 512
pl_using_string_cache, 513
pl_var, 514
pl_when (Expr_when_then_otherwise), 244
pl_with_string_cache, 515
polars data type, *506*
polars DataFrame, *24*
polars_class_object, 516
polars_code_completion_activate, 516
polars_code_completion_activate(), *520*
polars_code_completion_deactivate (polars_code_completion_activate), 516
polars_duration_string, 517
polars_envvars, 518
polars_info, 520
polars_info(), *251*, *252*, *353*
polars_options, 521
polars_options_reset (polars_options), 521
POSIXct, *20*, *22*, *34*, *81*, *83*, *373*, *535*, *555*
print.RPolarsSeries, 522
PTIME (pl_PTime), 484

RollingGroupBy, *71*
RollingGroupBy_agg, 523
RollingGroupBy_class, 524
RollingGroupBy_ungroup, 524
row.names.RPolarsDataFrame, 525
RPolarsChainedThen (Expr_when_then_otherwise), 244
RPolarsChainedWhen (Expr_when_then_otherwise), 244
RPolarsDataFrame (DataFrame_class), 33
RPolarsDataType (pl_dtypes), 461
RPolarsDataTypes, *443*

RPolarsDynamicGroupBy (DynamicGroupBy_class), 121
RPolarsExpr (Expr_class), 135
RPolarsGroupBy (GroupBy_class), 359
RPolarsLazyFrame (LazyFrame_class), 373
RPolarsLazyGroupBy (LazyGroupBy_class), 431
RPolarsRollingGroupBy (RollingGroupBy_class), 524
RPolarsRThreadHandle (RThreadHandle_class), 525
RPolarsSeries (Series_class), 534
RPolarsSQLContext (SQLContext_class), 558
RPolarsThen (Expr_when_then_otherwise), 244
RPolarsWhen (Expr_when_then_otherwise), 244
RThreadHandle, *379*
RThreadHandle_class, 525, *527*
RThreadHandle_is_finished, 526
RThreadHandle_join, 526

S3_arithmetic, 527
select (DataFrame_select), 73
Series, *17*, *30*, *46*, *84*, *434–436*, *506*, *518*, *529–531*, *537*, *538*, *540*, *543*, *545*, *546*, *548–552*, *563*
Series (pl_Series), 505
Series_add, 529
Series_alias, 530
Series_all, 530
Series_any, 531
Series_append, 531
Series_arg_max, 532
Series_arg_min, 533
Series_chunk_lengths, 533
Series_class, 534
Series_clear, 537
Series_clone, 537
Series_div, 538
Series_equals, 539
Series_floor_div, 540
Series_is_numeric, 540
Series_is_sorted, 541
Series_item, 541
Series_len, 542
Series_map_elements, 542
Series_max, 543
Series_mean, 544
Series_median, 544
Series_min, 545
Series_mod, 545
Series_mul, 546
Series_n_chunks, 547
Series_n_unique, 547
Series_pow, 548
Series_print, 548
Series_rename, 549
Series_rep, 549
Series_set_sorted, 550
Series_sort, 551
Series_std, 552
Series_sub, 552
Series_sum, 553
Series_to_frame, 553
Series_to_list (Series_to_r), 554
Series_to_lit, 554
Series_to_r, 554
Series_to_vector (Series_to_r), 554
Series_value_counts, 556
Series_var, 557
set_global_rpool_cap (global_rpool_cap), 357
show_all_public_functions, 557
show_all_public_methods, 558
SQLContext, *77*, *78*, *419*, *420*, *507*, *560*, *561*, *563*
SQLContext_class, 558
SQLContext_execute, 559
SQLContext_register, 559
SQLContext_register_globals, 560
SQLContext_register_many, 561
SQLContext_tables, 562
SQLContext_unregister, 562
strptime(), *345*
Struct, *89*, *143*, *195*, *327*, *425*
Struct(), *508*
sum.RPolarsDataFrame, 563
sum.RPolarsLazyFrame (sum.RPolarsDataFrame), 563
sum.RPolarsSeries (sum.RPolarsDataFrame), 563
Sys.timezone(), *20*, *22*, *34*, *81*, *83*, *373*, *535*, *555*

tail.RPolarsDataFrame (head.RPolarsDataFrame), 366

tail.RPolarsLazyFrame
(head.RPolarsDataFrame), 366
the Series class object, *505*
Then (Expr_when_then_otherwise), 244
then (Expr_when_then_otherwise), 244
Then_otherwise
(Expr_when_then_otherwise), 244
Then_when (Expr_when_then_otherwise),
244
to_physical (Expr_to_physical), 239
to_struct (DataFrame_to_struct), 86

UInt32, *448*, *475*
unique.RPolarsDataFrame, 564
unique.RPolarsLazyFrame
(unique.RPolarsDataFrame), 564

When (Expr_when_then_otherwise), 244
when (Expr_when_then_otherwise), 244
When_then (Expr_when_then_otherwise),
244
with_columns (DataFrame_with_columns),
91
with_columns(), *20*, *26*, *378*, *382*, *384*, *402*,
423