

Package: tarchetypes (via r-universe)

October 14, 2026

Title Archetypes for Targets

Description Function-oriented Make-like declarative pipelines for Statistics and data science are supported in the 'targets' R package. As an extension to 'targets', the 'tarchetypes' package provides convenient user-side functions to make 'targets' easier to use. By establishing reusable archetypes for common kinds of targets and pipelines, these functions help express complicated reproducible pipelines concisely and compactly. The methods in this package were influenced by the 'targets' R package. by Will Landau (2018)
<doi:10.21105/joss.00550>.

Version 0.14.1

License MIT + file LICENSE

URL <https://docs.ropensci.org/tarchetypes/>,
<https://github.com/ropensci/tarchetypes>

BugReports <https://github.com/ropensci/tarchetypes/issues>

Depends R (>= 4.1.0)

Imports dplyr (>= 1.0.0), fs (>= 1.4.2), parallel, rlang (>= 0.4.7), secretbase (>= 0.4.0), targets (>= 1.6.0), tibble (>= 3.0.1), tidyselect (>= 1.1.0), utils, vctrs (>= 0.3.4), withr (>= 2.1.2)

Suggests curl (>= 4.3), knitr (>= 1.28), nanoparquet, parsermd, quarto (>= 1.4.0), rmarkdown (>= 2.1), testthat (>= 3.0.0), xml2 (>= 1.3.2)

Encoding UTF-8

Language en-US

Config/testthat/edition 3

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

Config/pak/sysreqs cmake libglib-dev make libuv1-dev libxml2-dev

Repository <https://r-multiverse-staging.r-universe.dev>

Date/Publication 2026-03-23 19:21:54 UTC

RemoteUrl <https://github.com/ropensci/tarchetypes>

RemoteRef 020909b152e81f5891242672a3c2ef42312cfc2b

RemoteSha 020909b152e81f5891242672a3c2ef42312cfc2b

Contents

tarchetypes-package	3
tar_age	3
tar_assign	8
tar_change	9
tar_combine	14
tar_cue_age	20
tar_cue_force	22
tar_cue_skip	24
tar_download	26
tar_eval	31
tar_file_read	32
tar_files	37
tar_files_input	42
tar_force	46
tar_format_nanoparquet	51
tar_formats	52
tar_group_by	63
tar_group_count	68
tar_group_select	72
tar_group_size	77
tar_hook_before	82
tar_hook_inner	84
tar_hook_outer	87
tar_knit	89
tar_knitr_deps	94
tar_knitr_deps_expr	95
tar_map	96
tar_map_rep	98
tar_map2_count	105
tar_map2_size	112
tar_plan	120
tar_quarto	121
tar_quarto_files	128
tar_quarto_rep	129
tar_render	136
tar_render_rep	143
tar_rep	149
tar_rep_index	156

tar_rep2	157
tar_select_names	163
tar_select_targets	164
tar_skip	165
tar_sub	170
tar_tangle	172

Index	175
--------------	------------

tarchetypes-package	<i>targets: Archetypes for Targets</i>
---------------------	--

Description

A pipeline toolkit for R, the `targets` package brings together function-oriented programming and Make-like declarative pipelines for Statistics and data science. The `tarchetypes` package provides convenient helper functions to create specialized targets, making pipelines in `targets` easier and cleaner to write and understand.

tar_age	<i>Create a target that runs when the last run gets old</i>
---------	---

Description

`tar_age()` creates a target that reruns itself when it gets old enough. In other words, the target reruns periodically at regular intervals of time.

Usage

```
tar_age(
  name,
  command,
  age,
  pattern = NULL,
  tidy_eval = targets::tar_option_get("tidy_eval"),
  packages = targets::tar_option_get("packages"),
  library = targets::tar_option_get("library"),
  format = targets::tar_option_get("format"),
  repository = targets::tar_option_get("repository"),
  iteration = targets::tar_option_get("iteration"),
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),
  garbage_collection = targets::tar_option_get("garbage_collection"),
  deployment = targets::tar_option_get("deployment"),
  priority = targets::tar_option_get("priority"),
  resources = targets::tar_option_get("resources"),
```

```

storage = targets::tar_option_get("storage"),
retrieval = targets::tar_option_get("retrieval"),
cue = targets::tar_option_get("cue"),
description = targets::tar_option_get("description")
)

```

Arguments

name	Name of the target. <code>tar_cue_age()</code> expects an unevaluated symbol for the name argument, whereas <code>tar_cue_age_raw()</code> expects a character string for name.
command	R code to run the target and return a value.
age	A <code>difftime</code> object of length 1, such as <code>as.difftime(3, units = "days")</code> . If the target's output data files are older than age (according to the most recent time stamp over all the target's output files) then the target will rerun. On the other hand, if at least one data file is younger than <code>Sys.time() - age</code> , then the ordinary invalidation rules apply, and the target may or not rerun. If you want to force the target to run every 3 days, for example, set <code>age = as.difftime(3, units = "days")</code> .
pattern	Code to define a dynamic branching for a target. In <code>tar_target()</code> , pattern is an unevaluated expression, e.g. <code>tar_target(pattern = map(data))</code> . In <code>tar_target_raw()</code> , command is an evaluated expression, e.g. <code>tar_target_raw(pattern = quote(map(data)))</code> . To demonstrate dynamic branching patterns, suppose we have a pipeline with numeric vector targets <code>x</code> and <code>y</code> . Then, <code>tar_target(z, x + y, pattern = map(x, y))</code> implicitly defines branches of <code>z</code> that each compute <code>x[1] + y[1]</code> , <code>x[2] + y[2]</code> , and so on. See the user manual for details.
tidy_eval	Logical, whether to enable tidy evaluation when interpreting command and pattern. If TRUE, you can use the "bang-bang" operator <code>!!</code> to programmatically insert the values of global objects.
packages	Character vector of packages to load right before the target runs or the output data is reloaded for downstream targets. Use <code>tar_option_set()</code> to set packages globally for all subsequent targets you define.
library	Character vector of library paths to try when loading packages.
format	Logical, whether to rerun the target if the user-specified storage format changed. The storage format is user-specified through <code>tar_target()</code> or <code>tar_option_set()</code> .
repository	Logical, whether to rerun the target if the user-specified storage repository changed. The storage repository is user-specified through <code>tar_target()</code> or <code>tar_option_set()</code> .
iteration	Logical, whether to rerun the target if the user-specified iteration method changed. The iteration method is user-specified through <code>tar_target()</code> or <code>tar_option_set()</code> .
error	Character of length 1, what to do if the target stops and throws an error. Options: • "stop": the whole pipeline stops and throws an error. • "continue": the whole pipeline keeps going. • "null": The errored target continues and returns NULL. The data hash is deliberately wrong so the target is not up to date for the next run of the pipeline. In addition, as of targets version 1.8.0.9011, a value of NULL is given to upstream dependencies with <code>error = "null"</code> if loading fails.

- "abridge": any currently running targets keep running, but no new targets launch after that.
- "trim": all currently running targets stay running. A queued target is allowed to start if:
 1. It is not downstream of the error, and
 2. It is not a sibling branch from the same `tar_target()` call (if the error happened in a dynamic branch).

The idea is to avoid starting any new work that the immediate error impacts. `error = "trim"` is just like `error = "abridge"`, but it allows potentially healthy regions of the dependency graph to begin running. (Visit <https://books.ropensci.org/targets/debugging.html> to learn how to debug targets using saved workspaces.)

memory

Character of length 1, memory strategy. Possible values:

- "auto" (default): equivalent to `memory = "transient"` in almost all cases. But to avoid superfluous reads from disk, `memory = "auto"` is equivalent to `memory = "persistent"` for non-dynamically-branched targets that other targets dynamically branch over. For example: if your pipeline has `tar_target(name = y, command = x, pattern = map(x))`, then `tar_target(name = x, command = f(), memory = "auto")` will use persistent memory for `x` in order to avoid rereading all of `x` for every branch of `y`.
- "transient": the target gets unloaded after every new target completes. Either way, the target gets automatically loaded into memory whenever another target needs the value.
- "persistent": the target stays in memory until the end of the pipeline (unless storage is "worker", in which case targets unloads the value from memory right after storing it in order to avoid sending copious data over a network).

For cloud-based file targets (e.g. `format = "file"` with `repository = "aws"`), the memory option applies to the temporary local copy of the file: "persistent" means it remains until the end of the pipeline and is then deleted, and "transient" means it gets deleted as soon as possible. The former conserves bandwidth, and the latter conserves local storage.

garbage_collection

Logical: TRUE to run `base::gc()` just before the target runs, in whatever R process it is about to run (which could be a parallel worker). FALSE to omit garbage collection. Numeric values get converted to FALSE. The `garbage_collection` option in `tar_option_set()` is independent of the argument of the same name in `tar_target()`.

deployment

Character of length 1. If deployment is "main", then the target will run on the central controlling R process. Otherwise, if deployment is "worker" and you set up the pipeline with distributed/parallel computing, then the target runs on a parallel worker. For more on distributed/parallel computing in targets, please visit <https://books.ropensci.org/targets/crew.html>.

priority

Deprecated on 2025-04-08 (targets version 1.10.1.9013). targets has moved to a more efficient scheduling algorithm (<https://github.com/ropensci/targets/issues/1458>) which cannot support priorities. The `priority` argument of `tar_target()` no longer has a reliable effect on execution order.

resources	Object returned by <code>tar_resources()</code> with optional settings for high-performance computing functionality, alternative data storage formats, and other optional capabilities of targets. See <code>tar_resources()</code> for details.
storage	Character string to control when the output of the target is saved to storage. Only relevant when using targets with parallel workers (https://books.ropensci.org/targets/crew.html). Must be one of the following values: • "worker" (default): the worker saves/uploads the value. • "main": the target's return value is sent back to the host machine and saved/uploaded locally. • "none": targets makes no attempt to save the result of the target to storage in the location where targets expects it to be. Saving to storage is the responsibility of the user. Use with caution.
retrieval	Character string to control when the current target loads its dependencies into memory before running. (Here, a "dependency" is another target upstream that the current one depends on.) Only relevant when using targets with parallel workers (https://books.ropensci.org/targets/crew.html). Must be one of the following values: • "auto" (default): equivalent to <code>retrieval = "worker"</code> in almost all cases. But to avoid unnecessary reads from disk, <code>retrieval = "auto"</code> is equivalent to <code>retrieval = "main"</code> for dynamic branches that branch over non-dynamic targets. For example: if your pipeline has <code>tar_target(x, command = f())</code>, then <code>tar_target(y, command = x, pattern = map(x), retrieval = "auto")</code> will use "main" retrieval in order to avoid rereading all of <code>x</code> for every branch of <code>y</code>. • "worker": the worker loads the target's dependencies. • "main": the target's dependencies are loaded on the host machine and sent to the worker before the target runs. • "none": targets makes no attempt to load its dependencies. With <code>retrieval = "none"</code>, loading dependencies is the responsibility of the user. Use with caution.
cue	A <code>targets::tar_cue()</code> object. (See the "Cue objects" section for background.) This cue object should contain any optional secondary invalidation rules, anything except the mode argument. mode will be automatically determined by the age argument of <code>tar_age()</code> .
description	Character of length 1, a custom free-form human-readable text description of the target. Descriptions appear as target labels in functions like <code>tar_manifest()</code> and <code>tar_visnetwork()</code> , and they let you select subsets of targets for the names argument of functions like <code>tar_make()</code> . For example, <code>tar_manifest(names = tar_described_as(starts_with("survival model")))</code> lists all the targets whose descriptions start with the character string "survival model".

Details

`tar_age()` uses the cue from `tar_cue_age()`, which uses the time stamps from `targets::tar_meta()`\$time. See the help file of `targets::tar_timestamp()` for an explanation of how this time stamp is calculated.

Value

A target definition object. See the "Target definition objects" section for background.

Dynamic branches at regular time intervals

Time stamps are not recorded for whole dynamic targets, so `tar_age()` is not a good fit for dynamic branching. To invalidate dynamic branches at regular intervals, it is recommended to use `targets::tar_older()` in combination with `targets::tar_invalidate()` right before calling `tar_make()`. For example, the call:

```
tar_invalidate(
  any_of(
    tar_older(Sys.time - as.difftime(1, units = "weeks"))
  )
)
```

invalidates all targets more than a week old. Then, the next `tar_make()` will rerun those targets.

Target definition objects

Most `tarchetypes` functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

See Also

Other cues: [tar_cue_age\(\)](#), [tar_cue_force\(\)](#), [tar_cue_skip\(\)](#)

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      library(tarchetypes)
      list(
        tarchetypes::tar_age(
          data,
          data.frame(x = seq_len(26)),
          age = as.difftime(0.5, units = "secs")
        )
      )
    })
  })
  targets::tar_make()
```

```

Sys.sleep(0.6)
targets::tar_make()
})
}

```

tar_assign

An assignment-based pipeline DSL

Description

An assignment-based domain-specific language for pipeline construction.

Usage

```
tar_assign(targets)
```

Arguments

- | | |
|---------|---|
| targets | <p>An expression with special syntax to define a collection of targets in a pipeline. Example: <code>tar_assign(x <- tar_target(get_data()))</code> is equivalent to <code>list(tar_target(x, get_data()))</code>. The rules of the syntax are as follows:</p> <ul style="list-style-type: none"> • The code supplied to <code>tar_assign()</code> must be enclosed in curly braces beginning with <code>{</code> and <code>}</code> unless it only contains a one-line statement or uses <code>=</code> as the assignment. • Each statement in the code block must be of the form <code>x <- f()</code>, or <code>x = f()</code> where <code>x</code> is the name of a target and <code>f()</code> is a function like <code>tar_target()</code> or <code>tar_quarto()</code> which accepts a name argument. • The native pipe operator <code> ></code> is allowed because it lazily evaluates its arguments and be converted into non-pipe syntax without evaluating the code. |
|---------|---|

Value

A list of target definition objects. See the "Target definition objects" section for background.

Target definition objects

Most tarchetypes functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

See Also

Other Domain-specific languages for pipeline construction: [tar_tangle\(\)](#)

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    write.csv(airquality, "data.csv", row.names = FALSE)
    targets::tar_script({
      library(tarchetypes)
      tar_option_set(packages = c("readr", "dplyr", "ggplot2"))
      tar_assign({
        file <- tar_target("data.csv", format = "file")

        data <- read_csv(file, col_types = cols()) |>
          filter(!is.na(Ozone)) |>
          tar_target()

        model = lm(Ozone ~ Temp, data) |>
          coefficients() |>
          tar_target()

        plot <- {
          ggplot(data) +
            geom_point(aes(x = Temp, y = Ozone)) +
            geom_abline(intercept = model[1], slope = model[2]) +
            theme_gray(24)
        } |>
          tar_target()
      })
    })
    targets::tar_make()
  })
}
```

tar_change

*Target that responds to an arbitrary change.***Description**

Create a target that responds to a change in an arbitrary value. If the value changes, the target reruns.

Usage

```
tar_change(
  name,
  command,
  change,
  tidy_eval = targets::tar_option_get("tidy_eval"),
```

```

packages = targets::tar_option_get("packages"),
library = targets::tar_option_get("library"),
format = targets::tar_option_get("format"),
repository = targets::tar_option_get("repository"),
iteration = targets::tar_option_get("iteration"),
error = targets::tar_option_get("error"),
memory = targets::tar_option_get("memory"),
garbage_collection = targets::tar_option_get("garbage_collection"),
deployment = targets::tar_option_get("deployment"),
priority = targets::tar_option_get("priority"),
resources = targets::tar_option_get("resources"),
storage = targets::tar_option_get("storage"),
retrieval = targets::tar_option_get("retrieval"),
cue = targets::tar_option_get("cue"),
description = targets::tar_option_get("description")
)

```

Arguments

name	Symbol, name of the target. In <code>tar_target()</code>, name is an unevaluated symbol, e.g. <code>tar_target(name = data)</code>. In <code>tar_target_raw()</code>, name is a character string, e.g. <code>tar_target_raw(name = "data")</code>. A target name must be a valid name for a symbol in R, and it must not start with a dot. Subsequent targets can refer to this name symbolically to induce a dependency relationship: e.g. <code>tar_target(downstream_target, f(upstream_target))</code> is a target named <code>downstream_target</code> which depends on a target <code>upstream_target</code> and a function <code>f()</code>. In most cases, The target name is the name of its local data file in storage. Some file systems are not case sensitive, which means converting a name to a different case may overwrite a different target. Please ensure all target names have unique names when converted to lower case. In addition, a target's name determines its random number generator seed. In this way, each target runs with a reproducible seed so someone else running the same pipeline should get the same results, and no two targets in the same pipeline share the same seed. (Even dynamic branches have different names and thus different seeds.) You can recover the seed of a completed target with <code>tar_meta(your_target, seed)</code> and run <code>tar_seed_set()</code> on the result to locally recreate the target's initial RNG state.
command	R code to run the target. In <code>tar_target()</code> , command is an unevaluated expression, e.g. <code>tar_target(command = data)</code> . In <code>tar_target_raw()</code> , command is an evaluated expression, e.g. <code>tar_target_raw(command = quote(data))</code> .
change	R code for the upstream change-inducing target.
tidy_eval	Whether to invoke tidy evaluation (e.g. the <code>!!</code> operator from <code>rlang</code>) as soon as the target is defined (before <code>tar_make()</code>). Applies to arguments <code>command</code> and <code>change</code> .
packages	Character vector of packages to load right before the target runs or the output data is reloaded for downstream targets. Use <code>tar_option_set()</code> to set packages globally for all subsequent targets you define.

library	Character vector of library paths to try when loading packages.
format	Optional storage format for the target's return value. With the exception of <code>format = "file"</code> , each target gets a file in <code>_targets/objects</code> , and each format is a different way to save and load this file. See the "Storage formats" section for a detailed list of possible data storage formats.
repository	Character of length 1, remote repository for target storage. Choices: • <code>"local"</code>: file system of the local machine. • <code>"aws"</code>: Amazon Web Services (AWS) S3 bucket. Can be configured with a non-AWS S3 bucket using the endpoint argument of <code>tar_resources_aws()</code>, but versioning capabilities may be lost in doing so. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions. • <code>"gcp"</code>: Google Cloud Platform storage bucket. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions. • A character string from <code>tar_repository_cas()</code> for content-addressable storage. Note: if <code>repository</code> is not <code>"local"</code> and <code>format</code> is <code>"file"</code> then the target should create a single output file. That output file is uploaded to the cloud and tracked for changes where it exists in the cloud. As of targets version 1.11.0 and higher, the local file is no longer deleted after the target runs.
iteration	Character of length 1, name of the iteration mode of the target. Choices: • <code>"vector"</code>: branching happens with <code>vctrs::vec_slice()</code> and aggregation happens with <code>vctrs::vec_c()</code>. • <code>"list"</code>, branching happens with <code>[[]]</code> and aggregation happens with <code>list()</code>. • <code>"group"</code>: <code>dplyr::group_by()</code>-like functionality to branch over subsets of a non-dynamic data frame. For <code>iteration = "group"</code>, the target must not be dynamic (the <code>pattern</code> argument of <code>tar_target()</code> must be left <code>NULL</code>). The target's return value must be a data frame with a special <code>tar_group</code> column of consecutive integers from 1 through the number of groups. Each integer designates a group, and a branch is created for each collection of rows in a group. See the <code>tar_group()</code> function to see how you can create the special <code>tar_group</code> column with <code>dplyr::group_by()</code>.
error	Character of length 1, what to do if the target stops and throws an error. Options: • <code>"stop"</code>: the whole pipeline stops and throws an error. • <code>"continue"</code>: the whole pipeline keeps going. • <code>"null"</code>: The errored target continues and returns <code>NULL</code>. The data hash is deliberately wrong so the target is not up to date for the next run of the pipeline. In addition, as of targets version 1.8.0.9011, a value of <code>NULL</code> is given to upstream dependencies with <code>error = "null"</code> if loading fails. • <code>"abridge"</code>: any currently running targets keep running, but no new targets launch after that. • <code>"trim"</code>: all currently running targets stay running. A queued target is allowed to start if: 1. It is not downstream of the error, and

2. It is not a sibling branch from the same `tar_target()` call (if the error happened in a dynamic branch).

The idea is to avoid starting any new work that the immediate error impacts. `error = "trim"` is just like `error = "abridge"`, but it allows potentially healthy regions of the dependency graph to begin running. (Visit <https://books.ropensci.org/targets/debugging.html> to learn how to debug targets using saved workspaces.)

memory

Character of length 1, memory strategy. Possible values:

- "auto" (default): equivalent to `memory = "transient"` in almost all cases. But to avoid superfluous reads from disk, `memory = "auto"` is equivalent to `memory = "persistent"` for non-dynamically-branched targets that other targets dynamically branch over. For example: if your pipeline has `tar_target(name = y, command = x, pattern = map(x))`, then `tar_target(name = x, command = f(), memory = "auto")` will use persistent memory for `x` in order to avoid rereading all of `x` for every branch of `y`.
- "transient": the target gets unloaded after every new target completes. Either way, the target gets automatically loaded into memory whenever another target needs the value.
- "persistent": the target stays in memory until the end of the pipeline (unless storage is "worker", in which case targets unloads the value from memory right after storing it in order to avoid sending copious data over a network).

For cloud-based file targets (e.g. `format = "file"` with `repository = "aws"`), the memory option applies to the temporary local copy of the file: "persistent" means it remains until the end of the pipeline and is then deleted, and "transient" means it gets deleted as soon as possible. The former conserves bandwidth, and the latter conserves local storage.

garbage_collection

Logical: TRUE to run `base::gc()` just before the target runs, in whatever R process it is about to run (which could be a parallel worker). FALSE to omit garbage collection. Numeric values get converted to FALSE. The `garbage_collection` option in `tar_option_set()` is independent of the argument of the same name in `tar_target()`.

deployment

Character of length 1. If deployment is "main", then the target will run on the central controlling R process. Otherwise, if deployment is "worker" and you set up the pipeline with distributed/parallel computing, then the target runs on a parallel worker. For more on distributed/parallel computing in targets, please visit <https://books.ropensci.org/targets/crew.html>.

priority

Deprecated on 2025-04-08 (targets version 1.10.1.9013). targets has moved to a more efficient scheduling algorithm (<https://github.com/ropensci/targets/issues/1458>) which cannot support priorities. The `priority` argument of `tar_target()` no longer has a reliable effect on execution order.

resources

Object returned by `tar_resources()` with optional settings for high-performance computing functionality, alternative data storage formats, and other optional capabilities of targets. See `tar_resources()` for details.

storage	Character string to control when the output of the target is saved to storage. Only relevant when using targets with parallel workers (https://books.ropensci.org/targets/crew.html). Must be one of the following values: • "worker" (default): the worker saves/uploads the value. • "main": the target's return value is sent back to the host machine and saved/uploaded locally. • "none": targets makes no attempt to save the result of the target to storage in the location where targets expects it to be. Saving to storage is the responsibility of the user. Use with caution.
retrieval	Character string to control when the current target loads its dependencies into memory before running. (Here, a "dependency" is another target upstream that the current one depends on.) Only relevant when using targets with parallel workers (https://books.ropensci.org/targets/crew.html). Must be one of the following values: • "auto" (default): equivalent to retrieval = "worker" in almost all cases. But to avoid unnecessary reads from disk, retrieval = "auto" is equivalent to retrieval = "main" for dynamic branches that branch over non-dynamic targets. For example: if your pipeline has <code>tar_target(x, command = f())</code>, then <code>tar_target(y, command = x, pattern = map(x), retrieval = "auto")</code> will use "main" retrieval in order to avoid rereading all of x for every branch of y. • "worker": the worker loads the target's dependencies. • "main": the target's dependencies are loaded on the host machine and sent to the worker before the target runs. • "none": targets makes no attempt to load its dependencies. With retrieval = "none", loading dependencies is the responsibility of the user. Use with caution.
cue	An optional object from <code>tar_cue()</code> to customize the rules that decide whether the target is up to date. Only applies to the downstream target. The upstream target always runs.
description	Character of length 1, a custom free-form human-readable text description of the target. Descriptions appear as target labels in functions like <code>tar_manifest()</code> and <code>tar_visnetwork()</code>, and they let you select subsets of targets for the names argument of functions like <code>tar_make()</code>. For example, <code>tar_manifest(names = tar_described_as(starts_with("survival model")))</code> lists all the targets whose descriptions start with the character string "survival model".

Details

`tar_change()` creates a pair of targets, one upstream and one downstream. The upstream target always runs and returns an auxiliary value. This auxiliary value gets referenced in the downstream target, which causes the downstream target to rerun if the auxiliary value changes. The behavior is cancelled if cue is `tar_cue(depend = FALSE)` or `tar_cue(mode = "never")`.

Because the upstream target always runs, `tar_outdated()` and `tar_visnetwork()` will always show both targets as outdated. However, `tar_make()` will still skip the downstream one if the upstream target did not detect a change.

Value

A list of two target definition objects, one upstream and one downstream. The upstream one triggers the change, and the downstream one responds to it. See the "Target definition objects" section for background.

Target definition objects

Most `tarchetypes` functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

See Also

Other targets with custom invalidation rules: `tar_download()`, `tar_force()`, `tar_skip()`

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      list(
        tarchetypes::tar_change(x, command = tempfile(), change = tempfile())
      )
    })
    targets::tar_make()
    targets::tar_make()
  })
}
```

tar_combine

Static aggregation

Description

Aggregate the results of upstream targets into a new target.

`tar_combine()` expects unevaluated expressions for the name, and command arguments, whereas `tar_combine_raw()` uses a character string for name and an evaluated expression object for command. See the examples for details.

Usage

```

tar_combine(
  name,
  ...,
  command = vctrs::vec_c(!!!.x),
  use_names = TRUE,
  pattern = NULL,
  packages = targets::tar_option_get("packages"),
  library = targets::tar_option_get("library"),
  format = targets::tar_option_get("format"),
  repository = targets::tar_option_get("repository"),
  iteration = targets::tar_option_get("iteration"),
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),
  garbage_collection = targets::tar_option_get("garbage_collection"),
  deployment = targets::tar_option_get("deployment"),
  priority = targets::tar_option_get("priority"),
  resources = targets::tar_option_get("resources"),
  storage = targets::tar_option_get("storage"),
  retrieval = targets::tar_option_get("retrieval"),
  cue = targets::tar_option_get("cue"),
  description = targets::tar_option_get("description")
)

tar_combine_raw(
  name,
  ...,
  command = expression(vctrs::vec_c(!!!.x)),
  use_names = TRUE,
  pattern = NULL,
  packages = targets::tar_option_get("packages"),
  library = targets::tar_option_get("library"),
  format = targets::tar_option_get("format"),
  repository = targets::tar_option_get("repository"),
  iteration = targets::tar_option_get("iteration"),
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),
  garbage_collection = targets::tar_option_get("garbage_collection"),
  deployment = targets::tar_option_get("deployment"),
  priority = targets::tar_option_get("priority"),
  resources = targets::tar_option_get("resources"),
  storage = targets::tar_option_get("storage"),
  retrieval = targets::tar_option_get("retrieval"),
  cue = targets::tar_option_get("cue"),
  description = targets::tar_option_get("description")
)

```

Arguments

name	Name of the new target. <code>tar_combine()</code> expects unevaluated expressions for the name, and command arguments, whereas <code>tar_combine_raw()</code> uses a character string for name and an evaluated expression object for command. See the examples for details.
...	One or more target definition objects or list of target definition objects. Lists can be arbitrarily nested, as in <code>list()</code> .
command	R command to aggregate the targets. Must contain <code>!!!.x</code> where the arguments are to be inserted, where <code>!!!</code> is the unquote splice operator from <code>rlang</code> . <code>tar_combine()</code> expects unevaluated expressions for the name, and command arguments, whereas <code>tar_combine_raw()</code> uses a character string for name and an evaluated expression object for command. See the examples for details.
use_names	Logical, whether to insert the names of the targets into the command when splicing.
pattern	Code to define a dynamic branching for a target. In <code>tar_target()</code> , pattern is an unevaluated expression, e.g. <code>tar_target(pattern = map(data))</code> . In <code>tar_target_raw()</code> , command is an evaluated expression, e.g. <code>tar_target_raw(pattern = quote(map(data)))</code> . To demonstrate dynamic branching patterns, suppose we have a pipeline with numeric vector targets <code>x</code> and <code>y</code> . Then, <code>tar_target(z, x + y, pattern = map(x, y))</code> implicitly defines branches of <code>z</code> that each compute <code>x[1] + y[1]</code> , <code>x[2] + y[2]</code> , and so on. See the user manual for details.
packages	Character vector of packages to load right before the target runs or the output data is reloaded for downstream targets. Use <code>tar_option_set()</code> to set packages globally for all subsequent targets you define.
library	Character vector of library paths to try when loading packages.
format	Optional storage format for the target's return value. With the exception of <code>format = "file"</code> , each target gets a file in <code>_targets/objects</code> , and each format is a different way to save and load this file. See the "Storage formats" section for a detailed list of possible data storage formats.
repository	Character of length 1, remote repository for target storage. Choices: • "local": file system of the local machine. • "aws": Amazon Web Services (AWS) S3 bucket. Can be configured with a non-AWS S3 bucket using the endpoint argument of <code>tar_resources_aws()</code>, but versioning capabilities may be lost in doing so. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions. • "gcp": Google Cloud Platform storage bucket. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions. • A character string from <code>tar_repository_cas()</code> for content-addressable storage.

Note: if `repository` is not "local" and `format` is "file" then the target should create a single output file. That output file is uploaded to the cloud and

tracked for changes where it exists in the cloud. As of targets version 1.11.0 and higher, the local file is no longer deleted after the target runs.

iteration	Character of length 1, name of the iteration mode of the target. Choices: • "vector": branching happens with <code>vctrs::vec_slice()</code> and aggregation happens with <code>vctrs::vec_c()</code>. • "list", branching happens with <code>[[]]</code> and aggregation happens with <code>list()</code>. • "group": <code>dplyr::group_by()</code>-like functionality to branch over subsets of a non-dynamic data frame. For <code>iteration = "group"</code>, the target must not be dynamic (the <code>pattern</code> argument of <code>tar_target()</code> must be left <code>NULL</code>). The target's return value must be a data frame with a special <code>tar_group</code> column of consecutive integers from 1 through the number of groups. Each integer designates a group, and a branch is created for each collection of rows in a group. See the <code>tar_group()</code> function to see how you can create the special <code>tar_group</code> column with <code>dplyr::group_by()</code>.
error	Character of length 1, what to do if the target stops and throws an error. Options: • "stop": the whole pipeline stops and throws an error. • "continue": the whole pipeline keeps going. • "null": The errored target continues and returns <code>NULL</code>. The data hash is deliberately wrong so the target is not up to date for the next run of the pipeline. In addition, as of targets version 1.8.0.9011, a value of <code>NULL</code> is given to upstream dependencies with <code>error = "null"</code> if loading fails. • "abridge": any currently running targets keep running, but no new targets launch after that. • "trim": all currently running targets stay running. A queued target is allowed to start if: 1. It is not downstream of the error, and 2. It is not a sibling branch from the same <code>tar_target()</code> call (if the error happened in a dynamic branch). The idea is to avoid starting any new work that the immediate error impacts. <code>error = "trim"</code> is just like <code>error = "abridge"</code>, but it allows potentially healthy regions of the dependency graph to begin running. (Visit https://books.ropensci.org/targets/debugging.html to learn how to debug targets using saved workspaces.)
memory	Character of length 1, memory strategy. Possible values: • "auto" (default): equivalent to <code>memory = "transient"</code> in almost all cases. But to avoid superfluous reads from disk, <code>memory = "auto"</code> is equivalent to <code>memory = "persistent"</code> for non-dynamically-branched targets that other targets dynamically branch over. For example: if your pipeline has <code>tar_target(name = y, command = x, pattern = map(x))</code>, then <code>tar_target(name = x, command = f(), memory = "auto")</code> will use persistent memory for <code>x</code> in order to avoid rereading all of <code>x</code> for every branch of <code>y</code>. • "transient": the target gets unloaded after every new target completes. Either way, the target gets automatically loaded into memory whenever another target needs the value.

- "persistent": the target stays in memory until the end of the pipeline (unless storage is "worker", in which case targets unloads the value from memory right after storing it in order to avoid sending copious data over a network).

For cloud-based file targets (e.g. format = "file" with repository = "aws"), the memory option applies to the temporary local copy of the file: "persistent" means it remains until the end of the pipeline and is then deleted, and "transient" means it gets deleted as soon as possible. The former conserves bandwidth, and the latter conserves local storage.

garbage_collection

Logical: TRUE to run `base::gc()` just before the target runs, in whatever R process it is about to run (which could be a parallel worker). FALSE to omit garbage collection. Numeric values get converted to FALSE. The garbage_collection option in `tar_option_set()` is independent of the argument of the same name in `tar_target()`.

deployment

Character of length 1. If deployment is "main", then the target will run on the central controlling R process. Otherwise, if deployment is "worker" and you set up the pipeline with distributed/parallel computing, then the target runs on a parallel worker. For more on distributed/parallel computing in targets, please visit <https://books.ropensci.org/targets/crew.html>.

priority

Deprecated on 2025-04-08 (targets version 1.10.1.9013). targets has moved to a more efficient scheduling algorithm (<https://github.com/ropensci/targets/issues/1458>) which cannot support priorities. The priority argument of `tar_target()` no longer has a reliable effect on execution order.

resources

Object returned by `tar_resources()` with optional settings for high-performance computing functionality, alternative data storage formats, and other optional capabilities of targets. See `tar_resources()` for details.

storage

Character string to control when the output of the target is saved to storage. Only relevant when using targets with parallel workers (<https://books.ropensci.org/targets/crew.html>). Must be one of the following values:

- "worker" (default): the worker saves/uploads the value.
- "main": the target's return value is sent back to the host machine and saved/uploaded locally.
- "none": targets makes no attempt to save the result of the target to storage in the location where targets expects it to be. Saving to storage is the responsibility of the user. Use with caution.

retrieval

Character string to control when the current target loads its dependencies into memory before running. (Here, a "dependency" is another target upstream that the current one depends on.) Only relevant when using targets with parallel workers (<https://books.ropensci.org/targets/crew.html>). Must be one of the following values:

- "auto" (default): equivalent to retrieval = "worker" in almost all cases. But to avoid unnecessary reads from disk, retrieval = "auto" is equivalent to retrieval = "main" for dynamic branches that branch over non-dynamic targets. For example: if your pipeline has `tar_target(x, command = f())`, then `tar_target(y, command = x, pattern = map(x), retrieval`

	= "auto") will use "main" retrieval in order to avoid rereading all of x for every branch of y. • "worker": the worker loads the target's dependencies. • "main": the target's dependencies are loaded on the host machine and sent to the worker before the target runs. • "none": targets makes no attempt to load its dependencies. With retrieval = "none", loading dependencies is the responsibility of the user. Use with caution.
cue	An optional object from tar_cue() to customize the rules that decide whether the target is up to date.
description	Character of length 1, a custom free-form human-readable text description of the target. Descriptions appear as target labels in functions like tar_manifest() and tar_visnetwork(), and they let you select subsets of targets for the names argument of functions like tar_make(). For example, tar_manifest(names = tar_described_as(starts_with("survival model"))) lists all the targets whose descriptions start with the character string "survival model".

Value

A new target definition object to combine the return values from the upstream targets. See the "Target definition objects" section for background.

Target definition objects

Most tarchetypes functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

See Also

Other static branching: [tar_map\(\)](#)

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      library(tarchetypes)
      target1 <- tar_target(x, head(mtcars))
      target2 <- tar_target(y, tail(mtcars))
      target3 <- tar_combine(
        name = new_target_name,
        target1,
```

```

    target2,
    command = dplyr::bind_rows(!!!.x)
  )
  target4 <- tar_combine(
    name = new_target_name2,
    target1,
    target2,
    command = dplyr::bind_rows(!!!.x)
  )
  list(target1, target2, target3, target4)
})
targets::tar_make()
})
}
```

tar_cue_age

Cue to run a target when the last output reaches a certain age

Description

tar_cue_age() creates a cue object to rerun a target if the most recent output data becomes old enough. The age of the target is determined by targets::tar_timestamp(), and the way the time stamp is calculated is explained in the Details section of the help file of that function.

tar_cue_age() expects an unevaluated symbol for the name argument, whereas tar_cue_age_raw() expects a character string for name.

Usage

```

tar_cue_age(
  name,
  age,
  command = TRUE,
  depend = TRUE,
  format = TRUE,
  repository = TRUE,
  iteration = TRUE,
  file = TRUE
)

tar_cue_age_raw(
  name,
  age,
  command = TRUE,
  depend = TRUE,
  format = TRUE,
  repository = TRUE,
  iteration = TRUE,
  file = TRUE
)
```

Arguments

name	Name of the target. <code>tar_cue_age()</code> expects an unevaluated symbol for the name argument, whereas <code>tar_cue_age_raw()</code> expects a character string for name.
age	A <code>difftime</code> object of length 1, such as <code>as.difftime(3, units = "days")</code> . If the target's output data files are older than age (according to the most recent time stamp over all the target's output files) then the target will rerun. On the other hand, if at least one data file is younger than <code>Sys.time() - age</code> , then the ordinary invalidation rules apply, and the target may or not rerun. If you want to force the target to run every 3 days, for example, set <code>age = as.difftime(3, units = "days")</code> .
command	Logical, whether to rerun the target if command changed since last time.
depend	Logical, whether to rerun the target if the value of one of the dependencies changed.
format	Logical, whether to rerun the target if the user-specified storage format changed. The storage format is user-specified through <code>tar_target()</code> or <code>tar_option_set()</code> .
repository	Logical, whether to rerun the target if the user-specified storage repository changed. The storage repository is user-specified through <code>tar_target()</code> or <code>tar_option_set()</code> .
iteration	Logical, whether to rerun the target if the user-specified iteration method changed. The iteration method is user-specified through <code>tar_target()</code> or <code>tar_option_set()</code> .
file	Logical, whether to rerun the target if the file(s) with the return value changed or at least one is missing.

Details

`tar_cue_age()` uses the time stamps from `tar_meta()$time`. If no time stamp is recorded, the cue defaults to the ordinary invalidation rules (i.e. `mode = "thorough"` in `targets::tar_cue()`).

Value

A cue object. See the "Cue objects" section for background.

Dynamic branches at regular time intervals

Time stamps are not recorded for whole dynamic targets, so `tar_age()` is not a good fit for dynamic branching. To invalidate dynamic branches at regular intervals, it is recommended to use `targets::tar_older()` in combination with `targets::tar_invalidate()` right before calling `tar_make()`. For example, the call:

```
tar_invalidate(
  any_of(
    tar_older(Sys.time - as.difftime(1, units = "weeks"))
  )
)
```

invalidates all targets more than a week old. Then, the next `tar_make()` will rerun those targets.

Cue objects

A cue object is an object generated by `targets::tar_cue()`, `tarchetypes::tar_cue_force()`, or similar. It is a collection of decision rules that decide when a target is invalidated/outdated (e.g. when `tar_make()` or similar reruns the target). You can supply these cue objects to the `tar_target()` function or similar. For example, `tar_target(x, run_stuff(), cue = tar_cue(mode = "always"))` is a target that always calls `run_stuff()` during `tar_make()` and always shows as invalidated/outdated in `tar_outdated()`, `tar_visnetwork()`, and similar functions.

A cue object is an object generated by `targets::tar_cue()`, `tarchetypes::tar_cue_force()`, or similar. It is a collection of decision rules that decide when a target is invalidated/outdated (e.g. when `tar_make()` or similar reruns the target). You can supply these cue objects to the `tar_target()` function or similar. For example, `tar_target(x, run_stuff(), cue = tar_cue(mode = "always"))` is a target that always calls `run_stuff()` during `tar_make()` and always shows as invalidated/outdated in `tar_outdated()`, `tar_visnetwork()`, and similar functions.

See Also

Other cues: [tar_age\(\)](#), [tar_cue_force\(\)](#), [tar_cue_skip\(\)](#)

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      library(tarchetypes)
      list(
        targets::tar_target(
          data,
          data.frame(x = seq_len(26)),
          cue = tarchetypes::tar_cue_age(
            name = data,
            age = as.difftime(0.5, units = "secs")
          )
        )
      )
    })
  })
  targets::tar_make()
  Sys.sleep(0.6)
  targets::tar_make()
}
```

tar_cue_force

Cue to force a target to run if a condition is true

Description

`tar_cue_force()` creates a cue object to force a target to run if an arbitrary condition evaluates to TRUE. Supply the returned cue object to the `cue` argument of `targets::tar_target()` or similar.

Usage

```
tar_cue_force(
  condition,
  command = TRUE,
  depend = TRUE,
  format = TRUE,
  repository = TRUE,
  iteration = TRUE,
  file = TRUE
)
```

Arguments

condition	Logical vector evaluated locally when the target is defined. If any element of condition is TRUE, the target will definitely rerun when the pipeline runs. Otherwise, the target may or may not rerun, depending on the other invalidation rules. condition is evaluated when this cue factory is called, so the condition cannot depend on upstream targets, and it should be quick to calculate.
command	Logical, whether to rerun the target if command changed since last time.
depend	Logical, whether to rerun the target if the value of one of the dependencies changed.
format	Logical, whether to rerun the target if the user-specified storage format changed. The storage format is user-specified through tar_target() or tar_option_set() .
repository	Logical, whether to rerun the target if the user-specified storage repository changed. The storage repository is user-specified through tar_target() or tar_option_set() .
iteration	Logical, whether to rerun the target if the user-specified iteration method changed. The iteration method is user-specified through tar_target() or tar_option_set() .
file	Logical, whether to rerun the target if the file(s) with the return value changed or at least one is missing.

Details

`tar_cue_force()` and [tar_force\(\)](#) operate differently. The former defines a cue object based on an eagerly evaluated condition, and [tar_force\(\)](#) puts the condition in a special upstream target that always runs. Unlike `tar_cue_force()`, the condition in [tar_force\(\)](#) can depend on upstream targets, but the drawback is that targets defined with [tar_force\(\)](#) will always show up as outdated in functions like `tar_outdated()` and `tar_visnetwork()` even though `tar_make()` may still skip the main target if the condition is not met.

Value

A cue object. See the "Cue objects" section for background.

Cue objects

A cue object is an object generated by `targets::tar_cue()`, `tarchetypes::tar_cue_force()`, or similar. It is a collection of decision rules that decide when a target is invalidated/outdated

(e.g. when `tar_make()` or similar reruns the target). You can supply these cue objects to the `tar_target()` function or similar. For example, `tar_target(x, run_stuff(), cue = tar_cue(mode = "always"))` is a target that always calls `run_stuff()` during `tar_make()` and always shows as invalidated/outdated in `tar_outdated()`, `tar_visnetwork()`, and similar functions.

See Also

Other cues: `tar_age()`, `tar_cue_age()`, `tar_cue_skip()`

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      library(tarchetypes)
      list(
        targets::tar_target(
          data,
          data.frame(x = seq_len(26)),
          cue = tarchetypes::tar_cue_force(1 > 0)
        )
      )
    })
  })
  targets::tar_make()
  targets::tar_make()
}
```

tar_cue_skip

Cue to skip a target if a condition is true

Description

`tar_cue_skip()` creates a cue object to skip a target if an arbitrary condition evaluates to TRUE. The target still builds if it was never built before. Supply the returned cue object to the cue argument of `targets::tar_target()` or similar.

Usage

```
tar_cue_skip(
  condition,
  command = TRUE,
  depend = TRUE,
  format = TRUE,
  repository = TRUE,
  iteration = TRUE,
  file = TRUE
)
```

Arguments

condition	Logical vector evaluated locally when the target is defined. If any element of condition is TRUE, the pipeline will skip the target unless the target has never been built before. If all elements of condition are FALSE, then the target may or may not rerun, depending on the other invalidation rules. condition is evaluated when this cue factory is called, so the condition cannot depend on upstream targets, and it should be quick to calculate.
command	Logical, whether to rerun the target if command changed since last time.
depend	Logical, whether to rerun the target if the value of one of the dependencies changed.
format	Logical, whether to rerun the target if the user-specified storage format changed. The storage format is user-specified through <code>tar_target()</code> or <code>tar_option_set()</code> .
repository	Logical, whether to rerun the target if the user-specified storage repository changed. The storage repository is user-specified through <code>tar_target()</code> or <code>tar_option_set()</code> .
iteration	Logical, whether to rerun the target if the user-specified iteration method changed. The iteration method is user-specified through <code>tar_target()</code> or <code>tar_option_set()</code> .
file	Logical, whether to rerun the target if the file(s) with the return value changed or at least one is missing.

Value

A cue object. See the "Cue objects" section for background.

Cue objects

A cue object is an object generated by `targets::tar_cue()`, `tarchetypes::tar_cue_force()`, or similar. It is a collection of decision rules that decide when a target is invalidated/outdated (e.g. when `tar_make()` or similar reruns the target). You can supply these cue objects to the `tar_target()` function or similar. For example, `tar_target(x, run_stuff(), cue = tar_cue(mode = "always"))` is a target that always calls `run_stuff()` during `tar_make()` and always shows as invalidated/outdated in `tar_outdated()`, `tar_visnetwork()`, and similar functions.

See Also

Other cues: `tar_age()`, `tar_cue_age()`, `tar_cue_force()`

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      library(tarchetypes)
      list(
        targets::tar_target(
          data,
          data.frame(x = seq_len(26)),
          cue = tarchetypes::tar_cue_skip(1 > 0)
        )
      )
    })
  })
}
```

```

    )
  })
  targets::tar_make()
  targets::tar_script({
    library(tarchetypes)
    list(
      targets::tar_target(
        data,
        data.frame(x = seq_len(25)), # Change the command.
        cue = tarchetypes::tar_cue_skip(1 > 0)
      )
    )
  })
  targets::tar_make()
  targets::tar_make()
})
}

```

tar_download	<i>Target that downloads URLs.</i>
--------------	------------------------------------

Description

Create a target that downloads file from one or more URLs and automatically reruns when the remote data changes (according to the ETags or last-modified time stamps).

Usage

```

tar_download(
  name,
  urls,
  paths,
  method = NULL,
  quiet = TRUE,
  mode = "w",
  cacheOK = TRUE,
  extra = NULL,
  headers = NULL,
  iteration = targets::tar_option_get("iteration"),
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),
  garbage_collection = targets::tar_option_get("garbage_collection"),
  deployment = targets::tar_option_get("deployment"),
  priority = targets::tar_option_get("priority"),
  resources = targets::tar_option_get("resources"),
  storage = targets::tar_option_get("storage"),
  retrieval = targets::tar_option_get("retrieval"),
  cue = targets::tar_option_get("cue"),
  description = targets::tar_option_get("description")
)

```

Arguments

name	Symbol, name of the target. In <code>tar_target()</code>, name is an unevaluated symbol, e.g. <code>tar_target(name = data)</code>. In <code>tar_target_raw()</code>, name is a character string, e.g. <code>tar_target_raw(name = "data")</code>. A target name must be a valid name for a symbol in R, and it must not start with a dot. Subsequent targets can refer to this name symbolically to induce a dependency relationship: e.g. <code>tar_target(downstream_target, f(upstream_target))</code> is a target named <code>downstream_target</code> which depends on a target <code>upstream_target</code> and a function <code>f()</code>. In most cases, The target name is the name of its local data file in storage. Some file systems are not case sensitive, which means converting a name to a different case may overwrite a different target. Please ensure all target names have unique names when converted to lower case. In addition, a target's name determines its random number generator seed. In this way, each target runs with a reproducible seed so someone else running the same pipeline should get the same results, and no two targets in the same pipeline share the same seed. (Even dynamic branches have different names and thus different seeds.) You can recover the seed of a completed target with <code>tar_meta(your_target, seed)</code> and run <code>tar_seed_set()</code> on the result to locally recreate the target's initial RNG state.
urls	Character vector of URLs to track and download. Must be known and declared before the pipeline runs.
paths	Character vector of local file paths to download each of the URLs. Must be known and declared before the pipeline runs.
method	Method to be used for downloading files. Current download methods are "internal", "libcurl", "wget", "curl" and "wininet" (Windows only), and there is a value "auto": see 'Details' and 'Note'. The method can also be set through the option "download.file.method": see <code>options()</code>.
quiet	If TRUE, suppress status messages (if any), and the progress bar.
mode	character. The mode with which to write the file. Useful values are "w", "wb" (binary), "a" (append) and "ab". Not used for methods "wget" and "curl". See also 'Details', notably about using "wb" for Windows.
cacheOK	logical. Is a server-side cached value acceptable?
extra	character vector of additional command-line arguments for the "wget" and "curl" methods.
headers	named character vector of additional HTTP headers to use in HTTP[S] requests. It is ignored for non-HTTP[S] URLs. The User-Agent header taken from the HTTPUserAgent option (see <code>options()</code>) is automatically used as the first header.
iteration	Character of length 1, name of the iteration mode of the target. Choices: • "vector": branching happens with <code>vctrs::vec_slice()</code> and aggregation happens with <code>vctrs::vec_c()</code>. • "list", branching happens with <code>[[]]</code> and aggregation happens with <code>list()</code>.

- "group": `dplyr::group_by()`-like functionality to branch over subsets of a non-dynamic data frame. For `iteration = "group"`, the target must not be dynamic (the `pattern` argument of `tar_target()` must be left `NULL`). The target's return value must be a data frame with a special `tar_group` column of consecutive integers from 1 through the number of groups. Each integer designates a group, and a branch is created for each collection of rows in a group. See the `tar_group()` function to see how you can create the special `tar_group` column with `dplyr::group_by()`.

error

Character of length 1, what to do if the target stops and throws an error. Options:

- "stop": the whole pipeline stops and throws an error.
- "continue": the whole pipeline keeps going.
- "null": The errored target continues and returns `NULL`. The data hash is deliberately wrong so the target is not up to date for the next run of the pipeline. In addition, as of targets version 1.8.0.9011, a value of `NULL` is given to upstream dependencies with `error = "null"` if loading fails.
- "abridge": any currently running targets keep running, but no new targets launch after that.
- "trim": all currently running targets stay running. A queued target is allowed to start if:
 1. It is not downstream of the error, and
 2. It is not a sibling branch from the same `tar_target()` call (if the error happened in a dynamic branch).

The idea is to avoid starting any new work that the immediate error impacts. `error = "trim"` is just like `error = "abridge"`, but it allows potentially healthy regions of the dependency graph to begin running. (Visit <https://books.ropensci.org/targets/debugging.html> to learn how to debug targets using saved workspaces.)

memory

Character of length 1, memory strategy. Possible values:

- "auto" (default): equivalent to `memory = "transient"` in almost all cases. But to avoid superfluous reads from disk, `memory = "auto"` is equivalent to `memory = "persistent"` for non-dynamically-branched targets that other targets dynamically branch over. For example: if your pipeline has `tar_target(name = y, command = x, pattern = map(x))`, then `tar_target(name = x, command = f(), memory = "auto")` will use persistent memory for `x` in order to avoid rereading all of `x` for every branch of `y`.
- "transient": the target gets unloaded after every new target completes. Either way, the target gets automatically loaded into memory whenever another target needs the value.
- "persistent": the target stays in memory until the end of the pipeline (unless `storage = "worker"`, in which case targets unloads the value from memory right after storing it in order to avoid sending copious data over a network).

For cloud-based file targets (e.g. `format = "file"` with `repository = "aws"`), the memory option applies to the temporary local copy of the file: "persistent" means it remains until the end of the pipeline and is then deleted, and "transient" means it gets deleted as soon as possible. The former conserves bandwidth, and the latter conserves local storage.

garbage_collection	Logical: TRUE to run <code>base::gc()</code> just before the target runs, in whatever R process it is about to run (which could be a parallel worker). FALSE to omit garbage collection. Numeric values get converted to FALSE. The <code>garbage_collection</code> option in <code>tar_option_set()</code> is independent of the argument of the same name in <code>tar_target()</code> .
deployment	Character of length 1. If deployment is "main", then the target will run on the central controlling R process. Otherwise, if deployment is "worker" and you set up the pipeline with distributed/parallel computing, then the target runs on a parallel worker. For more on distributed/parallel computing in targets, please visit https://books.ropensci.org/targets/crew.html .
priority	Deprecated on 2025-04-08 (targets version 1.10.1.9013). targets has moved to a more efficient scheduling algorithm (https://github.com/ropensci/targets/issues/1458) which cannot support priorities. The <code>priority</code> argument of <code>tar_target()</code> no longer has a reliable effect on execution order.
resources	Object returned by <code>tar_resources()</code> with optional settings for high-performance computing functionality, alternative data storage formats, and other optional capabilities of targets. See <code>tar_resources()</code> for details.
storage	Character string to control when the output of the target is saved to storage. Only relevant when using targets with parallel workers (https://books.ropensci.org/targets/crew.html). Must be one of the following values: • "worker" (default): the worker saves/uploads the value. • "main": the target's return value is sent back to the host machine and saved/uploaded locally. • "none": targets makes no attempt to save the result of the target to storage in the location where targets expects it to be. Saving to storage is the responsibility of the user. Use with caution.
retrieval	Character string to control when the current target loads its dependencies into memory before running. (Here, a "dependency" is another target upstream that the current one depends on.) Only relevant when using targets with parallel workers (https://books.ropensci.org/targets/crew.html). Must be one of the following values: • "auto" (default): equivalent to <code>retrieval = "worker"</code> in almost all cases. But to avoid unnecessary reads from disk, <code>retrieval = "auto"</code> is equivalent to <code>retrieval = "main"</code> for dynamic branches that branch over non-dynamic targets. For example: if your pipeline has <code>tar_target(x, command = f())</code>, then <code>tar_target(y, command = x, pattern = map(x), retrieval = "auto")</code> will use "main" retrieval in order to avoid rereading all of <code>x</code> for every branch of <code>y</code>. • "worker": the worker loads the target's dependencies. • "main": the target's dependencies are loaded on the host machine and sent to the worker before the target runs. • "none": targets makes no attempt to load its dependencies. With <code>retrieval = "none"</code>, loading dependencies is the responsibility of the user. Use with caution.

cue	An optional object from <code>tar_cue()</code> to customize the rules that decide whether the target is up to date.
description	Character of length 1, a custom free-form human-readable text description of the target. Descriptions appear as target labels in functions like <code>tar_manifest()</code> and <code>tar_visnetwork()</code> , and they let you select subsets of targets for the <code>names</code> argument of functions like <code>tar_make()</code> . For example, <code>tar_manifest(names = tar_described_as(starts_with("survival model")))</code> lists all the targets whose descriptions start with the character string "survival model".

Details

`tar_download()` creates a pair of targets, one upstream and one downstream. The upstream target uses `format = "url"` (see `targets::tar_target()`) to track files at one or more URLs, and automatically invalidate the target if the ETags or last-modified time stamps change. The downstream target depends on the upstream one, downloads the files, and tracks them using `format = "file"`.

Value

A list of two target definition objects, one upstream and one downstream. The upstream one watches a URL for changes, and the downstream one downloads it. See the "Target definition objects" section for background.

Target definition objects

Most tarchetypes functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

See Also

Other targets with custom invalidation rules: `tar_change()`, `tar_force()`, `tar_skip()`

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      list(
        tarchetypes::tar_download(
          x,
          urls = c("https://httpbin.org/etag/test", "https://r-project.org"),
          paths = c("downloaded_file_1", "downloaded_file_2")
        )
      )
    })
  })
}
```

```

}))
targets::tar_make()
targets::tar_read(x)
}))
}

```

tar_eval

*Evaluate multiple expressions created with symbol substitution.***Description**

Loop over a grid of values, create an expression object from each one, and then evaluate that expression. Helps with general metaprogramming.

`tar_eval()` expects an unevaluated expression for the `expr` object, whereas `tar_eval_raw()` expects an evaluated expression object.

Usage

```
tar_eval(expr, values, envir = parent.frame())
```

```
tar_eval_raw(expr, values, envir = parent.frame())
```

Arguments

<code>expr</code>	Starting expression. Values are iteratively substituted in place of symbols in <code>expr</code> to create each new expression, and then each new expression is evaluated. <code>tar_eval()</code> expects an unevaluated expression for the <code>expr</code> object, whereas <code>tar_eval_raw()</code> expects an evaluated expression object.
<code>values</code>	List of values to substitute into <code>expr</code> to create the expressions. All elements of <code>values</code> must have the same length.
<code>envir</code>	Environment in which to evaluate the new expressions.

Value

A list of return values from the generated expression objects. Often, these values are target definition objects. See the "Target definition objects" section for background on target definition objects specifically.

Target definition objects

Most tarchetypes functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

See Also

Other Metaprogramming utilities: `tar_sub()`

Examples

```
# tar_map() is incompatible with tar_render() because the latter
# operates on preexisting tar_target() objects. By contrast,
# tar_eval() and tar_sub() iterate over the literal code
# farther upstream.
values <- list(
  name = lapply(c("name1", "name2"), as.symbol),
  file = list("file1.Rmd", "file2.Rmd")
)
tar_sub(list(name, file), values = values)
tar_sub(tar_render(name, file), values = values)
path <- tempfile()
file.create(path)
str(tar_eval(tar_render(name, path), values = values))
str(tar_eval_raw(quote(tar_render(name, path)), values = values))
# So in your _targets.R file, you can define a pipeline like as below.
# Just make sure to set a unique name for each target
# (which tar_map() does automatically).
values <- list(
  name = lapply(c("name1", "name2"), as.symbol),
  file = c(path, path)
)
list(
  tar_eval(tar_render(name, file), values = values)
)
```

tar_file_read

Track a file and read the contents.

Description

Create a pair of targets: one to track a file with `format = "file"`, and another to read the file.

Usage

```
tar_file_read(
  name,
  command,
  read,
```

```

tidy_eval = targets::tar_option_get("tidy_eval"),
packages = targets::tar_option_get("packages"),
library = targets::tar_option_get("library"),
format = targets::tar_option_get("format"),
format_file = c("file", "file_fast"),
repository = targets::tar_option_get("repository"),
error = targets::tar_option_get("error"),
memory = targets::tar_option_get("memory"),
garbage_collection = targets::tar_option_get("garbage_collection"),
deployment = targets::tar_option_get("deployment"),
priority = targets::tar_option_get("priority"),
resources = targets::tar_option_get("resources"),
storage = targets::tar_option_get("storage"),
retrieval = targets::tar_option_get("retrieval"),
cue = targets::tar_option_get("cue"),
description = targets::tar_option_get("description")
)

```

Arguments

name	Symbol, name of the target. In <code>tar_target()</code>, name is an unevaluated symbol, e.g. <code>tar_target(name = data)</code>. In <code>tar_target_raw()</code>, name is a character string, e.g. <code>tar_target_raw(name = "data")</code>. A target name must be a valid name for a symbol in R, and it must not start with a dot. Subsequent targets can refer to this name symbolically to induce a dependency relationship: e.g. <code>tar_target(downstream_target, f(upstream_target))</code> is a target named <code>downstream_target</code> which depends on a target <code>upstream_target</code> and a function <code>f()</code>. In most cases, The target name is the name of its local data file in storage. Some file systems are not case sensitive, which means converting a name to a different case may overwrite a different target. Please ensure all target names have unique names when converted to lower case. In addition, a target's name determines its random number generator seed. In this way, each target runs with a reproducible seed so someone else running the same pipeline should get the same results, and no two targets in the same pipeline share the same seed. (Even dynamic branches have different names and thus different seeds.) You can recover the seed of a completed target with <code>tar_meta(your_target, seed)</code> and run <code>tar_seed_set()</code> on the result to locally recreate the target's initial RNG state.
command	R code that runs in the <code>format = "file"</code> target and returns the file to be tracked.
read	R code to read the file. Must include <code>!! .x</code> where the file path goes: for example, <code>read = readr::read_csv(file = !!.x, col_types = readr::cols())</code> .
tidy_eval	Logical, whether to enable tidy evaluation when interpreting command and pattern. If TRUE, you can use the "bang-bang" operator <code>!!</code> to programmatically insert the values of global objects.
packages	Character vector of packages to load right before the target runs or the output data is reloaded for downstream targets. Use <code>tar_option_set()</code> to set packages globally for all subsequent targets you define.

library	Character vector of library paths to try when loading packages.
format	Optional storage format for the target's return value. With the exception of <code>format = "file"</code> , each target gets a file in <code>_targets/objects</code> , and each format is a different way to save and load this file. See the "Storage formats" section for a detailed list of possible data storage formats.
format_file	Storage format of the file target, either <code>"file"</code> or <code>"file_fast"</code> .
repository	Character of length 1, remote repository for target storage. Choices: • <code>"local"</code>: file system of the local machine. • <code>"aws"</code>: Amazon Web Services (AWS) S3 bucket. Can be configured with a non-AWS S3 bucket using the <code>endpoint</code> argument of <code>tar_resources_aws()</code>, but versioning capabilities may be lost in doing so. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions. • <code>"gcp"</code>: Google Cloud Platform storage bucket. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions. • A character string from <code>tar_repository_cas()</code> for content-addressable storage. Note: if <code>repository</code> is not <code>"local"</code> and <code>format</code> is <code>"file"</code> then the target should create a single output file. That output file is uploaded to the cloud and tracked for changes where it exists in the cloud. As of <code>targets</code> version 1.11.0 and higher, the local file is no longer deleted after the target runs.
error	Character of length 1, what to do if the target stops and throws an error. Options: • <code>"stop"</code>: the whole pipeline stops and throws an error. • <code>"continue"</code>: the whole pipeline keeps going. • <code>"null"</code>: The errored target continues and returns <code>NULL</code>. The data hash is deliberately wrong so the target is not up to date for the next run of the pipeline. In addition, as of <code>targets</code> version 1.8.0.9011, a value of <code>NULL</code> is given to upstream dependencies with <code>error = "null"</code> if loading fails. • <code>"abridge"</code>: any currently running targets keep running, but no new targets launch after that. • <code>"trim"</code>: all currently running targets stay running. A queued target is allowed to start if: 1. It is not downstream of the error, and 2. It is not a sibling branch from the same <code>tar_target()</code> call (if the error happened in a dynamic branch). The idea is to avoid starting any new work that the immediate error impacts. <code>error = "trim"</code> is just like <code>error = "abridge"</code>, but it allows potentially healthy regions of the dependency graph to begin running. (Visit https://books.ropensci.org/targets/debugging.html to learn how to debug targets using saved workspaces.)
memory	Character of length 1, memory strategy. Possible values: • <code>"auto"</code> (default): equivalent to <code>memory = "transient"</code> in almost all cases. But to avoid superfluous reads from disk, <code>memory = "auto"</code> is equivalent

to memory = "persistent" for non-dynamically-branched targets that other targets dynamically branch over. For example: if your pipeline has `tar_target(name = y, command = x, pattern = map(x))`, then `tar_target(name = x, command = f(), memory = "auto")` will use persistent memory for x in order to avoid rereading all of x for every branch of y.

- "transient": the target gets unloaded after every new target completes. Either way, the target gets automatically loaded into memory whenever another target needs the value.
- "persistent": the target stays in memory until the end of the pipeline (unless storage is "worker", in which case targets unloads the value from memory right after storing it in order to avoid sending copious data over a network).

For cloud-based file targets (e.g. format = "file" with repository = "aws"), the memory option applies to the temporary local copy of the file: "persistent" means it remains until the end of the pipeline and is then deleted, and "transient" means it gets deleted as soon as possible. The former conserves bandwidth, and the latter conserves local storage.

garbage_collection

Logical: TRUE to run `base::gc()` just before the target runs, in whatever R process it is about to run (which could be a parallel worker). FALSE to omit garbage collection. Numeric values get converted to FALSE. The `garbage_collection` option in `tar_option_set()` is independent of the argument of the same name in `tar_target()`.

deployment

Character of length 1. If deployment is "main", then the target will run on the central controlling R process. Otherwise, if deployment is "worker" and you set up the pipeline with distributed/parallel computing, then the target runs on a parallel worker. For more on distributed/parallel computing in targets, please visit <https://books.ropensci.org/targets/crew.html>.

priority

Deprecated on 2025-04-08 (targets version 1.10.1.9013). targets has moved to a more efficient scheduling algorithm (<https://github.com/ropensci/targets/issues/1458>) which cannot support priorities. The `priority` argument of `tar_target()` no longer has a reliable effect on execution order.

resources

Object returned by `tar_resources()` with optional settings for high-performance computing functionality, alternative data storage formats, and other optional capabilities of targets. See `tar_resources()` for details.

storage

Character string to control when the output of the target is saved to storage. Only relevant when using targets with parallel workers (<https://books.ropensci.org/targets/crew.html>). Must be one of the following values:

- "worker" (default): the worker saves/uploads the value.
- "main": the target's return value is sent back to the host machine and saved/uploaded locally.
- "none": targets makes no attempt to save the result of the target to storage in the location where targets expects it to be. Saving to storage is the responsibility of the user. Use with caution.

retrieval

Character string to control when the current target loads its dependencies into memory before running. (Here, a "dependency" is another target upstream that

the current one depends on.) Only relevant when using targets with parallel workers (<https://books.ropensci.org/targets/crew.html>). Must be one of the following values:

- "auto" (default): equivalent to `retrieval = "worker"` in almost all cases. But to avoid unnecessary reads from disk, `retrieval = "auto"` is equivalent to `retrieval = "main"` for dynamic branches that branch over non-dynamic targets. For example: if your pipeline has `tar_target(x, command = f())`, then `tar_target(y, command = x, pattern = map(x), retrieval = "auto")` will use "main" retrieval in order to avoid rereading all of `x` for every branch of `y`.
- "worker": the worker loads the target's dependencies.
- "main": the target's dependencies are loaded on the host machine and sent to the worker before the target runs.
- "none": targets makes no attempt to load its dependencies. With `retrieval = "none"`, loading dependencies is the responsibility of the user. Use with caution.

cue	An optional object from <code>tar_cue()</code> to customize the rules that decide whether the target is up to date.
description	Character of length 1, a custom free-form human-readable text description of the target. Descriptions appear as target labels in functions like <code>tar_manifest()</code> and <code>tar_visnetwork()</code> , and they let you select subsets of targets for the <code>names</code> argument of functions like <code>tar_make()</code> . For example, <code>tar_manifest(names = tar_described_as(starts_with("survival model")))</code> lists all the targets whose descriptions start with the character string "survival model".

Value

A list of two new target definition objects to track a file and read the contents. See the "Target definition objects" section for background.

Target definition objects

Most tarchetypes functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      tar_file_read(data, get_path(), read_csv(file = !!x, col_types = cols()))
    })
  })
}
```

```

}))
targets::tar_manifest()
}))
}

```

tar_files

Dynamic branching over output or input files.

Description

Dynamic branching over output or input files. `tar_files()` expects a unevaluated symbol for the name argument and an unevaluated expression for command, whereas `tar_files_raw()` expects a character string for the name argument and an evaluated expression object for command. See the examples for a demo.

Usage

```

tar_files(
  name,
  command,
  tidy_eval = targets::tar_option_get("tidy_eval"),
  packages = targets::tar_option_get("packages"),
  library = targets::tar_option_get("library"),
  format = c("file", "file_fast", "url", "aws_file"),
  repository = targets::tar_option_get("repository"),
  iteration = targets::tar_option_get("iteration"),
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),
  garbage_collection = targets::tar_option_get("garbage_collection"),
  deployment = targets::tar_option_get("deployment"),
  priority = targets::tar_option_get("priority"),
  resources = targets::tar_option_get("resources"),
  storage = targets::tar_option_get("storage"),
  retrieval = targets::tar_option_get("retrieval"),
  cue = targets::tar_option_get("cue"),
  description = targets::tar_option_get("description")
)

tar_files_raw(
  name,
  command,
  packages = targets::tar_option_get("packages"),
  library = targets::tar_option_get("library"),
  format = c("file", "url", "aws_file", "file_fast"),
  repository = targets::tar_option_get("repository"),
  iteration = targets::tar_option_get("iteration"),
  error = targets::tar_option_get("error"),

```

```

memory = targets::tar_option_get("memory"),
garbage_collection = targets::tar_option_get("garbage_collection"),
deployment = targets::tar_option_get("deployment"),
priority = targets::tar_option_get("priority"),
resources = targets::tar_option_get("resources"),
storage = targets::tar_option_get("storage"),
retrieval = targets::tar_option_get("retrieval"),
cue = targets::tar_option_get("cue"),
description = targets::tar_option_get("description")
)

```

Arguments

name	Name of the target. <code>tar_files()</code> expects a unevaluated symbol for the name argument and an unevaluated expression for command, whereas <code>tar_files_raw()</code> expects a character string for the name argument and an evaluated expression object for command. See the examples for a demo.
command	R command for the target. <code>tar_files()</code> expects a unevaluated symbol for the name argument and an unevaluated expression for command, whereas <code>tar_files_raw()</code> expects a character string for the name argument and an evaluated expression object for command. See the examples for a demo.
tidy_eval	Logical, whether to enable tidy evaluation when interpreting command and pattern. If TRUE, you can use the "bang-bang" operator <code>!!</code> to programmatically insert the values of global objects.
packages	Character vector of packages to load right before the target runs or the output data is reloaded for downstream targets. Use <code>tar_option_set()</code> to set packages globally for all subsequent targets you define.
library	Character vector of library paths to try when loading packages.
format	Character of length 1. Must be "file", "url", or "aws_file". See the format argument of <code>targets::tar_target()</code> for details.
repository	Character of length 1, remote repository for target storage. Choices: • "local": file system of the local machine. • "aws": Amazon Web Services (AWS) S3 bucket. Can be configured with a non-AWS S3 bucket using the endpoint argument of <code>tar_resources_aws()</code>, but versioning capabilities may be lost in doing so. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions. • "gcp": Google Cloud Platform storage bucket. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions. • A character string from <code>tar_repository_cas()</code> for content-addressable storage.

Note: if repository is not "local" and format is "file" then the target should create a single output file. That output file is uploaded to the cloud and tracked for changes where it exists in the cloud. As of targets version 1.11.0 and higher, the local file is no longer deleted after the target runs.

iteration	Character of length 1, name of the iteration mode of the target. Choices: • "vector": branching happens with <code>vctrs::vec_slice()</code> and aggregation happens with <code>vctrs::vec_c()</code>. • "list", branching happens with <code>[[]]</code> and aggregation happens with <code>list()</code>. • "group": <code>dplyr::group_by()</code>-like functionality to branch over subsets of a non-dynamic data frame. For <code>iteration = "group"</code>, the target must not be dynamic (the <code>pattern</code> argument of <code>tar_target()</code> must be left <code>NULL</code>). The target's return value must be a data frame with a special <code>tar_group</code> column of consecutive integers from 1 through the number of groups. Each integer designates a group, and a branch is created for each collection of rows in a group. See the <code>tar_group()</code> function to see how you can create the special <code>tar_group</code> column with <code>dplyr::group_by()</code>.
error	Character of length 1, what to do if the target stops and throws an error. Options: • "stop": the whole pipeline stops and throws an error. • "continue": the whole pipeline keeps going. • "null": The errored target continues and returns <code>NULL</code>. The data hash is deliberately wrong so the target is not up to date for the next run of the pipeline. In addition, as of targets version 1.8.0.9011, a value of <code>NULL</code> is given to upstream dependencies with <code>error = "null"</code> if loading fails. • "abridge": any currently running targets keep running, but no new targets launch after that. • "trim": all currently running targets stay running. A queued target is allowed to start if: 1. It is not downstream of the error, and 2. It is not a sibling branch from the same <code>tar_target()</code> call (if the error happened in a dynamic branch). The idea is to avoid starting any new work that the immediate error impacts. <code>error = "trim"</code> is just like <code>error = "abridge"</code>, but it allows potentially healthy regions of the dependency graph to begin running. (Visit https://books.ropensci.org/targets/debugging.html to learn how to debug targets using saved workspaces.)
memory	Character of length 1, memory strategy. Possible values: • "auto" (default): equivalent to <code>memory = "transient"</code> in almost all cases. But to avoid superfluous reads from disk, <code>memory = "auto"</code> is equivalent to <code>memory = "persistent"</code> for non-dynamically-branched targets that other targets dynamically branch over. For example: if your pipeline has <code>tar_target(name = y, command = x, pattern = map(x))</code>, then <code>tar_target(name = x, command = f(), memory = "auto")</code> will use persistent memory for <code>x</code> in order to avoid rereading all of <code>x</code> for every branch of <code>y</code>. • "transient": the target gets unloaded after every new target completes. Either way, the target gets automatically loaded into memory whenever another target needs the value. • "persistent": the target stays in memory until the end of the pipeline (unless <code>storage</code> is "worker", in which case targets unloads the value from memory right after storing it in order to avoid sending copious data over a network).

For cloud-based file targets (e.g. `format = "file"` with `repository = "aws"`), the memory option applies to the temporary local copy of the file: "persistent" means it remains until the end of the pipeline and is then deleted, and "transient" means it gets deleted as soon as possible. The former conserves bandwidth, and the latter conserves local storage.

garbage_collection	Logical: TRUE to run <code>base::gc()</code> just before the target runs, in whatever R process it is about to run (which could be a parallel worker). FALSE to omit garbage collection. Numeric values get converted to FALSE. The <code>garbage_collection</code> option in <code>tar_option_set()</code> is independent of the argument of the same name in <code>tar_target()</code> .
deployment	Character of length 1. If deployment is "main", then the target will run on the central controlling R process. Otherwise, if deployment is "worker" and you set up the pipeline with distributed/parallel computing, then the target runs on a parallel worker. For more on distributed/parallel computing in targets, please visit https://books.ropensci.org/targets/crew.html .
priority	Deprecated on 2025-04-08 (targets version 1.10.1.9013). targets has moved to a more efficient scheduling algorithm (https://github.com/ropensci/targets/issues/1458) which cannot support priorities. The <code>priority</code> argument of <code>tar_target()</code> no longer has a reliable effect on execution order.
resources	Object returned by <code>tar_resources()</code> with optional settings for high-performance computing functionality, alternative data storage formats, and other optional capabilities of targets. See <code>tar_resources()</code> for details.
storage	Character string to control when the output of the target is saved to storage. Only relevant when using targets with parallel workers (https://books.ropensci.org/targets/crew.html). Must be one of the following values: "worker" (default): the worker saves/uploads the value. "main": the target's return value is sent back to the host machine and saved/uploaded locally. "none": targets makes no attempt to save the result of the target to storage in the location where targets expects it to be. Saving to storage is the responsibility of the user. Use with caution.
retrieval	Character string to control when the current target loads its dependencies into memory before running. (Here, a "dependency" is another target upstream that the current one depends on.) Only relevant when using targets with parallel workers (https://books.ropensci.org/targets/crew.html). Must be one of the following values: "auto" (default): equivalent to <code>retrieval = "worker"</code> in almost all cases. But to avoid unnecessary reads from disk, <code>retrieval = "auto"</code> is equivalent to <code>retrieval = "main"</code> for dynamic branches that branch over non-dynamic targets. For example: if your pipeline has <code>tar_target(x, command = f())</code>, then <code>tar_target(y, command = x, pattern = map(x), retrieval = "auto")</code> will use "main" retrieval in order to avoid rereading all of x for every branch of y. "worker": the worker loads the target's dependencies.

	• "main": the target's dependencies are loaded on the host machine and sent to the worker before the target runs. • "none": targets makes no attempt to load its dependencies. With <code>retrieval = "none"</code>, loading dependencies is the responsibility of the user. Use with caution.
cue	An optional object from <code>tar_cue()</code> to customize the rules that decide whether the target is up to date. Only applies to the downstream target. The upstream target always runs.
description	Character of length 1, a custom free-form human-readable text description of the target. Descriptions appear as target labels in functions like <code>tar_manifest()</code> and <code>tar_visnetwork()</code> , and they let you select subsets of targets for the <code>names</code> argument of functions like <code>tar_make()</code> . For example, <code>tar_manifest(names = tar_described_as(starts_with("survival model")))</code> lists all the targets whose descriptions start with the character string "survival model".

Details

`tar_files()` creates a pair of targets, one upstream and one downstream.

The upstream target runs the command given by the `command` argument, and it should return a character vector of file paths. This upstream target needs to run on every `targets::tar_make()` because it needs to recheck which files are generated on disk. If your files are input files (not generated by the pipeline itself) and you do not want to rerun the upstream target every pipeline, use `tar_files_input()` instead.

The downstream target is a dynamic branching target that applies `format = "file"` (or `format = "url"`) to track changes in the files. (URLs are input-only, they must already exist beforehand.)

This approach correctly dynamically branches over individual files. It makes sure any downstream dynamic branches only rerun *some* of their branches if the files/urls change. For more information, visit <https://github.com/ropensci/targets/issues/136> and <https://github.com/ropensci/drake/issues/1302>.

Value

A list of two targets, one upstream and one downstream. The upstream one does some work and returns some file paths, and the downstream target is a pattern that applies `format = "file"` or `format = "url"`. See the "Target definition objects" section for background.

Target definition objects

Most `tarchetypes` functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

See Also

Other Dynamic branching over files: [tar_files_input\(\)](#)

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      library(tarchetypes)
      # Do not use temp files in real projects
      # or else your targets will always rerun.
      paths <- unlist(replicate(2, tempfile()))
      file.create(paths)
      list(
        tar_files(name = x, command = paths),
        tar_files_raw(name = "y", command = quote(paths))
      )
    })
  })
  targets::tar_make()
  targets::tar_read(x)
}
```

tar_files_input

Dynamic branching over input files or URLs

Description

Dynamic branching over input files or URLs.

[tar_files_input\(\)](#) expects a unevaluated symbol for the name argument, whereas [tar_files_input_raw\(\)](#) expects a character string for name. See the examples for a demo.

Usage

```
tar_files_input(
  name,
  files,
  batches = length(files),
  format = c("file", "file_fast", "url", "aws_file"),
  repository = targets::tar_option_get("repository"),
  iteration = targets::tar_option_get("iteration"),
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),
  garbage_collection = targets::tar_option_get("garbage_collection"),
  priority = targets::tar_option_get("priority"),
  resources = targets::tar_option_get("resources"),
  cue = targets::tar_option_get("cue"),
  description = targets::tar_option_get("description")
)
```

```

)

tar_files_input_raw(
  name,
  files,
  batches = length(files),
  format = c("file", "file_fast", "url", "aws_file"),
  repository = targets::tar_option_get("repository"),
  iteration = targets::tar_option_get("iteration"),
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),
  garbage_collection = targets::tar_option_get("garbage_collection"),
  priority = targets::tar_option_get("priority"),
  resources = targets::tar_option_get("resources"),
  cue = targets::tar_option_get("cue"),
  description = targets::tar_option_get("description")
)

```

Arguments

name	Name of the target. <code>tar_files_input()</code> expects a unevaluated symbol for the name argument, whereas <code>tar_files_input_raw()</code> expects a character string for name. See the examples for a demo.
files	Nonempty character vector of known existing input files to track for changes.
batches	Positive integer of length 1, number of batches to partition the files. The default is one file per batch (maximum number of batches) which is simplest to handle but could cause a lot of overhead and consume a lot of computing resources. Consider reducing the number of batches below the number of files for heavy workloads.
format	Character, either "file", "file_fast", or "url". See the format argument of <code>targets::tar_target()</code> for details.
repository	Character of length 1, remote repository for target storage. Choices: • "local": file system of the local machine. • "aws": Amazon Web Services (AWS) S3 bucket. Can be configured with a non-AWS S3 bucket using the endpoint argument of <code>tar_resources_aws()</code>, but versioning capabilities may be lost in doing so. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions. • "gcp": Google Cloud Platform storage bucket. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions. • A character string from <code>tar_repository_cas()</code> for content-addressable storage.

Note: if repository is not "local" and format is "file" then the target should create a single output file. That output file is uploaded to the cloud and tracked for changes where it exists in the cloud. As of targets version 1.11.0 and higher, the local file is no longer deleted after the target runs.

iteration	Character, iteration method. Must be a method supported by the iteration argument of <code>targets::tar_target()</code> . The iteration method for the upstream target is always "list" in order to support batching.
error	Character of length 1, what to do if the target stops and throws an error. Options: • "stop": the whole pipeline stops and throws an error. • "continue": the whole pipeline keeps going. • "null": The errored target continues and returns NULL. The data hash is deliberately wrong so the target is not up to date for the next run of the pipeline. In addition, as of targets version 1.8.0.9011, a value of NULL is given to upstream dependencies with <code>error = "null"</code> if loading fails. • "abridge": any currently running targets keep running, but no new targets launch after that. • "trim": all currently running targets stay running. A queued target is allowed to start if: 1. It is not downstream of the error, and 2. It is not a sibling branch from the same <code>tar_target()</code> call (if the error happened in a dynamic branch). The idea is to avoid starting any new work that the immediate error impacts. <code>error = "trim"</code> is just like <code>error = "abridge"</code>, but it allows potentially healthy regions of the dependency graph to begin running. (Visit https://books.ropensci.org/targets/debugging.html to learn how to debug targets using saved workspaces.)
memory	Character of length 1, memory strategy. Possible values: • "auto" (default): equivalent to <code>memory = "transient"</code> in almost all cases. But to avoid superfluous reads from disk, <code>memory = "auto"</code> is equivalent to <code>memory = "persistent"</code> for non-dynamically-branched targets that other targets dynamically branch over. For example: if your pipeline has <code>tar_target(name = y, command = x, pattern = map(x))</code>, then <code>tar_target(name = x, command = f(), memory = "auto")</code> will use persistent memory for <code>x</code> in order to avoid rereading all of <code>x</code> for every branch of <code>y</code>. • "transient": the target gets unloaded after every new target completes. Either way, the target gets automatically loaded into memory whenever another target needs the value. • "persistent": the target stays in memory until the end of the pipeline (unless storage is "worker", in which case targets unloads the value from memory right after storing it in order to avoid sending copious data over a network). For cloud-based file targets (e.g. <code>format = "file"</code> with <code>repository = "aws"</code>), the memory option applies to the temporary local copy of the file: "persistent" means it remains until the end of the pipeline and is then deleted, and "transient" means it gets deleted as soon as possible. The former conserves bandwidth, and the latter conserves local storage.
garbage_collection	Logical: TRUE to run <code>base::gc()</code> just before the target runs, in whatever R process it is about to run (which could be a parallel worker). FALSE to omit garbage

	collection. Numeric values get converted to FALSE. The garbage_collection option in <code>tar_option_set()</code> is independent of the argument of the same name in <code>tar_target()</code> .
priority	Deprecated on 2025-04-08 (targets version 1.10.1.9013). targets has moved to a more efficient scheduling algorithm (https://github.com/ropensci/targets/issues/1458) which cannot support priorities. The priority argument of <code>tar_target()</code> no longer has a reliable effect on execution order.
resources	Object returned by <code>tar_resources()</code> with optional settings for high-performance computing functionality, alternative data storage formats, and other optional capabilities of targets. See <code>tar_resources()</code> for details.
cue	An optional object from <code>tar_cue()</code> to customize the rules that decide whether the target is up to date. Only applies to the downstream target. The upstream target always runs.
description	Character of length 1, a custom free-form human-readable text description of the target. Descriptions appear as target labels in functions like <code>tar_manifest()</code> and <code>tar_visnetwork()</code> , and they let you select subsets of targets for the names argument of functions like <code>tar_make()</code> . For example, <code>tar_manifest(names = tar_described_as(starts_with("survival model")))</code> lists all the targets whose descriptions start with the character string "survival model".

Details

`tar_files_input()` is like `tar_files()` but more convenient when the files in question already exist and are known in advance. Whereas `tar_files()` always appears outdated (e.g. with `tar_outdated()`) because it always needs to check which files it needs to branch over, `tar_files_input()` will appear up to date if the files have not changed since last `tar_make()`. In addition, `tar_files_input()` automatically groups input files into batches to reduce overhead and increase the efficiency of parallel processing.

`tar_files_input()` creates a pair of targets, one upstream and one downstream. The upstream target does some work and returns some file paths, and the downstream target is a pattern that applies `format = "file"`, `format = "file_fast"`, or `format = "url"`. This is the correct way to dynamically iterate over file/url targets. It makes sure any downstream patterns only rerun some of their branches if the files/urls change. For more information, visit <https://github.com/ropensci/targets/issues/136> and <https://github.com/ropensci/drake/issues/1302>.

Value

A list of two targets, one upstream and one downstream. The upstream one does some work and returns some file paths, and the downstream target is a pattern that applies `format = "file"` or `format = "url"`. See the "Target definition objects" section for background.

Target definition objects

Most tarchetypes functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

See Also

Other Dynamic branching over files: `tar_files()`

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      library(tarchetypes)
      # Do not use temp files in real projects
      # or else your targets will always rerun.
      paths <- unlist(replicate(4, tempfile()))
      file.create(paths)
      list(
        tar_files_input(
          name = x,
          files = paths,
          batches = 2
        ),
        tar_files_input_raw(
          name = "y",
          files = paths,
          batches = 2
        )
      )
    })
    targets::tar_make()
    targets::tar_read(x)
    targets::tar_read(x, branches = 1)
  })
}
```

tar_force

Target with a custom condition to force execution.

Description

Create a target that always runs if a user-defined condition rule is met.

Usage

```
tar_force(
  name,
```

```

    command,
    force,
    tidy_eval = targets::tar_option_get("tidy_eval"),
    packages = targets::tar_option_get("packages"),
    library = targets::tar_option_get("library"),
    format = targets::tar_option_get("format"),
    repository = targets::tar_option_get("repository"),
    iteration = targets::tar_option_get("iteration"),
    error = targets::tar_option_get("error"),
    memory = targets::tar_option_get("memory"),
    garbage_collection = targets::tar_option_get("garbage_collection"),
    deployment = targets::tar_option_get("deployment"),
    priority = targets::tar_option_get("priority"),
    resources = targets::tar_option_get("resources"),
    storage = targets::tar_option_get("storage"),
    retrieval = targets::tar_option_get("retrieval"),
    cue = targets::tar_option_get("cue"),
    description = targets::tar_option_get("description")
  )

```

Arguments

name	Symbol, name of the target. In <code>tar_target()</code>, name is an unevaluated symbol, e.g. <code>tar_target(name = data)</code>. In <code>tar_target_raw()</code>, name is a character string, e.g. <code>tar_target_raw(name = "data")</code>. A target name must be a valid name for a symbol in R, and it must not start with a dot. Subsequent targets can refer to this name symbolically to induce a dependency relationship: e.g. <code>tar_target(downstream_target, f(upstream_target))</code> is a target named <code>downstream_target</code> which depends on a target <code>upstream_target</code> and a function <code>f()</code>. In most cases, The target name is the name of its local data file in storage. Some file systems are not case sensitive, which means converting a name to a different case may overwrite a different target. Please ensure all target names have unique names when converted to lower case. In addition, a target's name determines its random number generator seed. In this way, each target runs with a reproducible seed so someone else running the same pipeline should get the same results, and no two targets in the same pipeline share the same seed. (Even dynamic branches have different names and thus different seeds.) You can recover the seed of a completed target with <code>tar_meta(your_target, seed)</code> and run <code>tar_seed_set()</code> on the result to locally recreate the target's initial RNG state.
command	R code to run the target. In <code>tar_target()</code> , command is an unevaluated expression, e.g. <code>tar_target(command = data)</code> . In <code>tar_target_raw()</code> , command is an evaluated expression, e.g. <code>tar_target_raw(command = quote(data))</code> .
force	R code for the condition that forces a build. If it evaluates to TRUE, then your work will run during <code>tar_make()</code> .
tidy_eval	Whether to invoke tidy evaluation (e.g. the <code>!!</code> operator from <code>rlang</code>) as soon as

	the target is defined (before <code>tar_make()</code>). Applies to arguments <code>command</code> and <code>force</code> .
<code>packages</code>	Character vector of packages to load right before the target runs or the output data is reloaded for downstream targets. Use <code>tar_option_set()</code> to set packages globally for all subsequent targets you define.
<code>library</code>	Character vector of library paths to try when loading packages.
<code>format</code>	Optional storage format for the target's return value. With the exception of <code>format = "file"</code> , each target gets a file in <code>_targets/objects</code> , and each format is a different way to save and load this file. See the "Storage formats" section for a detailed list of possible data storage formats.
<code>repository</code>	Character of length 1, remote repository for target storage. Choices: • <code>"local"</code>: file system of the local machine. • <code>"aws"</code>: Amazon Web Services (AWS) S3 bucket. Can be configured with a non-AWS S3 bucket using the <code>endpoint</code> argument of <code>tar_resources_aws()</code>, but versioning capabilities may be lost in doing so. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions. • <code>"gcp"</code>: Google Cloud Platform storage bucket. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions. • A character string from <code>tar_repository_cas()</code> for content-addressable storage. Note: if <code>repository</code> is not <code>"local"</code> and <code>format</code> is <code>"file"</code> then the target should create a single output file. That output file is uploaded to the cloud and tracked for changes where it exists in the cloud. As of targets version 1.11.0 and higher, the local file is no longer deleted after the target runs.
<code>iteration</code>	Character of length 1, name of the iteration mode of the target. Choices: • <code>"vector"</code>: branching happens with <code>vctrs::vec_slice()</code> and aggregation happens with <code>vctrs::vec_c()</code>. • <code>"list"</code>, branching happens with <code>[[]]</code> and aggregation happens with <code>list()</code>. • <code>"group"</code>: <code>dplyr::group_by()</code>-like functionality to branch over subsets of a non-dynamic data frame. For <code>iteration = "group"</code>, the target must not be dynamic (the <code>pattern</code> argument of <code>tar_target()</code> must be left <code>NULL</code>). The target's return value must be a data frame with a special <code>tar_group</code> column of consecutive integers from 1 through the number of groups. Each integer designates a group, and a branch is created for each collection of rows in a group. See the <code>tar_group()</code> function to see how you can create the special <code>tar_group</code> column with <code>dplyr::group_by()</code>.
<code>error</code>	Character of length 1, what to do if the target stops and throws an error. Options: • <code>"stop"</code>: the whole pipeline stops and throws an error. • <code>"continue"</code>: the whole pipeline keeps going. • <code>"null"</code>: The errored target continues and returns <code>NULL</code>. The data hash is deliberately wrong so the target is not up to date for the next run of the pipeline. In addition, as of targets version 1.8.0.9011, a value of <code>NULL</code> is given to upstream dependencies with <code>error = "null"</code> if loading fails.

- "abridge": any currently running targets keep running, but no new targets launch after that.
- "trim": all currently running targets stay running. A queued target is allowed to start if:
 1. It is not downstream of the error, and
 2. It is not a sibling branch from the same `tar_target()` call (if the error happened in a dynamic branch).

The idea is to avoid starting any new work that the immediate error impacts. `error = "trim"` is just like `error = "abridge"`, but it allows potentially healthy regions of the dependency graph to begin running. (Visit <https://books.ropensci.org/targets/debugging.html> to learn how to debug targets using saved workspaces.)

memory

Character of length 1, memory strategy. Possible values:

- "auto" (default): equivalent to `memory = "transient"` in almost all cases. But to avoid superfluous reads from disk, `memory = "auto"` is equivalent to `memory = "persistent"` for non-dynamically-branched targets that other targets dynamically branch over. For example: if your pipeline has `tar_target(name = y, command = x, pattern = map(x))`, then `tar_target(name = x, command = f(), memory = "auto")` will use persistent memory for `x` in order to avoid rereading all of `x` for every branch of `y`.
- "transient": the target gets unloaded after every new target completes. Either way, the target gets automatically loaded into memory whenever another target needs the value.
- "persistent": the target stays in memory until the end of the pipeline (unless storage is "worker", in which case targets unloads the value from memory right after storing it in order to avoid sending copious data over a network).

For cloud-based file targets (e.g. `format = "file"` with `repository = "aws"`), the memory option applies to the temporary local copy of the file: "persistent" means it remains until the end of the pipeline and is then deleted, and "transient" means it gets deleted as soon as possible. The former conserves bandwidth, and the latter conserves local storage.

garbage_collection

Logical: TRUE to run `base::gc()` just before the target runs, in whatever R process it is about to run (which could be a parallel worker). FALSE to omit garbage collection. Numeric values get converted to FALSE. The `garbage_collection` option in `tar_option_set()` is independent of the argument of the same name in `tar_target()`.

deployment

Character of length 1. If deployment is "main", then the target will run on the central controlling R process. Otherwise, if deployment is "worker" and you set up the pipeline with distributed/parallel computing, then the target runs on a parallel worker. For more on distributed/parallel computing in targets, please visit <https://books.ropensci.org/targets/crew.html>.

priority

Deprecated on 2025-04-08 (targets version 1.10.1.9013). targets has moved to a more efficient scheduling algorithm (<https://github.com/ropensci/targets/issues/1458>) which cannot support priorities. The `priority` argument of `tar_target()` no longer has a reliable effect on execution order.

resources	Object returned by <code>tar_resources()</code> with optional settings for high-performance computing functionality, alternative data storage formats, and other optional capabilities of targets. See <code>tar_resources()</code> for details.
storage	Character string to control when the output of the target is saved to storage. Only relevant when using targets with parallel workers (https://books.ropensci.org/targets/crew.html). Must be one of the following values: • "worker" (default): the worker saves/uploads the value. • "main": the target's return value is sent back to the host machine and saved/uploaded locally. • "none": targets makes no attempt to save the result of the target to storage in the location where targets expects it to be. Saving to storage is the responsibility of the user. Use with caution.
retrieval	Character string to control when the current target loads its dependencies into memory before running. (Here, a "dependency" is another target upstream that the current one depends on.) Only relevant when using targets with parallel workers (https://books.ropensci.org/targets/crew.html). Must be one of the following values: • "auto" (default): equivalent to <code>retrieval = "worker"</code> in almost all cases. But to avoid unnecessary reads from disk, <code>retrieval = "auto"</code> is equivalent to <code>retrieval = "main"</code> for dynamic branches that branch over non-dynamic targets. For example: if your pipeline has <code>tar_target(x, command = f())</code>, then <code>tar_target(y, command = x, pattern = map(x), retrieval = "auto")</code> will use "main" retrieval in order to avoid rereading all of <code>x</code> for every branch of <code>y</code>. • "worker": the worker loads the target's dependencies. • "main": the target's dependencies are loaded on the host machine and sent to the worker before the target runs. • "none": targets makes no attempt to load its dependencies. With <code>retrieval = "none"</code>, loading dependencies is the responsibility of the user. Use with caution.
cue	An optional object from <code>tar_cue()</code> to customize the rules that decide whether the target is up to date. Only applies to the downstream target. The upstream target always runs.
description	Character of length 1, a custom free-form human-readable text description of the target. Descriptions appear as target labels in functions like <code>tar_manifest()</code> and <code>tar_visnetwork()</code> , and they let you select subsets of targets for the <code>names</code> argument of functions like <code>tar_make()</code> . For example, <code>tar_manifest(names = tar_described_as(starts_with("survival model")))</code> lists all the targets whose descriptions start with the character string "survival model".

Details

`tar_force()` creates a target that always runs when a custom condition is met. The implementation builds on top of `tar_change()`. Thus, a pair of targets is created: an upstream auxiliary target to indicate the custom condition and a downstream target that responds to it and does your work.

tar_force() does not actually use tar_cue_force(), and the mechanism is totally different. Because the upstream target always runs, tar_outdated() and tar_visnetwork() will always show both targets as outdated. However, tar_make() will still skip the downstream one if the upstream custom condition is not met.

Value

A list of 2 targets objects: one to indicate whether the custom condition is met, and another to respond to it and do your actual work. See the "Target definition objects" section for background.

Target definition objects

Most tarchetypes functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

See Also

Other targets with custom invalidation rules: [tar_change\(\)](#), [tar_download\(\)](#), [tar_skip\(\)](#)

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      list(
        tarchetypes::tar_force(x, tempfile(), force = 1 > 0)
      )
    })
    targets::tar_make()
    targets::tar_make()
  })
}
```

tar_format_nanoparquet

Nanoparquet format

Description

Nanoparquet storage format for data frames. Uses [nanoparquet::read_parquet\(\)](#) and [nanoparquet::write_parquet\(\)](#) to read and write data frames returned by targets in a pipeline. Note: attributes such as dplyr row groupings and posterior draws info are dropped during the writing process.

Usage

```
tar_format_nanoparquet(compression = "snappy", class = "tbl")
```

Arguments

compression	Character string, compression type for saving the data. See the compression argument of <code>nanoparquet::write_parquet()</code> for details.
class	Character vector with the data frame subclasses to assign. See the class argument of <code>nanoparquet::parquet_options()</code> for details.

Value

A `targets::tar_format()` storage format specification string that can be directly supplied to the format argument of `targets::tar_target()` or `targets::tar_option_set()`.

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      library(targets)
      library(tarchetypes)
      list(
        tar_target(
          name = data,
          command = data.frame(x = 1),
          format = tar_format_nanoparquet()
        )
      )
    })
    tar_make()
    tar_read(data)
  })
}
```

tar_formats

*Target factories for storage formats***Description**

Target factories for targets with specialized storage formats. For example, `tar_qs(name = data, command = get_data())` is shorthand for `tar_target(name = data, command = get_data(), format = "qs")`.

Most of the formats are shorthand for built-in formats in `targets`. The only exception currently is the `nanoparquet` format: `tar_nanoparquet(data, get_data())` is shorthand for `tar_target(data, get_data(), format = tar_format_nanoparquet())` where `tar_format_nanoparquet()` resides in `tarchetypes`.

`tar_format_feather()` is superseded in favor of `tar_arrow_feather()`, and all the `tar_aws_*`() functions are superseded because of the introduction of the `aws` argument into `targets::tar_target()`.

Usage

```
tar_url(  
  name,  
  command,  
  pattern = NULL,  
  tidy_eval = targets::tar_option_get("tidy_eval"),  
  packages = targets::tar_option_get("packages"),  
  library = targets::tar_option_get("library"),  
  repository = targets::tar_option_get("repository"),  
  iteration = targets::tar_option_get("iteration"),  
  error = targets::tar_option_get("error"),  
  memory = targets::tar_option_get("memory"),  
  garbage_collection = targets::tar_option_get("garbage_collection"),  
  deployment = targets::tar_option_get("deployment"),  
  priority = targets::tar_option_get("priority"),  
  resources = targets::tar_option_get("resources"),  
  storage = targets::tar_option_get("storage"),  
  retrieval = targets::tar_option_get("retrieval"),  
  cue = targets::tar_option_get("cue"),  
  description = targets::tar_option_get("description")  
)  
  
tar_file(  
  name,  
  command,  
  pattern = NULL,  
  tidy_eval = targets::tar_option_get("tidy_eval"),  
  packages = targets::tar_option_get("packages"),  
  library = targets::tar_option_get("library"),  
  repository = targets::tar_option_get("repository"),  
  iteration = targets::tar_option_get("iteration"),  
  error = targets::tar_option_get("error"),  
  memory = targets::tar_option_get("memory"),  
  garbage_collection = targets::tar_option_get("garbage_collection"),  
  deployment = targets::tar_option_get("deployment"),  
  priority = targets::tar_option_get("priority"),  
  resources = targets::tar_option_get("resources"),  
  storage = targets::tar_option_get("storage"),  
  retrieval = targets::tar_option_get("retrieval"),  
  cue = targets::tar_option_get("cue"),  
  description = targets::tar_option_get("description")  
)  
  
tar_file_fast(  
  name,  
  command,  
  pattern = NULL,  
  tidy_eval = targets::tar_option_get("tidy_eval"),
```

```

    packages = targets::tar_option_get("packages"),
    library = targets::tar_option_get("library"),
    repository = targets::tar_option_get("repository"),
    iteration = targets::tar_option_get("iteration"),
    error = targets::tar_option_get("error"),
    memory = targets::tar_option_get("memory"),
    garbage_collection = targets::tar_option_get("garbage_collection"),
    deployment = targets::tar_option_get("deployment"),
    priority = targets::tar_option_get("priority"),
    resources = targets::tar_option_get("resources"),
    storage = targets::tar_option_get("storage"),
    retrieval = targets::tar_option_get("retrieval"),
    cue = targets::tar_option_get("cue"),
    description = targets::tar_option_get("description")
  )

tar_rds(
  name,
  command,
  pattern = NULL,
  tidy_eval = targets::tar_option_get("tidy_eval"),
  packages = targets::tar_option_get("packages"),
  library = targets::tar_option_get("library"),
  repository = targets::tar_option_get("repository"),
  iteration = targets::tar_option_get("iteration"),
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),
  garbage_collection = targets::tar_option_get("garbage_collection"),
  deployment = targets::tar_option_get("deployment"),
  priority = targets::tar_option_get("priority"),
  resources = targets::tar_option_get("resources"),
  storage = targets::tar_option_get("storage"),
  retrieval = targets::tar_option_get("retrieval"),
  cue = targets::tar_option_get("cue"),
  description = targets::tar_option_get("description")
)

tar_qs(
  name,
  command,
  pattern = NULL,
  tidy_eval = targets::tar_option_get("tidy_eval"),
  packages = targets::tar_option_get("packages"),
  library = targets::tar_option_get("library"),
  repository = targets::tar_option_get("repository"),
  iteration = targets::tar_option_get("iteration"),
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),

```

```
garbage_collection = targets::tar_option_get("garbage_collection"),
deployment = targets::tar_option_get("deployment"),
priority = targets::tar_option_get("priority"),
resources = targets::tar_option_get("resources"),
storage = targets::tar_option_get("storage"),
retrieval = targets::tar_option_get("retrieval"),
cue = targets::tar_option_get("cue"),
description = targets::tar_option_get("description")
)

tar_keras(
  name,
  command,
  pattern = NULL,
  tidy_eval = targets::tar_option_get("tidy_eval"),
  packages = targets::tar_option_get("packages"),
  library = targets::tar_option_get("library"),
  repository = targets::tar_option_get("repository"),
  iteration = targets::tar_option_get("iteration"),
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),
  garbage_collection = targets::tar_option_get("garbage_collection"),
  deployment = targets::tar_option_get("deployment"),
  priority = targets::tar_option_get("priority"),
  resources = targets::tar_option_get("resources"),
  storage = targets::tar_option_get("storage"),
  retrieval = targets::tar_option_get("retrieval"),
  cue = targets::tar_option_get("cue"),
  description = targets::tar_option_get("description")
)

tar_torch(
  name,
  command,
  pattern = NULL,
  tidy_eval = targets::tar_option_get("tidy_eval"),
  packages = targets::tar_option_get("packages"),
  library = targets::tar_option_get("library"),
  repository = targets::tar_option_get("repository"),
  iteration = targets::tar_option_get("iteration"),
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),
  garbage_collection = targets::tar_option_get("garbage_collection"),
  deployment = targets::tar_option_get("deployment"),
  priority = targets::tar_option_get("priority"),
  resources = targets::tar_option_get("resources"),
  storage = targets::tar_option_get("storage"),
  retrieval = targets::tar_option_get("retrieval"),
```

```

    cue = targets::tar_option_get("cue"),
    description = targets::tar_option_get("description")
)

tar_arrow_feather(
  name,
  command,
  pattern = NULL,
  tidy_eval = targets::tar_option_get("tidy_eval"),
  packages = targets::tar_option_get("packages"),
  library = targets::tar_option_get("library"),
  repository = targets::tar_option_get("repository"),
  iteration = targets::tar_option_get("iteration"),
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),
  garbage_collection = targets::tar_option_get("garbage_collection"),
  deployment = targets::tar_option_get("deployment"),
  priority = targets::tar_option_get("priority"),
  resources = targets::tar_option_get("resources"),
  storage = targets::tar_option_get("storage"),
  retrieval = targets::tar_option_get("retrieval"),
  cue = targets::tar_option_get("cue"),
  description = targets::tar_option_get("description")
)

tar_parquet(
  name,
  command,
  pattern = NULL,
  tidy_eval = targets::tar_option_get("tidy_eval"),
  packages = targets::tar_option_get("packages"),
  library = targets::tar_option_get("library"),
  repository = targets::tar_option_get("repository"),
  iteration = targets::tar_option_get("iteration"),
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),
  garbage_collection = targets::tar_option_get("garbage_collection"),
  deployment = targets::tar_option_get("deployment"),
  priority = targets::tar_option_get("priority"),
  resources = targets::tar_option_get("resources"),
  storage = targets::tar_option_get("storage"),
  retrieval = targets::tar_option_get("retrieval"),
  cue = targets::tar_option_get("cue"),
  description = targets::tar_option_get("description")
)

tar_fst(
  name,

```

```

    command,
    pattern = NULL,
    tidy_eval = targets::tar_option_get("tidy_eval"),
    packages = targets::tar_option_get("packages"),
    library = targets::tar_option_get("library"),
    repository = targets::tar_option_get("repository"),
    iteration = targets::tar_option_get("iteration"),
    error = targets::tar_option_get("error"),
    memory = targets::tar_option_get("memory"),
    garbage_collection = targets::tar_option_get("garbage_collection"),
    deployment = targets::tar_option_get("deployment"),
    priority = targets::tar_option_get("priority"),
    resources = targets::tar_option_get("resources"),
    storage = targets::tar_option_get("storage"),
    retrieval = targets::tar_option_get("retrieval"),
    cue = targets::tar_option_get("cue"),
    description = targets::tar_option_get("description")
  )

tar_fst_dt(
  name,
  command,
  pattern = NULL,
  tidy_eval = targets::tar_option_get("tidy_eval"),
  packages = targets::tar_option_get("packages"),
  library = targets::tar_option_get("library"),
  repository = targets::tar_option_get("repository"),
  iteration = targets::tar_option_get("iteration"),
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),
  garbage_collection = targets::tar_option_get("garbage_collection"),
  deployment = targets::tar_option_get("deployment"),
  priority = targets::tar_option_get("priority"),
  resources = targets::tar_option_get("resources"),
  storage = targets::tar_option_get("storage"),
  retrieval = targets::tar_option_get("retrieval"),
  cue = targets::tar_option_get("cue"),
  description = targets::tar_option_get("description")
)

tar_fst_tbl(
  name,
  command,
  pattern = NULL,
  tidy_eval = targets::tar_option_get("tidy_eval"),
  packages = targets::tar_option_get("packages"),
  library = targets::tar_option_get("library"),
  repository = targets::tar_option_get("repository"),

```

```

iteration = targets::tar_option_get("iteration"),
error = targets::tar_option_get("error"),
memory = targets::tar_option_get("memory"),
garbage_collection = targets::tar_option_get("garbage_collection"),
deployment = targets::tar_option_get("deployment"),
priority = targets::tar_option_get("priority"),
resources = targets::tar_option_get("resources"),
storage = targets::tar_option_get("storage"),
retrieval = targets::tar_option_get("retrieval"),
cue = targets::tar_option_get("cue"),
description = targets::tar_option_get("description")
)

tar_nanoparquet(
  name,
  command,
  pattern = NULL,
  tidy_eval = targets::tar_option_get("tidy_eval"),
  packages = targets::tar_option_get("packages"),
  library = targets::tar_option_get("library"),
  repository = targets::tar_option_get("repository"),
  iteration = targets::tar_option_get("iteration"),
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),
  garbage_collection = targets::tar_option_get("garbage_collection"),
  deployment = targets::tar_option_get("deployment"),
  priority = targets::tar_option_get("priority"),
  resources = targets::tar_option_get("resources"),
  storage = targets::tar_option_get("storage"),
  retrieval = targets::tar_option_get("retrieval"),
  cue = targets::tar_option_get("cue"),
  description = targets::tar_option_get("description"),
  compression = "snappy",
  class = "tbl"
)

```

Arguments

name	Symbol, name of the target. In <code>tar_target()</code>, name is an unevaluated symbol, e.g. <code>tar_target(name = data)</code>. In <code>tar_target_raw()</code>, name is a character string, e.g. <code>tar_target_raw(name = "data")</code>. A target name must be a valid name for a symbol in R, and it must not start with a dot. Subsequent targets can refer to this name symbolically to induce a dependency relationship: e.g. <code>tar_target(downstream_target, f(upstream_target))</code> is a target named <code>downstream_target</code> which depends on a target <code>upstream_target</code> and a function <code>f()</code>. In most cases, The target name is the name of its local data file in storage. Some file systems are not case sensitive, which means converting a name to a different
------	---

case may overwrite a different target. Please ensure all target names have unique names when converted to lower case.

In addition, a target's name determines its random number generator seed. In this way, each target runs with a reproducible seed so someone else running the same pipeline should get the same results, and no two targets in the same pipeline share the same seed. (Even dynamic branches have different names and thus different seeds.) You can recover the seed of a completed target with `tar_meta(your_target, seed)` and run `tar_seed_set()` on the result to locally recreate the target's initial RNG state.

command	R code to run the target. In <code>tar_target()</code> , command is an unevaluated expression, e.g. <code>tar_target(command = data)</code> . In <code>tar_target_raw()</code> , command is an evaluated expression, e.g. <code>tar_target_raw(command = quote(data))</code> .
pattern	Code to define a dynamic branching for a target. In <code>tar_target()</code> , pattern is an unevaluated expression, e.g. <code>tar_target(pattern = map(data))</code> . In <code>tar_target_raw()</code> , command is an evaluated expression, e.g. <code>tar_target_raw(pattern = quote(map(data)))</code> . To demonstrate dynamic branching patterns, suppose we have a pipeline with numeric vector targets <code>x</code> and <code>y</code> . Then, <code>tar_target(z, x + y, pattern = map(x, y))</code> implicitly defines branches of <code>z</code> that each compute <code>x[1] + y[1]</code> , <code>x[2] + y[2]</code> , and so on. See the user manual for details.
tidy_eval	Logical, whether to enable tidy evaluation when interpreting command and pattern. If TRUE, you can use the "bang-bang" operator <code>!!</code> to programmatically insert the values of global objects.
packages	Character vector of packages to load right before the target runs or the output data is reloaded for downstream targets. Use <code>tar_option_set()</code> to set packages globally for all subsequent targets you define.
library	Character vector of library paths to try when loading packages.
repository	Character of length 1, remote repository for target storage. Choices: • "local": file system of the local machine. • "aws": Amazon Web Services (AWS) S3 bucket. Can be configured with a non-AWS S3 bucket using the <code>endpoint</code> argument of <code>tar_resources_aws()</code>, but versioning capabilities may be lost in doing so. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions. • "gcp": Google Cloud Platform storage bucket. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions. • A character string from <code>tar_repository_cas()</code> for content-addressable storage. Note: if repository is not "local" and format is "file" then the target should create a single output file. That output file is uploaded to the cloud and tracked for changes where it exists in the cloud. As of targets version 1.11.0 and higher, the local file is no longer deleted after the target runs.
iteration	Character of length 1, name of the iteration mode of the target. Choices:

- "vector": branching happens with `vctrs::vec_slice()` and aggregation happens with `vctrs::vec_c()`.
- "list", branching happens with `[[[]]` and aggregation happens with `list()`.
- "group": `dplyr::group_by()`-like functionality to branch over subsets of a non-dynamic data frame. For `iteration = "group"`, the target must not be dynamic (the `pattern` argument of `tar_target()` must be left `NULL`). The target's return value must be a data frame with a special `tar_group` column of consecutive integers from 1 through the number of groups. Each integer designates a group, and a branch is created for each collection of rows in a group. See the `tar_group()` function to see how you can create the special `tar_group` column with `dplyr::group_by()`.

error

Character of length 1, what to do if the target stops and throws an error. Options:

- "stop": the whole pipeline stops and throws an error.
- "continue": the whole pipeline keeps going.
- "null": The errored target continues and returns `NULL`. The data hash is deliberately wrong so the target is not up to date for the next run of the pipeline. In addition, as of targets version 1.8.0.9011, a value of `NULL` is given to upstream dependencies with `error = "null"` if loading fails.
- "abridge": any currently running targets keep running, but no new targets launch after that.
- "trim": all currently running targets stay running. A queued target is allowed to start if:
 1. It is not downstream of the error, and
 2. It is not a sibling branch from the same `tar_target()` call (if the error happened in a dynamic branch).

The idea is to avoid starting any new work that the immediate error impacts. `error = "trim"` is just like `error = "abridge"`, but it allows potentially healthy regions of the dependency graph to begin running. (Visit <https://books.ropensci.org/targets/debugging.html> to learn how to debug targets using saved workspaces.)

memory

Character of length 1, memory strategy. Possible values:

- "auto" (default): equivalent to `memory = "transient"` in almost all cases. But to avoid superfluous reads from disk, `memory = "auto"` is equivalent to `memory = "persistent"` for non-dynamically-branched targets that other targets dynamically branch over. For example: if your pipeline has `tar_target(name = y, command = x, pattern = map(x))`, then `tar_target(name = x, command = f(), memory = "auto")` will use persistent memory for `x` in order to avoid rereading all of `x` for every branch of `y`.
- "transient": the target gets unloaded after every new target completes. Either way, the target gets automatically loaded into memory whenever another target needs the value.
- "persistent": the target stays in memory until the end of the pipeline (unless `storage` is "worker", in which case targets unloads the value from memory right after storing it in order to avoid sending copious data over a network).

For cloud-based file targets (e.g. `format = "file"` with `repository = "aws"`), the memory option applies to the temporary local copy of the file: "persistent" means it remains until the end of the pipeline and is then deleted, and "transient" means it gets deleted as soon as possible. The former conserves bandwidth, and the latter conserves local storage.

garbage_collection

Logical: TRUE to run `base::gc()` just before the target runs, in whatever R process it is about to run (which could be a parallel worker). FALSE to omit garbage collection. Numeric values get converted to FALSE. The `garbage_collection` option in `tar_option_set()` is independent of the argument of the same name in `tar_target()`.

deployment

Character of length 1. If deployment is "main", then the target will run on the central controlling R process. Otherwise, if deployment is "worker" and you set up the pipeline with distributed/parallel computing, then the target runs on a parallel worker. For more on distributed/parallel computing in targets, please visit <https://books.ropensci.org/targets/crew.html>.

priority

Deprecated on 2025-04-08 (targets version 1.10.1.9013). targets has moved to a more efficient scheduling algorithm (<https://github.com/ropensci/targets/issues/1458>) which cannot support priorities. The `priority` argument of `tar_target()` no longer has a reliable effect on execution order.

resources

Object returned by `tar_resources()` with optional settings for high-performance computing functionality, alternative data storage formats, and other optional capabilities of targets. See `tar_resources()` for details.

storage

Character string to control when the output of the target is saved to storage. Only relevant when using targets with parallel workers (<https://books.ropensci.org/targets/crew.html>). Must be one of the following values:

- "worker" (default): the worker saves/uploads the value.
- "main": the target's return value is sent back to the host machine and saved/uploaded locally.
- "none": targets makes no attempt to save the result of the target to storage in the location where targets expects it to be. Saving to storage is the responsibility of the user. Use with caution.

retrieval

Character string to control when the current target loads its dependencies into memory before running. (Here, a "dependency" is another target upstream that the current one depends on.) Only relevant when using targets with parallel workers (<https://books.ropensci.org/targets/crew.html>). Must be one of the following values:

- "auto" (default): equivalent to `retrieval = "worker"` in almost all cases. But to avoid unnecessary reads from disk, `retrieval = "auto"` is equivalent to `retrieval = "main"` for dynamic branches that branch over non-dynamic targets. For example: if your pipeline has `tar_target(x, command = f())`, then `tar_target(y, command = x, pattern = map(x), retrieval = "auto")` will use "main" retrieval in order to avoid rereading all of x for every branch of y.
- "worker": the worker loads the target's dependencies.

	• "main": the target's dependencies are loaded on the host machine and sent to the worker before the target runs. • "none": targets makes no attempt to load its dependencies. With retrieval = "none", loading dependencies is the responsibility of the user. Use with caution.
cue	An optional object from <code>tar_cue()</code> to customize the rules that decide whether the target is up to date.
description	Character of length 1, a custom free-form human-readable text description of the target. Descriptions appear as target labels in functions like <code>tar_manifest()</code> and <code>tar_visnetwork()</code> , and they let you select subsets of targets for the names argument of functions like <code>tar_make()</code> . For example, <code>tar_manifest(names = tar_described_as(starts_with("survival model")))</code> lists all the targets whose descriptions start with the character string "survival model".
compression	Character string, compression type for saving the data. See the compression argument of <code>nanoparquet::write_parquet()</code> for details.
class	Character vector with the data frame subclasses to assign. See the class argument of <code>nanoparquet::parquet_options()</code> for details.

Details

These functions are shorthand for targets with specialized storage formats. For example, `tar_qs(name, fun())` is equivalent to `tar_target(name, fun(), format = "qs")`. For details on specialized storage formats, open the help file of the `targets::tar_target()` function and read about the format argument.

Value

A `tar_target()` object with the eponymous storage format. See the "Target definition objects" section for background.

Target definition objects

Most tarchetypes functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      library(targets)
```

```

library(tarchetypes)
list(
  tar_rds(name = x, command = 1),
  tar_nanoparquet(name = y, command = data.frame(x = x))
)
})
targets::tar_make()
})
}

```

tar_group_by

Group a data frame target by one or more variables.

Description

Create a target that outputs a grouped data frame with `dplyr::group_by()` and `targets::tar_group()`. Downstream dynamic branching targets will iterate over the groups of rows.

Usage

```

tar_group_by(
  name,
  command,
  ...,
  tidy_eval = targets::tar_option_get("tidy_eval"),
  packages = targets::tar_option_get("packages"),
  library = targets::tar_option_get("library"),
  format = targets::tar_option_get("format"),
  repository = targets::tar_option_get("repository"),
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),
  garbage_collection = targets::tar_option_get("garbage_collection"),
  deployment = targets::tar_option_get("deployment"),
  priority = targets::tar_option_get("priority"),
  resources = targets::tar_option_get("resources"),
  storage = targets::tar_option_get("storage"),
  retrieval = targets::tar_option_get("retrieval"),
  cue = targets::tar_option_get("cue"),
  description = targets::tar_option_get("description")
)

```

Arguments

name	Symbol, name of the target. In <code>tar_target()</code> , name is an unevaluated symbol, e.g. <code>tar_target(name = data)</code> . In <code>tar_target_raw()</code> , name is a character string, e.g. <code>tar_target_raw(name = "data")</code> .
------	--

A target name must be a valid name for a symbol in R, and it must not start with a dot. Subsequent targets can refer to this name symbolically to induce a dependency relationship: e.g. `tar_target(downstream_target, f(upstream_target))` is a target named `downstream_target` which depends on a target `upstream_target` and a function `f()`.

In most cases, The target name is the name of its local data file in storage. Some file systems are not case sensitive, which means converting a name to a different case may overwrite a different target. Please ensure all target names have unique names when converted to lower case.

In addition, a target's name determines its random number generator seed. In this way, each target runs with a reproducible seed so someone else running the same pipeline should get the same results, and no two targets in the same pipeline share the same seed. (Even dynamic branches have different names and thus different seeds.) You can recover the seed of a completed target with `tar_meta(your_target, seed)` and run `tar_seed_set()` on the result to locally recreate the target's initial RNG state.

command	R code to run the target. In <code>tar_target()</code> , <code>command</code> is an unevaluated expression, e.g. <code>tar_target(command = data)</code> . In <code>tar_target_raw()</code> , <code>command</code> is an evaluated expression, e.g. <code>tar_target_raw(command = quote(data))</code> .
...	Symbols, variables in the output data frame to group by.
tidy_eval	Logical, whether to enable tidy evaluation when interpreting <code>command</code> and <code>pattern</code> . If TRUE, you can use the "bang-bang" operator <code>!!</code> to programmatically insert the values of global objects.
packages	Character vector of packages to load right before the target runs or the output data is reloaded for downstream targets. Use <code>tar_option_set()</code> to set packages globally for all subsequent targets you define.
library	Character vector of library paths to try when loading packages.
format	Optional storage format for the target's return value. With the exception of <code>format = "file"</code> , each target gets a file in <code>_targets/objects</code> , and each format is a different way to save and load this file. See the "Storage formats" section for a detailed list of possible data storage formats.
repository	Character of length 1, remote repository for target storage. Choices: • "local": file system of the local machine. • "aws": Amazon Web Services (AWS) S3 bucket. Can be configured with a non-AWS S3 bucket using the endpoint argument of <code>tar_resources_aws()</code>, but versioning capabilities may be lost in doing so. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions. • "gcp": Google Cloud Platform storage bucket. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions. • A character string from <code>tar_repository_cas()</code> for content-addressable storage.

Note: if `repository` is not "local" and `format` is "file" then the target should create a single output file. That output file is uploaded to the cloud and

tracked for changes where it exists in the cloud. As of targets version 1.11.0 and higher, the local file is no longer deleted after the target runs.

error

Character of length 1, what to do if the target stops and throws an error. Options:

- "stop": the whole pipeline stops and throws an error.
- "continue": the whole pipeline keeps going.
- "null": The errored target continues and returns NULL. The data hash is deliberately wrong so the target is not up to date for the next run of the pipeline. In addition, as of targets version 1.8.0.9011, a value of NULL is given to upstream dependencies with error = "null" if loading fails.
- "abridge": any currently running targets keep running, but no new targets launch after that.
- "trim": all currently running targets stay running. A queued target is allowed to start if:
 1. It is not downstream of the error, and
 2. It is not a sibling branch from the same `tar_target()` call (if the error happened in a dynamic branch).

The idea is to avoid starting any new work that the immediate error impacts. error = "trim" is just like error = "abridge", but it allows potentially healthy regions of the dependency graph to begin running. (Visit <https://books.ropensci.org/targets/debugging.html> to learn how to debug targets using saved workspaces.)

memory

Character of length 1, memory strategy. Possible values:

- "auto" (default): equivalent to memory = "transient" in almost all cases. But to avoid superfluous reads from disk, memory = "auto" is equivalent to memory = "persistent" for non-dynamically-branched targets that other targets dynamically branch over. For example: if your pipeline has `tar_target(name = y, command = x, pattern = map(x))`, then `tar_target(name = x, command = f(), memory = "auto")` will use persistent memory for x in order to avoid rereading all of x for every branch of y.
- "transient": the target gets unloaded after every new target completes. Either way, the target gets automatically loaded into memory whenever another target needs the value.
- "persistent": the target stays in memory until the end of the pipeline (unless storage is "worker", in which case targets unloads the value from memory right after storing it in order to avoid sending copious data over a network).

For cloud-based file targets (e.g. format = "file" with repository = "aws"), the memory option applies to the temporary local copy of the file: "persistent" means it remains until the end of the pipeline and is then deleted, and "transient" means it gets deleted as soon as possible. The former conserves bandwidth, and the latter conserves local storage.

garbage_collection

Logical: TRUE to run `base::gc()` just before the target runs, in whatever R process it is about to run (which could be a parallel worker). FALSE to omit garbage collection. Numeric values get converted to FALSE. The garbage_collection

	option in <code>tar_option_set()</code> is independent of the argument of the same name in <code>tar_target()</code> .
deployment	Character of length 1. If deployment is "main", then the target will run on the central controlling R process. Otherwise, if deployment is "worker" and you set up the pipeline with distributed/parallel computing, then the target runs on a parallel worker. For more on distributed/parallel computing in targets, please visit https://books.ropensci.org/targets/crew.html .
priority	Deprecated on 2025-04-08 (targets version 1.10.1.9013). targets has moved to a more efficient scheduling algorithm (https://github.com/ropensci/targets/issues/1458) which cannot support priorities. The priority argument of <code>tar_target()</code> no longer has a reliable effect on execution order.
resources	Object returned by <code>tar_resources()</code> with optional settings for high-performance computing functionality, alternative data storage formats, and other optional capabilities of targets. See <code>tar_resources()</code> for details.
storage	Character string to control when the output of the target is saved to storage. Only relevant when using targets with parallel workers (https://books.ropensci.org/targets/crew.html). Must be one of the following values: • "worker" (default): the worker saves/uploads the value. • "main": the target's return value is sent back to the host machine and saved/uploaded locally. • "none": targets makes no attempt to save the result of the target to storage in the location where targets expects it to be. Saving to storage is the responsibility of the user. Use with caution.
retrieval	Character string to control when the current target loads its dependencies into memory before running. (Here, a "dependency" is another target upstream that the current one depends on.) Only relevant when using targets with parallel workers (https://books.ropensci.org/targets/crew.html). Must be one of the following values: • "auto" (default): equivalent to <code>retrieval = "worker"</code> in almost all cases. But to avoid unnecessary reads from disk, <code>retrieval = "auto"</code> is equivalent to <code>retrieval = "main"</code> for dynamic branches that branch over non-dynamic targets. For example: if your pipeline has <code>tar_target(x, command = f())</code>, then <code>tar_target(y, command = x, pattern = map(x), retrieval = "auto")</code> will use "main" retrieval in order to avoid rereading all of x for every branch of y. • "worker": the worker loads the target's dependencies. • "main": the target's dependencies are loaded on the host machine and sent to the worker before the target runs. • "none": targets makes no attempt to load its dependencies. With <code>retrieval = "none"</code>, loading dependencies is the responsibility of the user. Use with caution.
cue	An optional object from <code>tar_cue()</code> to customize the rules that decide whether the target is up to date.
description	Character of length 1, a custom free-form human-readable text description of the target. Descriptions appear as target labels in functions like <code>tar_manifest()</code>

and `tar_visnetwork()`, and they let you select subsets of targets for the names argument of functions like `tar_make()`. For example, `tar_manifest(names = tar_described_as(starts_with("survival model")))` lists all the targets whose descriptions start with the character string "survival model".

Value

A target definition object to generate a grouped data frame to allows downstream dynamic targets to branch over the groups of rows. See the "Target definition objects" section for background.

Target definition objects

Most tarchetypes functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

See Also

Other Grouped data frame targets: `tar_group_count()`, `tar_group_select()`, `tar_group_size()`

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      produce_data <- function() {
        expand.grid(var1 = c("a", "b"), var2 = c("c", "d"), rep = c(1, 2, 3))
      }
      list(
        tarchetypes::tar_group_by(data, produce_data(), var1, var2),
        tar_target(group, data, pattern = map(data))
      )
    })
    targets::tar_make()
    # Read the first row group:
    targets::tar_read(group, branches = 1)
    # Read the second row group:
    targets::tar_read(group, branches = 2)
  })
}
```

tar_group_count

Group the rows of a data frame into a given number groups

Description

Create a target that outputs a grouped data frame for downstream dynamic branching. Set the maximum number of groups using count. The number of rows per group varies but is approximately uniform.

Usage

```
tar_group_count(
  name,
  command,
  count,
  tidy_eval = targets::tar_option_get("tidy_eval"),
  packages = targets::tar_option_get("packages"),
  library = targets::tar_option_get("library"),
  format = targets::tar_option_get("format"),
  repository = targets::tar_option_get("repository"),
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),
  garbage_collection = targets::tar_option_get("garbage_collection"),
  deployment = targets::tar_option_get("deployment"),
  priority = targets::tar_option_get("priority"),
  resources = targets::tar_option_get("resources"),
  storage = targets::tar_option_get("storage"),
  retrieval = targets::tar_option_get("retrieval"),
  cue = targets::tar_option_get("cue"),
  description = targets::tar_option_get("description")
)
```

Arguments

name Symbol, name of the target. In `tar_target()`, name is an unevaluated symbol, e.g. `tar_target(name = data)`. In `tar_target_raw()`, name is a character string, e.g. `tar_target_raw(name = "data")`.

A target name must be a valid name for a symbol in R, and it must not start with a dot. Subsequent targets can refer to this name symbolically to induce a dependency relationship: e.g. `tar_target(downstream_target, f(upstream_target))` is a target named `downstream_target` which depends on a target `upstream_target` and a function `f()`.

In most cases, The target name is the name of its local data file in storage. Some file systems are not case sensitive, which means converting a name to a different case may overwrite a different target. Please ensure all target names have unique names when converted to lower case.

In addition, a target's name determines its random number generator seed. In this way, each target runs with a reproducible seed so someone else running the same pipeline should get the same results, and no two targets in the same pipeline share the same seed. (Even dynamic branches have different names and thus different seeds.) You can recover the seed of a completed target with `tar_meta(your_target, seed)` and run `tar_seed_set()` on the result to locally recreate the target's initial RNG state.

command	R code to run the target. In <code>tar_target()</code> , command is an unevaluated expression, e.g. <code>tar_target(command = data)</code> . In <code>tar_target_raw()</code> , command is an evaluated expression, e.g. <code>tar_target_raw(command = quote(data))</code> .
count	Positive integer, maximum number of row groups
tidy_eval	Logical, whether to enable tidy evaluation when interpreting command and pattern. If TRUE, you can use the "bang-bang" operator <code>!!</code> to programmatically insert the values of global objects.
packages	Character vector of packages to load right before the target runs or the output data is reloaded for downstream targets. Use <code>tar_option_set()</code> to set packages globally for all subsequent targets you define.
library	Character vector of library paths to try when loading packages.
format	Optional storage format for the target's return value. With the exception of <code>format = "file"</code> , each target gets a file in <code>_targets/objects</code> , and each format is a different way to save and load this file. See the "Storage formats" section for a detailed list of possible data storage formats.
repository	Character of length 1, remote repository for target storage. Choices: • "local": file system of the local machine. • "aws": Amazon Web Services (AWS) S3 bucket. Can be configured with a non-AWS S3 bucket using the <code>endpoint</code> argument of <code>tar_resources_aws()</code>, but versioning capabilities may be lost in doing so. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions. • "gcp": Google Cloud Platform storage bucket. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions. • A character string from <code>tar_repository_cas()</code> for content-addressable storage.

Note: if `repository` is not "local" and `format` is "file" then the target should create a single output file. That output file is uploaded to the cloud and tracked for changes where it exists in the cloud. As of `targets` version 1.11.0 and higher, the local file is no longer deleted after the target runs.

error	Character of length 1, what to do if the target stops and throws an error. Options: • "stop": the whole pipeline stops and throws an error. • "continue": the whole pipeline keeps going. • "null": The errored target continues and returns NULL. The data hash is deliberately wrong so the target is not up to date for the next run of the pipeline. In addition, as of <code>targets</code> version 1.8.0.9011, a value of NULL is given to upstream dependencies with <code>error = "null"</code> if loading fails.
-------	---

- "abridge": any currently running targets keep running, but no new targets launch after that.
- "trim": all currently running targets stay running. A queued target is allowed to start if:
 1. It is not downstream of the error, and
 2. It is not a sibling branch from the same `tar_target()` call (if the error happened in a dynamic branch).

The idea is to avoid starting any new work that the immediate error impacts. `error = "trim"` is just like `error = "abridge"`, but it allows potentially healthy regions of the dependency graph to begin running. (Visit <https://books.ropensci.org/targets/debugging.html> to learn how to debug targets using saved workspaces.)

memory

Character of length 1, memory strategy. Possible values:

- "auto" (default): equivalent to `memory = "transient"` in almost all cases. But to avoid superfluous reads from disk, `memory = "auto"` is equivalent to `memory = "persistent"` for non-dynamically-branched targets that other targets dynamically branch over. For example: if your pipeline has `tar_target(name = y, command = x, pattern = map(x))`, then `tar_target(name = x, command = f(), memory = "auto")` will use persistent memory for `x` in order to avoid rereading all of `x` for every branch of `y`.
- "transient": the target gets unloaded after every new target completes. Either way, the target gets automatically loaded into memory whenever another target needs the value.
- "persistent": the target stays in memory until the end of the pipeline (unless storage is "worker", in which case targets unloads the value from memory right after storing it in order to avoid sending copious data over a network).

For cloud-based file targets (e.g. `format = "file"` with `repository = "aws"`), the memory option applies to the temporary local copy of the file: "persistent" means it remains until the end of the pipeline and is then deleted, and "transient" means it gets deleted as soon as possible. The former conserves bandwidth, and the latter conserves local storage.

garbage_collection

Logical: TRUE to run `base::gc()` just before the target runs, in whatever R process it is about to run (which could be a parallel worker). FALSE to omit garbage collection. Numeric values get converted to FALSE. The `garbage_collection` option in `tar_option_set()` is independent of the argument of the same name in `tar_target()`.

deployment

Character of length 1. If deployment is "main", then the target will run on the central controlling R process. Otherwise, if deployment is "worker" and you set up the pipeline with distributed/parallel computing, then the target runs on a parallel worker. For more on distributed/parallel computing in targets, please visit <https://books.ropensci.org/targets/crew.html>.

priority

Deprecated on 2025-04-08 (targets version 1.10.1.9013). targets has moved to a more efficient scheduling algorithm (<https://github.com/ropensci/targets/issues/1458>) which cannot support priorities. The `priority` argument of `tar_target()` no longer has a reliable effect on execution order.

resources	Object returned by <code>tar_resources()</code> with optional settings for high-performance computing functionality, alternative data storage formats, and other optional capabilities of targets. See <code>tar_resources()</code> for details.
storage	Character string to control when the output of the target is saved to storage. Only relevant when using targets with parallel workers (https://books.ropensci.org/targets/crew.html). Must be one of the following values: • "worker" (default): the worker saves/uploads the value. • "main": the target's return value is sent back to the host machine and saved/uploaded locally. • "none": targets makes no attempt to save the result of the target to storage in the location where targets expects it to be. Saving to storage is the responsibility of the user. Use with caution.
retrieval	Character string to control when the current target loads its dependencies into memory before running. (Here, a "dependency" is another target upstream that the current one depends on.) Only relevant when using targets with parallel workers (https://books.ropensci.org/targets/crew.html). Must be one of the following values: • "auto" (default): equivalent to <code>retrieval = "worker"</code> in almost all cases. But to avoid unnecessary reads from disk, <code>retrieval = "auto"</code> is equivalent to <code>retrieval = "main"</code> for dynamic branches that branch over non-dynamic targets. For example: if your pipeline has <code>tar_target(x, command = f())</code>, then <code>tar_target(y, command = x, pattern = map(x), retrieval = "auto")</code> will use "main" retrieval in order to avoid rereading all of x for every branch of y. • "worker": the worker loads the target's dependencies. • "main": the target's dependencies are loaded on the host machine and sent to the worker before the target runs. • "none": targets makes no attempt to load its dependencies. With <code>retrieval = "none"</code>, loading dependencies is the responsibility of the user. Use with caution.
cue	An optional object from <code>tar_cue()</code> to customize the rules that decide whether the target is up to date.
description	Character of length 1, a custom free-form human-readable text description of the target. Descriptions appear as target labels in functions like <code>tar_manifest()</code> and <code>tar_visnetwork()</code> , and they let you select subsets of targets for the names argument of functions like <code>tar_make()</code> . For example, <code>tar_manifest(names = tar_described_as(starts_with("survival model")))</code> lists all the targets whose descriptions start with the character string "survival model".

Value

A target definition object to generate a grouped data frame to allows downstream dynamic targets to branch over the groups of rows. See the "Target definition objects" section for background.

Target definition objects

Most tarchetypes functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis

pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

See Also

Other Grouped data frame targets: `tar_group_by()`, `tar_group_select()`, `tar_group_size()`

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      produce_data <- function() {
        expand.grid(var1 = c("a", "b"), var2 = c("c", "d"), rep = c(1, 2, 3))
      }
      list(
        tarchetypes::tar_group_count(data, produce_data(), count = 2),
        tar_target(group, data, pattern = map(data))
      )
    })
    targets::tar_make()
    # Read the first row group:
    targets::tar_read(group, branches = 1)
    # Read the second row group:
    targets::tar_read(group, branches = 2)
  })
}
```

tar_group_select

Group a data frame target with tidyselect semantics.

Description

Create a target that outputs a grouped data frame with `dplyr::group_by()` and `targets::tar_group()`. Unlike `tar_group_by()`, `tar_group_select()` expects you to select grouping variables using tidyselect semantics. Downstream dynamic branching targets will iterate over the groups of rows.

Usage

```
tar_group_select(
  name,
  command,
```

```

by = NULL,
tidy_eval = targets::tar_option_get("tidy_eval"),
packages = targets::tar_option_get("packages"),
library = targets::tar_option_get("library"),
format = targets::tar_option_get("format"),
repository = targets::tar_option_get("repository"),
error = targets::tar_option_get("error"),
memory = targets::tar_option_get("memory"),
garbage_collection = targets::tar_option_get("garbage_collection"),
deployment = targets::tar_option_get("deployment"),
priority = targets::tar_option_get("priority"),
resources = targets::tar_option_get("resources"),
storage = targets::tar_option_get("storage"),
retrieval = targets::tar_option_get("retrieval"),
cue = targets::tar_option_get("cue"),
description = targets::tar_option_get("description")
)

```

Arguments

name	Symbol, name of the target. In <code>tar_target()</code>, name is an unevaluated symbol, e.g. <code>tar_target(name = data)</code>. In <code>tar_target_raw()</code>, name is a character string, e.g. <code>tar_target_raw(name = "data")</code>. A target name must be a valid name for a symbol in R, and it must not start with a dot. Subsequent targets can refer to this name symbolically to induce a dependency relationship: e.g. <code>tar_target(downstream_target, f(upstream_target))</code> is a target named <code>downstream_target</code> which depends on a target <code>upstream_target</code> and a function <code>f()</code>. In most cases, The target name is the name of its local data file in storage. Some file systems are not case sensitive, which means converting a name to a different case may overwrite a different target. Please ensure all target names have unique names when converted to lower case. In addition, a target's name determines its random number generator seed. In this way, each target runs with a reproducible seed so someone else running the same pipeline should get the same results, and no two targets in the same pipeline share the same seed. (Even dynamic branches have different names and thus different seeds.) You can recover the seed of a completed target with <code>tar_meta(your_target, seed)</code> and run <code>tar_seed_set()</code> on the result to locally recreate the target's initial RNG state.
command	R code to run the target. In <code>tar_target()</code>, command is an unevaluated expression, e.g. <code>tar_target(command = data)</code>. In <code>tar_target_raw()</code>, command is an evaluated expression, e.g. <code>tar_target_raw(command = quote(data))</code>.
by	Tidyselect semantics to specify variables to group over. Alternatively, you can supply a character vector.
tidy_eval	Logical, whether to enable tidy evaluation when interpreting command and pattern. If TRUE, you can use the "bang-bang" operator <code>!!</code> to programmatically insert the values of global objects.

packages	Character vector of packages to load right before the target runs or the output data is reloaded for downstream targets. Use <code>tar_option_set()</code> to set packages globally for all subsequent targets you define.
library	Character vector of library paths to try when loading packages.
format	Optional storage format for the target's return value. With the exception of <code>format = "file"</code> , each target gets a file in <code>_targets/objects</code> , and each format is a different way to save and load this file. See the "Storage formats" section for a detailed list of possible data storage formats.
repository	Character of length 1, remote repository for target storage. Choices: • <code>"local"</code>: file system of the local machine. • <code>"aws"</code>: Amazon Web Services (AWS) S3 bucket. Can be configured with a non-AWS S3 bucket using the <code>endpoint</code> argument of <code>tar_resources_aws()</code>, but versioning capabilities may be lost in doing so. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions. • <code>"gcp"</code>: Google Cloud Platform storage bucket. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions. • A character string from <code>tar_repository_cas()</code> for content-addressable storage. Note: if <code>repository</code> is not <code>"local"</code> and <code>format</code> is <code>"file"</code> then the target should create a single output file. That output file is uploaded to the cloud and tracked for changes where it exists in the cloud. As of targets version 1.11.0 and higher, the local file is no longer deleted after the target runs.
error	Character of length 1, what to do if the target stops and throws an error. Options: • <code>"stop"</code>: the whole pipeline stops and throws an error. • <code>"continue"</code>: the whole pipeline keeps going. • <code>"null"</code>: The errored target continues and returns <code>NULL</code>. The data hash is deliberately wrong so the target is not up to date for the next run of the pipeline. In addition, as of targets version 1.8.0.9011, a value of <code>NULL</code> is given to upstream dependencies with <code>error = "null"</code> if loading fails. • <code>"abridge"</code>: any currently running targets keep running, but no new targets launch after that. • <code>"trim"</code>: all currently running targets stay running. A queued target is allowed to start if: 1. It is not downstream of the error, and 2. It is not a sibling branch from the same <code>tar_target()</code> call (if the error happened in a dynamic branch). The idea is to avoid starting any new work that the immediate error impacts. <code>error = "trim"</code> is just like <code>error = "abridge"</code>, but it allows potentially healthy regions of the dependency graph to begin running. (Visit https://books.ropensci.org/targets/debugging.html to learn how to debug targets using saved workspaces.)
memory	Character of length 1, memory strategy. Possible values:

- "auto" (default): equivalent to memory = "transient" in almost all cases. But to avoid superfluous reads from disk, memory = "auto" is equivalent to memory = "persistent" for non-dynamically-branched targets that other targets dynamically branch over. For example: if your pipeline has `tar_target(name = y, command = x, pattern = map(x))`, then `tar_target(name = x, command = f(), memory = "auto")` will use persistent memory for x in order to avoid rereading all of x for every branch of y.
- "transient": the target gets unloaded after every new target completes. Either way, the target gets automatically loaded into memory whenever another target needs the value.
- "persistent": the target stays in memory until the end of the pipeline (unless storage is "worker", in which case targets unloads the value from memory right after storing it in order to avoid sending copious data over a network).

For cloud-based file targets (e.g. format = "file" with repository = "aws"), the memory option applies to the temporary local copy of the file: "persistent" means it remains until the end of the pipeline and is then deleted, and "transient" means it gets deleted as soon as possible. The former conserves bandwidth, and the latter conserves local storage.

garbage_collection

Logical: TRUE to run `base::gc()` just before the target runs, in whatever R process it is about to run (which could be a parallel worker). FALSE to omit garbage collection. Numeric values get converted to FALSE. The `garbage_collection` option in `tar_option_set()` is independent of the argument of the same name in `tar_target()`.

deployment

Character of length 1. If deployment is "main", then the target will run on the central controlling R process. Otherwise, if deployment is "worker" and you set up the pipeline with distributed/parallel computing, then the target runs on a parallel worker. For more on distributed/parallel computing in targets, please visit <https://books.ropensci.org/targets/crew.html>.

priority

Deprecated on 2025-04-08 (targets version 1.10.1.9013). targets has moved to a more efficient scheduling algorithm (<https://github.com/ropensci/targets/issues/1458>) which cannot support priorities. The `priority` argument of `tar_target()` no longer has a reliable effect on execution order.

resources

Object returned by `tar_resources()` with optional settings for high-performance computing functionality, alternative data storage formats, and other optional capabilities of targets. See `tar_resources()` for details.

storage

Character string to control when the output of the target is saved to storage. Only relevant when using targets with parallel workers (<https://books.ropensci.org/targets/crew.html>). Must be one of the following values:

- "worker" (default): the worker saves/uploads the value.
- "main": the target's return value is sent back to the host machine and saved/uploaded locally.
- "none": targets makes no attempt to save the result of the target to storage in the location where targets expects it to be. Saving to storage is the responsibility of the user. Use with caution.

retrieval	Character string to control when the current target loads its dependencies into memory before running. (Here, a "dependency" is another target upstream that the current one depends on.) Only relevant when using targets with parallel workers (https://books.ropensci.org/targets/crew.html). Must be one of the following values: • "auto" (default): equivalent to retrieval = "worker" in almost all cases. But to avoid unnecessary reads from disk, retrieval = "auto" is equivalent to retrieval = "main" for dynamic branches that branch over non-dynamic targets. For example: if your pipeline has tar_target(x, command = f()), then tar_target(y, command = x, pattern = map(x), retrieval = "auto") will use "main" retrieval in order to avoid rereading all of x for every branch of y. • "worker": the worker loads the target's dependencies. • "main": the target's dependencies are loaded on the host machine and sent to the worker before the target runs. • "none": targets makes no attempt to load its dependencies. With retrieval = "none", loading dependencies is the responsibility of the user. Use with caution.
cue	An optional object from tar_cue() to customize the rules that decide whether the target is up to date.
description	Character of length 1, a custom free-form human-readable text description of the target. Descriptions appear as target labels in functions like tar_manifest() and tar_visnetwork(), and they let you select subsets of targets for the names argument of functions like tar_make(). For example, tar_manifest(names = tar_described_as(starts_with("survival model"))) lists all the targets whose descriptions start with the character string "survival model".

Value

A target definition object to generate a grouped data frame to allows downstream dynamic targets to branch over the groups of rows. See the "Target definition objects" section for background.

Target definition objects

Most tarchetypes functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

See Also

Other Grouped data frame targets: [tar_group_by\(\)](#), [tar_group_count\(\)](#), [tar_group_size\(\)](#)

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      produce_data <- function() {
        expand.grid(var1 = c("a", "b"), var2 = c("c", "d"), rep = c(1, 2, 3))
      }
      list(
        tarchetypes::tar_group_select(data, produce_data(), starts_with("var")),
        tar_target(group, data, pattern = map(data))
      )
    })
  })
  targets::tar_make()
  # Read the first row group:
  targets::tar_read(group, branches = 1)
  # Read the second row group:
  targets::tar_read(group, branches = 2)
})
}
```

tar_group_size

Group the rows of a data frame into groups of a given size.

Description

Create a target that outputs a grouped data frame for downstream dynamic branching. Row groups have the number of rows you supply to size (plus the remainder in a group of its own, if applicable.) The total number of groups varies.

Usage

```
tar_group_size(
  name,
  command,
  size,
  tidy_eval = targets::tar_option_get("tidy_eval"),
  packages = targets::tar_option_get("packages"),
  library = targets::tar_option_get("library"),
  format = targets::tar_option_get("format"),
  repository = targets::tar_option_get("repository"),
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),
  garbage_collection = targets::tar_option_get("garbage_collection"),
  deployment = targets::tar_option_get("deployment"),
  priority = targets::tar_option_get("priority"),
  resources = targets::tar_option_get("resources"),
  storage = targets::tar_option_get("storage"),
  retrieval = targets::tar_option_get("retrieval"),
```

```

  cue = targets::tar_option_get("cue"),
  description = targets::tar_option_get("description")
)

```

Arguments

name	Symbol, name of the target. In <code>tar_target()</code>, name is an unevaluated symbol, e.g. <code>tar_target(name = data)</code>. In <code>tar_target_raw()</code>, name is a character string, e.g. <code>tar_target_raw(name = "data")</code>. A target name must be a valid name for a symbol in R, and it must not start with a dot. Subsequent targets can refer to this name symbolically to induce a dependency relationship: e.g. <code>tar_target(downstream_target, f(upstream_target))</code> is a target named <code>downstream_target</code> which depends on a target <code>upstream_target</code> and a function <code>f()</code>. In most cases, The target name is the name of its local data file in storage. Some file systems are not case sensitive, which means converting a name to a different case may overwrite a different target. Please ensure all target names have unique names when converted to lower case. In addition, a target's name determines its random number generator seed. In this way, each target runs with a reproducible seed so someone else running the same pipeline should get the same results, and no two targets in the same pipeline share the same seed. (Even dynamic branches have different names and thus different seeds.) You can recover the seed of a completed target with <code>tar_meta(your_target, seed)</code> and run <code>tar_seed_set()</code> on the result to locally recreate the target's initial RNG state.
command	R code to run the target. In <code>tar_target()</code> , command is an unevaluated expression, e.g. <code>tar_target(command = data)</code> . In <code>tar_target_raw()</code> , command is an evaluated expression, e.g. <code>tar_target_raw(command = quote(data))</code> .
size	Positive integer, maximum number of rows in each group.
tidy_eval	Logical, whether to enable tidy evaluation when interpreting command and pattern. If TRUE, you can use the "bang-bang" operator <code>!!</code> to programmatically insert the values of global objects.
packages	Character vector of packages to load right before the target runs or the output data is reloaded for downstream targets. Use <code>tar_option_set()</code> to set packages globally for all subsequent targets you define.
library	Character vector of library paths to try when loading packages.
format	Optional storage format for the target's return value. With the exception of <code>format = "file"</code> , each target gets a file in <code>_targets/objects</code> , and each format is a different way to save and load this file. See the "Storage formats" section for a detailed list of possible data storage formats.
repository	Character of length 1, remote repository for target storage. Choices: • <code>"local"</code>: file system of the local machine. • <code>"aws"</code>: Amazon Web Services (AWS) S3 bucket. Can be configured with a non-AWS S3 bucket using the endpoint argument of <code>tar_resources_aws()</code>, but versioning capabilities may be lost in doing so. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions.

- "gcp": Google Cloud Platform storage bucket. See the cloud storage section of <https://books.ropensci.org/targets/data.html> for details for instructions.
- A character string from `tar_repository_cas()` for content-addressable storage.

Note: if repository is not "local" and format is "file" then the target should create a single output file. That output file is uploaded to the cloud and tracked for changes where it exists in the cloud. As of targets version 1.11.0 and higher, the local file is no longer deleted after the target runs.

error

Character of length 1, what to do if the target stops and throws an error. Options:

- "stop": the whole pipeline stops and throws an error.
- "continue": the whole pipeline keeps going.
- "null": The errored target continues and returns NULL. The data hash is deliberately wrong so the target is not up to date for the next run of the pipeline. In addition, as of targets version 1.8.0.9011, a value of NULL is given to upstream dependencies with `error = "null"` if loading fails.
- "abridge": any currently running targets keep running, but no new targets launch after that.
- "trim": all currently running targets stay running. A queued target is allowed to start if:
 1. It is not downstream of the error, and
 2. It is not a sibling branch from the same `tar_target()` call (if the error happened in a dynamic branch).

The idea is to avoid starting any new work that the immediate error impacts. `error = "trim"` is just like `error = "abridge"`, but it allows potentially healthy regions of the dependency graph to begin running. (Visit <https://books.ropensci.org/targets/debugging.html> to learn how to debug targets using saved workspaces.)

memory

Character of length 1, memory strategy. Possible values:

- "auto" (default): equivalent to `memory = "transient"` in almost all cases. But to avoid superfluous reads from disk, `memory = "auto"` is equivalent to `memory = "persistent"` for for non-dynamically-branched targets that other targets dynamically branch over. For example: if your pipeline has `tar_target(name = y, command = x, pattern = map(x))`, then `tar_target(name = x, command = f(), memory = "auto")` will use persistent memory for x in order to avoid rereading all of x for every branch of y.
- "transient": the target gets unloaded after every new target completes. Either way, the target gets automatically loaded into memory whenever another target needs the value.
- "persistent": the target stays in memory until the end of the pipeline (unless storage is "worker", in which case targets unloads the value from memory right after storing it in order to avoid sending copious data over a network).

For cloud-based file targets (e.g. `format = "file"` with `repository = "aws"`), the memory option applies to the temporary local copy of the file: "persistent"

means it remains until the end of the pipeline and is then deleted, and "transient" means it gets deleted as soon as possible. The former conserves bandwidth, and the latter conserves local storage.

garbage_collection

Logical: TRUE to run `base::gc()` just before the target runs, in whatever R process it is about to run (which could be a parallel worker). FALSE to omit garbage collection. Numeric values get converted to FALSE. The `garbage_collection` option in `tar_option_set()` is independent of the argument of the same name in `tar_target()`.

deployment

Character of length 1. If deployment is "main", then the target will run on the central controlling R process. Otherwise, if deployment is "worker" and you set up the pipeline with distributed/parallel computing, then the target runs on a parallel worker. For more on distributed/parallel computing in targets, please visit <https://books.ropensci.org/targets/crew.html>.

priority

Deprecated on 2025-04-08 (targets version 1.10.1.9013). targets has moved to a more efficient scheduling algorithm (<https://github.com/ropensci/targets/issues/1458>) which cannot support priorities. The `priority` argument of `tar_target()` no longer has a reliable effect on execution order.

resources

Object returned by `tar_resources()` with optional settings for high-performance computing functionality, alternative data storage formats, and other optional capabilities of targets. See `tar_resources()` for details.

storage

Character string to control when the output of the target is saved to storage. Only relevant when using targets with parallel workers (<https://books.ropensci.org/targets/crew.html>). Must be one of the following values:

- "worker" (default): the worker saves/uploads the value.
- "main": the target's return value is sent back to the host machine and saved/uploaded locally.
- "none": targets makes no attempt to save the result of the target to storage in the location where targets expects it to be. Saving to storage is the responsibility of the user. Use with caution.

retrieval

Character string to control when the current target loads its dependencies into memory before running. (Here, a "dependency" is another target upstream that the current one depends on.) Only relevant when using targets with parallel workers (<https://books.ropensci.org/targets/crew.html>). Must be one of the following values:

- "auto" (default): equivalent to `retrieval = "worker"` in almost all cases. But to avoid unnecessary reads from disk, `retrieval = "auto"` is equivalent to `retrieval = "main"` for dynamic branches that branch over non-dynamic targets. For example: if your pipeline has `tar_target(x, command = f())`, then `tar_target(y, command = x, pattern = map(x), retrieval = "auto")` will use "main" retrieval in order to avoid rereading all of `x` for every branch of `y`.
- "worker": the worker loads the target's dependencies.
- "main": the target's dependencies are loaded on the host machine and sent to the worker before the target runs.

- "none": targets makes no attempt to load its dependencies. With retrieval = "none", loading dependencies is the responsibility of the user. Use with caution.
- cue An optional object from tar_cue() to customize the rules that decide whether the target is up to date.
- description Character of length 1, a custom free-form human-readable text description of the target. Descriptions appear as target labels in functions like tar_manifest() and tar_visnetwork(), and they let you select subsets of targets for the names argument of functions like tar_make(). For example, tar_manifest(names = tar_described_as(starts_with("survival model"))) lists all the targets whose descriptions start with the character string "survival model".

Value

A target definition object to generate a grouped data frame to allows downstream dynamic targets to branch over the groups of rows. See the "Target definition objects" section for background.

Target definition objects

Most tarchetypes functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

See Also

Other Grouped data frame targets: [tar_group_by\(\)](#), [tar_group_count\(\)](#), [tar_group_select\(\)](#)

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      produce_data <- function() {
        expand.grid(var1 = c("a", "b"), var2 = c("c", "d"), rep = c(1, 2, 3))
      }
      list(
        tarchetypes::tar_group_size(data, produce_data(), size = 7),
        tar_target(group, data, pattern = map(data))
      )
    })
    targets::tar_make()
    # Read the first row group:
    targets::tar_read(group, branches = 1)
    # Read the second row group:
```

```

targets::tar_read(group, branches = 2)
})
}

```

tar_hook_before	<i>Hook to prepend code</i>
-----------------	-----------------------------

Description

Prepend R code to the commands of multiple targets. `tar_hook_before()` expects unevaluated expressions for the hook and names arguments, whereas `tar_hook_before_raw()` expects evaluated expression objects.

Usage

```

tar_hook_before(
  targets,
  hook,
  names = NULL,
  set_deps = TRUE,
  envir = parent.frame()
)

tar_hook_before_raw(
  targets,
  hook,
  names = NULL,
  set_deps = TRUE,
  envir = parent.frame()
)

```

Arguments

targets	A list of target definition objects. The input target list can be arbitrarily nested, but it must consist entirely of target objects. In addition, the return value is a simple list where each element is a target definition object. All hook functions remove the nested structure of the input target list.
hook	R code to insert. <code>tar_hook_before()</code> expects unevaluated expressions for the hook and names arguments, whereas <code>tar_hook_before_raw()</code> expects evaluated expression objects.
names	Name of targets in the target list to apply the hook. Supplied using tidyselect helpers like <code>starts_with()</code> , as in <code>names = starts_with("your_prefix_")</code> . Set to <code>NULL</code> to include all targets supplied to the <code>targets</code> argument. Targets not included in <code>names</code> still remain in the target list, but they are not modified because the hook does not apply to them. The regular hook functions expects unevaluated expressions for the hook and names arguments, whereas the <code>"_raw"</code> versions expect evaluated expression objects.

set_deps	Logical of length 1, whether to refresh the dependencies of each modified target by scanning the newly generated target commands for dependencies. If FALSE, then the target will keep the original set of dependencies it had before the hook. Set to NULL to include all targets supplied to the targets argument. TRUE is recommended for nearly all situations. Only use FALSE if you have a specialized use case and you know what you are doing.
envir	Optional environment to construct the quosure for the names argument to select names.

Value

A flattened list of target definition objects with the hooks applied. Even if the input target list had a nested structure, the return value is a simple list where each element is a target definition object. All hook functions remove the nested structure of the input target list.

Target definition objects

Most tarchetypes functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

See Also

Other hooks: [tar_hook_inner\(\)](#), [tar_hook_outer\(\)](#)

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      targets <- list(
        # Nested target lists work with hooks.
        list(
          targets::tar_target(x1, task1()),
          targets::tar_target(x2, task2(x1))
        ),
        targets::tar_target(x3, task3(x2)),
        targets::tar_target(y1, task4(x3))
      )
    })
  targets::tar_hook_before(
    targets = targets,
    hook = print("Running hook."),
    names = starts_with("x")
  )
}
```

```

}))
targets::tar_manifest(fields = command)
}))
# With tar_hook_before_raw():
targets::tar_script({
  targets <- list(
    # Nested target lists work with hooks.
    list(
      targets::tar_target(x1, task1()),
      targets::tar_target(x2, task2(x1))
    ),
    targets::tar_target(x3, task3(x2)),
    targets::tar_target(y1, task4(x3))
  )
  tarchetypes::tar_hook_before_raw(
    targets = targets,
    hook = quote(print("Running hook.")),
    names = quote(starts_with("x"))
  )
}))
}

```

tar_hook_inner

Hook to wrap dependencies

Description

In the command of each target, wrap each mention of each dependency target in an arbitrary R expression.

tar_hook_inner() expects unevaluated expressions for the hook and names arguments, whereas tar_hook_inner_raw() expects evaluated expression objects.

Usage

```

tar_hook_inner(
  targets,
  hook,
  names = NULL,
  names_wrap = NULL,
  set_deps = TRUE,
  envir = parent.frame()
)

```

```

tar_hook_inner_raw(
  targets,
  hook,
  names = NULL,
  names_wrap = NULL,

```

```

    set_deps = TRUE,
    envir = parent.frame()
  )

```

Arguments

targets	A list of target definition objects. The input target list can be arbitrarily nested, but it must consist entirely of target objects. In addition, the return value is a simple list where each element is a target definition object. All hook functions remove the nested structure of the input target list.
hook	R code to wrap each target's command. The hook must contain the special placeholder symbol <code>.x</code> so <code>tar_hook_inner()</code> knows where to insert the code to wrap mentions of dependencies. <code>tar_hook_inner()</code> expects unevaluated expressions for the hook and names arguments, whereas <code>tar_hook_inner_raw()</code> expects evaluated expression objects.
names	Name of targets in the target list to apply the hook. Supplied using tidyselect helpers like <code>starts_with()</code> , as in <code>names = starts_with("your_prefix_")</code> . Set to <code>NULL</code> to include all targets supplied to the <code>targets</code> argument. Targets not included in <code>names</code> still remain in the target list, but they are not modified because the hook does not apply to them. The regular hook functions expects unevaluated expressions for the hook and names arguments, whereas the <code>"_raw"</code> versions expect evaluated expression objects.
names_wrap	Names of targets to wrap with the hook where they appear as dependencies in the commands of other targets. Use tidyselect helpers like <code>starts_with()</code> , as in <code>names_wrap = starts_with("your_prefix_")</code> .
set_deps	Logical of length 1, whether to refresh the dependencies of each modified target by scanning the newly generated target commands for dependencies. If <code>FALSE</code> , then the target will keep the original set of dependencies it had before the hook. Set to <code>NULL</code> to include all targets supplied to the <code>targets</code> argument. <code>TRUE</code> is recommended for nearly all situations. Only use <code>FALSE</code> if you have a specialized use case and you know what you are doing.
envir	Optional environment to construct the quosure for the names argument to select names.

Details

The expression you supply to hook must contain the special placeholder symbol `.x` so `tar_hook_inner()` knows where to insert the original command of the target.

Value

A flattened list of target definition objects with the hooks applied. Even if the input target list had a nested structure, the return value is a simple list where each element is a target definition object. All hook functions remove the nested structure of the input target list.

Target definition objects

Most tarchetypes functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

See Also

Other hooks: [tar_hook_before\(\)](#), [tar_hook_outer\(\)](#)

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      targets <- list(
        # Nested target lists work with hooks.
        list(
          targets::tar_target(x1, task1()),
          targets::tar_target(x2, task2(x1))
        ),
        targets::tar_target(x3, task3(x2, x1)),
        targets::tar_target(y1, task4(x3))
      )
      tarchetypes::tar_hook_inner(
        targets = targets,
        hook = fun(.x),
        names = starts_with("x")
      )
    })
    targets::tar_manifest(fields = command)
    # With tar_hook_inner_raw():
    targets::tar_script({
      targets <- list(
        # Nested target lists work with hooks.
        list(
          targets::tar_target(x1, task1()),
          targets::tar_target(x2, task2(x1))
        ),
        targets::tar_target(x3, task3(x2, x1)),
        targets::tar_target(y1, task4(x3))
      )
      tarchetypes::tar_hook_inner_raw(
        targets = targets,
        hook = quote(fun(.x)),
        names = quote(starts_with("x"))
      )
    })
  })
}
```

```

    )
  })
}

```

tar_hook_outer	<i>Hook to wrap commands</i>
----------------	------------------------------

Description

Wrap the command of each target in an arbitrary R expression. `tar_hook_outer()` expects unevaluated expressions for the hook and names arguments, whereas `tar_hook_outer_raw()` expects evaluated expression objects.

Usage

```

tar_hook_outer(
  targets,
  hook,
  names = NULL,
  set_deps = TRUE,
  envir = parent.frame()
)

tar_hook_outer_raw(
  targets,
  hook,
  names = NULL,
  set_deps = TRUE,
  envir = parent.frame()
)

```

Arguments

targets	A list of target definition objects. The input target list can be arbitrarily nested, but it must consist entirely of target objects. In addition, the return value is a simple list where each element is a target definition object. All hook functions remove the nested structure of the input target list.
hook	R code to wrap each target's command. The hook must contain the special placeholder symbol <code>.x</code> so <code>tar_hook_outer()</code> knows where to insert the original command of the target. <code>tar_hook_outer()</code> expects unevaluated expressions for the hook and names arguments, whereas <code>tar_hook_outer_raw()</code> expects evaluated expression objects.
names	Name of targets in the target list to apply the hook. Supplied using tidyselect helpers like <code>starts_with()</code> , as in <code>names = starts_with("your_prefix_")</code> . Set to <code>NULL</code> to include all targets supplied to the <code>targets</code> argument. Targets not

included in names still remain in the target list, but they are not modified because the hook does not apply to them.

The regular hook functions expects unevaluated expressions for the hook and names arguments, whereas the "_raw" versions expect evaluated expression objects.

set_deps	Logical of length 1, whether to refresh the dependencies of each modified target by scanning the newly generated target commands for dependencies. If FALSE, then the target will keep the original set of dependencies it had before the hook. Set to NULL to include all targets supplied to the targets argument. TRUE is recommended for nearly all situations. Only use FALSE if you have a specialized use case and you know what you are doing.
envir	Optional environment to construct the quosure for the names argument to select names.

Details

The expression you supply to hook must contain the special placeholder symbol `.x` so `tar_hook_outer()` knows where to insert the original command of the target.

Value

A flattened list of target definition objects with the hooks applied. Even if the input target list had a nested structure, the return value is a simple list where each element is a target definition object. All hook functions remove the nested structure of the input target list.

Target definition objects

Most `tarchetypes` functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

See Also

Other hooks: [tar_hook_before\(\)](#), [tar_hook_inner\(\)](#)

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      targets <- list(
        # Nested target lists work with hooks.
        list(
```

```

      targets::tar_target(x1, task1()),
      targets::tar_target(x2, task2(x1))
    ),
    targets::tar_target(x3, task3(x2)),
    targets::tar_target(y1, task4(x3))
  )
  tarchetypes::tar_hook_outer(
    targets = targets,
    hook = postprocess(.x, arg = "value"),
    names = starts_with("x")
  )
})
targets::tar_manifest(fields = command)
# Using tar_hook_outer_raw():
targets::tar_script({
  targets <- list(
    # Nested target lists work with hooks.
    list(
      targets::tar_target(x1, task1()),
      targets::tar_target(x2, task2(x1))
    ),
    targets::tar_target(x3, task3(x2)),
    targets::tar_target(y1, task4(x3))
  )
  tarchetypes::tar_hook_outer_raw(
    targets = targets,
    hook = quote(postprocess(.x, arg = "value")),
    names = quote(starts_with("x"))
  )
})
})
}
```

tar_knit

Target with a knitr document.

Description

Shorthand to include knitr document in a targets pipeline.

`tar_knit()` expects an unevaluated symbol for the name argument, and it supports named ... arguments for `knitr::knit()` arguments. `tar_knit_raw()` expects a character string for name and supports an evaluated expression object `knit_arguments` for `knitr::knit()` arguments.

Usage

```
tar_knit(
  name,
  path,
  output_file = NULL,
```

```

working_directory = NULL,
tidy_eval = targets::tar_option_get("tidy_eval"),
packages = targets::tar_option_get("packages"),
library = targets::tar_option_get("library"),
error = targets::tar_option_get("error"),
memory = targets::tar_option_get("memory"),
garbage_collection = targets::tar_option_get("garbage_collection"),
deployment = "main",
priority = targets::tar_option_get("priority"),
resources = targets::tar_option_get("resources"),
retrieval = targets::tar_option_get("retrieval"),
cue = targets::tar_option_get("cue"),
description = targets::tar_option_get("description"),
quiet = TRUE,
...
)

tar_knit_raw(
  name,
  path,
  output_file = NULL,
  working_directory = NULL,
  packages = targets::tar_option_get("packages"),
  library = targets::tar_option_get("library"),
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),
  garbage_collection = targets::tar_option_get("garbage_collection"),
  deployment = "main",
  priority = targets::tar_option_get("priority"),
  resources = targets::tar_option_get("resources"),
  retrieval = targets::tar_option_get("retrieval"),
  cue = targets::tar_option_get("cue"),
  description = targets::tar_option_get("description"),
  quiet = TRUE,
  knit_arguments = quote(list())
)

```

Arguments

name	Name of the target. <code>tar_knit()</code> expects an unevaluated symbol for the name argument, whereas <code>tar_knit_raw()</code> expects a character string for name.
path	Character string, file path to the knitr source file. Must have length 1.
output_file	Character string, file path to the rendered output file.
working_directory	Optional character string, path to the working directory to temporarily set when running the report. The default is NULL, which runs the report from the current working directory at the time the pipeline is run. This default is recommended in the vast majority of cases. To use anything other than NULL, you must manually

	set the value of the store argument relative to the working directory in all calls to <code>tar_read()</code> and <code>tar_load()</code> in the report. Otherwise, these functions will not know where to find the data.
tidy_eval	Logical, whether to enable tidy evaluation when interpreting command and pattern. If TRUE, you can use the "bang-bang" operator <code>!!</code> to programmatically insert the values of global objects.
packages	Character vector of packages to load right before the target runs or the output data is reloaded for downstream targets. Use <code>tar_option_set()</code> to set packages globally for all subsequent targets you define.
library	Character vector of library paths to try when loading packages.
error	Character of length 1, what to do if the target stops and throws an error. Options: • "stop": the whole pipeline stops and throws an error. • "continue": the whole pipeline keeps going. • "null": The errored target continues and returns NULL. The data hash is deliberately wrong so the target is not up to date for the next run of the pipeline. In addition, as of targets version 1.8.0.9011, a value of NULL is given to upstream dependencies with <code>error = "null"</code> if loading fails. • "abridge": any currently running targets keep running, but no new targets launch after that. • "trim": all currently running targets stay running. A queued target is allowed to start if: 1. It is not downstream of the error, and 2. It is not a sibling branch from the same <code>tar_target()</code> call (if the error happened in a dynamic branch). The idea is to avoid starting any new work that the immediate error impacts. <code>error = "trim"</code> is just like <code>error = "abridge"</code>, but it allows potentially healthy regions of the dependency graph to begin running. (Visit https://books.ropensci.org/targets/debugging.html to learn how to debug targets using saved workspaces.)
memory	Character of length 1, memory strategy. Possible values: • "auto" (default): equivalent to <code>memory = "transient"</code> in almost all cases. But to avoid superfluous reads from disk, <code>memory = "auto"</code> is equivalent to <code>memory = "persistent"</code> for non-dynamically-branched targets that other targets dynamically branch over. For example: if your pipeline has <code>tar_target(name = y, command = x, pattern = map(x))</code>, then <code>tar_target(name = x, command = f(), memory = "auto")</code> will use persistent memory for <code>x</code> in order to avoid rereading all of <code>x</code> for every branch of <code>y</code>. • "transient": the target gets unloaded after every new target completes. Either way, the target gets automatically loaded into memory whenever another target needs the value. • "persistent": the target stays in memory until the end of the pipeline (unless storage is "worker", in which case targets unloads the value from memory right after storing it in order to avoid sending copious data over a network).

For cloud-based file targets (e.g. `format = "file"` with `repository = "aws"`), the memory option applies to the temporary local copy of the file: "persistent" means it remains until the end of the pipeline and is then deleted, and "transient" means it gets deleted as soon as possible. The former conserves bandwidth, and the latter conserves local storage.

garbage_collection	Logical: TRUE to run <code>base::gc()</code> just before the target runs, in whatever R process it is about to run (which could be a parallel worker). FALSE to omit garbage collection. Numeric values get converted to FALSE. The <code>garbage_collection</code> option in <code>tar_option_set()</code> is independent of the argument of the same name in <code>tar_target()</code> .
deployment	Character of length 1. If deployment is "main", then the target will run on the central controlling R process. Otherwise, if deployment is "worker" and you set up the pipeline with distributed/parallel computing, then the target runs on a parallel worker. For more on distributed/parallel computing in targets, please visit https://books.ropensci.org/targets/crew.html .
priority	Deprecated on 2025-04-08 (targets version 1.10.1.9013). targets has moved to a more efficient scheduling algorithm (https://github.com/ropensci/targets/issues/1458) which cannot support priorities. The priority argument of <code>tar_target()</code> no longer has a reliable effect on execution order.
resources	Object returned by <code>tar_resources()</code> with optional settings for high-performance computing functionality, alternative data storage formats, and other optional capabilities of targets. See <code>tar_resources()</code> for details.
retrieval	Character string to control when the current target loads its dependencies into memory before running. (Here, a "dependency" is another target upstream that the current one depends on.) Only relevant when using targets with parallel workers (https://books.ropensci.org/targets/crew.html). Must be one of the following values: • "auto" (default): equivalent to <code>retrieval = "worker"</code> in almost all cases. But to avoid unnecessary reads from disk, <code>retrieval = "auto"</code> is equivalent to <code>retrieval = "main"</code> for dynamic branches that branch over non-dynamic targets. For example: if your pipeline has <code>tar_target(x, command = f())</code>, then <code>tar_target(y, command = x, pattern = map(x), retrieval = "auto")</code> will use "main" retrieval in order to avoid rereading all of <code>x</code> for every branch of <code>y</code>. • "worker": the worker loads the target's dependencies. • "main": the target's dependencies are loaded on the host machine and sent to the worker before the target runs. • "none": targets makes no attempt to load its dependencies. With <code>retrieval = "none"</code>, loading dependencies is the responsibility of the user. Use with caution.
cue	An optional object from <code>tar_cue()</code> to customize the rules that decide whether the target is up to date.
description	Character of length 1, a custom free-form human-readable text description of the target. Descriptions appear as target labels in functions like <code>tar_manifest()</code> and <code>tar_visnetwork()</code> , and they let you select subsets of targets for the names

	argument of functions like <code>tar_make()</code> . For example, <code>tar_manifest(names = tar_described_as(starts_with("survival model")))</code> lists all the targets whose descriptions start with the character string "survival model".
<code>quiet</code>	Boolean; suppress the progress bar and messages?
<code>...</code>	Named arguments to <code>knitr::knit()</code> . These arguments are unevaluated when supplied to <code>tar_knit()</code> . They are only evaluated when the target actually runs in <code>tar_make()</code> , not when the target is defined.
<code>knit_arguments</code>	Optional language object with a list of named arguments to <code>knitr::knit()</code> . Cannot be an expression object. (Use <code>quote()</code> , not <code>expression()</code> .) The reason for quoting is that these arguments may depend on upstream targets whose values are not available at the time the target is defined, and because <code>tar_knit_raw()</code> is the "raw" version of a function, we want to avoid all non-standard evaluation.

Details

`tar_knit()` is an alternative to `tar_target()` for knitr reports that depend on other targets. The knitr source should mention dependency targets with `tar_load()` and `tar_read()` in the active code chunks (which also allows you to knit the report outside the pipeline if the `_targets/` data store already exists). (Do not use `tar_load_raw()` or `tar_read_raw()` for this.) Then, `tar_knit()` defines a special kind of target. It 1. Finds all the `tar_load()/tar_read()` dependencies in the report and inserts them into the target's command. This enforces the proper dependency relationships. (Do not use `tar_load_raw()` or `tar_read_raw()` for this.) 2. Sets `format = "file"` (see `tar_target()`) so targets watches the files at the returned paths and reruns the report if those files change. 3. Configures the target's command to return both the output report files and the input source file. All these file paths are relative paths so the project stays portable. 4. Forces the report to run in the user's current working directory instead of the working directory of the report. 5. Sets convenient default options such as `deployment = "main"` in the target and `quiet = TRUE` in `knitr::knit()`.

Value

A `tar_target()` object with `format = "file"`. When this target runs, it returns a character vector of file paths. The first file paths are the output files (returned by `knitr::knit()`) and the knitr source file is last. But unlike `knitr::knit()`, all returned paths are *relative* paths to ensure portability (so that the project can be moved from one file system to another without invalidating the target). See the "Target definition objects" section for background.

Target definition objects

Most `tarchetypes` functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

See Also

Other Literate programming targets: `tar_quarto()`, `tar_quarto_rep()`, `tar_render()`, `tar_render_rep()`

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      library(tarchetypes)
      # Ordinarily, you should create the report outside
      # tar_script() and avoid temporary files.
      lines <- c(
        "---",
        "title: report",
        "output_format: html_document",
        "---",
        "",
        "````{r}",
        "targets::tar_read(data)",
        "````"
      )
      path <- tempfile()
      writeLines(lines, path)
      list(
        tar_target(data, data.frame(x = seq_len(26), y = letters)),
        tar_knit(name = report, path = path),
        tar_knit_raw(name = "report2", path = path)
      )
    })
  })
  targets::tar_make()
}
```

tar_knitr_deps

List literate programming dependencies.

Description

List the target dependencies of one or more literate programming reports (R Markdown or knitr).

Usage

```
tar_knitr_deps(path)
```

Arguments

path Character vector, path to one or more R Markdown or knitr reports.

Value

Character vector of the names of targets that are dependencies of the knitr report.

See Also

Other Literate programming utilities: [tar_knitr_deps_expr\(\)](#), [tar_quarto_files\(\)](#)

Examples

```
lines <- c(
  "----",
  "title: report",
  "output_format: html_document",
  "----",
  "",
  "```{r}",
  "targets::tar_load(data1)",
  "targets::tar_read(data2)",
  "```"
)
report <- tempfile()
writeLines(lines, report)
tar_knitr_deps(report)
```

tar_knitr_deps_expr	<i>Expression with literate programming dependencies.</i>
---------------------	---

Description

Construct an expression whose global variable dependencies are the target dependencies of one or more literate programming reports (R Markdown or knitr). This helps third-party developers create their own third-party target factories for literate programming targets (similar to [tar_knit\(\)](#) and [tar_render\(\)](#)).

Usage

```
tar_knitr_deps_expr(path)
```

Arguments

path Character vector, path to one or more R Markdown or knitr reports.

Value

Expression object to name the dependency targets of the knitr report, which will be detected in the static code analysis of targets.

See Also

Other Literate programming utilities: `tar_knitr_deps()`, `tar_quarto_files()`

Examples

```
lines <- c(
  "___",
  "title: report",
  "output_format: html_document",
  "___",
  "",
  "```{r}",
  "targets::tar_load(data1)",
  "targets::tar_read(data2)",
  "```"
)
report <- tempfile()
writeLines(lines, report)
tar_knitr_deps_expr(report)
```

tar_map

*Static branching.***Description**

Define multiple new targets based on existing target definition objects.

Usage

```
tar_map(
  values,
  ...,
  names = tidyselect::everything(),
  descriptions = tidyselect::everything(),
  unlist = FALSE,
  delimiter = "_"
)
```

Arguments

values	Named list or data frame with values to iterate over. The names are the names of symbols in the commands and pattern statements, and the elements are values that get substituted in place of those symbols. <code>tar_map()</code> uses these elements to create new R code, so they should be basic types, symbols, or R expressions. For objects even a little bit complicated, especially objects with attributes, it is not obvious how to convert the object into code that generates it. For complicated objects, consider using <code>quote()</code> when you define values, as shown at https://github.com/ropensci/tarchetypes/discussions/105 .
--------	--

...	One or more target definition objects or list of target definition objects. Lists can be arbitrarily nested, as in <code>list()</code> .
names	Subset of names(values) used to generate the suffixes in the names of the new targets. The value of names should be a tidyselect expression such as a call to <code>any_of()</code> or <code>starts_with()</code> .
descriptions	Names of a column in values to append to the custom description of each generated target. The value of descriptions should be a tidyselect expression such as a call to <code>any_of()</code> or <code>starts_with()</code> .
unlist	Logical, whether to flatten the returned list of targets. If <code>unlist = FALSE</code> , the list is nested and sub-lists are named and grouped by the original input targets. If <code>unlist = TRUE</code> , the return value is a flat list of targets named by the new target names.
delimiter	Character of length 1, string to insert between other strings when creating names of targets.

Details

`tar_map()` creates collections of new targets by iterating over a list of arguments and substituting symbols into commands and pattern statements.

Value

A list of new target definition objects. If `unlist` is `FALSE`, the list is nested and sub-lists are named and grouped by the original input targets. If `unlist = TRUE`, the return value is a flat list of targets named by the new target names. See the "target definition objects" section for background.

Target definition objects

Most tarchetypes functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

See Also

Other static branching: `tar_combine()`

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      list(
```

```

    tarchetypes::tar_map(
      list(a = c(12, 34), b = c(45, 78)),
      targets::tar_target(x, a + b),
      targets::tar_target(y, x + a, pattern = map(x))
    )
  })
  targets::tar_manifest()
})
}

```

tar_map_rep

Dynamic batched replication within static branches for data frames.

Description

Define targets for batched replication within static branches for data frames.

`tar_map_rep()` expects an unevaluated symbol for the name argument and an unevaluated expression for command, whereas `tar_map_rep_raw()` expects a character string for name and an evaluated expression object for command.

Usage

```

tar_map_rep(
  name,
  command,
  values = NULL,
  names = NULL,
  descriptions = tidyselect::everything(),
  columns = tidyselect::everything(),
  batches = 1,
  reps = 1,
  rep_workers = 1,
  combine = TRUE,
  delimiter = "_",
  unlist = FALSE,
  tidy_eval = targets::tar_option_get("tidy_eval"),
  packages = targets::tar_option_get("packages"),
  library = targets::tar_option_get("library"),
  format = targets::tar_option_get("format"),
  repository = targets::tar_option_get("repository"),
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),
  garbage_collection = targets::tar_option_get("garbage_collection"),
  deployment = targets::tar_option_get("deployment"),
  priority = targets::tar_option_get("priority"),
  resources = targets::tar_option_get("resources"),

```

```

    storage = targets::tar_option_get("storage"),
    retrieval = targets::tar_option_get("retrieval"),
    cue = targets::tar_option_get("cue"),
    description = targets::tar_option_get("description")
  )

tar_map_rep_raw(
  name,
  command,
  values = NULL,
  names = NULL,
  descriptions = quote(tidyselect::everything()),
  columns = quote(tidyselect::everything()),
  batches = 1,
  reps = 1,
  rep_workers = 1,
  combine = TRUE,
  delimiter = "_",
  unlist = FALSE,
  tidy_eval = targets::tar_option_get("tidy_eval"),
  packages = targets::tar_option_get("packages"),
  library = targets::tar_option_get("library"),
  format = targets::tar_option_get("format"),
  repository = targets::tar_option_get("repository"),
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),
  garbage_collection = targets::tar_option_get("garbage_collection"),
  deployment = targets::tar_option_get("deployment"),
  priority = targets::tar_option_get("priority"),
  resources = targets::tar_option_get("resources"),
  storage = targets::tar_option_get("storage"),
  retrieval = targets::tar_option_get("retrieval"),
  cue = targets::tar_option_get("cue"),
  description = targets::tar_option_get("description")
)

```

Arguments

name	Name of the target. <code>tar_map_rep()</code> expects an unevaluated symbol for the name argument, whereas <code>tar_map_rep_raw()</code> expects a character string for name.
command	R code for a single replicate. Must return a data frame when run. <code>tar_map_rep()</code> expects an unevaluated expression for command, whereas <code>tar_map_rep_raw()</code> expects an evaluated expression object for command.
values	Named list or data frame with values to iterate over. The names are the names of symbols in the commands and pattern statements, and the elements are values that get substituted in place of those symbols. <code>tar_map()</code> uses these elements to create new R code, so they should be basic types, symbols, or R expressions. For objects even a little bit complicated, especially objects with attributes, it is not

obvious how to convert the object into code that generates it. For complicated objects, consider using `quote()` when you define values, as shown at <https://github.com/ropensci/tarchetypes/discussions/105>.

names	Subset of names(values) used to generate the suffixes in the names of the new targets. The value of names should be a tidyselect expression such as a call to <code>any_of()</code> or <code>starts_with()</code> .
descriptions	Names of a column in values to append to the custom description of each generated target. The value of descriptions should be a tidyselect expression such as a call to <code>any_of()</code> or <code>starts_with()</code> .
columns	A tidyselect expression to select which columns of values to append to the output. Columns already in the target output are not appended.
batches	Number of batches. This is also the number of dynamic branches created during <code>tar_make()</code> .
reps	Number of replications in each batch. The total number of replications is <code>batches * reps</code> .
rep_workers	Positive integer of length 1, number of local R processes to use to run reps within batches in parallel. If 1, then reps are run sequentially within each batch. If greater than 1, then reps within batch are run in parallel using a PSOCK cluster.
combine	Logical of length 1, whether to create additional downstream targets to combine the results of static branches. The values argument must not be NULL for this combining to take effect. If combine is TRUE and values is not NULL, then separate targets aggregate all dynamic branches within each static branch, and then a final target combines all the static branches together.
delimiter	Character of length 1, string to insert between other strings when creating names of targets.
unlist	Logical, whether to flatten the returned list of targets. If <code>unlist = FALSE</code> , the list is nested and sub-lists are named and grouped by the original input targets. If <code>unlist = TRUE</code> , the return value is a flat list of targets named by the new target names.
tidy_eval	Whether to invoke tidy evaluation (e.g. the <code>!!</code> operator from <code>rlang</code>) as soon as the target is defined (before <code>tar_make()</code>). Applies to the command argument.
packages	Character vector of packages to load right before the target runs or the output data is reloaded for downstream targets. Use <code>tar_option_set()</code> to set packages globally for all subsequent targets you define.
library	Character vector of library paths to try when loading packages.
format	Optional storage format for the target's return value. With the exception of <code>format = "file"</code> , each target gets a file in <code>_targets/objects</code> , and each format is a different way to save and load this file. See the "Storage formats" section for a detailed list of possible data storage formats.
repository	Character of length 1, remote repository for target storage. Choices: • "local": file system of the local machine. • "aws": Amazon Web Services (AWS) S3 bucket. Can be configured with a non-AWS S3 bucket using the endpoint argument of <code>tar_resources_aws()</code>,

but versioning capabilities may be lost in doing so. See the cloud storage section of <https://books.ropensci.org/targets/data.html> for details for instructions.

- "gcp": Google Cloud Platform storage bucket. See the cloud storage section of <https://books.ropensci.org/targets/data.html> for details for instructions.
- A character string from `tar_repository_cas()` for content-addressable storage.

Note: if repository is not "local" and format is "file" then the target should create a single output file. That output file is uploaded to the cloud and tracked for changes where it exists in the cloud. As of targets version 1.11.0 and higher, the local file is no longer deleted after the target runs.

error

Character of length 1, what to do if the target stops and throws an error. Options:

- "stop": the whole pipeline stops and throws an error.
- "continue": the whole pipeline keeps going.
- "null": The errored target continues and returns NULL. The data hash is deliberately wrong so the target is not up to date for the next run of the pipeline. In addition, as of targets version 1.8.0.9011, a value of NULL is given to upstream dependencies with `error = "null"` if loading fails.
- "abridge": any currently running targets keep running, but no new targets launch after that.
- "trim": all currently running targets stay running. A queued target is allowed to start if:
 1. It is not downstream of the error, and
 2. It is not a sibling branch from the same `tar_target()` call (if the error happened in a dynamic branch).

The idea is to avoid starting any new work that the immediate error impacts. `error = "trim"` is just like `error = "abridge"`, but it allows potentially healthy regions of the dependency graph to begin running. (Visit <https://books.ropensci.org/targets/debugging.html> to learn how to debug targets using saved workspaces.)

memory

Character of length 1, memory strategy. Possible values:

- "auto" (default): equivalent to `memory = "transient"` in almost all cases. But to avoid superfluous reads from disk, `memory = "auto"` is equivalent to `memory = "persistent"` for non-dynamically-branched targets that other targets dynamically branch over. For example: if your pipeline has `tar_target(name = y, command = x, pattern = map(x))`, then `tar_target(name = x, command = f(), memory = "auto")` will use persistent memory for `x` in order to avoid rereading all of `x` for every branch of `y`.
- "transient": the target gets unloaded after every new target completes. Either way, the target gets automatically loaded into memory whenever another target needs the value.
- "persistent": the target stays in memory until the end of the pipeline (unless storage is "worker", in which case targets unloads the value from memory right after storing it in order to avoid sending copious data over a network).

For cloud-based file targets (e.g. `format = "file"` with `repository = "aws"`), the memory option applies to the temporary local copy of the file: "persistent" means it remains until the end of the pipeline and is then deleted, and "transient" means it gets deleted as soon as possible. The former conserves bandwidth, and the latter conserves local storage.

garbage_collection	Logical: TRUE to run <code>base::gc()</code> just before the target runs, in whatever R process it is about to run (which could be a parallel worker). FALSE to omit garbage collection. Numeric values get converted to FALSE. The <code>garbage_collection</code> option in <code>tar_option_set()</code> is independent of the argument of the same name in <code>tar_target()</code> .
deployment	Character of length 1. If deployment is "main", then the target will run on the central controlling R process. Otherwise, if deployment is "worker" and you set up the pipeline with distributed/parallel computing, then the target runs on a parallel worker. For more on distributed/parallel computing in targets, please visit https://books.ropensci.org/targets/crew.html .
priority	Deprecated on 2025-04-08 (targets version 1.10.1.9013). targets has moved to a more efficient scheduling algorithm (https://github.com/ropensci/targets/issues/1458) which cannot support priorities. The <code>priority</code> argument of <code>tar_target()</code> no longer has a reliable effect on execution order.
resources	Object returned by <code>tar_resources()</code> with optional settings for high-performance computing functionality, alternative data storage formats, and other optional capabilities of targets. See <code>tar_resources()</code> for details.
storage	Character string to control when the output of the target is saved to storage. Only relevant when using targets with parallel workers (https://books.ropensci.org/targets/crew.html). Must be one of the following values: "worker" (default): the worker saves/uploads the value. "main": the target's return value is sent back to the host machine and saved/uploaded locally. "none": targets makes no attempt to save the result of the target to storage in the location where targets expects it to be. Saving to storage is the responsibility of the user. Use with caution.
retrieval	Character string to control when the current target loads its dependencies into memory before running. (Here, a "dependency" is another target upstream that the current one depends on.) Only relevant when using targets with parallel workers (https://books.ropensci.org/targets/crew.html). Must be one of the following values: "auto" (default): equivalent to <code>retrieval = "worker"</code> in almost all cases. But to avoid unnecessary reads from disk, <code>retrieval = "auto"</code> is equivalent to <code>retrieval = "main"</code> for dynamic branches that branch over non-dynamic targets. For example: if your pipeline has <code>tar_target(x, command = f())</code>, then <code>tar_target(y, command = x, pattern = map(x), retrieval = "auto")</code> will use "main" retrieval in order to avoid rereading all of x for every branch of y. "worker": the worker loads the target's dependencies.

	• "main": the target's dependencies are loaded on the host machine and sent to the worker before the target runs. • "none": targets makes no attempt to load its dependencies. With <code>retrieval = "none"</code>, loading dependencies is the responsibility of the user. Use with caution.
cue	An optional object from <code>tar_cue()</code> to customize the rules that decide whether the target is up to date.
description	Character of length 1, a custom free-form human-readable text description of the target. Descriptions appear as target labels in functions like <code>tar_manifest()</code> and <code>tar_visnetwork()</code> , and they let you select subsets of targets for the <code>names</code> argument of functions like <code>tar_make()</code> . For example, <code>tar_manifest(names = tar_described_as(starts_with("survival model")))</code> lists all the targets whose descriptions start with the character string "survival model".

Value

A list of new target definition objects. See the "Target definition objects" section for background.

Target definition objects

Most `tarchetypes` functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

Replicate-specific seeds

In ordinary pipelines, each target has its own unique deterministic pseudo-random number generator seed derived from its target name. In batched replicate, however, each batch is a target with multiple replicate within that batch. That is why `tar_rep()` and friends give each *replicate* its own unique seed. Each replicate-specific seed is created based on the dynamic parent target name, `tar_option_get("seed")` (for `targets` version 0.13.5.9000 and above), batch index, and rep-within-batch index. The seed is set just before the replicate runs. Replicate-specific seeds are invariant to batching structure. In other words, `tar_rep(name = x, command = rnorm(1), batches = 100, reps = 1, ...)` produces the same numerical output as `tar_rep(name = x, command = rnorm(1), batches = 10, reps = 10, ...)` (but with different batch names). Other target factories with this seed scheme are `tar_rep2()`, `tar_map_rep()`, `tar_map2_count()`, `tar_map2_size()`, and `tar_render_rep()`. For the `tar_map2_*` functions, it is possible to manually supply your own seeds through the `command1` argument and then invoke them in your custom code for `command2` (`set.seed()`, `withr::with_seed`, or `withr::local_seed()`). For `tar_render_rep()`, custom seeds can be supplied to the `params` argument and then invoked in the individual R Markdown reports. Likewise with `tar_quarto_rep()` and the `execute_params` argument.

See Also

Other branching: `tar_map2()`, `tar_map2_count()`, `tar_map2_size()`, `tar_rep()`, `tar_rep2()`, `tar_rep_map()`, `tar_rep_map_raw()`

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      library(tarchetypes)
      # Just a sketch of a Bayesian sensitivity analysis of hyperparameters:
      assess_hyperparameters <- function(sigma1, sigma2) {
        # data <- simulate_random_data() # user-defined function
        # run_model(data, sigma1, sigma2) # user-defined function
        # Mock output from the model:
        posterior_samples <- stats::rnorm(1000, 0, sigma1 + sigma2)
        tibble::tibble(
          posterior_median = median(posterior_samples),
          posterior_quantile_0.025 = quantile(posterior_samples, 0.025),
          posterior_quantile_0.975 = quantile(posterior_samples, 0.975)
        )
      }
      hyperparameters <- tibble::tibble(
        scenario = c("tight", "medium", "diffuse"),
        sigma1 = c(10, 50, 50),
        sigma2 = c(10, 5, 10)
      )
    })
    list(
      tar_map_rep(
        name = sensitivity_analysis,
        command = assess_hyperparameters(sigma1, sigma2),
        values = hyperparameters,
        names = tidyselect::any_of("scenario"),
        batches = 2,
        reps = 3
      ),
      tar_map_rep_raw(
        name = "sensitivity_analysis2",
        command = quote(assess_hyperparameters(sigma1, sigma2)),
        values = hyperparameters,
        names = tidyselect::any_of("scenario"),
        batches = 2,
        reps = 3
      )
    )
  })
  targets::tar_make()
  targets::tar_read(sensitivity_analysis)
}
```

tar_map2_count

*Dynamic-within-static branching for data frames (count batching).***Description**

Define targets for batched dynamic-within-static branching for data frames, where the user sets the (maximum) number of batches.

`tar_map2_count()` expects unevaluated language for arguments `name`, `command1`, `command2`, `columns1`, and `columns2`. `tar_map2_count_raw()` expects a character string for `name` and an evaluated expression object for each of `command1`, `command2`, `columns1`, and `columns2`.

Usage

```
tar_map2_count(
  name,
  command1,
  command2,
  values = NULL,
  names = NULL,
  descriptions = tidyselect::everything(),
  batches = 1L,
  combine = TRUE,
  suffix1 = "1",
  suffix2 = "2",
  columns1 = tidyselect::everything(),
  columns2 = tidyselect::everything(),
  rep_workers = 1,
  delimiter = "_",
  unlist = FALSE,
  tidy_eval = targets::tar_option_get("tidy_eval"),
  packages = targets::tar_option_get("packages"),
  library = targets::tar_option_get("library"),
  format = targets::tar_option_get("format"),
  repository = targets::tar_option_get("repository"),
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),
  garbage_collection = targets::tar_option_get("garbage_collection"),
  deployment = targets::tar_option_get("deployment"),
  priority = targets::tar_option_get("priority"),
  resources = targets::tar_option_get("resources"),
  storage = targets::tar_option_get("storage"),
  retrieval = targets::tar_option_get("retrieval"),
  cue = targets::tar_option_get("cue"),
  description = targets::tar_option_get("description")
)
```

```

tar_map2_count_raw(
  name,
  command1,
  command2,
  values = NULL,
  names = NULL,
  descriptions = quote(tidyselect::everything()),
  batches = 1L,
  combine = TRUE,
  suffix1 = "1",
  suffix2 = "2",
  columns1 = quote(tidyselect::everything()),
  columns2 = quote(tidyselect::everything()),
  rep_workers = 1,
  delimiter = "_",
  unlist = FALSE,
  tidy_eval = targets::tar_option_get("tidy_eval"),
  packages = targets::tar_option_get("packages"),
  library = targets::tar_option_get("library"),
  format = targets::tar_option_get("format"),
  repository = targets::tar_option_get("repository"),
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),
  garbage_collection = targets::tar_option_get("garbage_collection"),
  deployment = targets::tar_option_get("deployment"),
  priority = targets::tar_option_get("priority"),
  resources = targets::tar_option_get("resources"),
  storage = targets::tar_option_get("storage"),
  retrieval = targets::tar_option_get("retrieval"),
  cue = targets::tar_option_get("cue"),
  description = targets::tar_option_get("description")
)

```

Arguments

name	Name of the target. <code>tar_rep()</code> expects unevaluated name and command arguments (e.g. <code>tar_rep(name = sim, command = simulate())</code>) whereas <code>tar_rep_raw()</code> expects an evaluated string for name and an evaluated expression object for command (e.g. <code>tar_rep_raw(name = "sim", command = quote(simulate()))</code>).
command1	R code to create named arguments to command2. Must return a data frame with one row per call to command2 when run. In regular <code>tarchetypes</code> functions, the <code>command1</code> argument is an unevaluated expression. In the <code>"_raw"</code> versions of functions, <code>command1</code> is an evaluated expression object.
command2	R code to map over the data frame of arguments produced by <code>command1</code> . Must return a data frame. In regular <code>tarchetypes</code> functions, the <code>command2</code> argument is an unevaluated

	expression. In the "_raw" versions of functions, command2 is an evaluated expression object.
values	Named list or data frame with values to iterate over. The names are the names of symbols in the commands and pattern statements, and the elements are values that get substituted in place of those symbols. <code>tar_map()</code> uses these elements to create new R code, so they should be basic types, symbols, or R expressions. For objects even a little bit complicated, especially objects with attributes, it is not obvious how to convert the object into code that generates it. For complicated objects, consider using <code>quote()</code> when you define values, as shown at https://github.com/ropensci/tarchetypes/discussions/105 .
names	Subset of names(values) used to generate the suffixes in the names of the new targets. The value of names should be a tidyselect expression such as a call to <code>any_of()</code> or <code>starts_with()</code> .
descriptions	Names of a column in values to append to the custom description of each generated target. The value of descriptions should be a tidyselect expression such as a call to <code>any_of()</code> or <code>starts_with()</code> .
batches	Positive integer of length 1, maximum number of batches (dynamic branches within static branches) of the downstream (command2) targets. Batches are formed from row groups of the command1 target output.
combine	Logical of length 1, whether to create additional downstream targets to combine the results of static branches. The values argument must not be NULL for this combining to take effect. If combine is TRUE and values is not NULL, then separate targets aggregate all dynamic branches within each static branch, and then a final target combines all the static branches together.
suffix1	Character of length 1, suffix to apply to the command1 targets to distinguish them from the command2 targets.
suffix2	Character of length 1, suffix to apply to the command2 targets to distinguish them from the command1 targets.
columns1	A tidyselect expression to select which columns of values to append to the output of all targets. Columns already in the target output are not appended. In regular tarchetypes functions, the columns1 argument is an unevaluated expression. In the "_raw" versions of functions, columns1 is an evaluated expression object.
columns2	A tidyselect expression to select which columns of command1 output to append to command2 output. Columns already in the target output are not appended. columns1 takes precedence over columns2. In regular tarchetypes functions, the columns2 argument is an unevaluated expression. In the "_raw" versions of functions, columns2 is an evaluated expression object.
rep_workers	Positive integer of length 1, number of local R processes to use to run reps within batches in parallel. If 1, then reps are run sequentially within each batch. If greater than 1, then reps within batch are run in parallel using a PSOCK cluster.
delimiter	Character of length 1, string to insert between other strings when creating names of targets.

unlist	Logical, whether to flatten the returned list of targets. If <code>unlist = FALSE</code> , the list is nested and sub-lists are named and grouped by the original input targets. If <code>unlist = TRUE</code> , the return value is a flat list of targets named by the new target names.
tidy_eval	Whether to invoke tidy evaluation (e.g. the <code>!!</code> operator from <code>rlang</code>) as soon as the target is defined (before <code>tar_make()</code>). Applies to the command argument.
packages	Character vector of packages to load right before the target runs or the output data is reloaded for downstream targets. Use <code>tar_option_set()</code> to set packages globally for all subsequent targets you define.
library	Character vector of library paths to try when loading packages.
format	Optional storage format for the target's return value. With the exception of <code>format = "file"</code> , each target gets a file in <code>_targets/objects</code> , and each format is a different way to save and load this file. See the "Storage formats" section for a detailed list of possible data storage formats.
repository	Character of length 1, remote repository for target storage. Choices: • <code>"local"</code>: file system of the local machine. • <code>"aws"</code>: Amazon Web Services (AWS) S3 bucket. Can be configured with a non-AWS S3 bucket using the <code>endpoint</code> argument of <code>tar_resources_aws()</code>, but versioning capabilities may be lost in doing so. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions. • <code>"gcp"</code>: Google Cloud Platform storage bucket. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions. • A character string from <code>tar_repository_cas()</code> for content-addressable storage. Note: if <code>repository</code> is not <code>"local"</code> and <code>format</code> is <code>"file"</code> then the target should create a single output file. That output file is uploaded to the cloud and tracked for changes where it exists in the cloud. As of targets version 1.11.0 and higher, the local file is no longer deleted after the target runs.
error	Character of length 1, what to do if the target stops and throws an error. Options: • <code>"stop"</code>: the whole pipeline stops and throws an error. • <code>"continue"</code>: the whole pipeline keeps going. • <code>"null"</code>: The errored target continues and returns <code>NULL</code>. The data hash is deliberately wrong so the target is not up to date for the next run of the pipeline. In addition, as of targets version 1.8.0.9011, a value of <code>NULL</code> is given to upstream dependencies with <code>error = "null"</code> if loading fails. • <code>"abridge"</code>: any currently running targets keep running, but no new targets launch after that. • <code>"trim"</code>: all currently running targets stay running. A queued target is allowed to start if: 1. It is not downstream of the error, and 2. It is not a sibling branch from the same <code>tar_target()</code> call (if the error happened in a dynamic branch).

The idea is to avoid starting any new work that the immediate error impacts. `error = "trim"` is just like `error = "abridge"`, but it allows potentially healthy regions of the dependency graph to begin running. (Visit <https://books.ropensci.org/targets/debugging.html> to learn how to debug targets using saved workspaces.)

memory

Character of length 1, memory strategy. Possible values:

- "auto" (default): equivalent to `memory = "transient"` in almost all cases. But to avoid superfluous reads from disk, `memory = "auto"` is equivalent to `memory = "persistent"` for non-dynamically-branched targets that other targets dynamically branch over. For example: if your pipeline has `tar_target(name = y, command = x, pattern = map(x))`, then `tar_target(name = x, command = f(), memory = "auto")` will use persistent memory for `x` in order to avoid rereading all of `x` for every branch of `y`.
- "transient": the target gets unloaded after every new target completes. Either way, the target gets automatically loaded into memory whenever another target needs the value.
- "persistent": the target stays in memory until the end of the pipeline (unless storage is "worker", in which case targets unloads the value from memory right after storing it in order to avoid sending copious data over a network).

For cloud-based file targets (e.g. `format = "file"` with `repository = "aws"`), the memory option applies to the temporary local copy of the file: "persistent" means it remains until the end of the pipeline and is then deleted, and "transient" means it gets deleted as soon as possible. The former conserves bandwidth, and the latter conserves local storage.

garbage_collection

Logical: TRUE to run `base::gc()` just before the target runs, in whatever R process it is about to run (which could be a parallel worker). FALSE to omit garbage collection. Numeric values get converted to FALSE. The `garbage_collection` option in `tar_option_set()` is independent of the argument of the same name in `tar_target()`.

deployment

Character of length 1. If deployment is "main", then the target will run on the central controlling R process. Otherwise, if deployment is "worker" and you set up the pipeline with distributed/parallel computing, then the target runs on a parallel worker. For more on distributed/parallel computing in targets, please visit <https://books.ropensci.org/targets/crew.html>.

priority

Deprecated on 2025-04-08 (targets version 1.10.1.9013). targets has moved to a more efficient scheduling algorithm (<https://github.com/ropensci/targets/issues/1458>) which cannot support priorities. The `priority` argument of `tar_target()` no longer has a reliable effect on execution order.

resources

Object returned by `tar_resources()` with optional settings for high-performance computing functionality, alternative data storage formats, and other optional capabilities of targets. See `tar_resources()` for details.

storage

Character string to control when the output of the target is saved to storage. Only relevant when using targets with parallel workers (<https://books.ropensci.org/targets/crew.html>). Must be one of the following values:

	• "worker" (default): the worker saves/uploads the value. • "main": the target's return value is sent back to the host machine and saved/uploaded locally. • "none": targets makes no attempt to save the result of the target to storage in the location where targets expects it to be. Saving to storage is the responsibility of the user. Use with caution.
retrieval	Character string to control when the current target loads its dependencies into memory before running. (Here, a "dependency" is another target upstream that the current one depends on.) Only relevant when using targets with parallel workers (https://books.ropensci.org/targets/crew.html). Must be one of the following values: • "auto" (default): equivalent to retrieval = "worker" in almost all cases. But to avoid unnecessary reads from disk, retrieval = "auto" is equivalent to retrieval = "main" for dynamic branches that branch over non-dynamic targets. For example: if your pipeline has <code>tar_target(x, command = f())</code>, then <code>tar_target(y, command = x, pattern = map(x), retrieval = "auto")</code> will use "main" retrieval in order to avoid rereading all of x for every branch of y. • "worker": the worker loads the target's dependencies. • "main": the target's dependencies are loaded on the host machine and sent to the worker before the target runs. • "none": targets makes no attempt to load its dependencies. With retrieval = "none", loading dependencies is the responsibility of the user. Use with caution.
cue	An optional object from <code>tar_cue()</code> to customize the rules that decide whether the target is up to date.
description	Character of length 1, a custom free-form human-readable text description of the target. Descriptions appear as target labels in functions like <code>tar_manifest()</code> and <code>tar_visnetwork()</code> , and they let you select subsets of targets for the names argument of functions like <code>tar_make()</code> . For example, <code>tar_manifest(names = tar_described_as(starts_with("survival model")))</code> lists all the targets whose descriptions start with the character string "survival model".

Details

Static branching creates one pair of targets for each row in values. In each pair, there is an upstream non-dynamic target that runs `command1` and a downstream dynamic target that runs `command2`. `command1` produces a data frame of arguments to `command2`, and `command2` dynamically maps over these arguments in batches.

Value

A list of new target definition objects. See the "Target definition objects" section for background.

Target definition objects

Most tarchetypes functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis

pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

Replicate-specific seeds

In ordinary pipelines, each target has its own unique deterministic pseudo-random number generator seed derived from its target name. In batched replicate, however, each batch is a target with multiple replicate within that batch. That is why `tar_rep()` and friends give each *replicate* its own unique seed. Each replicate-specific seed is created based on the dynamic parent target name, `tar_option_get("seed")` (for targets version 0.13.5.9000 and above), batch index, and rep-within-batch index. The seed is set just before the replicate runs. Replicate-specific seeds are invariant to batching structure. In other words, `tar_rep(name = x, command = rnorm(1), batches = 100, reps = 1, ...)` produces the same numerical output as `tar_rep(name = x, command = rnorm(1), batches = 10, reps = 10, ...)` (but with different batch names). Other target factories with this seed scheme are `tar_rep2()`, `tar_map_rep()`, `tar_map2_count()`, `tar_map2_size()`, and `tar_render_rep()`. For the `tar_map2_*`() functions, it is possible to manually supply your own seeds through the `command1` argument and then invoke them in your custom code for `command2` (`set.seed()`, `withr::with_seed`, or `withr::local_seed()`). For `tar_render_rep()`, custom seeds can be supplied to the `params` argument and then invoked in the individual R Markdown reports. Likewise with `tar_quarto_rep()` and the `execute_params` argument.

See Also

Other branching: `tar_map2()`, `tar_map2_size()`, `tar_map_rep()`, `tar_rep()`, `tar_rep2()`, `tar_rep_map()`, `tar_rep_map_raw()`

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      tarchetypes::tar_map2_count(
        x,
        command1 = tibble::tibble(
          arg1 = arg1,
          arg2 = seq_len(6)
        ),
        command2 = tibble::tibble(
          result = paste(arg1, arg2),
          random = sample.int(1e9, size = 1),
          length_input = length(arg1)
        ),
        values = tibble::tibble(arg1 = letters[seq_len(2)]),
        batches = 3
      )
    })
  })
}
```

```

}))
targets::tar_make()
targets::tar_read(x)
# With tar_map2_count_raw():
targets::tar_script({
  tarchetypes::tar_map2_count_raw(
    name = "x",
    command1 = quote(
      tibble::tibble(
        arg1 = arg1,
        arg2 = seq_len(6)
      )
    ),
    command2 = quote(
      tibble::tibble(
        result = paste(arg1, arg2),
        random = sample.int(1e9, size = 1),
        length_input = length(arg1)
      )
    ),
    values = tibble::tibble(arg1 = letters[seq_len(2)]),
    batches = 3
  )
})
})
}

```

tar_map2_size

Dynamic-within-static branching for data frames (size batching).

Description

Define targets for batched dynamic-within-static branching for data frames, where the user sets the (maximum) size of each batch.

`tar_map2_size()` expects unevaluated language for arguments `name`, `command1`, `command2`, `columns1`, and `columns2`. `tar_map2_size_raw()` expects a character string for `name` and an evaluated expression object for each of `command1`, `command2`, `columns1`, and `columns2`.

Usage

```

tar_map2_size(
  name,
  command1,
  command2,
  values = NULL,
  names = NULL,
  descriptions = tidyselect::everything(),
  size = Inf,
  combine = TRUE,

```

```

    suffix1 = "1",
    suffix2 = "2",
    columns1 = tidyselect::everything(),
    columns2 = tidyselect::everything(),
    rep_workers = 1,
    delimiter = "_",
    unlist = FALSE,
    tidy_eval = targets::tar_option_get("tidy_eval"),
    packages = targets::tar_option_get("packages"),
    library = targets::tar_option_get("library"),
    format = targets::tar_option_get("format"),
    repository = targets::tar_option_get("repository"),
    error = targets::tar_option_get("error"),
    memory = targets::tar_option_get("memory"),
    garbage_collection = targets::tar_option_get("garbage_collection"),
    deployment = targets::tar_option_get("deployment"),
    priority = targets::tar_option_get("priority"),
    resources = targets::tar_option_get("resources"),
    storage = targets::tar_option_get("storage"),
    retrieval = targets::tar_option_get("retrieval"),
    cue = targets::tar_option_get("cue"),
    description = targets::tar_option_get("description")
  )

tar_map2_size_raw(
  name,
  command1,
  command2,
  values = NULL,
  names = NULL,
  descriptions = quote(tidyselect::everything()),
  size = Inf,
  combine = TRUE,
  suffix1 = "1",
  suffix2 = "2",
  columns1 = quote(tidyselect::everything()),
  columns2 = quote(tidyselect::everything()),
  rep_workers = 1,
  delimiter = "_",
  unlist = FALSE,
  tidy_eval = targets::tar_option_get("tidy_eval"),
  packages = targets::tar_option_get("packages"),
  library = targets::tar_option_get("library"),
  format = targets::tar_option_get("format"),
  repository = targets::tar_option_get("repository"),
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),
  garbage_collection = targets::tar_option_get("garbage_collection"),

```

```

deployment = targets::tar_option_get("deployment"),
priority = targets::tar_option_get("priority"),
resources = targets::tar_option_get("resources"),
storage = targets::tar_option_get("storage"),
retrieval = targets::tar_option_get("retrieval"),
cue = targets::tar_option_get("cue"),
description = targets::tar_option_get("description")
)

```

Arguments

name	Name of the target. <code>tar_rep()</code> expects unevaluated name and command arguments (e.g. <code>tar_rep(name = sim, command = simulate())</code>) whereas <code>tar_rep_raw()</code> expects an evaluated string for name and an evaluated expression object for command (e.g. <code>tar_rep_raw(name = "sim", command = quote(simulate()))</code>).
command1	R code to create named arguments to command2. Must return a data frame with one row per call to command2 when run. In regular tarchetypes functions, the command1 argument is an unevaluated expression. In the "_raw" versions of functions, command1 is an evaluated expression object.
command2	R code to map over the data frame of arguments produced by command1. Must return a data frame. In regular tarchetypes functions, the command2 argument is an unevaluated expression. In the "_raw" versions of functions, command2 is an evaluated expression object.
values	Named list or data frame with values to iterate over. The names are the names of symbols in the commands and pattern statements, and the elements are values that get substituted in place of those symbols. <code>tar_map()</code> uses these elements to create new R code, so they should be basic types, symbols, or R expressions. For objects even a little bit complicated, especially objects with attributes, it is not obvious how to convert the object into code that generates it. For complicated objects, consider using <code>quote()</code> when you define values, as shown at https://github.com/ropensci/tarchetypes/discussions/105 .
names	Subset of names(values) used to generate the suffixes in the names of the new targets. The value of names should be a tidyselect expression such as a call to <code>any_of()</code> or <code>starts_with()</code> .
descriptions	Names of a column in values to append to the custom description of each generated target. The value of descriptions should be a tidyselect expression such as a call to <code>any_of()</code> or <code>starts_with()</code> .
size	Positive integer of length 1, maximum number of rows in each batch for the downstream (command2) targets. Batches are formed from row groups of the command1 target output.
combine	Logical of length 1, whether to create additional downstream targets to combine the results of static branches. The values argument must not be NULL for this combining to take effect. If combine is TRUE and values is not NULL, then separate targets aggregate all dynamic branches within each static branch, and then a final target combines all the static branches together.

suffix1	Character of length 1, suffix to apply to the command1 targets to distinguish them from the command2 targets.
suffix2	Character of length 1, suffix to apply to the command2 targets to distinguish them from the command1 targets.
columns1	A tidyselect expression to select which columns of values to append to the output of all targets. Columns already in the target output are not appended. In regular tarchetypes functions, the columns1 argument is an unevaluated expression. In the "_raw" versions of functions, columns1 is an evaluated expression object.
columns2	A tidyselect expression to select which columns of command1 output to append to command2 output. Columns already in the target output are not appended. columns1 takes precedence over columns2. In regular tarchetypes functions, the columns2 argument is an unevaluated expression. In the "_raw" versions of functions, columns2 is an evaluated expression object.
rep_workers	Positive integer of length 1, number of local R processes to use to run reps within batches in parallel. If 1, then reps are run sequentially within each batch. If greater than 1, then reps within batch are run in parallel using a PSOCK cluster.
delimiter	Character of length 1, string to insert between other strings when creating names of targets.
unlist	Logical, whether to flatten the returned list of targets. If unlist = FALSE, the list is nested and sub-lists are named and grouped by the original input targets. If unlist = TRUE, the return value is a flat list of targets named by the new target names.
tidy_eval	Whether to invoke tidy evaluation (e.g. the !! operator from rlang) as soon as the target is defined (before tar_make()). Applies to the command argument.
packages	Character vector of packages to load right before the target runs or the output data is reloaded for downstream targets. Use tar_option_set() to set packages globally for all subsequent targets you define.
library	Character vector of library paths to try when loading packages.
format	Optional storage format for the target's return value. With the exception of format = "file", each target gets a file in _targets/objects, and each format is a different way to save and load this file. See the "Storage formats" section for a detailed list of possible data storage formats.
repository	Character of length 1, remote repository for target storage. Choices: • "local": file system of the local machine. • "aws": Amazon Web Services (AWS) S3 bucket. Can be configured with a non-AWS S3 bucket using the endpoint argument of <code>tar_resources_aws()</code>, but versioning capabilities may be lost in doing so. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions. • "gcp": Google Cloud Platform storage bucket. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions.

- A character string from `tar_repository_cas()` for content-addressable storage.

Note: if repository is not "local" and format is "file" then the target should create a single output file. That output file is uploaded to the cloud and tracked for changes where it exists in the cloud. As of targets version 1.11.0 and higher, the local file is no longer deleted after the target runs.

error

Character of length 1, what to do if the target stops and throws an error. Options:

- "stop": the whole pipeline stops and throws an error.
- "continue": the whole pipeline keeps going.
- "null": The errored target continues and returns NULL. The data hash is deliberately wrong so the target is not up to date for the next run of the pipeline. In addition, as of targets version 1.8.0.9011, a value of NULL is given to upstream dependencies with `error = "null"` if loading fails.
- "abridge": any currently running targets keep running, but no new targets launch after that.
- "trim": all currently running targets stay running. A queued target is allowed to start if:
 1. It is not downstream of the error, and
 2. It is not a sibling branch from the same `tar_target()` call (if the error happened in a dynamic branch).

The idea is to avoid starting any new work that the immediate error impacts. `error = "trim"` is just like `error = "abridge"`, but it allows potentially healthy regions of the dependency graph to begin running. (Visit <https://books.ropensci.org/targets/debugging.html> to learn how to debug targets using saved workspaces.)

memory

Character of length 1, memory strategy. Possible values:

- "auto" (default): equivalent to `memory = "transient"` in almost all cases. But to avoid superfluous reads from disk, `memory = "auto"` is equivalent to `memory = "persistent"` for non-dynamically-branched targets that other targets dynamically branch over. For example: if your pipeline has `tar_target(name = y, command = x, pattern = map(x))`, then `tar_target(name = x, command = f(), memory = "auto")` will use persistent memory for `x` in order to avoid rereading all of `x` for every branch of `y`.
- "transient": the target gets unloaded after every new target completes. Either way, the target gets automatically loaded into memory whenever another target needs the value.
- "persistent": the target stays in memory until the end of the pipeline (unless storage is "worker", in which case targets unloads the value from memory right after storing it in order to avoid sending copious data over a network).

For cloud-based file targets (e.g. `format = "file"` with `repository = "aws"`), the memory option applies to the temporary local copy of the file: "persistent" means it remains until the end of the pipeline and is then deleted, and "transient" means it gets deleted as soon as possible. The former conserves bandwidth, and the latter conserves local storage.

garbage_collection	Logical: TRUE to run <code>base::gc()</code> just before the target runs, in whatever R process it is about to run (which could be a parallel worker). FALSE to omit garbage collection. Numeric values get converted to FALSE. The <code>garbage_collection</code> option in <code>tar_option_set()</code> is independent of the argument of the same name in <code>tar_target()</code> .
deployment	Character of length 1. If deployment is "main", then the target will run on the central controlling R process. Otherwise, if deployment is "worker" and you set up the pipeline with distributed/parallel computing, then the target runs on a parallel worker. For more on distributed/parallel computing in targets, please visit https://books.ropensci.org/targets/crew.html .
priority	Deprecated on 2025-04-08 (targets version 1.10.1.9013). targets has moved to a more efficient scheduling algorithm (https://github.com/ropensci/targets/issues/1458) which cannot support priorities. The <code>priority</code> argument of <code>tar_target()</code> no longer has a reliable effect on execution order.
resources	Object returned by <code>tar_resources()</code> with optional settings for high-performance computing functionality, alternative data storage formats, and other optional capabilities of targets. See <code>tar_resources()</code> for details.
storage	Character string to control when the output of the target is saved to storage. Only relevant when using targets with parallel workers (https://books.ropensci.org/targets/crew.html). Must be one of the following values: • "worker" (default): the worker saves/uploads the value. • "main": the target's return value is sent back to the host machine and saved/uploaded locally. • "none": targets makes no attempt to save the result of the target to storage in the location where targets expects it to be. Saving to storage is the responsibility of the user. Use with caution.
retrieval	Character string to control when the current target loads its dependencies into memory before running. (Here, a "dependency" is another target upstream that the current one depends on.) Only relevant when using targets with parallel workers (https://books.ropensci.org/targets/crew.html). Must be one of the following values: • "auto" (default): equivalent to <code>retrieval = "worker"</code> in almost all cases. But to avoid unnecessary reads from disk, <code>retrieval = "auto"</code> is equivalent to <code>retrieval = "main"</code> for dynamic branches that branch over non-dynamic targets. For example: if your pipeline has <code>tar_target(x, command = f())</code>, then <code>tar_target(y, command = x, pattern = map(x), retrieval = "auto")</code> will use "main" retrieval in order to avoid rereading all of <code>x</code> for every branch of <code>y</code>. • "worker": the worker loads the target's dependencies. • "main": the target's dependencies are loaded on the host machine and sent to the worker before the target runs. • "none": targets makes no attempt to load its dependencies. With <code>retrieval = "none"</code>, loading dependencies is the responsibility of the user. Use with caution.

cue	An optional object from <code>tar_cue()</code> to customize the rules that decide whether the target is up to date.
description	Character of length 1, a custom free-form human-readable text description of the target. Descriptions appear as target labels in functions like <code>tar_manifest()</code> and <code>tar_visnetwork()</code> , and they let you select subsets of targets for the <code>names</code> argument of functions like <code>tar_make()</code> . For example, <code>tar_manifest(names = tar_described_as(starts_with("survival model")))</code> lists all the targets whose descriptions start with the character string "survival model".

Details

Static branching creates one pair of targets for each row in `values`. In each pair, there is an upstream non-dynamic target that runs `command1` and a downstream dynamic target that runs `command2`. `command1` produces a data frame of arguments to `command2`, and `command2` dynamically maps over these arguments in batches.

Value

A list of new target definition objects. See the "Target definition objects" section for background.

Target definition objects

Most `tarchetypes` functions are target factories, which means they return target definition objects or lists of target definition objects. Target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

Replicate-specific seeds

In ordinary pipelines, each target has its own unique deterministic pseudo-random number generator seed derived from its target name. In batched replicate, however, each batch is a target with multiple replicate within that batch. That is why `tar_rep()` and friends give each *replicate* its own unique seed. Each replicate-specific seed is created based on the dynamic parent target name, `tar_option_get("seed")` (for `targets` version 0.13.5.9000 and above), batch index, and rep-within-batch index. The seed is set just before the replicate runs. Replicate-specific seeds are invariant to batching structure. In other words, `tar_rep(name = x, command = rnorm(1), batches = 100, reps = 1, ...)` produces the same numerical output as `tar_rep(name = x, command = rnorm(1), batches = 10, reps = 10, ...)` (but with different batch names). Other target factories with this seed scheme are `tar_rep2()`, `tar_map_rep()`, `tar_map2_count()`, `tar_map2_size()`, and `tar_render_rep()`. For the `tar_map2_*` functions, it is possible to manually supply your own seeds through the `command1` argument and then invoke them in your custom code for `command2` (`set.seed()`, `withr::with_seed`, or `withr::local_seed()`). For `tar_render_rep()`, custom seeds can be supplied to the `params` argument and then invoked in the individual R Markdown reports. Likewise with `tar_quarto_rep()` and the `execute_params` argument.

See Also

Other branching: [tar_map2\(\)](#), [tar_map2_count\(\)](#), [tar_map_rep\(\)](#), [tar_rep\(\)](#), [tar_rep2\(\)](#), [tar_rep_map\(\)](#), [tar_rep_map_raw\(\)](#)

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      tarchetypes::tar_map2_size(
        x,
        command1 = tibble::tibble(
          arg1 = arg1,
          arg2 = seq_len(6)
        ),
        command2 = tibble::tibble(
          result = paste(arg1, arg2),
          random = sample.int(1e9, size = 1),
          length_input = length(arg1)
        ),
        values = tibble::tibble(arg1 = letters[seq_len(2)]),
        size = 2
      )
    })
    targets::tar_make()
    targets::tar_read(x)
    # With tar_map2_size_raw():
    targets::tar_script({
      tarchetypes::tar_map2_size_raw(
        name = "x",
        command1 = quote(
          tibble::tibble(
            arg1 = arg1,
            arg2 = seq_len(6)
          )
        ),
        command2 = quote(
          tibble::tibble(
            result = paste(arg1, arg2),
            random = sample.int(1e9, size = 1),
            length_input = length(arg1)
          )
        ),
        values = tibble::tibble(arg1 = letters[seq_len(2)]),
        size = 2
      )
    })
  })
}
```

tar_plan	<i>A drake-plan-like pipeline DSL</i>
----------	---------------------------------------

Description

Simplify target specification in pipelines.

Usage

```
tar_plan(...)
```

Arguments

... Named and unnamed targets. All named targets must follow the drake-plan-like `target = command` syntax, and all unnamed arguments must be explicit calls to create target definition objects, e.g. `tar_target()`, target factories like `tar_render()`, or similar.

Details

Allows targets with just targets and commands to be written in the pipeline as `target = command` instead of `tar_target(target, command)`. Also supports ordinary target definition objects if they are unnamed. `tar_plan(x = 1, y = 2, tar_target(z, 3), tar_render(r, "r.Rmd"))` is equivalent to:

```
list(
  tar_target(x, 1),
  tar_target(y, 2),
  tar_target(z, 3),
  tar_render(r, "r.Rmd")
)
```

Value

A list of `tar_target()` objects. See the "Target definition objects" section for background.

Target definition objects

Most tarctypes functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      library(tarchetypes)
      tar_plan(
        tarchetypes::tar_fst_tbl(data, data.frame(x = seq_len(26))),
        means = colMeans(data) # No need for tar_target() for simple cases.
      )
    })
  })
  targets::tar_make()
}
```

tar_quarto	<i>Target with a Quarto project.</i>
------------	--------------------------------------

Description

Shorthand to include a Quarto project in a targets pipeline.

`tar_quarto()` expects an unevaluated symbol for the name argument and an unevaluated expression for the `execute_params` argument. `tar_quarto_raw()` expects a character string for the name argument and an evaluated expression object for the `execute_params` argument.

Usage

```
tar_quarto(
  name,
  path = ".",
  output_file = NULL,
  working_directory = NULL,
  extra_files = character(0),
  execute = TRUE,
  execute_params = list(),
  cache = NULL,
  cache_refresh = FALSE,
  debug = FALSE,
  quiet = TRUE,
  quarto_args = NULL,
  pandoc_args = NULL,
  profile = NULL,
  tidy_eval = targets::tar_option_get("tidy_eval"),
  packages = NULL,
  library = NULL,
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),
  garbage_collection = targets::tar_option_get("garbage_collection"),
```

```

    deployment = targets::tar_option_get("deployment"),
    priority = targets::tar_option_get("priority"),
    resources = targets::tar_option_get("resources"),
    retrieval = targets::tar_option_get("retrieval"),
    cue = targets::tar_option_get("cue"),
    description = targets::tar_option_get("description")
  )

tar_quarto_raw(
  name,
  path = ".",
  output_file = NULL,
  working_directory = NULL,
  extra_files = character(0),
  execute = TRUE,
  execute_params = NULL,
  cache = NULL,
  cache_refresh = FALSE,
  debug = FALSE,
  quiet = TRUE,
  quarto_args = NULL,
  pandoc_args = NULL,
  profile = NULL,
  packages = NULL,
  library = NULL,
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),
  garbage_collection = targets::tar_option_get("garbage_collection"),
  deployment = targets::tar_option_get("deployment"),
  priority = targets::tar_option_get("priority"),
  resources = targets::tar_option_get("resources"),
  retrieval = targets::tar_option_get("retrieval"),
  cue = targets::tar_option_get("cue"),
  description = targets::tar_option_get("description")
)

```

Arguments

name	Name of the target. <code>tar_quarto()</code> expects an unevaluated symbol for the name argument, and <code>tar_quarto_raw()</code> expects a character string for name.
path	Character string, path to the Quarto source file if rendering a single file, or the path to the root of the project if rendering a whole Quarto project.
output_file	Base name for single-file output (e.g. PDF, ePub, MS Word). This sets the output-file Quarto metadata. If NULL, the output filename will be based on the input filename.
working_directory	Optional character string, path to the working directory to temporarily set when running the report. The default is NULL, which runs the report from the current

	working directory at the time the pipeline is run. This default is recommended in the vast majority of cases. To use anything other than NULL, you must manually set the value of the store argument relative to the working directory in all calls to tar_read() and tar_load() in the report. Otherwise, these functions will not know where to find the data.
extra_files	Character vector of extra files and directories to track for changes. The target will be invalidated (rerun on the next tar_make()) if the contents of these files changes. No need to include anything already in the output of tar_quarto_files(), the list of file dependencies automatically detected through quarto::quarto_inspect().
execute	Whether to execute embedded code chunks.
execute_params	Named collection of parameters for parameterized Quarto documents. These parameters override the custom elements of the params list in the YAML front-matter of the Quarto source files. tar_quarto() expects an unevaluated expression for the execute_params argument, whereas tar_quarto_raw() expects an evaluated expression object.
cache	Cache execution output (uses knitr cache and jupyter-cache respectively for Rmd and Jupyter input files).
cache_refresh	Force refresh of execution cache.
debug	Leave intermediate files in place after render.
quiet	Suppress warning and other messages, from R and also Quarto CLI (i.e --quiet is passed as command line). quarto.quiet R option or R_QUIETO_QUIET environment variable can be used to globally override a function call (This can be useful to debug tool that calls quarto_* functions directly). On Github Actions, it will always be quiet = FALSE.
quarto_args	Character vector of other quarto CLI arguments to append to the Quarto command executed by this function. This is mainly intended for advanced usage and useful for CLI arguments which are not yet mirrored in a dedicated parameter of this R function. See quarto render --help for options.
pandoc_args	Additional command line arguments to pass on to Pandoc.
profile	Quarto project profile(s) to use. Either a character vector of profile names or NULL to use the default profile.
tidy_eval	Logical, whether to enable tidy evaluation when interpreting command and pattern. If TRUE, you can use the "bang-bang" operator !! to programmatically insert the values of global objects.
packages	Character vector of packages to load right before the target runs or the output data is reloaded for downstream targets. Use tar_option_set() to set packages globally for all subsequent targets you define.
library	Character vector of library paths to try when loading packages.
error	Character of length 1, what to do if the target stops and throws an error. Options: • "stop": the whole pipeline stops and throws an error. • "continue": the whole pipeline keeps going.

- "null": The errored target continues and returns NULL. The data hash is deliberately wrong so the target is not up to date for the next run of the pipeline. In addition, as of targets version 1.8.0.9011, a value of NULL is given to upstream dependencies with error = "null" if loading fails.
- "abridge": any currently running targets keep running, but no new targets launch after that.
- "trim": all currently running targets stay running. A queued target is allowed to start if:
 1. It is not downstream of the error, and
 2. It is not a sibling branch from the same `tar_target()` call (if the error happened in a dynamic branch).

The idea is to avoid starting any new work that the immediate error impacts. error = "trim" is just like error = "abridge", but it allows potentially healthy regions of the dependency graph to begin running. (Visit <https://books.ropensci.org/targets/debugging.html> to learn how to debug targets using saved workspaces.)

memory

Character of length 1, memory strategy. Possible values:

- "auto" (default): equivalent to memory = "transient" in almost all cases. But to avoid superfluous reads from disk, memory = "auto" is equivalent to memory = "persistent" for non-dynamically-branched targets that other targets dynamically branch over. For example: if your pipeline has `tar_target(name = y, command = x, pattern = map(x))`, then `tar_target(name = x, command = f(), memory = "auto")` will use persistent memory for x in order to avoid rereading all of x for every branch of y.
- "transient": the target gets unloaded after every new target completes. Either way, the target gets automatically loaded into memory whenever another target needs the value.
- "persistent": the target stays in memory until the end of the pipeline (unless storage is "worker", in which case targets unloads the value from memory right after storing it in order to avoid sending copious data over a network).

For cloud-based file targets (e.g. format = "file" with repository = "aws"), the memory option applies to the temporary local copy of the file: "persistent" means it remains until the end of the pipeline and is then deleted, and "transient" means it gets deleted as soon as possible. The former conserves bandwidth, and the latter conserves local storage.

garbage_collection

Logical: TRUE to run `base::gc()` just before the target runs, in whatever R process it is about to run (which could be a parallel worker). FALSE to omit garbage collection. Numeric values get converted to FALSE. The garbage_collection option in `tar_option_set()` is independent of the argument of the same name in `tar_target()`.

deployment

Character of length 1. If deployment is "main", then the target will run on the central controlling R process. Otherwise, if deployment is "worker" and you set up the pipeline with distributed/parallel computing, then the target runs on a parallel worker. For more on distributed/parallel computing in targets, please visit <https://books.ropensci.org/targets/crew.html>.

priority	Deprecated on 2025-04-08 (targets version 1.10.1.9013). targets has moved to a more efficient scheduling algorithm (https://github.com/ropensci/targets/issues/1458) which cannot support priorities. The priority argument of <code>tar_target()</code> no longer has a reliable effect on execution order.
resources	Object returned by <code>tar_resources()</code> with optional settings for high-performance computing functionality, alternative data storage formats, and other optional capabilities of targets. See <code>tar_resources()</code> for details.
retrieval	Character string to control when the current target loads its dependencies into memory before running. (Here, a "dependency" is another target upstream that the current one depends on.) Only relevant when using targets with parallel workers (https://books.ropensci.org/targets/crew.html). Must be one of the following values: • "auto" (default): equivalent to <code>retrieval = "worker"</code> in almost all cases. But to avoid unnecessary reads from disk, <code>retrieval = "auto"</code> is equivalent to <code>retrieval = "main"</code> for dynamic branches that branch over non-dynamic targets. For example: if your pipeline has <code>tar_target(x, command = f())</code>, then <code>tar_target(y, command = x, pattern = map(x), retrieval = "auto")</code> will use "main" retrieval in order to avoid rereading all of x for every branch of y. • "worker": the worker loads the target's dependencies. • "main": the target's dependencies are loaded on the host machine and sent to the worker before the target runs. • "none": targets makes no attempt to load its dependencies. With <code>retrieval = "none"</code>, loading dependencies is the responsibility of the user. Use with caution.
cue	An optional object from <code>tar_cue()</code> to customize the rules that decide whether the target is up to date.
description	Character of length 1, a custom free-form human-readable text description of the target. Descriptions appear as target labels in functions like <code>tar_manifest()</code> and <code>tar_visnetwork()</code> , and they let you select subsets of targets for the names argument of functions like <code>tar_make()</code> . For example, <code>tar_manifest(names = tar_described_as(starts_with("survival model")))</code> lists all the targets whose descriptions start with the character string "survival model".

Details

`tar_quarto()` is an alternative to `tar_target()` for Quarto projects and standalone Quarto source documents that depend on upstream targets. The Quarto R source documents (*.qmd and *.Rmd files) should mention dependency targets with `tar_load()` and `tar_read()` in the active R code chunks (which also allows you to render the project outside the pipeline if the `_targets/` data store already exists). (Do not use `tar_load_raw()` or `tar_read_raw()` for this.) Then, `tar_quarto()` defines a special kind of target. It 1. Finds all the `tar_load()/tar_read()` dependencies in the R source reports and inserts them into the target's command. This enforces the proper dependency relationships. (Do not use `tar_load_raw()` or `tar_read_raw()` for this.) 2. Sets `format = "file"` (see `tar_target()`) so targets watches the files at the returned paths and reruns the report if those files change. 3. Configures the target's command to return both the output rendered files and the input dependency files (such as Quarto source documents). All these file paths are relative paths so

the project stays portable. 4. Forces the report to run in the user's current working directory instead of the working directory of the report. 5. Sets convenient default options such as `deployment = "main"` in the target and `quiet = TRUE` in `quarto::quarto_render()`.

Value

A target definition object with `format = "file"`. When this target runs, it returns a character vector of file paths: the rendered documents, the Quarto source files, and other input and output files. The output files are determined by the YAML front-matter of standalone Quarto documents and `_quarto.yml` in Quarto projects, and you can see these files with `tar_quarto_files()` (powered by `quarto::quarto_inspect()`). All returned paths are *relative* paths to ensure portability (so that the project can be moved from one file system to another without invalidating the target). See the "Target definition objects" section for background.

Quarto troubleshooting

If you encounter difficult errors, please read <https://github.com/quarto-dev/quarto-r/issues/16>. In addition, please try to reproduce the error using `quarto::quarto_render("your_report.qmd", execute_dir = getwd())` without using targets at all. Isolating errors this way makes them much easier to solve.

Literate programming limitations

Literate programming files are messy and variable, so functions like `tar_render()` have limitations: * Child documents are not tracked for changes. * Upstream target dependencies are not detected if `tar_read()` and/or `tar_load()` are called from a user-defined function. In addition, single target names must be mentioned and they must be symbols. `tar_load("x")` and `tar_load(contains("x"))` may not detect target `x`. * Special/optional input/output files may not be detected in all cases. * `tar_render()` and friends are for local files only. They do not integrate with the cloud storage capabilities of targets.

Target definition objects

Most tarchetypes functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

See Also

Other Literate programming targets: `tar_knit()`, `tar_quarto_rep()`, `tar_render()`, `tar_render_rep()`

Examples

```

if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    # Unparameterized Quarto document:
    lines <- c(
      "----",
      "title: report.qmd source file",
      "output_format: html",
      "----",
      "Assume these lines are in report.qmd.",
      "```${r}"",
      "targets::tar_read(data)",
      "````"
    )
    writeLines(lines, "report.qmd")
    # Include the report in a pipeline as follows.
    targets::tar_script({
      library(tarchetypes)
      list(
        tar_target(data, data.frame(x = seq_len(26), y = letters)),
        tar_quarto(name = report, path = "report.qmd")
      )
    }, ask = FALSE)
    # Then, run the pipeline as usual.

    # Parameterized Quarto:
    lines <- c(
      "----",
      "title: 'report.qmd source file with parameters'",
      "output_format: html_document",
      "params:",
      "  your_param: \"default value\"",
      "----",
      "Assume these lines are in report.qmd.",
      "```${r}"",
      "print(params$your_param)",
      "````"
    )
    writeLines(lines, "report.qmd")
    # Include the report in the pipeline as follows.
    unlink("_targets.R") # In tar_dir(), not the user's file space.
    targets::tar_script({
      library(tarchetypes)
      list(
        tar_target(data, data.frame(x = seq_len(26), y = letters)),
        tar_quarto(
          name = report,
          path = "report.qmd",
          execute_params = list(your_param = data)
        ),
        tar_quarto_raw(
          name = "report2",

```

```

      path = "report.qmd",
      execute_params = quote(list(your_param = data))
    )
  }, ask = FALSE)
})
# Then, run the pipeline as usual.
}
```

tar_quarto_files

*Quarto file detection***Description**

Detect the important files in a Quarto project.

Usage

```
tar_quarto_files(path = ".", profile = NULL, quiet = TRUE)
```

Arguments

path	Character of length 1, either the file path to a Quarto source document or the directory path to a Quarto project. Defaults to the Quarto project in the current working directory.
profile	Character of length 1, Quarto profile. If NULL, the default profile will be used. Requires Quarto version 1.2 or higher. See https://quarto.org/docs/projects/profiles.html for details.
quiet	Suppress warning and other messages, from R and also Quarto CLI (i.e --quiet is passed as command line). quarto.quiet R option or R_QUARTO_QUIET environment variable can be used to globally override a function call (This can be useful to debug tool that calls quarto_* functions directly). On Github Actions, it will always be quiet = FALSE.

Details

This function is just a thin wrapper that interprets the output of `quarto::quarto_inspect()` and returns what tarchetypes needs to know about the current Quarto project or document.

Value

A named list of important file paths in a Quarto project or document:

- **sources:** source files which may reference upstream target dependencies in code chunks using `tar_load()/tar_read()`.
- **output:** output files that will be generated during `quarto::quarto_render()`.
- **input:** pre-existing files required to render the project or document, such as `_quarto.yml` and quarto extensions.

See Also

Other Literate programming utilities: [tar_knitr_deps\(\)](#), [tar_knitr_deps_expr\(\)](#)

Examples

```
lines <- c(
  "---",
  "title: source file",
  "---",
  "Assume these lines are in report.qmd.",
  "```{r}",
  "1 + 1",
  "```"
)
path <- tempfile(fileext = ".qmd")
writeLines(lines, path)
# If Quarto is installed, run:
# tar_quarto_files(path)
```

tar_quarto_rep

*Parameterized Quarto with dynamic branching.***Description**

Targets to render a parameterized Quarto document with multiple sets of parameters. Assumes you do not specify output-dir in _quarto.yml.

[tar_quarto_rep\(\)](#) expects an unevaluated symbol for the name argument and an unevaluated expression for the execute_params argument. [tar_quarto_rep_raw\(\)](#) expects a character string for the name argument and an evaluated expression object for the execute_params argument.

Usage

```
tar_quarto_rep(
  name,
  path,
  working_directory = NULL,
  execute_params = data.frame(),
  batches = NULL,
  extra_files = character(0),
  execute = TRUE,
  cache = NULL,
  cache_refresh = FALSE,
  debug = FALSE,
  quiet = TRUE,
  quarto_args = NULL,
  pandoc_args = NULL,
  rep_workers = 1,
```

```

tidy_eval = targets::tar_option_get("tidy_eval"),
packages = targets::tar_option_get("packages"),
library = targets::tar_option_get("library"),
format = targets::tar_option_get("format"),
iteration = targets::tar_option_get("iteration"),
error = targets::tar_option_get("error"),
memory = targets::tar_option_get("memory"),
garbage_collection = targets::tar_option_get("garbage_collection"),
deployment = targets::tar_option_get("deployment"),
priority = targets::tar_option_get("priority"),
resources = targets::tar_option_get("resources"),
retrieval = targets::tar_option_get("retrieval"),
cue = targets::tar_option_get("cue"),
description = targets::tar_option_get("description")
)

tar_quarto_rep_raw(
  name,
  path,
  working_directory = NULL,
  execute_params = expression(NULL),
  batches = NULL,
  extra_files = character(0),
  execute = TRUE,
  cache = NULL,
  cache_refresh = FALSE,
  debug = FALSE,
  quiet = TRUE,
  quarto_args = NULL,
  pandoc_args = NULL,
  rep_workers = 1,
  packages = targets::tar_option_get("packages"),
  library = targets::tar_option_get("library"),
  format = targets::tar_option_get("format"),
  iteration = targets::tar_option_get("iteration"),
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),
  garbage_collection = targets::tar_option_get("garbage_collection"),
  deployment = targets::tar_option_get("deployment"),
  priority = targets::tar_option_get("priority"),
  resources = targets::tar_option_get("resources"),
  retrieval = targets::tar_option_get("retrieval"),
  cue = targets::tar_option_get("cue"),
  description = targets::tar_option_get("description")
)

```

Arguments

name	Name of the target. <code>tar_quarto_rep()</code> expects an unevaluated symbol for the name argument, and <code>tar_quarto_rep_raw()</code> expects a character string for name.
path	Character string, path to the Quarto source file if rendering a single file, or the path to the root of the project if rendering a whole Quarto project.
working_directory	Optional character string, path to the working directory to temporarily set when running the report. The default is NULL, which runs the report from the current working directory at the time the pipeline is run. This default is recommended in the vast majority of cases. To use anything other than NULL, you must manually set the value of the store argument relative to the working directory in all calls to <code>tar_read()</code> and <code>tar_load()</code> in the report. Otherwise, these functions will not know where to find the data.
execute_params	Code to generate a data frame or tibble with one row per rendered report and one column per Quarto parameter. <code>tar_quarto_rep()</code> expects an unevaluated expression for the <code>execute_params</code> argument, whereas <code>tar_quarto_rep_raw()</code> expects an evaluated expression object. You may also include an <code>output_file</code> column in the parameters to specify the path of each rendered report. If included, the <code>output_file</code> column must be a character vector with one and only one output file for each row of parameters. If an <code>output_file</code> column is not included, then the output files are automatically determined using the parameters, and the default file format is determined by the YAML front-matter of the Quarto source document. Only the first file format is used, the others are not generated. Quarto parameters must not be named <code>tar_group</code> or <code>output_file</code> . This <code>execute_params</code> argument is converted into the command for a target that supplies the Quarto parameters.
batches	Number of batches. This is also the number of dynamic branches created during <code>tar_make()</code> .
extra_files	Character vector of extra files and directories to track for changes. The target will be invalidated (rerun on the next <code>tar_make()</code>) if the contents of these files changes. No need to include anything already in the output of <code>tar_quarto_files()</code> , the list of file dependencies automatically detected through <code>quarto::quarto_inspect()</code> .
execute	Whether to execute embedded code chunks.
cache	Cache execution output (uses knitr cache and jupyter-cache respectively for Rmd and Jupyter input files).
cache_refresh	Force refresh of execution cache.
debug	Leave intermediate files in place after render.
quiet	Suppress warning and other messages, from R and also Quarto CLI (i.e <code>--quiet</code> is passed as command line). <code>quarto.quiet</code> R option or <code>R_QUARTO_QUIET</code> environment variable can be used to globally override a function call (This can be useful to debug tool that calls <code>quarto_*</code> functions directly). On Github Actions, it will always be <code>quiet = FALSE</code> .

quarto_args	Character vector of other quarto CLI arguments to append to the Quarto command executed by this function. This is mainly intended for advanced usage and useful for CLI arguments which are not yet mirrored in a dedicated parameter of this R function. See <code>quarto render --help</code> for options.
pandoc_args	Additional command line arguments to pass on to Pandoc.
rep_workers	Positive integer of length 1, number of local R processes to use to run reps within batches in parallel. If 1, then reps are run sequentially within each batch. If greater than 1, then reps within batch are run in parallel using a PSOCK cluster.
tidy_eval	Logical of length 1, whether to use tidy evaluation to resolve <code>execute_params</code> . Similar to the <code>tidy_eval</code> argument of <code>targets::tar_target()</code> .
packages	Character vector of packages to load right before the target runs or the output data is reloaded for downstream targets. Use <code>tar_option_set()</code> to set packages globally for all subsequent targets you define.
library	Character vector of library paths to try when loading packages.
format	Optional storage format for the target's return value. With the exception of <code>format = "file"</code> , each target gets a file in <code>_targets/objects</code> , and each format is a different way to save and load this file. See the "Storage formats" section for a detailed list of possible data storage formats.
iteration	Character of length 1, name of the iteration mode of the target. Choices: • <code>"vector"</code>: branching happens with <code>vectors::vec_slice()</code> and aggregation happens with <code>vctrs::vec_c()</code>. • <code>"list"</code>, branching happens with <code>[[]]</code> and aggregation happens with <code>list()</code>. In the case of list iteration, <code>tar_read(your_target)</code> will return a list of lists, where the outer list has one element per batch and each inner list has one element per rep within batch. To un-batch this nested list, call <code>tar_read(your_target, recursive = FALSE)</code>. • <code>"group"</code>: <code>dplyr::group_by()</code>-like functionality to branch over subsets of a data frame. The target's return value must be a data frame with a special <code>tar_group</code> column of consecutive integers from 1 through the number of groups. Each integer designates a group, and a branch is created for each collection of rows in a group. See the <code>tar_group()</code> function in <code>targets</code> to see how you can create the special <code>tar_group</code> column with <code>dplyr::group_by()</code>.
error	Character of length 1, what to do if the target stops and throws an error. Options: • <code>"stop"</code>: the whole pipeline stops and throws an error. • <code>"continue"</code>: the whole pipeline keeps going. • <code>"null"</code>: The errored target continues and returns <code>NULL</code>. The data hash is deliberately wrong so the target is not up to date for the next run of the pipeline. In addition, as of <code>targets</code> version 1.8.0.9011, a value of <code>NULL</code> is given to upstream dependencies with <code>error = "null"</code> if loading fails. • <code>"abridge"</code>: any currently running targets keep running, but no new targets launch after that. • <code>"trim"</code>: all currently running targets stay running. A queued target is allowed to start if:

1. It is not downstream of the error, and
2. It is not a sibling branch from the same `tar_target()` call (if the error happened in a dynamic branch).

The idea is to avoid starting any new work that the immediate error impacts. `error = "trim"` is just like `error = "abridge"`, but it allows potentially healthy regions of the dependency graph to begin running. (Visit <https://books.ropensci.org/targets/debugging.html> to learn how to debug targets using saved workspaces.)

memory

Character of length 1, memory strategy. Possible values:

- "auto" (default): equivalent to `memory = "transient"` in almost all cases. But to avoid superfluous reads from disk, `memory = "auto"` is equivalent to `memory = "persistent"` for non-dynamically-branched targets that other targets dynamically branch over. For example: if your pipeline has `tar_target(name = y, command = x, pattern = map(x))`, then `tar_target(name = x, command = f(), memory = "auto")` will use persistent memory for `x` in order to avoid rereading all of `x` for every branch of `y`.
- "transient": the target gets unloaded after every new target completes. Either way, the target gets automatically loaded into memory whenever another target needs the value.
- "persistent": the target stays in memory until the end of the pipeline (unless `storage` is "worker", in which case targets unloads the value from memory right after storing it in order to avoid sending copious data over a network).

For cloud-based file targets (e.g. `format = "file"` with `repository = "aws"`), the memory option applies to the temporary local copy of the file: "persistent" means it remains until the end of the pipeline and is then deleted, and "transient" means it gets deleted as soon as possible. The former conserves bandwidth, and the latter conserves local storage.

garbage_collection

Logical: TRUE to run `base::gc()` just before the target runs, in whatever R process it is about to run (which could be a parallel worker). FALSE to omit garbage collection. Numeric values get converted to FALSE. The `garbage_collection` option in `tar_option_set()` is independent of the argument of the same name in `tar_target()`.

deployment

Character of length 1. If deployment is "main", then the target will run on the central controlling R process. Otherwise, if deployment is "worker" and you set up the pipeline with distributed/parallel computing, then the target runs on a parallel worker. For more on distributed/parallel computing in targets, please visit <https://books.ropensci.org/targets/crew.html>.

priority

Deprecated on 2025-04-08 (targets version 1.10.1.9013). targets has moved to a more efficient scheduling algorithm (<https://github.com/ropensci/targets/issues/1458>) which cannot support priorities. The `priority` argument of `tar_target()` no longer has a reliable effect on execution order.

resources

Object returned by `tar_resources()` with optional settings for high-performance computing functionality, alternative data storage formats, and other optional capabilities of targets. See `tar_resources()` for details.

retrieval	Character string to control when the current target loads its dependencies into memory before running. (Here, a "dependency" is another target upstream that the current one depends on.) Only relevant when using targets with parallel workers (https://books.ropensci.org/targets/crew.html). Must be one of the following values: • "auto" (default): equivalent to <code>retrieval = "worker"</code> in almost all cases. But to avoid unnecessary reads from disk, <code>retrieval = "auto"</code> is equivalent to <code>retrieval = "main"</code> for dynamic branches that branch over non-dynamic targets. For example: if your pipeline has <code>tar_target(x, command = f())</code>, then <code>tar_target(y, command = x, pattern = map(x), retrieval = "auto")</code> will use "main" retrieval in order to avoid rereading all of <code>x</code> for every branch of <code>y</code>. • "worker": the worker loads the target's dependencies. • "main": the target's dependencies are loaded on the host machine and sent to the worker before the target runs. • "none": targets makes no attempt to load its dependencies. With <code>retrieval = "none"</code>, loading dependencies is the responsibility of the user. Use with caution.
cue	An optional object from <code>tar_cue()</code> to customize the rules that decide whether the target is up to date.
description	Character of length 1, a custom free-form human-readable text description of the target. Descriptions appear as target labels in functions like <code>tar_manifest()</code> and <code>tar_visnetwork()</code> , and they let you select subsets of targets for the <code>names</code> argument of functions like <code>tar_make()</code> . For example, <code>tar_manifest(names = tar_described_as(starts_with("survival model")))</code> lists all the targets whose descriptions start with the character string "survival model".

Details

`tar_quarto_rep()` is an alternative to `tar_target()` for a parameterized Quarto document that depends on other targets. Parameters must be given as a data frame with one row per rendered report and one column per parameter. An optional `output_file` column may be included to set the output file path of each rendered report. (See the `execute_params` argument for details.)

The Quarto source should mention other dependency targets `tar_load()` and `tar_read()` in the active code chunks (which also allows you to render the report outside the pipeline if the `_targets/` data store already exists and appropriate defaults are specified for the parameters). (Do not use `tar_load_raw()` or `tar_read_raw()` for this.) Then, `tar_quarto()` defines a special kind of target. It 1. Finds all the `tar_load()/tar_read()` dependencies in the report and inserts them into the target's command. This enforces the proper dependency relationships. (Do not use `tar_load_raw()` or `tar_read_raw()` for this.) 2. Sets `format = "file"` (see `tar_target()`) so targets watches the files at the returned paths and reruns the report if those files change. 3. Configures the target's command to return the output report files: the rendered document, the source file, and file paths mentioned in files. All these file paths are relative paths so the project stays portable. 4. Forces the report to run in the user's current working directory instead of the working directory of the report. 5. Sets convenient default options such as `deployment = "main"` in the target and `quiet = TRUE` in `quarto::quarto_render()`.

Value

A list of target definition objects to render the Quarto reports. Changes to the parameters, source file, dependencies, etc. will cause the appropriate targets to rerun during `tar_make()`. See the "Target definition objects" section for background.

Target definition objects

Most `tarchetypes` functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

Replicate-specific seeds

In ordinary pipelines, each target has its own unique deterministic pseudo-random number generator seed derived from its target name. In batched replicate, however, each batch is a target with multiple replicate within that batch. That is why `tar_rep()` and friends give each *replicate* its own unique seed. Each replicate-specific seed is created based on the dynamic parent target name, `tar_option_get("seed")` (for targets version 0.13.5.9000 and above), batch index, and rep-within-batch index. The seed is set just before the replicate runs. Replicate-specific seeds are invariant to batching structure. In other words, `tar_rep(name = x, command = rnorm(1), batches = 100, reps = 1, ...)` produces the same numerical output as `tar_rep(name = x, command = rnorm(1), batches = 10, reps = 10, ...)` (but with different batch names). Other target factories with this seed scheme are `tar_rep2()`, `tar_map_rep()`, `tar_map2_count()`, `tar_map2_size()`, and `tar_render_rep()`. For the `tar_map2_*`() functions, it is possible to manually supply your own seeds through the `command1` argument and then invoke them in your custom code for `command2` (`set.seed()`, `withr::with_seed`, or `withr::local_seed()`). For `tar_render_rep()`, custom seeds can be supplied to the `params` argument and then invoked in the individual R Markdown reports. Likewise with `tar_quarto_rep()` and the `execute_params` argument.

Literate programming limitations

Literate programming files are messy and variable, so functions like `tar_render()` have limitations: * Child documents are not tracked for changes. * Upstream target dependencies are not detected if `tar_read()` and/or `tar_load()` are called from a user-defined function. In addition, single target names must be mentioned and they must be symbols. `tar_load("x")` and `tar_load(contains("x"))` may not detect target `x`. * Special/optional input/output files may not be detected in all cases. * `tar_render()` and friends are for local files only. They do not integrate with the cloud storage capabilities of targets.

Quarto troubleshooting

If you encounter difficult errors, please read <https://github.com/quarto-dev/quarto-r/issues/16>. In addition, please try to reproduce the error using `quarto::quarto_render("your_report.qmd")`,

`execute_dir = getwd())` without using targets at all. Isolating errors this way makes them much easier to solve.

See Also

Other Literate programming targets: `tar_knit()`, `tar_quarto()`, `tar_render()`, `tar_render_rep()`

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    # Parameterized Quarto:
    lines <- c(
      "___",
      "title: 'report.qmd file'",
      "output_format: html_document",
      "params:",
      "  par: \"default value\"",
      "___",
      "Assume these lines are in a file called report.qmd.",
      "```{r}",
      "print(params$par)",
      "```"
    )
    writeLines(lines, "report.qmd") # In tar_dir(), not the user's file space.
    # The following pipeline will run the report for each row of params.
    targets::tar_script({
      library(tarchetypes)
      list(
        tar_quarto_rep(
          name = report,
          path = "report.qmd",
          execute_params = tibble::tibble(par = c(1, 2))
        ),
        tar_quarto_rep_raw(
          name = "report",
          path = "report.qmd",
          execute_params = quote(tibble::tibble(par = c(1, 2)))
        )
      )
    }, ask = FALSE)
    # Then, run the targets pipeline as usual.
  })
}
```

Description

Shorthand to include an R Markdown document in a targets pipeline.

`tar_render()` expects an unevaluated symbol for the name argument, and it supports named ... arguments for `rmarkdown::render()` arguments. `tar_render_raw()` expects a character string for name and supports an evaluated expression object `render_arguments` for `rmarkdown::render()` arguments.

Usage

```
tar_render(
  name,
  path,
  output_file = NULL,
  working_directory = NULL,
  tidy_eval = targets::tar_option_get("tidy_eval"),
  packages = targets::tar_option_get("packages"),
  library = targets::tar_option_get("library"),
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),
  garbage_collection = targets::tar_option_get("garbage_collection"),
  deployment = targets::tar_option_get("deployment"),
  priority = targets::tar_option_get("priority"),
  resources = targets::tar_option_get("resources"),
  retrieval = targets::tar_option_get("retrieval"),
  cue = targets::tar_option_get("cue"),
  description = targets::tar_option_get("description"),
  quiet = TRUE,
  ...
)

tar_render_raw(
  name,
  path,
  output_file = NULL,
  working_directory = NULL,
  packages = targets::tar_option_get("packages"),
  library = targets::tar_option_get("library"),
  error = targets::tar_option_get("error"),
  deployment = targets::tar_option_get("deployment"),
  priority = targets::tar_option_get("priority"),
  resources = targets::tar_option_get("resources"),
  retrieval = targets::tar_option_get("retrieval"),
  cue = targets::tar_option_get("cue"),
  description = targets::tar_option_get("description"),
  quiet = TRUE,
  render_arguments = quote(list())
)
```

Arguments

name	Name of the target. <code>tar_render()</code> expects an unevaluated symbol for the name argument, whereas <code>tar_render_raw()</code> expects a character string for name.
path	Character string, file path to the R Markdown source file. Must have length 1.
output_file	Character string, file path to the rendered output file.
working_directory	Optional character string, path to the working directory to temporarily set when running the report. The default is NULL, which runs the report from the current working directory at the time the pipeline is run. This default is recommended in the vast majority of cases. To use anything other than NULL, you must manually set the value of the store argument relative to the working directory in all calls to <code>tar_read()</code> and <code>tar_load()</code> in the report. Otherwise, these functions will not know where to find the data.
tidy_eval	Logical, whether to enable tidy evaluation when interpreting command and pattern. If TRUE, you can use the "bang-bang" operator <code>!!</code> to programmatically insert the values of global objects.
packages	Character vector of packages to load right before the target runs or the output data is reloaded for downstream targets. Use <code>tar_option_set()</code> to set packages globally for all subsequent targets you define.
library	Character vector of library paths to try when loading packages.
error	Character of length 1, what to do if the target stops and throws an error. Options: • "stop": the whole pipeline stops and throws an error. • "continue": the whole pipeline keeps going. • "null": The errored target continues and returns NULL. The data hash is deliberately wrong so the target is not up to date for the next run of the pipeline. In addition, as of targets version 1.8.0.9011, a value of NULL is given to upstream dependencies with <code>error = "null"</code> if loading fails. • "abridge": any currently running targets keep running, but no new targets launch after that. • "trim": all currently running targets stay running. A queued target is allowed to start if: 1. It is not downstream of the error, and 2. It is not a sibling branch from the same <code>tar_target()</code> call (if the error happened in a dynamic branch). The idea is to avoid starting any new work that the immediate error impacts. <code>error = "trim"</code> is just like <code>error = "abridge"</code>, but it allows potentially healthy regions of the dependency graph to begin running. (Visit https://books.ropensci.org/targets/debugging.html to learn how to debug targets using saved workspaces.)
memory	Character of length 1, memory strategy. Possible values: • "auto" (default): equivalent to <code>memory = "transient"</code> in almost all cases. But to avoid superfluous reads from disk, <code>memory = "auto"</code> is equivalent to <code>memory = "persistent"</code> for non-dynamically-branched targets that other targets dynamically branch over. For example: if your pipeline has

`tar_target(name = y, command = x, pattern = map(x))`, then `tar_target(name = x, command = f(), memory = "auto")` will use persistent memory for `x` in order to avoid rereading all of `x` for every branch of `y`.

- "transient": the target gets unloaded after every new target completes. Either way, the target gets automatically loaded into memory whenever another target needs the value.
- "persistent": the target stays in memory until the end of the pipeline (unless storage is "worker", in which case targets unloads the value from memory right after storing it in order to avoid sending copious data over a network).

For cloud-based file targets (e.g. `format = "file"` with `repository = "aws"`), the memory option applies to the temporary local copy of the file: "persistent" means it remains until the end of the pipeline and is then deleted, and "transient" means it gets deleted as soon as possible. The former conserves bandwidth, and the latter conserves local storage.

garbage_collection

Logical: TRUE to run `base::gc()` just before the target runs, in whatever R process it is about to run (which could be a parallel worker). FALSE to omit garbage collection. Numeric values get converted to FALSE. The `garbage_collection` option in `tar_option_set()` is independent of the argument of the same name in `tar_target()`.

deployment

Character of length 1. If deployment is "main", then the target will run on the central controlling R process. Otherwise, if deployment is "worker" and you set up the pipeline with distributed/parallel computing, then the target runs on a parallel worker. For more on distributed/parallel computing in targets, please visit <https://books.ropensci.org/targets/crew.html>.

priority

Deprecated on 2025-04-08 (targets version 1.10.1.9013). targets has moved to a more efficient scheduling algorithm (<https://github.com/ropensci/targets/issues/1458>) which cannot support priorities. The `priority` argument of `tar_target()` no longer has a reliable effect on execution order.

resources

Object returned by `tar_resources()` with optional settings for high-performance computing functionality, alternative data storage formats, and other optional capabilities of targets. See `tar_resources()` for details.

retrieval

Character string to control when the current target loads its dependencies into memory before running. (Here, a "dependency" is another target upstream that the current one depends on.) Only relevant when using targets with parallel workers (<https://books.ropensci.org/targets/crew.html>). Must be one of the following values:

- "auto" (default): equivalent to `retrieval = "worker"` in almost all cases. But to avoid unnecessary reads from disk, `retrieval = "auto"` is equivalent to `retrieval = "main"` for dynamic branches that branch over non-dynamic targets. For example: if your pipeline has `tar_target(x, command = f())`, then `tar_target(y, command = x, pattern = map(x), retrieval = "auto")` will use "main" retrieval in order to avoid rereading all of `x` for every branch of `y`.
- "worker": the worker loads the target's dependencies.

	• "main": the target's dependencies are loaded on the host machine and sent to the worker before the target runs. • "none": targets makes no attempt to load its dependencies. With retrieval = "none", loading dependencies is the responsibility of the user. Use with caution.
cue	An optional object from <code>tar_cue()</code> to customize the rules that decide whether the target is up to date.
description	Character of length 1, a custom free-form human-readable text description of the target. Descriptions appear as target labels in functions like <code>tar_manifest()</code> and <code>tar_visnetwork()</code> , and they let you select subsets of targets for the names argument of functions like <code>tar_make()</code> . For example, <code>tar_manifest(names = tar_described_as(starts_with("survival model")))</code> lists all the targets whose descriptions start with the character string "survival model".
quiet	An option to suppress printing during rendering from knitr, pandoc command line and others. To only suppress printing of the last "Output created: " message, you can set <code>rmarkdown.render.message</code> to FALSE
...	Named arguments to <code>rmarkdown::render()</code> . These arguments are evaluated when the target actually runs in <code>tar_make()</code> , not when the target is defined. That means, for example, you can use upstream targets as parameters of parameterized R Markdown reports. The target: <pre>tar_render(your_target, "your_report.Rmd", params = list(your_param = your_target))</pre> will run: <pre>rmarkdown::render("your_report.Rmd", params = list(your_param = your_target))</pre> For parameterized reports, it is recommended to supply a distinct <code>output_file</code> argument to each <code>tar_render()</code> call and set useful defaults for parameters in the R Markdown source. See the examples section for a demonstration.
render_arguments	Optional language object with a list of named arguments to <code>rmarkdown::render()</code> . Cannot be an expression object. (Use <code>quote()</code> , not <code>expression()</code> .) The reason for quoting is that these arguments may depend on upstream targets whose values are not available at the time the target is defined, and because <code>tar_render_raw()</code> is the "raw" version of a function, we want to avoid all non-standard evaluation.

Details

`tar_render()` is an alternative to `tar_target()` for R Markdown reports that depend on other targets. The R Markdown source should mention dependency targets with `tar_load()` and `tar_read()` in the active code chunks (which also allows you to render the report outside the pipeline if the

_targets/ data store already exists). (Do not use `tar_load_raw()` or `tar_read_raw()` for this.) Then, `tar_render()` defines a special kind of target. It 1. Finds all the `tar_load()/tar_read()` dependencies in the report and inserts them into the target's command. This enforces the proper dependency relationships. (Do not use `tar_load_raw()` or `tar_read_raw()` for this.) 2. Sets `format = "file"` (see `tar_target()`) so targets watches the files at the returned paths and reruns the report if those files change. 3. Configures the target's command to return both the output report files and the input source file. All these file paths are relative paths so the project stays portable. 4. Forces the report to run in the user's current working directory instead of the working directory of the report. 5. Sets convenient default options such as `deployment = "main"` in the target and `quiet = TRUE` in `rmarkdown::render()`.

Value

A target definition object with `format = "file"`. When this target runs, it returns a character vector of file paths: the rendered document, the source file, and then the `*_files/` directory if it exists. Unlike `rmarkdown::render()`, all returned paths are *relative* paths to ensure portability (so that the project can be moved from one file system to another without invalidating the target). See the "Target definition objects" section for background.

Literate programming limitations

Literate programming files are messy and variable, so functions like `tar_render()` have limitations: * Child documents are not tracked for changes. * Upstream target dependencies are not detected if `tar_read()` and/or `tar_load()` are called from a user-defined function. In addition, single target names must be mentioned and they must be symbols. `tar_load("x")` and `tar_load(contains("x"))` may not detect target `x`. * Special/optional input/output files may not be detected in all cases. * `tar_render()` and friends are for local files only. They do not integrate with the cloud storage capabilities of targets.

Target definition objects

Most tarchetypes functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

See Also

Other Literate programming targets: `tar_knit()`, `tar_quarto()`, `tar_quarto_rep()`, `tar_render_rep()`

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
```

```

# Unparameterized R Markdown:
lines <- c(
  "----",
  "title: report.Rmd source file",
  "output_format: html_document",
  "----",
  "Assume these lines are in report.Rmd.",
  "```{r}",
  "targets::tar_read(data)",
  "```"
)

# Include the report in a pipeline as follows.
targets::tar_script({
  library(tarchetypes)
  list(
    tar_target(data, data.frame(x = seq_len(26), y = letters)),
    tar_render(report, "report.Rmd")
  )
}, ask = FALSE)

# Then, run the targets pipeline as usual.

# Parameterized R Markdown:
lines <- c(
  "----",
  "title: 'report.Rmd source file with parameters'",
  "output_format: html_document",
  "params:",
  "  your_param: \"default value\"",
  "----",
  "Assume these lines are in report.Rmd.",
  "```{r}",
  "print(params$your_param)",
  "```"
)

# Include the report in the pipeline as follows.
targets::tar_script({
  library(tarchetypes)
  list(
    tar_target(data, data.frame(x = seq_len(26), y = letters)),
    tar_render(
      name = report,
      "report.Rmd",
      params = list(your_param = data)
    ),
    tar_render_raw(
      name = "report2",
      "report.Rmd",
      params = quote(list(your_param = data))
    )
  )
}, ask = FALSE)
})

# Then, run the targets pipeline as usual.

```

```
}
```

tar_render_rep

Parameterized R Markdown with dynamic branching.

Description

Targets to render a parameterized R Markdown report with multiple sets of parameters.

`tar_render_rep()` expects an unevaluated symbol for the name argument, and it supports named `...` arguments for `rmarkdown::render()` arguments. `tar_render_rep_raw()` expects a character string for name and supports an evaluated expression object `render_arguments` for `rmarkdown::render()` arguments.

Usage

```
tar_render_rep(
  name,
  path,
  working_directory = NULL,
  params = data.frame(),
  batches = NULL,
  rep_workers = 1,
  packages = targets::tar_option_get("packages"),
  library = targets::tar_option_get("library"),
  format = targets::tar_option_get("format"),
  iteration = targets::tar_option_get("iteration"),
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),
  garbage_collection = targets::tar_option_get("garbage_collection"),
  deployment = targets::tar_option_get("deployment"),
  priority = targets::tar_option_get("priority"),
  resources = targets::tar_option_get("resources"),
  retrieval = targets::tar_option_get("retrieval"),
  cue = targets::tar_option_get("cue"),
  description = targets::tar_option_get("description"),
  quiet = TRUE,
  ...
)

tar_render_rep_raw(
  name,
  path,
  working_directory = NULL,
  params = expression(NULL),
  batches = NULL,
  rep_workers = 1,
  packages = targets::tar_option_get("packages"),
```

```

library = targets::tar_option_get("library"),
format = targets::tar_option_get("format"),
iteration = targets::tar_option_get("iteration"),
error = targets::tar_option_get("error"),
memory = targets::tar_option_get("memory"),
garbage_collection = targets::tar_option_get("garbage_collection"),
deployment = targets::tar_option_get("deployment"),
priority = targets::tar_option_get("priority"),
resources = targets::tar_option_get("resources"),
retrieval = targets::tar_option_get("retrieval"),
cue = targets::tar_option_get("cue"),
description = targets::tar_option_get("description"),
quiet = TRUE,
args = list()
)

```

Arguments

name	Name of the target. <code>tar_render_rep()</code> expects an unevaluated symbol for the name argument, whereas <code>tar_render_rep_raw()</code> expects a character string for name.
path	Character string, file path to the R Markdown source file. Must have length 1.
working_directory	Optional character string, path to the working directory to temporarily set when running the report. The default is NULL, which runs the report from the current working directory at the time the pipeline is run. This default is recommended in the vast majority of cases. To use anything other than NULL, you must manually set the value of the store argument relative to the working directory in all calls to <code>tar_read()</code> and <code>tar_load()</code> in the report. Otherwise, these functions will not know where to find the data.
params	Code to generate a data frame or tibble with one row per rendered report and one column per R Markdown parameter. You may also include an <code>output_file</code> column to specify the path of each rendered report. This <code>params</code> argument is converted into the command for a target that supplies the R Markdown parameters.
batches	Number of batches. This is also the number of dynamic branches created during <code>tar_make()</code> .
rep_workers	Positive integer of length 1, number of local R processes to use to run reps within batches in parallel. If 1, then reps are run sequentially within each batch. If greater than 1, then reps within batch are run in parallel using a PSOCK cluster.
packages	Character vector of packages to load right before the target runs or the output data is reloaded for downstream targets. Use <code>tar_option_set()</code> to set packages globally for all subsequent targets you define.
library	Character vector of library paths to try when loading packages.
format	Optional storage format for the target's return value. With the exception of <code>format = "file"</code> , each target gets a file in <code>_targets/objects</code> , and each format

is a different way to save and load this file. See the "Storage formats" section for a detailed list of possible data storage formats.

iteration	Character of length 1, name of the iteration mode of the target. Choices: • "vector": branching happens with <code>vectors::vec_slice()</code> and aggregation happens with <code>vctrs::vec_c()</code>. • "list", branching happens with <code>[[]]</code> and aggregation happens with <code>list()</code>. In the case of list iteration, <code>tar_read(your_target)</code> will return a list of lists, where the outer list has one element per batch and each inner list has one element per rep within batch. To un-batch this nested list, call <code>tar_read(your_target, recursive = FALSE)</code>. • "group": <code>dplyr::group_by()</code>-like functionality to branch over subsets of a data frame. The target's return value must be a data frame with a special <code>tar_group</code> column of consecutive integers from 1 through the number of groups. Each integer designates a group, and a branch is created for each collection of rows in a group. See the <code>tar_group()</code> function in <code>targets</code> to see how you can create the special <code>tar_group</code> column with <code>dplyr::group_by()</code>.
error	Character of length 1, what to do if the target stops and throws an error. Options: • "stop": the whole pipeline stops and throws an error. • "continue": the whole pipeline keeps going. • "null": The errored target continues and returns NULL. The data hash is deliberately wrong so the target is not up to date for the next run of the pipeline. In addition, as of <code>targets</code> version 1.8.0.9011, a value of NULL is given to upstream dependencies with <code>error = "null"</code> if loading fails. • "abridge": any currently running targets keep running, but no new targets launch after that. • "trim": all currently running targets stay running. A queued target is allowed to start if: 1. It is not downstream of the error, and 2. It is not a sibling branch from the same <code>tar_target()</code> call (if the error happened in a dynamic branch). The idea is to avoid starting any new work that the immediate error impacts. <code>error = "trim"</code> is just like <code>error = "abridge"</code>, but it allows potentially healthy regions of the dependency graph to begin running. (Visit https://books.ropensci.org/targets/debugging.html to learn how to debug targets using saved workspaces.)
memory	Character of length 1, memory strategy. Possible values: • "auto" (default): equivalent to <code>memory = "transient"</code> in almost all cases. But to avoid superfluous reads from disk, <code>memory = "auto"</code> is equivalent to <code>memory = "persistent"</code> for for non-dynamically-branched targets that other targets dynamically branch over. For example: if your pipeline has <code>tar_target(name = y, command = x, pattern = map(x))</code>, then <code>tar_target(name = x, command = f(), memory = "auto")</code> will use persistent memory for <code>x</code> in order to avoid rereading all of <code>x</code> for every branch of <code>y</code>.

- "transient": the target gets unloaded after every new target completes. Either way, the target gets automatically loaded into memory whenever another target needs the value.
- "persistent": the target stays in memory until the end of the pipeline (unless storage is "worker", in which case targets unloads the value from memory right after storing it in order to avoid sending copious data over a network).

For cloud-based file targets (e.g. format = "file" with repository = "aws"), the memory option applies to the temporary local copy of the file: "persistent" means it remains until the end of the pipeline and is then deleted, and "transient" means it gets deleted as soon as possible. The former conserves bandwidth, and the latter conserves local storage.

garbage_collection

Logical: TRUE to run base: :gc() just before the target runs, in whatever R process it is about to run (which could be a parallel worker). FALSE to omit garbage collection. Numeric values get converted to FALSE. The garbage_collection option in tar_option_set() is independent of the argument of the same name in tar_target().

deployment

Character of length 1. If deployment is "main", then the target will run on the central controlling R process. Otherwise, if deployment is "worker" and you set up the pipeline with distributed/parallel computing, then the target runs on a parallel worker. For more on distributed/parallel computing in targets, please visit <https://books.ropensci.org/targets/crew.html>.

priority

Deprecated on 2025-04-08 (targets version 1.10.1.9013). targets has moved to a more efficient scheduling algorithm (<https://github.com/ropensci/targets/issues/1458>) which cannot support priorities. The priority argument of tar_target() no longer has a reliable effect on execution order.

resources

Object returned by tar_resources() with optional settings for high-performance computing functionality, alternative data storage formats, and other optional capabilities of targets. See tar_resources() for details.

retrieval

Character string to control when the current target loads its dependencies into memory before running. (Here, a "dependency" is another target upstream that the current one depends on.) Only relevant when using targets with parallel workers (<https://books.ropensci.org/targets/crew.html>). Must be one of the following values:

- "auto" (default): equivalent to retrieval = "worker" in almost all cases. But to avoid unnecessary reads from disk, retrieval = "auto" is equivalent to retrieval = "main" for dynamic branches that branch over non-dynamic targets. For example: if your pipeline has tar_target(x, command = f()), then tar_target(y, command = x, pattern = map(x), retrieval = "auto") will use "main" retrieval in order to avoid rereading all of x for every branch of y.
- "worker": the worker loads the target's dependencies.
- "main": the target's dependencies are loaded on the host machine and sent to the worker before the target runs.

	• "none": targets makes no attempt to load its dependencies. With retrieval = "none", loading dependencies is the responsibility of the user. Use with caution.
cue	An optional object from tar_cue() to customize the rules that decide whether the target is up to date.
description	Character of length 1, a custom free-form human-readable text description of the target. Descriptions appear as target labels in functions like tar_manifest() and tar_visnetwork(), and they let you select subsets of targets for the names argument of functions like tar_make(). For example, tar_manifest(names = tar_described_as(starts_with("survival model"))) lists all the targets whose descriptions start with the character string "survival model".
quiet	An option to suppress printing during rendering from knitr, pandoc command line and others. To only suppress printing of the last "Output created: " message, you can set rmarkdown.render.message to FALSE
...	Other named arguments to rmarkdown::render(). Unlike tar_render(), these arguments are evaluated when the target is defined, not when it is run. (The only reason to delay evaluation in tar_render() was to handle R Markdown parameters, and tar_render_rep() handles them differently.)
args	Named list of other arguments to rmarkdown::render(). Must not include params or output_file. Evaluated when the target is defined.

Details

tar_render_rep() is an alternative to tar_target() for parameterized R Markdown reports that depend on other targets. Parameters must be given as a data frame with one row per rendered report and one column per parameter. An optional output_file column may be included to set the output file path of each rendered report. The R Markdown source should mention other dependency targets tar_load() and tar_read() in the active code chunks (which also allows you to render the report outside the pipeline if the _targets/ data store already exists and appropriate defaults are specified for the parameters). (Do not use tar_load_raw() or tar_read_raw() for this.) Then, tar_render() defines a special kind of target. It 1. Finds all the tar_load()/tar_read() dependencies in the report and inserts them into the target's command. This enforces the proper dependency relationships. (Do not use tar_load_raw() or tar_read_raw() for this.) 2. Sets format = "file" (see tar_target()) so targets watches the files at the returned paths and re-runs the report if those files change. 3. Configures the target's command to return the output report files: the rendered document, the source file, and then the *_files/ directory if it exists. All these file paths are relative paths so the project stays portable. 4. Forces the report to run in the user's current working directory instead of the working directory of the report. 5. Sets convenient default options such as deployment = "main" in the target and quiet = TRUE in rmarkdown::render().

Value

A list of target definition objects to render the R Markdown reports. Changes to the parameters, source file, dependencies, etc. will cause the appropriate targets to rerun during tar_make(). See the "Target definition objects" section for background.

Target definition objects

Most tarchetypes functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

Replicate-specific seeds

In ordinary pipelines, each target has its own unique deterministic pseudo-random number generator seed derived from its target name. In batched replicate, however, each batch is a target with multiple replicate within that batch. That is why `tar_rep()` and friends give each *replicate* its own unique seed. Each replicate-specific seed is created based on the dynamic parent target name, `tar_option_get("seed")` (for targets version 0.13.5.9000 and above), batch index, and rep-within-batch index. The seed is set just before the replicate runs. Replicate-specific seeds are invariant to batching structure. In other words, `tar_rep(name = x, command = rnorm(1), batches = 100, reps = 1, ...)` produces the same numerical output as `tar_rep(name = x, command = rnorm(1), batches = 10, reps = 10, ...)` (but with different batch names). Other target factories with this seed scheme are `tar_rep2()`, `tar_map_rep()`, `tar_map2_count()`, `tar_map2_size()`, and `tar_render_rep()`. For the `tar_map2_*()` functions, it is possible to manually supply your own seeds through the `command1` argument and then invoke them in your custom code for `command2` (`set.seed()`, `withr::with_seed`, or `withr::local_seed()`). For `tar_render_rep()`, custom seeds can be supplied to the `params` argument and then invoked in the individual R Markdown reports. Likewise with `tar_quarto_rep()` and the `execute_params` argument.

Literate programming limitations

Literate programming files are messy and variable, so functions like `tar_render()` have limitations: * Child documents are not tracked for changes. * Upstream target dependencies are not detected if `tar_read()` and/or `tar_load()` are called from a user-defined function. In addition, single target names must be mentioned and they must be symbols. `tar_load("x")` and `tar_load(contains("x"))` may not detect target `x`. * Special/optional input/output files may not be detected in all cases. * `tar_render()` and friends are for local files only. They do not integrate with the cloud storage capabilities of targets.

See Also

Other Literate programming targets: `tar_knit()`, `tar_quarto()`, `tar_quarto_rep()`, `tar_render()`

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    # Parameterized R Markdown:
    lines <- c(
```

```

    "----",
    "title: 'report.Rmd file'",
    "output_format: html_document",
    "params:",
    "  par: \"default value\"",
    "----",
    "Assume these lines are in a file called report.Rmd.",
    "```{r}",
    "print(params$par)",
    "```"
  )
# The following pipeline will run the report for each row of params.
targets::tar_script({
  library(tarchetypes)
  list(
    tar_render_rep(
      name = report,
      "report.Rmd",
      params = tibble::tibble(par = c(1, 2))
    ),
    tar_render_rep_raw(
      name = "report2",
      "report.Rmd",
      params = quote(tibble::tibble(par = c(1, 2)))
    )
  )
}, ask = FALSE)
# Then, run the targets pipeline as usual.
})
}

```

tar_rep

Batched replication with dynamic branching.

Description

Batching is important for optimizing the efficiency of heavily dynamically-branched workflows: <https://books.ropensci.org/targets/dynamic.html#batching>. `tar_rep()` replicates a command in strategically sized batches.

`tar_rep()` expects unevaluated name and command arguments (e.g. `tar_rep(name = sim, command = simulate())`) whereas `tar_rep_raw()` expects an evaluated string for name and an evaluated expression object for command (e.g. `tar_rep_raw(name = "sim", command = quote(simulate()))`).

Usage

```

tar_rep(
  name,
  command,
  batches = 1,

```

```

    reps = 1,
    rep_workers = 1,
    tidy_eval = targets::tar_option_get("tidy_eval"),
    packages = targets::tar_option_get("packages"),
    library = targets::tar_option_get("library"),
    format = targets::tar_option_get("format"),
    repository = targets::tar_option_get("repository"),
    iteration = targets::tar_option_get("iteration"),
    error = targets::tar_option_get("error"),
    memory = targets::tar_option_get("memory"),
    garbage_collection = targets::tar_option_get("garbage_collection"),
    deployment = targets::tar_option_get("deployment"),
    priority = targets::tar_option_get("priority"),
    resources = targets::tar_option_get("resources"),
    storage = targets::tar_option_get("storage"),
    retrieval = targets::tar_option_get("retrieval"),
    cue = targets::tar_option_get("cue"),
    description = targets::tar_option_get("description")
  )

tar_rep_raw(
  name,
  command,
  batches = 1,
  reps = 1,
  rep_workers = 1,
  tidy_eval = targets::tar_option_get("tidy_eval"),
  packages = targets::tar_option_get("packages"),
  library = targets::tar_option_get("library"),
  format = targets::tar_option_get("format"),
  repository = targets::tar_option_get("repository"),
  iteration = targets::tar_option_get("iteration"),
  error = targets::tar_option_get("error"),
  memory = targets::tar_option_get("memory"),
  garbage_collection = targets::tar_option_get("garbage_collection"),
  deployment = targets::tar_option_get("deployment"),
  priority = targets::tar_option_get("priority"),
  resources = targets::tar_option_get("resources"),
  storage = targets::tar_option_get("storage"),
  retrieval = targets::tar_option_get("retrieval"),
  cue = targets::tar_option_get("cue"),
  description = targets::tar_option_get("description")
)

```

Arguments

name	Name of the target. <code>tar_rep()</code> expects unevaluated name and command arguments (e.g. <code>tar_rep(name = sim, command = simulate())</code>) whereas <code>tar_rep_raw()</code> expects an evaluated string for name and an evaluated expression object for
------	---

	command (e.g. <code>tar_rep_raw(name = "sim", command = quote(simulate()))</code>).
command	R code to run multiple times. Must return a list or data frame because <code>tar_rep()</code> will try to append new elements/columns <code>tar_batch</code> and <code>tar_rep</code> to the output to denote the batch and rep-within-batch IDs, respectively. <code>tar_rep()</code> expects unevaluated name and command arguments (e.g. <code>tar_rep(name = sim, command = simulate())</code>) whereas <code>tar_rep_raw()</code> expects an evaluated string for name and an evaluated expression object for command (e.g. <code>tar_rep_raw(name = "sim", command = quote(simulate()))</code>).
batches	Number of batches. This is also the number of dynamic branches created during <code>tar_make()</code> .
reps	Number of replications in each batch. The total number of replications is <code>batches * reps</code> .
rep_workers	Positive integer of length 1, number of local R processes to use to run reps within batches in parallel. If 1, then reps are run sequentially within each batch. If greater than 1, then reps within batch are run in parallel using a PSOCK cluster.
tidy_eval	Whether to invoke tidy evaluation (e.g. the <code>!!</code> operator from <code>rlang</code>) as soon as the target is defined (before <code>tar_make()</code>). Applies to the command argument.
packages	Character vector of packages to load right before the target runs or the output data is reloaded for downstream targets. Use <code>tar_option_set()</code> to set packages globally for all subsequent targets you define.
library	Character vector of library paths to try when loading packages.
format	Optional storage format for the target's return value. With the exception of <code>format = "file"</code> , each target gets a file in <code>_targets/objects</code> , and each format is a different way to save and load this file. See the "Storage formats" section for a detailed list of possible data storage formats.
repository	Character of length 1, remote repository for target storage. Choices: • "local": file system of the local machine. • "aws": Amazon Web Services (AWS) S3 bucket. Can be configured with a non-AWS S3 bucket using the <code>endpoint</code> argument of <code>tar_resources_aws()</code>, but versioning capabilities may be lost in doing so. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions. • "gcp": Google Cloud Platform storage bucket. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions. • A character string from <code>tar_repository_cas()</code> for content-addressable storage. Note: if <code>repository</code> is not "local" and <code>format</code> is "file" then the target should create a single output file. That output file is uploaded to the cloud and tracked for changes where it exists in the cloud. As of targets version 1.11.0 and higher, the local file is no longer deleted after the target runs.
iteration	Character of length 1, name of the iteration mode of the target. Choices: • "vector": branching happens with <code>vectors::vec_slice()</code> and aggregation happens with <code>vctrs::vec_c()</code>.

- "list", branching happens with `[[ ]]` and aggregation happens with `list()`. In the case of list iteration, `tar_read(your_target)` will return a list of lists, where the outer list has one element per batch and each inner list has one element per rep within batch. To un-batch this nested list, call `tar_read(your_target, recursive = FALSE)`.
- "group": `dplyr::group_by()`-like functionality to branch over subsets of a data frame. The target's return value must be a data frame with a special `tar_group` column of consecutive integers from 1 through the number of groups. Each integer designates a group, and a branch is created for each collection of rows in a group. See the `tar_group()` function in `targets` to see how you can create the special `tar_group` column with `dplyr::group_by()`.

error

Character of length 1, what to do if the target stops and throws an error. Options:

- "stop": the whole pipeline stops and throws an error.
- "continue": the whole pipeline keeps going.
- "null": The errored target continues and returns NULL. The data hash is deliberately wrong so the target is not up to date for the next run of the pipeline. In addition, as of `targets` version 1.8.0.9011, a value of NULL is given to upstream dependencies with `error = "null"` if loading fails.
- "abridge": any currently running targets keep running, but no new targets launch after that.
- "trim": all currently running targets stay running. A queued target is allowed to start if:
 1. It is not downstream of the error, and
 2. It is not a sibling branch from the same `tar_target()` call (if the error happened in a dynamic branch).

The idea is to avoid starting any new work that the immediate error impacts. `error = "trim"` is just like `error = "abridge"`, but it allows potentially healthy regions of the dependency graph to begin running. (Visit <https://books.ropensci.org/targets/debugging.html> to learn how to debug targets using saved workspaces.)

memory

Character of length 1, memory strategy. Possible values:

- "auto" (default): equivalent to `memory = "transient"` in almost all cases. But to avoid superfluous reads from disk, `memory = "auto"` is equivalent to `memory = "persistent"` for non-dynamically-branched targets that other targets dynamically branch over. For example: if your pipeline has `tar_target(name = y, command = x, pattern = map(x))`, then `tar_target(name = x, command = f(), memory = "auto")` will use persistent memory for `x` in order to avoid rereading all of `x` for every branch of `y`.
- "transient": the target gets unloaded after every new target completes. Either way, the target gets automatically loaded into memory whenever another target needs the value.
- "persistent": the target stays in memory until the end of the pipeline (unless storage is "worker", in which case targets unloads the value from memory right after storing it in order to avoid sending copious data over a network).

For cloud-based file targets (e.g. `format = "file"` with `repository = "aws"`), the memory option applies to the temporary local copy of the file: "persistent" means it remains until the end of the pipeline and is then deleted, and "transient" means it gets deleted as soon as possible. The former conserves bandwidth, and the latter conserves local storage.

garbage_collection	Logical: TRUE to run <code>base::gc()</code> just before the target runs, in whatever R process it is about to run (which could be a parallel worker). FALSE to omit garbage collection. Numeric values get converted to FALSE. The <code>garbage_collection</code> option in <code>tar_option_set()</code> is independent of the argument of the same name in <code>tar_target()</code> .
deployment	Character of length 1. If deployment is "main", then the target will run on the central controlling R process. Otherwise, if deployment is "worker" and you set up the pipeline with distributed/parallel computing, then the target runs on a parallel worker. For more on distributed/parallel computing in targets, please visit https://books.ropensci.org/targets/crew.html .
priority	Deprecated on 2025-04-08 (targets version 1.10.1.9013). targets has moved to a more efficient scheduling algorithm (https://github.com/ropensci/targets/issues/1458) which cannot support priorities. The <code>priority</code> argument of <code>tar_target()</code> no longer has a reliable effect on execution order.
resources	Object returned by <code>tar_resources()</code> with optional settings for high-performance computing functionality, alternative data storage formats, and other optional capabilities of targets. See <code>tar_resources()</code> for details.
storage	Character string to control when the output of the target is saved to storage. Only relevant when using targets with parallel workers (https://books.ropensci.org/targets/crew.html). Must be one of the following values: "worker" (default): the worker saves/uploads the value. "main": the target's return value is sent back to the host machine and saved/uploaded locally. "none": targets makes no attempt to save the result of the target to storage in the location where targets expects it to be. Saving to storage is the responsibility of the user. Use with caution.
retrieval	Character string to control when the current target loads its dependencies into memory before running. (Here, a "dependency" is another target upstream that the current one depends on.) Only relevant when using targets with parallel workers (https://books.ropensci.org/targets/crew.html). Must be one of the following values: "auto" (default): equivalent to <code>retrieval = "worker"</code> in almost all cases. But to avoid unnecessary reads from disk, <code>retrieval = "auto"</code> is equivalent to <code>retrieval = "main"</code> for dynamic branches that branch over non-dynamic targets. For example: if your pipeline has <code>tar_target(x, command = f())</code>, then <code>tar_target(y, command = x, pattern = map(x), retrieval = "auto")</code> will use "main" retrieval in order to avoid rereading all of x for every branch of y. "worker": the worker loads the target's dependencies.

	• "main": the target's dependencies are loaded on the host machine and sent to the worker before the target runs. • "none": targets makes no attempt to load its dependencies. With <code>retrieval = "none"</code>, loading dependencies is the responsibility of the user. Use with caution.
cue	An optional object from <code>tar_cue()</code> to customize the rules that decide whether the target is up to date.
description	Character of length 1, a custom free-form human-readable text description of the target. Descriptions appear as target labels in functions like <code>tar_manifest()</code> and <code>tar_visnetwork()</code> , and they let you select subsets of targets for the <code>names</code> argument of functions like <code>tar_make()</code> . For example, <code>tar_manifest(names = tar_described_as(starts_with("survival model")))</code> lists all the targets whose descriptions start with the character string "survival model".

Details

`tar_rep()` and `tar_rep_raw()` each create two targets: an upstream local stem with an integer vector of batch ids, and a downstream pattern that maps over the batch ids. (Thus, each batch is a branch.) Each batch/branch replicates the command a certain number of times. If the command returns a list or data frame, then the targets from `tar_rep()` will try to append new elements/columns `tar_batch`, `tar_rep`, and `tar_seed` to the output to denote the batch, rep-within-batch index, and rep-specific seed, respectively.

Both batches and reps within each batch are aggregated according to the method you specify in the `iteration` argument. If "list", reps and batches are aggregated with `list()`. If "vector", then `vctrs::vec_c()`. If "group", then `vctrs::vec_rbind()`.

Value

A list of two targets, one upstream and one downstream. The upstream target returns a numeric index of batch ids, and the downstream one dynamically maps over the batch ids to run the command multiple times. If the command returns a list or data frame, then the targets from `tar_rep()` will try to append new elements/columns `tar_batch`, `tar_rep`, and `tar_seed` to the output to denote the batch, rep-within-batch ID, and random number generator seed, respectively.

`tar_read(your_target)` (on the downstream target with the actual work) will return a list of lists, where the outer list has one element per batch and each inner list has one element per rep within batch. To un-batch this nested list, call `tar_read(your_target, recursive = FALSE)`.

Replicate-specific seeds

In ordinary pipelines, each target has its own unique deterministic pseudo-random number generator seed derived from its target name. In batched replicate, however, each batch is a target with multiple replicate within that batch. That is why `tar_rep()` and friends give each *replicate* its own unique seed. Each replicate-specific seed is created based on the dynamic parent target name, `tar_option_get("seed")` (for targets version 0.13.5.9000 and above), batch index, and rep-within-batch index. The seed is set just before the replicate runs. Replicate-specific seeds are invariant to batching structure. In other words, `tar_rep(name = x, command = rnorm(1), batches = 100, reps = 1, ...)` produces the same numerical output as `tar_rep(name = x, command = rnorm(1), batches = 10, reps = 10, ...)` (but with different batch names). Other target factories with this

seed scheme are `tar_rep2()`, `tar_map_rep()`, `tar_map2_count()`, `tar_map2_size()`, and `tar_render_rep()`. For the `tar_map2_*` functions, it is possible to manually supply your own seeds through the `command1` argument and then invoke them in your custom code for `command2` (`set.seed()`, `withr::with_seed`, or `withr::local_seed()`). For `tar_render_rep()`, custom seeds can be supplied to the `params` argument and then invoked in the individual R Markdown reports. Likewise with `tar_quarto_rep()` and the `execute_params` argument.

Target definition objects

Most tarchetypes functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

See Also

Other branching: `tar_map2()`, `tar_map2_count()`, `tar_map2_size()`, `tar_map_rep()`, `tar_rep2()`, `tar_rep_map()`, `tar_rep_map_raw()`

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      list(
        tarchetypes::tar_rep(
          x,
          data.frame(x = sample.int(1e4, 2)),
          batches = 2,
          reps = 3
        )
      )
    })
    targets::tar_make()
    targets::tar_read(x)
    targets::tar_script({
      list(
        tarchetypes::tar_rep_raw(
          "x",
          quote(data.frame(x = sample.int(1e4, 2))),
          batches = 2,
          reps = 3
        )
      )
    })
    targets::tar_make()
  })
}
```

```

targets::tar_read(x)
})
}

```

tar_rep_index	<i>Get overall rep index.</i>
---------------	-------------------------------

Description

Get the integer index of the current replication in certain target factories.

Usage

```
tar_rep_index()
```

Details

`tar_rep_index()` cannot run in your interactive R session or even the setup portion of `_targets.R`. It must be part of the R command of a target actively running in a pipeline.

In addition, `tar_rep_index()` is only compatible with `tar_rep()`, `tar_rep2()`, `tar_map_rep()`, `tar_map2_count()`, and `tar_map2_size()`. In the latter 3 cases, `tar_rep_index()` cannot be part of the values or command1 arguments.

In `tar_map_rep()`, each row of the values argument (each "scenario") gets its own independent set of index values from 1 to batches * reps.

Value

Positive integer from 1 to batches * reps, index of the current replication in an ongoing pipeline.

Examples

```

if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      tar_map_rep(
        x,
        data.frame(index = tar_rep_index()),
        batches = 2L,
        reps = 3L,
        values = list(value = c("a", "b")))
      )
    })
  targets::tar_make()
  x <- targets::tar_read(x)
  all(x$index == x$tar_rep + (3L * (x$tar_batch - 1L)))
  #> TRUE
})
}

```

Description

Batching is important for optimizing the efficiency of heavily dynamically-branched workflows: <https://books.ropensci.org/targets/dynamic.html#batching>. `tar_rep2()` uses dynamic branching to iterate over the batches and reps of existing upstream targets.

`tar_rep2()` expects unevaluated language for the name, command, and ... arguments (e.g. `tar_rep2(name = sim, command = simulate(), data1, data2)`) whereas `tar_rep2_raw()` expects an evaluated string for name, an evaluated expression object for command, and a character vector for targets (e.g. `tar_rep2_raw("sim", quote(simulate(x, y)), targets = c("x", "y"))`).

Usage

```
tar_rep2(  
  name,  
  command,  
  ...,  
  rep_workers = 1,  
  tidy_eval = targets::tar_option_get("tidy_eval"),  
  packages = targets::tar_option_get("packages"),  
  library = targets::tar_option_get("library"),  
  format = targets::tar_option_get("format"),  
  repository = targets::tar_option_get("repository"),  
  iteration = targets::tar_option_get("iteration"),  
  error = targets::tar_option_get("error"),  
  memory = targets::tar_option_get("memory"),  
  garbage_collection = targets::tar_option_get("garbage_collection"),  
  deployment = targets::tar_option_get("deployment"),  
  priority = targets::tar_option_get("priority"),  
  resources = targets::tar_option_get("resources"),  
  storage = targets::tar_option_get("storage"),  
  retrieval = targets::tar_option_get("retrieval"),  
  cue = targets::tar_option_get("cue"),  
  description = targets::tar_option_get("description")  
)  
  
tar_rep2_raw(  
  name,  
  command,  
  targets,  
  rep_workers = 1,  
  tidy_eval = targets::tar_option_get("tidy_eval"),  
  packages = targets::tar_option_get("packages"),  
  library = targets::tar_option_get("library"),
```

```

format = targets::tar_option_get("format"),
repository = targets::tar_option_get("repository"),
iteration = targets::tar_option_get("iteration"),
error = targets::tar_option_get("error"),
memory = targets::tar_option_get("memory"),
garbage_collection = targets::tar_option_get("garbage_collection"),
deployment = targets::tar_option_get("deployment"),
priority = targets::tar_option_get("priority"),
resources = targets::tar_option_get("resources"),
storage = targets::tar_option_get("storage"),
retrieval = targets::tar_option_get("retrieval"),
cue = targets::tar_option_get("cue"),
description = targets::tar_option_get("description")
)

```

Arguments

name	Name of the target. <code>tar_rep2()</code> expects unevaluated language for the name, command, and ... arguments (e.g. <code>tar_rep2(name = sim, command = simulate(), data1, data2)</code>) whereas <code>tar_rep2_raw()</code> expects an evaluated string for name, an evaluated expression object for command, and a character vector for targets (e.g. <code>tar_rep2_raw("sim", quote(simulate(x, y)), targets = c("x", "y"))</code>).
command	R code to run multiple times. Must return a list or data frame because <code>tar_rep()</code> will try to append new elements/columns <code>tar_batch</code> and <code>tar_rep</code> to the output to denote the batch and rep-within-batch IDs, respectively. <code>tar_rep2()</code> expects unevaluated language for the name, command, and ... arguments (e.g. <code>tar_rep2(name = sim, command = simulate(), data1, data2)</code>) whereas <code>tar_rep2_raw()</code> expects an evaluated string for name, an evaluated expression object for command, and a character vector for targets (e.g. <code>tar_rep2_raw("sim", quote(simulate(x, y)), targets = c("x", "y"))</code>).
...	Symbols to name one or more upstream batched targets created by <code>tar_rep()</code> . If you supply more than one such target, all those targets must have the same number of batches and reps per batch. And they must all return either data frames or lists. List targets must use <code>iteration = "list"</code> in <code>tar_rep()</code> .
rep_workers	Positive integer of length 1, number of local R processes to use to run reps within batches in parallel. If 1, then reps are run sequentially within each batch. If greater than 1, then reps within batch are run in parallel using a PSOCK cluster.
tidy_eval	Logical, whether to enable tidy evaluation when interpreting command and pattern. If TRUE, you can use the "bang-bang" operator <code>!!</code> to programmatically insert the values of global objects.
packages	Character vector of packages to load right before the target runs or the output data is reloaded for downstream targets. Use <code>tar_option_set()</code> to set packages globally for all subsequent targets you define.
library	Character vector of library paths to try when loading packages.
format	Optional storage format for the target's return value. With the exception of <code>format = "file"</code> , each target gets a file in <code>_targets/objects</code> , and each format is a different way to save and load this file. See the "Storage formats" section for a detailed list of possible data storage formats.

repository	Character of length 1, remote repository for target storage. Choices: • "local": file system of the local machine. • "aws": Amazon Web Services (AWS) S3 bucket. Can be configured with a non-AWS S3 bucket using the endpoint argument of <code>tar_resources_aws()</code>, but versioning capabilities may be lost in doing so. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions. • "gcp": Google Cloud Platform storage bucket. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions. • A character string from <code>tar_repository_cas()</code> for content-addressable storage. Note: if repository is not "local" and format is "file" then the target should create a single output file. That output file is uploaded to the cloud and tracked for changes where it exists in the cloud. As of targets version 1.11.0 and higher, the local file is no longer deleted after the target runs.
iteration	Character of length 1, name of the iteration mode of the target. Choices: • "vector": branching happens with <code>vctrs::vec_slice()</code> and aggregation happens with <code>vctrs::vec_c()</code>. • "list", branching happens with <code>[[]]</code> and aggregation happens with <code>list()</code>. • "group": <code>dplyr::group_by()</code>-like functionality to branch over subsets of a non-dynamic data frame. For iteration = "group", the target must not be dynamic (the pattern argument of <code>tar_target()</code> must be left NULL). The target's return value must be a data frame with a special <code>tar_group</code> column of consecutive integers from 1 through the number of groups. Each integer designates a group, and a branch is created for each collection of rows in a group. See the <code>tar_group()</code> function to see how you can create the special <code>tar_group</code> column with <code>dplyr::group_by()</code>.
error	Character of length 1, what to do if the target stops and throws an error. Options: • "stop": the whole pipeline stops and throws an error. • "continue": the whole pipeline keeps going. • "null": The errored target continues and returns NULL. The data hash is deliberately wrong so the target is not up to date for the next run of the pipeline. In addition, as of targets version 1.8.0.9011, a value of NULL is given to upstream dependencies with <code>error = "null"</code> if loading fails. • "abridge": any currently running targets keep running, but no new targets launch after that. • "trim": all currently running targets stay running. A queued target is allowed to start if: 1. It is not downstream of the error, and 2. It is not a sibling branch from the same <code>tar_target()</code> call (if the error happened in a dynamic branch). The idea is to avoid starting any new work that the immediate error impacts. <code>error = "trim"</code> is just like <code>error = "abridge"</code>, but it allows potentially healthy regions of the dependency graph to begin running. (Visit https://

books.ropensci.org/targets/debugging.html to learn how to debug targets using saved workspaces.)

memory	Character of length 1, memory strategy. Possible values: • "auto" (default): equivalent to <code>memory = "transient"</code> in almost all cases. But to avoid superfluous reads from disk, <code>memory = "auto"</code> is equivalent to <code>memory = "persistent"</code> for non-dynamically-branched targets that other targets dynamically branch over. For example: if your pipeline has <code>tar_target(name = y, command = x, pattern = map(x))</code>, then <code>tar_target(name = x, command = f(), memory = "auto")</code> will use persistent memory for <code>x</code> in order to avoid rereading all of <code>x</code> for every branch of <code>y</code>. • "transient": the target gets unloaded after every new target completes. Either way, the target gets automatically loaded into memory whenever another target needs the value. • "persistent": the target stays in memory until the end of the pipeline (unless storage is "worker", in which case targets unloads the value from memory right after storing it in order to avoid sending copious data over a network). For cloud-based file targets (e.g. <code>format = "file"</code> with <code>repository = "aws"</code>), the memory option applies to the temporary local copy of the file: "persistent" means it remains until the end of the pipeline and is then deleted, and "transient" means it gets deleted as soon as possible. The former conserves bandwidth, and the latter conserves local storage.
garbage_collection	Logical: TRUE to run <code>base::gc()</code> just before the target runs, in whatever R process it is about to run (which could be a parallel worker). FALSE to omit garbage collection. Numeric values get converted to FALSE. The <code>garbage_collection</code> option in <code>tar_option_set()</code> is independent of the argument of the same name in <code>tar_target()</code>.
deployment	Character of length 1. If deployment is "main", then the target will run on the central controlling R process. Otherwise, if deployment is "worker" and you set up the pipeline with distributed/parallel computing, then the target runs on a parallel worker. For more on distributed/parallel computing in targets, please visit https://books.ropensci.org/targets/crew.html.
priority	Deprecated on 2025-04-08 (targets version 1.10.1.9013). targets has moved to a more efficient scheduling algorithm (https://github.com/ropensci/targets/issues/1458) which cannot support priorities. The <code>priority</code> argument of <code>tar_target()</code> no longer has a reliable effect on execution order.
resources	Object returned by <code>tar_resources()</code> with optional settings for high-performance computing functionality, alternative data storage formats, and other optional capabilities of targets. See <code>tar_resources()</code> for details.
storage	Character string to control when the output of the target is saved to storage. Only relevant when using targets with parallel workers (https://books.ropensci.org/targets/crew.html). Must be one of the following values: • "worker" (default): the worker saves/uploads the value. • "main": the target's return value is sent back to the host machine and saved/uploaded locally.

	• "none": targets makes no attempt to save the result of the target to storage in the location where targets expects it to be. Saving to storage is the responsibility of the user. Use with caution.
retrieval	Character string to control when the current target loads its dependencies into memory before running. (Here, a "dependency" is another target upstream that the current one depends on.) Only relevant when using targets with parallel workers (https://books.ropensci.org/targets/crew.html). Must be one of the following values: • "auto" (default): equivalent to retrieval = "worker" in almost all cases. But to avoid unnecessary reads from disk, retrieval = "auto" is equivalent to retrieval = "main" for dynamic branches that branch over non-dynamic targets. For example: if your pipeline has tar_target(x, command = f()), then tar_target(y, command = x, pattern = map(x), retrieval = "auto") will use "main" retrieval in order to avoid rereading all of x for every branch of y. • "worker": the worker loads the target's dependencies. • "main": the target's dependencies are loaded on the host machine and sent to the worker before the target runs. • "none": targets makes no attempt to load its dependencies. With retrieval = "none", loading dependencies is the responsibility of the user. Use with caution.
cue	An optional object from tar_cue() to customize the rules that decide whether the target is up to date.
description	Character of length 1, a custom free-form human-readable text description of the target. Descriptions appear as target labels in functions like tar_manifest() and tar_visnetwork(), and they let you select subsets of targets for the names argument of functions like tar_make(). For example, tar_manifest(names = tar_described_as(starts_with("survival model"))) lists all the targets whose descriptions start with the character string "survival model".
targets	Character vector of names of upstream batched targets created by tar_rep(). If you supply more than one such target, all those targets must have the same number of batches and reps per batch. And they must all return either data frames or lists. List targets must use iteration = "list" in tar_rep().

Value

A new target definition object to perform batched computation. See the "Target definition objects" section for background.

Target definition objects

Most tarchetypes functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

Replicate-specific seeds

In ordinary pipelines, each target has its own unique deterministic pseudo-random number generator seed derived from its target name. In batched replicate, however, each batch is a target with multiple replicate within that batch. That is why `tar_rep()` and friends give each *replicate* its own unique seed. Each replicate-specific seed is created based on the dynamic parent target name, `tar_option_get("seed")` (for targets version 0.13.5.9000 and above), batch index, and rep-within-batch index. The seed is set just before the replicate runs. Replicate-specific seeds are invariant to batching structure. In other words, `tar_rep(name = x, command = rnorm(1), batches = 100, reps = 1, ...)` produces the same numerical output as `tar_rep(name = x, command = rnorm(1), batches = 10, reps = 10, ...)` (but with different batch names). Other target factories with this seed scheme are `tar_rep2()`, `tar_map_rep()`, `tar_map2_count()`, `tar_map2_size()`, and `tar_render_rep()`. For the `tar_map2_*` functions, it is possible to manually supply your own seeds through the `command1` argument and then invoke them in your custom code for `command2` (`set.seed()`, `withr::with_seed`, or `withr::local_seed()`). For `tar_render_rep()`, custom seeds can be supplied to the `params` argument and then invoked in the individual R Markdown reports. Likewise with `tar_quarto_rep()` and the `execute_params` argument.

See Also

Other branching: `tar_map2()`, `tar_map2_count()`, `tar_map2_size()`, `tar_map_rep()`, `tar_rep()`, `tar_rep_map()`, `tar_rep_map_raw()`

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      library(tarchetypes)
      list(
        tar_rep(
          data1,
          data.frame(value = rnorm(1)),
          batches = 2,
          reps = 3
        ),
        tar_rep(
          data2,
          list(value = rnorm(1)),
          batches = 2, reps = 3,
          iteration = "list" # List iteration is important for batched lists.
        ),
        tar_rep2(
          aggregate,
          data.frame(value = data1$value + data2$value),
          data1,
```

```

      data2
    ),
    tar_rep2_raw(
      "aggregate2",
      quote(data.frame(value = data1$value + data2$value)),
      targets = c("data1", "data2")
    )
  )
})
targets::tar_make()
targets::tar_read(aggregate)
})
}
```

tar_select_names	Select target names from a target list
------------------	--

Description

Select the names of targets from a target list.

Usage

```
tar_select_names(targets, ...)
```

Arguments

targets	A list of target definition objects as described in the "Target definition objects" section. It does not matter how nested the list is as long as the only leaf nodes are targets.
...	One or more comma-separated tidyselect expressions, e.g. starts_with("prefix"). Just like ... in dplyr::select().

Value

A character vector of target names.

Target definition objects

Most tarchetypes functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

See Also

Other target selection: `tar_select_targets()`

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets <- list(
      list(
        targets::tar_target(x, 1),
        targets::tar_target(y1, 2)
      ),
      targets::tar_target(y2, 3),
      targets::tar_target(z, 4)
    )
    tar_select_names(targets, starts_with("y"), contains("z"))
  })
}
```

tar_select_targets	Select target definition objects from a target list
--------------------	---

Description

Select target definition objects from a target list.

Usage

```
tar_select_targets(targets, ...)
```

Arguments

targets	A list of target definition objects as described in the "Target definition objects" section. It does not matter how nested the list is as long as the only leaf nodes are targets.
...	One or more comma-separated tidyselect expressions, e.g. <code>starts_with("prefix")</code> . Just like ... in <code>dplyr::select()</code> .

Value

A list of target definition objects. See the "Target definition objects" section of this help file.

Target definition objects

Most tarchetypes functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

See Also

Other target selection: `tar_select_names()`

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets <- list(
      list(
        targets::tar_target(x, 1),
        targets::tar_target(y1, 2)
      ),
      targets::tar_target(y2, 3),
      targets::tar_target(z, 4)
    )
    tar_select_targets(targets, starts_with("y"), contains("z"))
  })
}
```

tar_skip

Target with a custom cancellation condition.

Description

Create a target that cancels itself if a user-defined decision rule is met.

Usage

```
tar_skip(
  name,
  command,
  skip,
  pattern = NULL,
  tidy_eval = targets::tar_option_get("tidy_eval"),
  packages = targets::tar_option_get("packages"),
  library = targets::tar_option_get("library"),
```

```

format = targets::tar_option_get("format"),
repository = targets::tar_option_get("repository"),
iteration = targets::tar_option_get("iteration"),
error = targets::tar_option_get("error"),
memory = targets::tar_option_get("memory"),
garbage_collection = targets::tar_option_get("garbage_collection"),
deployment = targets::tar_option_get("deployment"),
priority = targets::tar_option_get("priority"),
resources = targets::tar_option_get("resources"),
storage = targets::tar_option_get("storage"),
retrieval = targets::tar_option_get("retrieval"),
cue = targets::tar_option_get("cue"),
description = targets::tar_option_get("description")
)

```

Arguments

name	Symbol, name of the target. In <code>tar_target()</code>, name is an unevaluated symbol, e.g. <code>tar_target(name = data)</code>. In <code>tar_target_raw()</code>, name is a character string, e.g. <code>tar_target_raw(name = "data")</code>. A target name must be a valid name for a symbol in R, and it must not start with a dot. Subsequent targets can refer to this name symbolically to induce a dependency relationship: e.g. <code>tar_target(downstream_target, f(upstream_target))</code> is a target named <code>downstream_target</code> which depends on a target <code>upstream_target</code> and a function <code>f()</code>. In most cases, The target name is the name of its local data file in storage. Some file systems are not case sensitive, which means converting a name to a different case may overwrite a different target. Please ensure all target names have unique names when converted to lower case. In addition, a target's name determines its random number generator seed. In this way, each target runs with a reproducible seed so someone else running the same pipeline should get the same results, and no two targets in the same pipeline share the same seed. (Even dynamic branches have different names and thus different seeds.) You can recover the seed of a completed target with <code>tar_meta(your_target, seed)</code> and run <code>tar_seed_set()</code> on the result to locally recreate the target's initial RNG state.
command	R code to run the target. In <code>tar_target()</code>, command is an unevaluated expression, e.g. <code>tar_target(command = data)</code>. In <code>tar_target_raw()</code>, command is an evaluated expression, e.g. <code>tar_target_raw(command = quote(data))</code>.
skip	R code for the skipping condition. If it evaluates to TRUE during <code>tar_make()</code>, the target will cancel itself.
pattern	Code to define a dynamic branching for a target. In <code>tar_target()</code>, pattern is an unevaluated expression, e.g. <code>tar_target(pattern = map(data))</code>. In <code>tar_target_raw()</code>, command is an evaluated expression, e.g. <code>tar_target_raw(pattern = quote(map(data)))</code>. To demonstrate dynamic branching patterns, suppose we have a pipeline with numeric vector targets <code>x</code> and <code>y</code>. Then, <code>tar_target(z, x + y, pattern = map(x,</code>

	y)) implicitly defines branches of <code>z</code> that each compute <code>x[1] + y[1]</code> , <code>x[2] + y[2]</code> , and so on. See the user manual for details.
tidy_eval	Whether to invoke tidy evaluation (e.g. the <code>!!</code> operator from <code>rlang</code>) as soon as the target is defined (before <code>tar_make()</code>). Applies to arguments <code>command</code> and <code>skip</code> .
packages	Character vector of packages to load right before the target runs or the output data is reloaded for downstream targets. Use <code>tar_option_set()</code> to set packages globally for all subsequent targets you define.
library	Character vector of library paths to try when loading packages.
format	Optional storage format for the target's return value. With the exception of <code>format = "file"</code> , each target gets a file in <code>_targets/objects</code> , and each format is a different way to save and load this file. See the "Storage formats" section for a detailed list of possible data storage formats.
repository	Character of length 1, remote repository for target storage. Choices: • <code>"local"</code>: file system of the local machine. • <code>"aws"</code>: Amazon Web Services (AWS) S3 bucket. Can be configured with a non-AWS S3 bucket using the <code>endpoint</code> argument of <code>tar_resources_aws()</code>, but versioning capabilities may be lost in doing so. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions. • <code>"gcp"</code>: Google Cloud Platform storage bucket. See the cloud storage section of https://books.ropensci.org/targets/data.html for details for instructions. • A character string from <code>tar_repository_cas()</code> for content-addressable storage. Note: if <code>repository</code> is not <code>"local"</code> and <code>format</code> is <code>"file"</code> then the target should create a single output file. That output file is uploaded to the cloud and tracked for changes where it exists in the cloud. As of targets version 1.11.0 and higher, the local file is no longer deleted after the target runs.
iteration	Character of length 1, name of the iteration mode of the target. Choices: • <code>"vector"</code>: branching happens with <code>vctrs::vec_slice()</code> and aggregation happens with <code>vctrs::vec_c()</code>. • <code>"list"</code>, branching happens with <code>[[]]</code> and aggregation happens with <code>list()</code>. • <code>"group"</code>: <code>dplyr::group_by()</code>-like functionality to branch over subsets of a non-dynamic data frame. For <code>iteration = "group"</code>, the target must not be dynamic (the <code>pattern</code> argument of <code>tar_target()</code> must be left <code>NULL</code>). The target's return value must be a data frame with a special <code>tar_group</code> column of consecutive integers from 1 through the number of groups. Each integer designates a group, and a branch is created for each collection of rows in a group. See the <code>tar_group()</code> function to see how you can create the special <code>tar_group</code> column with <code>dplyr::group_by()</code>.
error	Character of length 1, what to do if the target stops and throws an error. Options: • <code>"stop"</code>: the whole pipeline stops and throws an error. • <code>"continue"</code>: the whole pipeline keeps going.

- "null": The errored target continues and returns NULL. The data hash is deliberately wrong so the target is not up to date for the next run of the pipeline. In addition, as of targets version 1.8.0.9011, a value of NULL is given to upstream dependencies with error = "null" if loading fails.
- "abridge": any currently running targets keep running, but no new targets launch after that.
- "trim": all currently running targets stay running. A queued target is allowed to start if:
 1. It is not downstream of the error, and
 2. It is not a sibling branch from the same `tar_target()` call (if the error happened in a dynamic branch).

The idea is to avoid starting any new work that the immediate error impacts. error = "trim" is just like error = "abridge", but it allows potentially healthy regions of the dependency graph to begin running. (Visit <https://books.ropensci.org/targets/debugging.html> to learn how to debug targets using saved workspaces.)

memory

Character of length 1, memory strategy. Possible values:

- "auto" (default): equivalent to memory = "transient" in almost all cases. But to avoid superfluous reads from disk, memory = "auto" is equivalent to memory = "persistent" for non-dynamically-branched targets that other targets dynamically branch over. For example: if your pipeline has `tar_target(name = y, command = x, pattern = map(x))`, then `tar_target(name = x, command = f(), memory = "auto")` will use persistent memory for x in order to avoid rereading all of x for every branch of y.
- "transient": the target gets unloaded after every new target completes. Either way, the target gets automatically loaded into memory whenever another target needs the value.
- "persistent": the target stays in memory until the end of the pipeline (unless storage is "worker", in which case targets unloads the value from memory right after storing it in order to avoid sending copious data over a network).

For cloud-based file targets (e.g. format = "file" with repository = "aws"), the memory option applies to the temporary local copy of the file: "persistent" means it remains until the end of the pipeline and is then deleted, and "transient" means it gets deleted as soon as possible. The former conserves bandwidth, and the latter conserves local storage.

garbage_collection

Logical: TRUE to run `base::gc()` just before the target runs, in whatever R process it is about to run (which could be a parallel worker). FALSE to omit garbage collection. Numeric values get converted to FALSE. The garbage_collection option in `tar_option_set()` is independent of the argument of the same name in `tar_target()`.

deployment

Character of length 1. If deployment is "main", then the target will run on the central controlling R process. Otherwise, if deployment is "worker" and you set up the pipeline with distributed/parallel computing, then the target runs on a parallel worker. For more on distributed/parallel computing in targets, please visit <https://books.ropensci.org/targets/crew.html>.

priority	Deprecated on 2025-04-08 (targets version 1.10.1.9013). targets has moved to a more efficient scheduling algorithm (https://github.com/ropensci/targets/issues/1458) which cannot support priorities. The priority argument of <code>tar_target()</code> no longer has a reliable effect on execution order.
resources	Object returned by <code>tar_resources()</code> with optional settings for high-performance computing functionality, alternative data storage formats, and other optional capabilities of targets. See <code>tar_resources()</code> for details.
storage	Character string to control when the output of the target is saved to storage. Only relevant when using targets with parallel workers (https://books.ropensci.org/targets/crew.html). Must be one of the following values: • "worker" (default): the worker saves/uploads the value. • "main": the target's return value is sent back to the host machine and saved/uploaded locally. • "none": targets makes no attempt to save the result of the target to storage in the location where targets expects it to be. Saving to storage is the responsibility of the user. Use with caution.
retrieval	Character string to control when the current target loads its dependencies into memory before running. (Here, a "dependency" is another target upstream that the current one depends on.) Only relevant when using targets with parallel workers (https://books.ropensci.org/targets/crew.html). Must be one of the following values: • "auto" (default): equivalent to <code>retrieval = "worker"</code> in almost all cases. But to avoid unnecessary reads from disk, <code>retrieval = "auto"</code> is equivalent to <code>retrieval = "main"</code> for dynamic branches that branch over non-dynamic targets. For example: if your pipeline has <code>tar_target(x, command = f())</code>, then <code>tar_target(y, command = x, pattern = map(x), retrieval = "auto")</code> will use "main" retrieval in order to avoid rereading all of x for every branch of y. • "worker": the worker loads the target's dependencies. • "main": the target's dependencies are loaded on the host machine and sent to the worker before the target runs. • "none": targets makes no attempt to load its dependencies. With <code>retrieval = "none"</code>, loading dependencies is the responsibility of the user. Use with caution.
cue	An optional object from <code>tar_cue()</code> to customize the rules that decide whether the target is up to date.
description	Character of length 1, a custom free-form human-readable text description of the target. Descriptions appear as target labels in functions like <code>tar_manifest()</code> and <code>tar_visnetwork()</code> , and they let you select subsets of targets for the names argument of functions like <code>tar_make()</code> . For example, <code>tar_manifest(names = tar_described_as(starts_with("survival model")))</code> lists all the targets whose descriptions start with the character string "survival model".

Details

`tar_skip()` creates a target that cancels itself whenever a custom condition is met. The mechanism of cancellation is `targets::tar_cancel(your_condition)`, which allows skipping to hap-

pen even if the target does not exist yet. This behavior differs from `tar_cue(mode = "never")`, which still runs if the target does not exist.

Value

A target definition object with `targets::tar_cancel(your_condition)` inserted into the command. See the "Target definition objects" section for background.

Target definition objects

Most `tarchetypes` functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

See Also

Other targets with custom invalidation rules: `tar_change()`, `tar_download()`, `tar_force()`

Examples

```
if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    targets::tar_script({
      list(
        tarchetypes::tar_skip(x, command = "value", skip = 1 > 0)
      )
    })
    targets::tar_make()
  })
}
```

tar_sub

Create multiple expressions with symbol substitution.

Description

Loop over a grid of values and create an expression object from each one. Helps with general metaprogramming.

`tar_sub()` expects an unevaluated expression for the `expr` object, whereas `tar_sub_raw()` expects an evaluated expression object.

Usage

```
tar_sub(expr, values)
```

```
tar_sub_raw(expr, values)
```

Arguments

expr	Starting expression. Values are iteratively substituted in place of symbols in expr to create each new expression. tar_sub() expects an unevaluated expression for the expr object, whereas tar_sub_raw() expects an evaluated expression object.
values	List of values to substitute into expr to create the expressions. All elements of values must have the same length.

Value

A list of expression objects. Often, these expression objects evaluate to target definition objects (but not necessarily). See the "Target definition objects" section for background.

Target definition objects

Most tarchetypes functions are target factories, which means they return target definition objects or lists of target definition objects. target definition objects represent skippable steps of the analysis pipeline as described at <https://books.ropensci.org/targets/>. Please read the walkthrough at <https://books.ropensci.org/targets/walkthrough.html> to understand the role of target definition objects in analysis pipelines.

For developers, <https://wlandau.github.io/targetopia/contributing.html#target-factories> explains target factories (functions like this one which generate targets) and the design specification at <https://books.ropensci.org/targets-design/> details the structure and composition of target definition objects.

See Also

Other Metaprogramming utilities: [tar_eval\(\)](#)

Examples

```
# tar_map() is incompatible with tar_render() because the latter
# operates on preexisting tar_target() objects. By contrast,
# tar_eval() and tar_sub() iterate over code farther upstream.
values <- list(
  name = lapply(c("name1", "name2"), as.symbol),
  file = list("file1.Rmd", "file2.Rmd")
)
tar_sub(tar_render(name, file), values = values)
tar_sub_raw(quote(tar_render(name, file)), values = values)
```

tar_tangle

*Convert Quarto or R Markdown to a pipeline***Description**

Convert a literate programming source file into a targets pipeline.

Usage

```
tar_tangle(path)
```

Arguments

path	File path to the literate programming source file. The file can be a Quarto or R Markdown document.
------	---

Details

The word "tangle" comes from the early days of literate programming (see Knuth 1984). To "tangle" means to convert a literate programming source document into pure code: code that a human may find cryptic but a machine can run. For example, `knitr::knit(tangle = TRUE)` (and `knitr::purl()`) accepts an `.Rmd` file and returns an R script with all the R code chunks pasted together.

`tar_tangle()` is similar, but for a targets pipeline. It accepts a Quarto or R Markdown source file as input, and it returns a list of target definition objects. Each target definition object comes from evaluating `targets::tar_target()` on each of the assignment statements in each R code chunk in the file.

For example, consider the following code chunk:

```
```{r, deployment = "main"}
#| pattern: map(data)
#| format: qs
#| cue: tar_cue(mode = "always")
data <- get_data(data)
```
```

`tar_tangle()` converts this chunk into:

```
tar_target(
  name = target_name,
  command = command_to_run(data),
  pattern = map(data),
  format = "qs",
  deployment = "main",
  cue = tar_cue(mode = "always")
)
```

To put it all together, suppose our `_targets.R` script for the pipeline looks like this:

```
library(targets)
tar_source()
list(
  tar_tangle("example.qmd"),
  tar_target(model, fit_model(data))
)
```

The pipeline above is equivalent to:

```
library(targets)
tar_source()
list(
  tar_target(
    name = target_name,
    command = command_to_run(data),
    pattern = map(data),
    format = "qs",
    deployment = "main",
    cue = tar_cue(mode = "always")
  ),
  tar_target(model, fit_model(data))
)
```

This pattern is a nice compromise between interactivity and automation: you can run the whole pipeline with `targets::tar_make()`, or you can explore individual code chunks in the report using an IDE like RStudio, Positron, or VSCode. However, there is a chance other tools like Quarto or pkgdown may automatically detect the report and inappropriately try to run the whole thing from end to end. To prevent this, you may wish to write `knitr::opts_chunk$set(eval = FALSE)` in a code chunk at the top of the report.

See the "Examples" section in this help file for a runnable demonstration with multiple code chunks.

Each code chunk can have more than one top-level assignment statement (with `<-`, `=`, or `->`), and each assignment statement gets converted into its own target. Non-assignment statements such as `library(dplyr)` are ignored. It is always good practice to check your pipeline with `targets::tar_manifest()` and `targets::tar_visnetwork()` before running it with `targets::tar_make()`.

Value

A list of new target definition objects. See the "Target definition objects" section for background.

References

- Knuth, Donald E. (1984). "Literate Programming". The Computer Journal. 27 (2). British Computer Society: 97-111. doi:10.1093/comjnl/27.2.97.

See Also

Other Domain-specific languages for pipeline construction: `tar_assign()`

Examples

```

if (identical(Sys.getenv("TAR_LONG_EXAMPLES"), "true")) {
  targets::tar_dir({ # tar_dir() runs code from a temporary directory.
    write.csv(airquality, "data.csv")
    lines <- c(
      "----",
      "title: \"Example pipeline\"",
      "----",
      "",
      "```{r}",
      "knitr::opts_chunk$set(eval = FALSE)",
      "```",
      "",
      "```{r}",
      "#| format: file",
      "file <- \"data.csv\"",
      "```",
      "",
      "```{r}",
      "#| memory: persistent",
      "#| packages: [dplyr, readr]",
      "data <- read_csv(file, col_types = cols()) |>",
      "  filter(!is.na(Ozone))",
      "```",
      "",
      "```{r}",
      "#| format: qs",
      "#| cue: tar_cue(mode = \"never\")",
      "model <- lm(Ozone ~ Temp, data) |>",
      "  coefficients()",
      "```",
      "",
      "```{r}",
      "#| deployment: main",
      "#| packages: ggplot2",
      "plot <- ggplot(data) +",
      "  geom_point(aes(x = Temp, y = Ozone)) +",
      "  geom_abline(intercept = model[1], slope = model[2]) +",
      "  theme_gray(24)",
      "```"
    )
    writeLines(lines, "pipeline.qmd")
    targets::tar_script(tarchetypes::tar_tangle("pipeline.qmd"))
    targets::tar_make()
    targets::tar_read(plot)
  })
}

```

Index

- * **Domain-specific languages for pipeline construction**
 - tar_assign, 8
 - tar_tangle, 172
 - * **Dynamic batched replication indexing**
 - tar_rep_index, 156
 - * **Dynamic branching over files**
 - tar_files, 37
 - tar_files_input, 42
 - * **Grouped data frame targets**
 - tar_group_by, 63
 - tar_group_count, 68
 - tar_group_select, 72
 - tar_group_size, 77
 - * **Literate programming targets**
 - tar_knit, 89
 - tar_quarto, 121
 - tar_quarto_rep, 129
 - tar_render, 136
 - tar_render_rep, 143
 - * **Literate programming utilities**
 - tar_knitr_deps, 94
 - tar_knitr_deps_expr, 95
 - tar_quarto_files, 128
 - * **Metaprogramming utilities**
 - tar_eval, 31
 - tar_sub, 170
 - * **Pipeline factories**
 - tar_plan, 120
 - * **Simple files**
 - tar_file_read, 32
 - * **branching**
 - tar_map2_count, 105
 - tar_map2_size, 112
 - tar_map_rep, 98
 - tar_rep, 149
 - tar_rep2, 157
 - * **cues**
 - tar_age, 3
 - tar_cue_age, 20
 - tar_cue_force, 22
 - tar_cue_skip, 24
 - * **formats**
 - tar_format_nanoparquet, 51
 - * **hooks**
 - tar_hook_before, 82
 - tar_hook_inner, 84
 - tar_hook_outer, 87
 - * **static branching**
 - tar_combine, 14
 - tar_map, 96
 - * **storage**
 - tar_format_nanoparquet, 51
 - * **target factories for storage formats**
 - tar_formats, 52
 - * **target selection**
 - tar_select_names, 163
 - tar_select_targets, 164
 - * **targets with custom invalidation rules**
 - tar_change, 9
 - tar_download, 26
 - tar_force, 46
 - tar_skip, 165
- any_of(), 97, 100, 107, 114
- knitr::purl(), 172
- nanoparquet::parquet_options(), 52, 62
- nanoparquet::read_parquet(), 51
- nanoparquet::write_parquet(), 51, 52, 62
- options, 27
- starts_with(), 82, 85, 87, 97, 100, 107, 114
- tar_age, 3, 22, 24, 25
- tar_arrow_feather(tar_formats), 52
- tar_arrow_feather(), 52
- tar_assign, 8, 173

tar_assign(), 8
 tar_change, 9, 30, 51, 170
 tar_change(), 50
 tar_combine, 14, 97
 tar_combine(), 14, 16
 tar_combine_raw(tar_combine), 14
 tar_combine_raw(), 14, 16
 tar_cue_age, 7, 20, 24, 25
 tar_cue_age(), 6
 tar_cue_age_raw(tar_cue_age), 20
 tar_cue_force, 7, 22, 22, 25
 tar_cue_force(), 51
 tar_cue_skip, 7, 22, 24, 24
 tar_download, 14, 26, 51, 170
 tar_eval, 31, 171
 tar_eval(), 31
 tar_eval_raw(tar_eval), 31
 tar_eval_raw(), 31
 tar_file(tar_formats), 52
 tar_file_fast(tar_formats), 52
 tar_file_read, 32
 tar_files, 37, 46
 tar_files(), 37, 38
 tar_files_input, 42, 42
 tar_files_input(), 41–43
 tar_files_input_raw(tar_files_input), 42
 tar_files_input_raw(), 42, 43
 tar_files_raw(tar_files), 37
 tar_files_raw(), 37, 38
 tar_force, 14, 30, 46, 170
 tar_force(), 23
 tar_format_feather(), 52
 tar_format_nanoparquet, 51
 tar_format_nanoparquet(), 52
 tar_formats, 52
 tar_fst(tar_formats), 52
 tar_fst_dt(tar_formats), 52
 tar_fst_tbl(tar_formats), 52
 tar_group(), 11, 17, 28, 39, 48, 60, 159, 167
 tar_group_by, 63, 72, 76, 81
 tar_group_count, 67, 68, 76, 81
 tar_group_select, 67, 72, 72, 81
 tar_group_size, 67, 72, 76, 77
 tar_hook_before, 82, 86, 88
 tar_hook_before_raw(tar_hook_before), 82
 tar_hook_inner, 83, 84, 88
 tar_hook_inner_raw(tar_hook_inner), 84
 tar_hook_outer, 83, 86, 87
 tar_hook_outer_raw(tar_hook_outer), 87
 tar_keras(tar_formats), 52
 tar_knit, 89, 126, 136, 141, 148
 tar_knit(), 89, 90, 93, 95
 tar_knit_raw(tar_knit), 89
 tar_knit_raw(), 89, 90
 tar_knitr_deps, 94, 96, 129
 tar_knitr_deps_expr, 95, 95, 129
 tar_make(), 6, 13, 19, 30, 36, 41, 45, 50, 62, 67, 71, 76, 81, 93, 103, 110, 118, 125, 134, 140, 147, 154, 161, 169
 tar_manifest(), 6, 13, 19, 30, 36, 41, 45, 50, 62, 66, 71, 76, 81, 92, 103, 110, 118, 125, 134, 140, 147, 154, 161, 169
 tar_map, 19, 96
 tar_map(), 96, 99, 107, 114
 tar_map2, 104, 111, 119, 155, 162
 tar_map2_count, 104, 105, 119, 155, 162
 tar_map2_count(), 103, 105, 111, 118, 135, 148, 155, 156, 162
 tar_map2_count_raw(tar_map2_count), 105
 tar_map2_count_raw(), 105
 tar_map2_size, 104, 111, 112, 155, 162
 tar_map2_size(), 103, 111, 112, 118, 135, 148, 155, 156, 162
 tar_map2_size_raw(tar_map2_size), 112
 tar_map2_size_raw(), 112
 tar_map_rep, 98, 111, 119, 155, 162
 tar_map_rep(), 98, 99, 103, 111, 118, 135, 148, 155, 156, 162
 tar_map_rep_raw(tar_map_rep), 98
 tar_map_rep_raw(), 98, 99
 tar_nanoparquet(tar_formats), 52
 tar_option_set(), 4, 5, 12, 18, 21, 23, 25, 29, 35, 40, 45, 49, 61, 66, 70, 75, 80, 92, 102, 109, 117, 124, 133, 139, 146, 153, 160, 168
 tar_parquet(tar_formats), 52
 tar_plan, 120
 tar_qs(tar_formats), 52
 tar_quarto, 94, 121, 136, 141, 148
 tar_quarto(), 8, 121–123
 tar_quarto_files, 95, 96, 128
 tar_quarto_files(), 123, 126, 131
 tar_quarto_raw(tar_quarto), 121
 tar_quarto_raw(), 121–123

tar_quarto_rep, [94](#), [126](#), [129](#), [141](#), [148](#)
 tar_quarto_rep(), [103](#), [111](#), [118](#), [129](#), [131](#),
 [135](#), [148](#), [155](#), [162](#)
 tar_quarto_rep_raw(tar_quarto_rep), [129](#)
 tar_quarto_rep_raw(), [129](#), [131](#)
 tar_rds(tar_formats), [52](#)
 tar_render, [94](#), [126](#), [136](#), [136](#), [148](#)
 tar_render(), [95](#), [120](#), [126](#), [135](#), [137](#), [138](#),
 [141](#), [147](#), [148](#)
 tar_render_raw(tar_render), [136](#)
 tar_render_raw(), [137](#), [138](#)
 tar_render_rep, [94](#), [126](#), [136](#), [141](#), [143](#)
 tar_render_rep(), [103](#), [111](#), [118](#), [135](#), [143](#),
 [144](#), [148](#), [155](#), [162](#)
 tar_render_rep_raw(tar_render_rep), [143](#)
 tar_render_rep_raw(), [143](#), [144](#)
 tar_rep, [104](#), [111](#), [119](#), [149](#), [162](#)
 tar_rep(), [103](#), [106](#), [111](#), [114](#), [118](#), [135](#),
 [148–151](#), [154](#), [156–158](#), [161](#), [162](#)
 tar_rep2, [104](#), [111](#), [119](#), [155](#), [157](#)
 tar_rep2(), [103](#), [111](#), [118](#), [135](#), [148](#),
 [155–158](#), [162](#)
 tar_rep2_raw(tar_rep2), [157](#)
 tar_rep2_raw(), [157](#), [158](#)
 tar_rep_index, [156](#)
 tar_rep_index(), [156](#)
 tar_rep_map, [104](#), [111](#), [119](#), [155](#), [162](#)
 tar_rep_map_raw, [104](#), [111](#), [119](#), [155](#), [162](#)
 tar_rep_raw(tar_rep), [149](#)
 tar_rep_raw(), [106](#), [114](#), [149–151](#)
 tar_repository_cas(), [11](#), [16](#), [34](#), [38](#), [43](#),
 [48](#), [59](#), [64](#), [69](#), [74](#), [79](#), [101](#), [108](#), [116](#),
 [151](#), [159](#), [167](#)
 tar_resources_aws(), [11](#), [16](#), [34](#), [38](#), [43](#), [48](#),
 [59](#), [64](#), [69](#), [74](#), [78](#), [100](#), [108](#), [115](#),
 [151](#), [159](#), [167](#)
 tar_seed_set(), [10](#), [27](#), [33](#), [47](#), [59](#), [64](#), [69](#),
 [73](#), [78](#), [166](#)
 tar_select_names, [163](#), [165](#)
 tar_select_targets, [164](#), [164](#)
 tar_skip, [14](#), [30](#), [51](#), [165](#)
 tar_sub, [32](#), [170](#)
 tar_sub(), [170](#), [171](#)
 tar_sub_raw(tar_sub), [170](#)
 tar_sub_raw(), [170](#), [171](#)
 tar_tangle, [9](#), [172](#)
 tar_target(), [4](#), [5](#), [10–12](#), [16–18](#), [21](#), [23](#), [25](#),
 [27–29](#), [33–35](#), [39](#), [40](#), [44](#), [45](#), [47–49](#),
 [58–61](#), [63–66](#), [68–70](#), [73–75](#), [78–80](#),
 [91](#), [92](#), [101](#), [102](#), [108](#), [109](#), [116](#), [117](#),
 [124](#), [125](#), [133](#), [138](#), [139](#), [145](#), [146](#),
 [152](#), [153](#), [159](#), [160](#), [166–169](#)
 tar_target_raw(), [4](#), [10](#), [16](#), [27](#), [33](#), [47](#), [58](#),
 [59](#), [63](#), [64](#), [68](#), [69](#), [73](#), [78](#), [166](#)
 tar_torch(tar_formats), [52](#)
 tar_url(tar_formats), [52](#)
 tar_visnetwork(), [6](#), [13](#), [19](#), [30](#), [36](#), [41](#), [45](#),
 [50](#), [62](#), [67](#), [71](#), [76](#), [81](#), [92](#), [103](#), [110](#),
 [118](#), [125](#), [134](#), [140](#), [147](#), [154](#), [161](#),
 [169](#)
 tarchetypes-package, [3](#)
 targets::tar_format(), [52](#)
 targets::tar_make(), [41](#), [173](#)
 targets::tar_manifest(), [173](#)
 targets::tar_option_set(), [52](#)
 targets::tar_target(), [52](#), [172](#)
 targets::tar_visnetwork(), [173](#)