

Package: unigd (via r-universe)

October 15, 2024

Type Package

Title Universal Graphics Device

Version 0.1.2

Description A unified R graphics backend. Render R graphics fast and easy to many common file formats. Provides a thread safe 'C' interface for asynchronous rendering of R graphics.

License GPL (>= 2)

Depends R (>= 3.2.0)

Imports systemfonts (>= 1.0.0)

LinkingTo cpp11 (>= 0.2.4), systemfonts

Encoding UTF-8

SystemRequirements libpng, cairo, freetype2, fontconfig

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.0

URL <https://github.com/nx10/unigd>, <https://nx10.github.io/unigd/>

BugReports <https://github.com/nx10/unigd/issues>

Suggests testthat (>= 3.0.0), xml2 (>= 1.0.0), fontquiver (>= 0.2.0), covr, knitr, rmarkdown

Config/testthat/edition 3

Config/Needs/website tidyverse/tidytemplate

VignetteBuilder knitr

Repository <https://r-multiverse-staging.r-universe.dev>

RemoteUrl <https://github.com/nx10/unigd>

RemoteRef c7d55c984624bdf89e385a2d86fcb93c692b400c

RemoteSha c7d55c984624bdf89e385a2d86fcb93c692b400c

Contents

| | |
|-----------------------------|-----------|
| unigd-package | 2 |
| ugd | 3 |
| ugd_clear | 4 |
| ugd_close | 5 |
| ugd_id | 6 |
| ugd_info | 7 |
| ugd_remove | 7 |
| ugd_render | 8 |
| ugd_renderers | 9 |
| ugd_render_inline | 9 |
| ugd_save | 10 |
| ugd_save_inline | 11 |
| ugd_state | 12 |
| ugd_test_pattern | 13 |
| Index | 14 |

| | |
|---------------|---|
| unigd-package | <i>unigd: Universal graphics device</i> |
|---------------|---|

Description

Universal graphics device

Author(s)

Maintainer: Florian Rupprecht <floruppr@gmail.com> ([ORCID](#))

Other contributors:

- Kun Ren <mail@renkun.me> [contributor]
- Tatsuya Shima <ts1s1andn@gmail.com> [contributor]
- Jeroen Ooms <jeroen@berkeley.edu> ([ORCID](#)) [contributor]
- Hadley Wickham <hadley@rstudio.com> (Author of included svglite code) [copyright holder]
- Lionel Henry <lionel@rstudio.com> (Author of included svglite code) [copyright holder]
- Thomas Lin Pedersen <thomas.pedersen@rstudio.com> (Author and creator of included svglite code) [copyright holder]
- T Jake Luciani <jake@apache.org> (Author of included svglite code) [copyright holder]
- Matthieu Decorde <matthieu.decorde@ens-lyon.fr> (Author of included svglite code) [copyright holder]
- Vaudor Lise <lise.vaudor@ens-lyon.fr> (Author of included svglite code) [copyright holder]
- Tony Plate (Contributor to included svglite code) [copyright holder]
- David Gohel (Contributor to included svglite code) [copyright holder]
- Yixuan Qiu (Contributor to included svglite code) [copyright holder]

- Håkon Malmedal (Contributor to included svglite code) [copyright holder]
- RStudio (Copyright holder of included svglite code) [copyright holder]
- Brett Robinson (Author of included belle library) [copyright holder]
- Google (Copyright holder of included material design icons) [copyright holder]
- Victor Zverovich (Author of included fmt library) [copyright holder]
- Andrzej Krzemienski (Author of included std::experimental::optional library) [copyright holder]

See Also

Useful links:

- <https://github.com/nx10/unigd>
- <https://nx10.github.io/unigd/>
- Report bugs at <https://github.com/nx10/unigd/issues>

ugd

A unified R graphics backend.

Description

This function initializes a unigd graphics device.

Usage

```
ugd(  
  width = getOption("unigd.width", 720),  
  height = getOption("unigd.height", 576),  
  bg = getOption("unigd.bg", "white"),  
  pointsize = getOption("unigd.pointsize", 12),  
  system_fonts = getOption("unigd.system_fonts", list()),  
  user_fonts = getOption("unigd.user_fonts", list()),  
  reset_par = getOption("unigd.reset_par", FALSE)  
)
```

Arguments

| | |
|--------------|---|
| width | Graphics device width (pixels). |
| height | Graphics device height (pixels). |
| bg | Background color. |
| pointsize | Graphics device point size. |
| system_fonts | Named list of font names to be aliased with fonts installed on your system. If unspecified, the R default families sans, serif, mono and symbol are aliased to the family returned by <code>systemfonts::font_info()</code> . |

| | |
|------------|--|
| user_fonts | Named list of fonts to be aliased with font files provided by the user rather than fonts properly installed on the system. The aliases can be fonts from the fontquiver package, strings containing a path to a font file, or a list containing name and file elements with name indicating the font alias in the SVG output and file the path to a font file. |
| reset_par | If set to TRUE, global graphics parameters will be saved on device start and reset every time <code>ugd_clear()</code> is called (see <code>graphics::par()</code>). |

Details

All font settings and descriptions are adopted from the excellent 'svglite' package.

Value

No return value, called to initialize graphics device.

Examples

```
ugd() # Initialize graphics device

# Plot something
x <- seq(0, 3 * pi, by = 0.1)
plot(x, sin(x), type = "l")

# Render plot as SVG
ugd_render(width = 600, height = 400, as = "svg")

dev.off() # alternatively: ugd_close()
```

| | |
|-----------|------------------------------------|
| ugd_clear | <i>Clear all unigd plot pages.</i> |
|-----------|------------------------------------|

Description

This function will only work after starting a device with `ugd()`.

Usage

```
ugd_clear(which = dev.cur())
```

Arguments

which Which device (ID).

Value

Whether there were any pages to remove.

Examples

```
ugd()
plot(1, 1)
hist(rnorm(100))
ugd_clear() # Clear all previous plots
hist(rnorm(100))

dev.off()
```

| | |
|-----------|----------------------------|
| ugd_close | <i>Close unigd device.</i> |
|-----------|----------------------------|

Description

This achieves the same effect as `grDevices::dev.off()`, but will only close the device if it has the unigd type.

Usage

```
ugd_close(which = dev.cur(), all = FALSE)
```

Arguments

| | |
|--------------------|---|
| <code>which</code> | Which device (ID). |
| <code>all</code> | Should all running unigd devices be closed. |

Value

Number and name of the new active device (after the specified device has been shut down).

Examples

```
ugd()
hist(rnorm(100))
ugd_close() # Equivalent to dev.off()

ugd()
ugd()
ugd()
ugd_close(all = TRUE)
```

ugd_id *Query unigd plot IDs*

Description

Query unigd graphics device static plot IDs. Available plot IDs starting from `index` will be returned. `limit` specifies the number of plots. This function will only work after starting a device with `ugd()`.

Usage

```
ugd_id(index = 0, limit = 1, which = dev.cur(), state = FALSE)
```

Arguments

| | |
|--------------------|---|
| <code>index</code> | Plot index. If this is set to 0, the last page will be selected. |
| <code>limit</code> | Limit the number of returned IDs. If this is set to a value > 1 the returned type is a list if IDs. Set to 0 for all. |
| <code>which</code> | Which device (ID). |
| <code>state</code> | Include the current device state in the returned result (see also: <code>ugd_state()</code>). |

Value

List containing static plot IDs.

Examples

```
ugd() # Initialize graphics device

# Page 1
plot.new()
text(.5, .5, "#1")

# Page 2
plot.new()
text(.5, .5, "#2")

# Page 3
plot.new()
text(.5, .5, "#3")

third <- ugd_id() # Get ID of page 3 (last page)
second <- ugd_id(2) # Get ID of page 2
all <- ugd_id(1, limit = Inf) # Get all IDs

ugd_remove(1) # Remove page 1
ugd_render(second) # Render page 2

dev.off() # Close device
```

| | |
|----------|----------------------------------|
| ugd_info | <i>unigd device information.</i> |
|----------|----------------------------------|

Description

Access general information of a unigd graphics device. This function will only work after starting a device with `ugd()`.

Usage

```
ugd_info(which = dev.cur())
```

Arguments

| | |
|-------|--------------------|
| which | Which device (ID). |
|-------|--------------------|

Value

List of status variables with the following named items: `$id`: Server unique ID, `$version`: unigd and library versions.

Examples

```
ugd() # Initialize graphics device
ugd_info() # Get device information
dev.off() # Close device
```

| | |
|------------|----------------------------------|
| ugd_remove | <i>Remove a unigd plot page.</i> |
|------------|----------------------------------|

Description

This function will only work after starting a device with `ugd()`.

Usage

```
ugd_remove(page = 0, which = dev.cur())
```

Arguments

| | |
|-------|---|
| page | Plot page to remove. If this is set to 0, the last page will be selected. Can be set to a numeric plot index or plot ID (see <code>ugd_id()</code>). |
| which | Which device (ID). |

Value

Whether the page existed (and thereby was successfully removed).

Examples

```

ugd()
plot(1, 1) # page 1
hist(rnorm(100)) # page 2
ugd_remove(page = 1) # remove page 1

dev.off()

```

ugd_render

Render unigd plot and return it.

Description

See [ugd_save\(\)](#) for saving rendered plots as files. This function will only work after starting a device with [ugd\(\)](#).

Usage

```

ugd_render(
  page = 0,
  width = -1,
  height = -1,
  zoom = 1,
  as = "svg",
  which = dev.cur()
)

```

Arguments

| | |
|--------|--|
| page | Plot page to render. If this is set to 0, the last page will be selected. Can be set to a numeric plot index or plot ID (see ugd_id()). |
| width | Width of the plot. If this is set to -1, the last width will be selected. |
| height | Height of the plot. If this is set to -1, the last height will be selected. |
| zoom | Zoom level. (For example: 2 corresponds to 200%, 0.5 would be 50%.) |
| as | Renderer. |
| which | Which device (ID). |

Value

Rendered plot. Text renderers return strings, binary renderers return byte arrays.

Examples

```

ugd()
plot(1, 1)
ugd_render(width = 600, height = 400, as = "svg")
dev.off()

```

| | |
|---------------|--------------------------------|
| ugd_renderers | <i>unigd device renderers.</i> |
|---------------|--------------------------------|

Description

Get a list of available renderers. This function will only work after starting a device with `ugd()`.

Usage

```
ugd_renderers()
```

Value

List of renderers with the following named items: `$id`: Renderer ID, `$mime`: File mime type, `$ext`: File extension, `$name`: Human readable name, `$type`: Renderer type (currently either plot or other), `$bin`: Is the file a binary blob or text.

Examples

```
ugd_renderers()
```

| | |
|-------------------|-------------------------------|
| ugd_render_inline | <i>Inline plot rendering.</i> |
|-------------------|-------------------------------|

Description

Convenience function for quick inline plot rendering. This is similar to `ugd_render()` but the plotting code is specified inline and an `unigd` graphics device is managed (created and closed) automatically. Starting a device with `ugd()` is therefore not necessary.

Usage

```
ugd_render_inline(  
  code,  
  page = 0,  
  width = getOption("unigd.width", 720),  
  height = getOption("unigd.height", 576),  
  zoom = 1,  
  as = "svg",  
  ...  
)
```

Arguments

| | |
|--------|--|
| code | Plotting code. See examples for more information. |
| page | Plot page to render. If this is set to 0, the last page will be selected. Can be set to a numeric plot index or plot ID (see ugd_id()). |
| width | Width of the plot. |
| height | Height of the plot. |
| zoom | Zoom level. (For example: 2 corresponds to 200%, 0.5 would be 50%.) |
| as | Renderer. |
| ... | Additional parameters passed to <code>ugd(...)</code> |

Value

Rendered plot. Text renderers return strings, binary renderers return byte arrays.

Examples

```
ugd_render_inline({
  hist(rnorm(100))
}, as = "svgz")

s <- ugd_render_inline({
  plot.new()
  lines(c(0.5, 1, 0.5), c(0.5, 1, 1))
})
cat(s)
```

ugd_save

Render unigd plot to a file.

Description

See [ugd_render\(\)](#) for accessing plot data directly in memory without saving as a file. This function will only work after starting a device with [ugd\(\)](#).

Usage

```
ugd_save(
  file,
  page = 0,
  width = -1,
  height = -1,
  zoom = 1,
  as = "auto",
  which = dev.cur()
)
```

Arguments

| | |
|--------|---|
| file | Filepath to save plot. |
| page | Plot page to render. If this is set to 0, the last page will be selected. Can be set to a numeric plot index or plot ID (see <code>ugd_id()</code>). |
| width | Width of the plot. If this is set to -1, the last width will be selected. |
| height | Height of the plot. If this is set to -1, the last height will be selected. |
| zoom | Zoom level. (For example: 2 corresponds to 200%, 0.5 would be 50%.) |
| as | Renderer. When set to "auto" renderer is inferred from the file extension. |
| which | Which device (ID). |

Value

No return value. Plot will be saved to file.

Examples

```
ugd()

plot(1, 1)

tf <- tempfile()
on.exit(unlink(tf))

ugd_save(file = tf, width = 600, height = 400, as = "png")

dev.off()
```

ugd_save_inline *Inline plot rendering to a file.*

Description

Convenience function for quick inline plot rendering. This is similar to `ugd_save()` but the plotting code is specified inline and an unigd graphics device is managed (created and closed) automatically. Starting a device with `ugd()` is therefore not necessary.

Usage

```
ugd_save_inline(
  code,
  file,
  page = 0,
  width = getOption("unigd.width", 720),
  height = getOption("unigd.height", 576),
  zoom = 1,
  as = "auto",
  ...
)
```

Arguments

| | |
|--------|--|
| code | Plotting code. See examples for more information. |
| file | Filepath to save plot. |
| page | Plot page to render. If this is set to 0, the last page will be selected. Can be set to a numeric plot index or plot ID (see ugd_id()). |
| width | Width of the plot. |
| height | Height of the plot. |
| zoom | Zoom level. (For example: 2 corresponds to 200%, 0.5 would be 50%.) |
| as | Renderer. |
| ... | Additional parameters passed to <code>ugd(...)</code> |

Value

No return value. Plot will be saved to file.

Examples

```
tf <- tempfile(fileext=".svg")
on.exit(unlink(tf))

ugd_save_inline({
  plot.new()
  lines(c(0.5, 1, 0.5), c(0.5, 1, 1))
}, file = tf)
```

ugd_state

unigd device status.

Description

Access status information of a unigd graphics device. This function will only work after starting a device with [ugd\(\)](#).

Usage

```
ugd_state(which = dev.cur())
```

Arguments

| | |
|-------|--------------------|
| which | Which device (ID). |
|-------|--------------------|

Value

List of status variables with the following named items: `$hsize`: Plot history size (how many plots are accessible), `$upid`: Update ID (changes when the device has received new information), `$active`: Is the device the currently activated device.

Examples

```
ugd()  
ugd_state()  
plot(1, 1)  
ugd_state()  
  
dev.off()
```

| | |
|------------------|---|
| ugd_test_pattern | <i>Plot a test pattern that can be used to evaluate and compare graphics devices.</i> |
|------------------|---|

Description

Plot a test pattern that can be used to evaluate and compare graphics devices.

Usage

```
ugd_test_pattern()
```

Value

Nothing, but a plot is generated.

Examples

```
## Not run:  
  
ugd_test_pattern()  
  
## End(Not run)
```

Index

graphics::par(), 4
grDevices::dev.off(), 5

systemfonts::font_info(), 3

ugd, 3
ugd(), 4, 6–12
ugd_clear, 4
ugd_clear(), 4
ugd_close, 5
ugd_id, 6
ugd_id(), 7, 8, 10–12
ugd_info, 7
ugd_remove, 7
ugd_render, 8
ugd_render(), 9, 10
ugd_render_inline, 9
ugd_renderers, 9
ugd_save, 10
ugd_save(), 8, 11
ugd_save_inline, 11
ugd_state, 12
ugd_state(), 6
ugd_test_pattern, 13
unigd (unigd-package), 2
unigd-package, 2